

STATE OF OHIO
DEPARTMENT OF ADMINISTRATIVE SERVICES
GENERAL SERVICES DIVISION
OFFICE OF PROCUREMENT SERVICES
4200 SURFACE ROAD, COLUMBUS, OH 43228-1395

AMENDMENT FOR CHANGE
AMENDMENT NO. 1

TO: LIMITED DISTRIBUTION – OHIO STATE HIGHWAY PATROL, DEPARTMENT OF PUBLIC SAFETY,
COLUMBUS, OH 43223

FROM: ROBERT BLAIR, DIRECTOR, DEPARTMENT OF ADMINISTRATIVE SERVICES

SUBJECT: TERM CONTRACT - HIGHWAY PATROL AUTOMOBILES, 2012 MODEL YEAR (OR NEWER)

Attached are pages 9 and 16 to this contract. Remove these pages from the existing contract and replace with the attached page on the effective and/or revision date.

This amendment is issued to indicate an update to option 21.

All other prices, terms and conditions remain unchanged.

Questions regarding this Amendment and/or the Requirements Contract may be directed to:

Rob Rounds
rob.rounds@das.state.oh.us

This Amendment, the main Requirements Contract and any additional amendments thereto are available from the DAS Web site at the following address:

<http://www.ohio.gov/procure>

Affected Contractor(s):

195138
Coughlin Chrysler Dodge Jeep Ram
15777 Watkins Road
Marysville, OH 43040

SPECIFICATIONS (cont.)

10. Lamp - Trunk compartment with automatic actuated switch when trunk is opened; trunk lamp shall be factory installed, if available.
11. Fuel Door – All gas caps shall be able to be locked and or keyed alike if required.
12. Front and rear - Heavy duty black rubber floor covering.
13. Exterior Mirrors - Dual fold-away mirrors with dual remote control power at the driver's position. Mirrors to be non-glare with the passenger side mirror of the convex design. Mirrors are to be heated.
14. Remote trunk release - With unlocking device located left of steering column near and within immediate reach of driver position. Control to operate with ignition on or off. Deck lid, when opened remotely, must be restrained from opening completely in order to prevent damage to the hinges. Deck lid must remain in the full open position when opened manually.
15. AM/FM stereo radio - Mounted in dash with a minimum of four (4) conventional radio speaker system. Two (2) rear speakers shall be connected to the commercial radio. The two (2) front speakers shall be wired with a minimum of 24 inches of lead in wire not connected under the center of the dash. Speakers shall be minimum 6 ohm, with 10 watts of power.
16. Gauges - In addition to the standard gauges, there shall be a fuel gauge and water temperature gauge, which are to be illuminated. Gauges are to be factory installed and mounted in instrument panel. Warning lights are also to be furnished.
17. Supplemental restraint system (air bags) – Shall come equipped with 2nd generation front (or newer) and side air bags installed and operational for driver and front seat passenger positions. Standard seat belts and shoulder harness as required under federal safety regulations. Both air bags and seat belts shall be factory installed.
18. Padded dash - Non-reflective, to eliminate glare on the windshield.
19. Hood Latch Release - Hood to be controlled by an inside release located on the driver's side so that the hood cannot be opened from outside the vehicle. The release shall be the pull-cable type and readily accessible to the driver. There must be a sufficient difference between the hood control and the brake release so that there will not be any confusion between the two.
20. Spotlight - Shall be a factory installed pillar mounted on left side, completely wired, control operated with ignition on or off.
21. Trunk lid warning lights - Two (2) 4 inch, LED lights mounted to the deck lid inner panel. A minimum of generation II or newer LED lights, with each light having at a minimum 4 LED lights in each light is required. Lights are activated by a separate switch when the deck lid is opened. Lights are to be wired to flash alternately. Both the left and right lights are to be blue. There should be a minimum of 38 inches of space between the left and right trunk lights on the deck lid to allow for the installation of Stop sticks. Inside Trunk Lid Flashing Warning Lights are to be installed as high as possible to provide maximum visibility from the rear of the vehicle.
22. Trunk trim package - Vehicles trunk area is to be equipped with a trim package to minimize damage to the inside quarter panel areas and protect special Highway Patrol equipment in the trunk.
23. License Plate Bracket – Vehicle shall be equipped with a minimum of a front license plate bracket installed.
24. Spare Tire: Vehicle must come with a standard factory spare.

* Indicates an update to option 21.

SUMMARY OF AMENDMENTS

Amendment Number	Revision Date	Description
1	01/06/12	Indicates an update to option 21.