

<u>Product Name</u>	<u>i2c Part #</u>	<u>Product Description</u>	<u>State Pricing</u>
i2c Video Management Software	VMS-001	Compatible with all Axis Cameras and Video Encoders. Enterprise class software that supports a limitless number of cameras, runs on standard file servers or virtualized servers, Microsoft Active Directory compatible. Priced per conneced camera. No additional charge for Desktop Viewing Station Installations.	\$ 160
i2c Onsite Installation and/or Remote Support	i2c-lab	Onsite or remote installation of Axis Cameras purchased through i2c, software configuration, remote support and setup. Priced per hour including travel	\$ 110
Dell 2U Rack Server for Use with i2c Video Management Software	i2c-d2u	Dell Poweredge R520 2U Rack Server with Intel Xeon ES-2403 v2 1.8GHz processor, 16GB of RAM, Server 2012 R2, 15TB of useable archive storage on a 6 disk RAID 5 Array.	\$ 7,200
AXIS Q2901-E 9MM 8.3 FPS	0645-001	AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform.	\$ 5,095
AXIS Q2901-E PTMOUNT 9MM 8.3 FPS	0646-001	AXIS Q2901-E PT Mount Temperature alarm camera ready for pan/tilt motor head, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, shock detection, AXIS Video Motion Detection 3.0, and AXIS Camera Application Platform.	\$ 5,095
AXIS Q2901-E 19MM 8.3 FPS	0647-001	AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform.	\$ 5,095

AXIS Q2901-E PTMOUNT 19MM 8.3 FPS	0648-001	AXIS Q2901-E PT Mount Temperature alarm camera ready for pan/tilt motor head, IP66-rated, 336x256 resolution, 8.3 fps, and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, shock detection, AXIS Video Motion Detection 3.0, and AXIS Camera Application Platform.	\$ 5,095
AXIS P8524 SILVER IMPERIAL	0653-001	Height strip camera with a pinhole sensor unit inside the height strip and a separate main unit. Silver aluminum housing with an imperial (feet) height indicator. When mounted on a wall, it serves as an eye-level camera for facial identification. HDTV 720p resolution at 30 fps, fixed focal pinhole lens, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Power over Ethernet and 8-28 V DC, input/output ports and microSD card slot for edge storage.	\$ 587
AXIS P8524 BLACK IMPERIAL	0657-001	Height strip camera with a pinhole sensor unit inside the height strip and a separate main unit. Black aluminum housing with an imperial (feet) height indicator. When mounted on a wall, it serves as an eye-level camera for facial identification. HDTV 720p resolution at 30 fps, fixed focal pinhole lens, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Power over Ethernet and 8-28 V DC, input/output ports and microSD card slot for edge storage.	\$ 587
AXIS P8524 SILVER METRIC	0687-001	Height strip camera with a pinhole sensor unit inside the height strip and a separate main unit. Silver aluminum housing with an metric height indicator. When mounted on a wall, it serves as an eye-level camera for facial identification. HDTV 720p resolution at 30 fps, fixed focal pinhole lens, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Power over Ethernet and 8-28 V DC, input/output ports and microSD card slot for edge storage.	\$ 587

AXIS P8524 BLACK METRIC	0688-001	Height strip camera with a pinhole sensor unit inside the height strip and a separate main unit. Black aluminum housing with a metric height indicator. When mounted on a wall, it serves as an eye-level camera for facial identification. HDTV 720p resolution at 30 fps, fixed focal pinhole lens, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Power over Ethernet and 8-28 V DC, input/output ports and microSD card slot for edge storage.	\$ 587
AXIS P8535 SILVER IMPERIAL	0711-001	HDTV 1080p height strip camera with a pinhole sensor unit inside the height strip and a separate main unit. Silver aluminum housing with an imperial height indicator. When mounted on a wall, it serves as an eye-level camera for face identification. WDR – Forensic Capture, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Two-way audio. Power over Ethernet and 8-28 V DC, Input/Output ports and SD card slot for Edge storage.	\$ 783
AXIS P8535 BLACK IMPERIAL	0712-001	HDTV 1080p height strip camera with a pinhole sensor unit inside the height strip and a separate main unit. Black aluminum housing with an imperial height indicator. When mounted on a wall, it serves as an eye-level camera for face identification. WDR – Forensic Capture, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Two-way audio. Power over Ethernet and 8-28 V DC, Input/Output ports and SD card slot for Edge storage.	\$ 783
AXIS P8535 SILVER METRIC	0713-001	HDTV 1080p height strip camera with a pinhole sensor unit inside the height strip and a separate main unit. Silver aluminum housing with a metric height indicator. When mounted on a wall, it serves as an eye-level camera for face identification. WDR – Forensic Capture, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Two-way audio. Power over Ethernet and 8-28 V DC, Input/Output ports and SD card slot for Edge storage.	\$ 783

AXIS P8535 BLACK METRIC	0714-001	HDTV 1080p height strip camera with a pinhole sensor unit inside the height strip and a separate main unit. Black aluminum housing with a metric height indicator. When mounted on a wall, it serves as an eye-level camera for face identification. WDR – Forensic Capture, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Two-way audio. Power over Ethernet and 8-28 V DC, Input/Output ports and SD card slot for Edge storage.	\$ 783
AXIS M1004-W	0554-004	Small-sized indoor network camera. Fixed lens and adjustable focus. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps and I/O ports. Video motion detection. Connects over wireless LAN (IEEE 802.11b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup protocol. Includes stand and clamp for easy mounting and power supply.	\$ 195
AXIS M1004-W BULK 10PCS	0554-024	AXIS M1004-W in 10-pack/bulk. Cannot be sold separately as single packs. Power supply included.	\$ 1,910
AXIS M1013	0519-004	Small-sized indoor network camera. Fixed lens and adjustable focus. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA 800 x 600 resolution at 30 fps. Video motion detection. Connects over wired Ethernet. MicroSD/SDHC memory card slot for edge storage. Includes stand and clamp for easy mounting and power supply.	\$ 175
AXIS M1013 BULK 10PCS	0519-024	AXIS M1013 in 10-pack/bulk. Cannot be sold separately as single packs. Power supplies included.	\$ 1,714
AXIS M1014	0520-004	Small-sized indoor network camera. Fixed lens and adjustable focus. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. Video motion detection. Connects over wired Ethernet. MicroSD/SDHC memory card slot for edge storage. Includes stand and clamp for easy mounting and power supply.	\$ 224
AXIS M1014 BULK 10PCS	0520-024	AXIS M1014 in 10-pack/bulk. Cannot be sold separately as single packs. Power supplies included.	\$ 2,204

AXIS M1014 SURVEILLANCE KIT	0520-044	Bundle with four units of AXIS M1014 network cameras. The cameras feature 1 megapixel/ HDTV 720p resolution and MicroSD/MicroSDHC card slot. Includes a CD with AXIS Camera Companion video management software with support for up to 16 cameras. Power supplies included. MicroSD/MicroSDHC cards are not included.	\$ 783
AXIS M1025	0555-004	Small-sized indoor network camera. Fixed lens and adjustable focus. Multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p or 2 MP resolutions at 30 fps. Video motion detection. Connects over wired Ethernet and supports Power over Ethernet. Memory card slot for edge storage. HDMI output (Micro) for public view monitors. Includes stand and clamp for easy mounting and power supply.	\$ 293
AXIS M1025 BULK 10PCS	0555-024	AXIS M1025 in 10-pack/bulk. Cannot be sold separately as single packs. Power supplies included.	\$ 2,890
AXIS M1034-W	0522-004	Small-sized indoor network camera. Fixed lens and adjustable focus. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. Two-way audio with built-in microphone and speaker. Video motion and audio detection. Integrated passive infrared (PIR) sensor, white LED illuminator and I/O ports. Connects over wireless LAN (IEEE 802.11b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup™ PBC compatible. Includes stand and clamp for easy mounting, optional extension for stand and power supply.	\$ 273
AXIS M1034-W BULK 10PCS	0522-024	AXIS M1034-W in 10-pack/bulk. Cannot be sold separately as single packs. Power supplies included.	\$ 2,694
AXIS M1054	0338-004	Small-sized indoor network camera. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. Two-way audio with built-in microphone and speaker. Video motion and audio detection. Integrated passive infrared (PIR) sensor, white LED illuminator and I/O ports. Powered over Ethernet or by power supply. Includes stand and clamp for easy mounting, optional extension for stand and power supply.	\$ 391

AXIS M1054 BULK 10PCS	0338-021	AXIS M1054 in 10-pack/bulk. Cannot be sold separately as single packs. Power supplies, clamps and stand extensions not included.	\$ 3,870
AXIS M1054 SURVEILLANCE KIT	0338-044	Bundle with 4 units of AXIS M1054 and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	\$ 1,567
AXIS M1103 2.8MM	0329-001	SVGA camera with fixed, 2.8 mm, CS-mount lens. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 342
AXIS M1103 2.8MM BULK 10PCS	0329-021	AXIS M1103 2.8MM in 10-pack. Cannot be sold separately as single packs. Midspans not included.	\$ 3,380
AXIS M1103 2.8MM SURVEILLANCE KIT	0329-041	Bundle with 4 units of AXIS M1103 2.8mm and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	\$ 1,371
AXIS M1103 BAREB BULK 10PCS	0329-031	AXIS M1103 Barebone in 10-pack. Cannot be sold separately as single packs. No midspans. No lens.	\$ 3,233
AXIS M1104 2.8MM	0339-001	HDTV camera with fixed, 2.8 mm, CS-mount lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 440
AXIS M1104 2.8MM BULK 10PCS	0339-021	AXIS M1104 2.8MM in 10-pack. Cannot be sold separately as single packs. Midspans not included.	\$ 4,360

AXIS M1104 2.8MM SURVEILLANCE KIT	0339-041	Bundle with 4 units of AXIS M1104 2.8mm and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	\$ 1,763
AXIS M1104 BAREB BULK 10PCS	0339-031	AXIS M1104 Barebone in 10-pack. Cannot be sold separately as single packs. No midspans. No lens.	\$ 4,213
AXIS M1113	0340-001	SVGA camera with varifocal 2.9-8.2 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 440
AXIS M1113 BAREB BULK 10PCS	0340-031	AXIS M1113 Barebone in 10-pack. Cannot be sold separately as single packs. No midspans. No lens.	\$ 4,115
AXIS M1113 BULK 10PCS	0340-021	AXIS M1113 in 10-pack. Cannot be sold separately as single packs. Midspans not included.	\$ 4,360
AXIS M1114	0341-001	HDTV camera with varifocal 2.8-8 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 538
AXIS M1113-E	0431-001	Outdoor, IP66-rated SVGA camera with varifocal 2.9-8.2 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. Video motion detection and active tampering alarm. Operation in -20°C to +50°C (4 °F to 122 °F). Power over Ethernet. Includes a removable sunshield and wall bracket. Midspan not included.	\$ 538
AXIS M1114 BAREB BULK 10PCS	0341-031	AXIS M1114 Barebone in 10-pack. Cannot be sold separately as single packs. No midspans. No lens.	\$ 5,046
AXIS M1114 BULK 10PCS	0341-021	AXIS M1114 in 10-pack. Cannot be sold separately as single packs. Midspans not included.	\$ 5,340

AXIS M1114-E	0432-001	Outdoor, IP66-rated HDTV camera with varifocal 2.8-8 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. Video motion detection and active tampering alarm. Operation in -20°C to +50°C (-4 °F to 122 °F). Power over Ethernet. Includes a removable sunshield and wall bracket. Midspan not included.	\$ 636
AXIS M1124	0747-001	HDTV 720p resolution, day/night, fixed camera with CS-mount varifocal 3-10.5 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p at 30 fps. WDR – Forensic Capture and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Power over Ethernet or 8-28 VDC input. Includes stand. Power supply not included.	\$ 342
AXIS M1124 BULK 10PCS	0747-021	AXIS M1124 in 10-pack. Cannot be sold separately as single packs.	\$ 3,380
AXIS M1124 BAREBONE	0747-031	AXIS M1124 Barebone. No lens.	\$ 322
AXIS M1124-E	0748-001	Outdoor, NEMA 4X, IP66 and IK10-rated, lightweight, HDTV 720p resolution, day/night, fixed camera with CS-mount varifocal 3-10.5 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p at 30 fps. WDR – Forensic Capture and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Power over Ethernet or 8-28 VDC input. Operation in -20°C to +50°C. Powered by IEEE 802.3af midspan. Includes a wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan not included.	\$ 440

AXIS M1125	0749-001	HDTV 1080p resolution, day/night, fixed camera with CS-mount varifocal 3-10.5 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps. WDR – Forensic Capture and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Power over Ethernet or 8-28 VDC input. Includes stand. Power supply not included.	\$ 411
AXIS M1125 BULK 10PCS	0749-021	AXIS M1125 in 10-pack. Cannot be sold separately as single packs.	\$ 4,066
AXIS M1125 BAREBONE	0749-031	AXIS M1125 Barebone. No lens.	\$ 391
AXIS M1125-E	0750-001	Outdoor, NEMA 4X, IP66 and IK10-rated, lightweight, HDTV 1080p resolution, day/night, fixed camera with CS-mount varifocal 3-10.5 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps. WDR – Forensic Capture and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Power over Ethernet or 8-28 VDC input. Operation in -20°C to +50°C. Powered by IEEE 802.3af midspan. Includes a wall bracket, Torx T20 screw driver and IP66-rated cable glands. Midspan not included.	\$ 509
AXIS M1144-L	0436-001	HDTV camera with varifocal boardmount 2.5-6 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. Video motion detection and active tampering alarm. Integrated IR LED illumination up to 15 meters and I/O ports. MicroSD/SDHC memory card slot for edge storage. Includes stand for easy mounting. Power over Ethernet. Midspan not included.	\$ 440
AXIS M1144-L BULK 10PCS	0436-021	AXIS M1144-L in 10-pack/bulk. Cannot be sold separately as single packs.	\$ 4,360

AXIS M1145	0590-001	HDTV camera for day and night surveillance with varifocal 3-10.5mm P-iris lens. Remote 3.5 x optical zoom and focus with automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p or 2MP resolution at 30 fps. Video motion detection and active tampering alarm and I/O ports. MicroSD/SDHC memory card slot for edge storage. Includes stand for easy mounting. Power over Ethernet. Midspan not included.	\$ 489
AXIS M1145 BULK 10PCS	0590-021	AXIS M1145 in 10-pack/bulk. Cannot be sold separately as single packs.	\$ 4,850
AXIS M1145-L	0591-001	HDTV camera for day and night surveillance with varifocal 3-10.5mm P-iris lens. Remote 3.5 x optical zoom and focus with automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p or 2MP resolution at 30 fps. Video motion detection and active tampering alarm and I/O ports. OptimizedIR, a power-efficient LED technology that provides an adaptable angle of IR illumination up to 15 meters (50 feet) MicroSD/SDHC memory card slot for edge storage. Includes stand for easy mounting. Power over Ethernet. Midspan not included.	\$ 538
AXIS M1145-L BULK 10PCS	0591-021	AXIS M1145-L in 10-pack/bulk. Cannot be sold separately as single packs.	\$ 5,340
AXIS M2014-E	0549-001	Compact, bullet-style HDTV network camera comprising a main unit and a separate IP66-rated camera unit. Edge storage using microSD card or NAS, Support for ACAP and AXIS Camera Companion, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support. Includes stand and clamp for camera unit and DIN rail mount for main unit. Midspan not included.	\$ 391
AXIS M2014-E BULK 10PCS	0549-021	AXIS M2014-E in 10-pack/bulk. Cannot be sold separately as single packs.	\$ 3,870
AXIS P1204	0531-001	Miniature HDTV pinhole camera for discreet surveillance. Cable from sensor unit going with a 90° angle vs the lens. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	\$ 489
AXIS P1204 BULK 10 PCS	0531-021	AXIS P1204 in pack of 10 units.	\$ 4,850

AXIS P1214	0532-001	Miniature HDTV pinhole camera for discreet surveillance. Cable from sensor unit going in the direction of the lens. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	\$ 489
AXIS P1214 BULK 10 PCS	0532-021	AXIS P1214 in pack of 10 units	\$ 4,850
AXIS P1214-E	0533-001	Miniature HDTV camera for discreet outdoor surveillance. Cable from sensor unit going in the direction of the lens. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	\$ 489
AXIS P1214-E BULK 10 PCS	0533-021	AXIS P1214-E in pack of 10 units	\$ 4,850
AXIS P1224-E	0654-001	Miniature HDTV camera for discreet indoor/outdoor surveillance with 145° horizontal field of view. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	\$ 489
AXIS P1347	0343-001	5MP, day/night, fixed camera with varifocal 3.5-10 mm P-Iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps, 3MP resolution at 20 fps, or HDTV 1080p at 30 fps. Digital PTZ support includes multi-view streaming of different view areas. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Power supply not included.	\$ 1,244
AXIS P1347 BAREBONE BULK 10PCS	0343-051	AXIS P1347 Barebone in 10-pack. Cannot be sold separately as single packs. No power supplies.	\$ 11,465
AXIS P1347 BULK 10PCS	0343-021	AXIS P1347 in 10-pack. Cannot be sold separately as single packs. No power supplies.	\$ 12,298

AXIS P1347-E	0368-001	Outdoor, IP66-rated, 5MP, day/night, fixed camera with varifocal 3.5-10 mm P-Iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps, 3MP resolution at 20 fps, or HDTV 1080p at 30 fps. Digital PTZ support includes multi-view streaming of different view areas. WDR. Video motion detection and active tampering alarm. Two-way audio. SD/SDHC memory card slot for optional local video storage. Operation in -30°C to +50°C when powered by IEEE 802.3af midspan or -40°C to +50°C with AXIS T8123 High PoE Midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66 rated cable glands. Midspan not included.	\$ 1,538
AXIS P1353	0523-001	Light-sensitive, SVGA resolution, day/night, fixed camera with varifocal 3-8 mm DC-iris lens and remote back focus. Lightfinder technology. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Power over Ethernet. Power supply not included.	\$ 685
AXIS P1353-E	0527-001	Outdoor, IP66-rated, Light-sensitive, SVGA, day/night, network camera with varifocal 3-8 mm DC-iris lens and remote back focus. Lightfinder technology. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio. MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Operation in -30°C to +50°C when powered by IEEE 802.3af compliant midspan or -40°C to +50°C with AXIS T8123/-E High PoE Midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66 rated cable glands. Midspan not included.	\$ 930
AXIS P1353 BULK 10PCS	0523-021	AXIS P1353 in 10-pack. Cannot be sold separately as single packs. No power supplies.	\$ 6,761

AXIS P1353 BAREBONE	0523-041	AXIS P1353 Barebone. No lens. No power supply.	\$ 636
AXIS P1353 BAREB BULK 10PCS	0523-051	AXIS P1353 Barebone in 10-pack. Cannot be sold separately as single packs. No lenses. No power supplies.	\$ 6,359
AXIS P1354	0524-001	Light-sensitive, HDTV resolution, day/night, fixed camera with varifocal 2.8-8 mm DC-iris lens and remote back focus. Lightfinder technology. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Power over Ethernet. Power supply not included.	\$ 685
AXIS P1354-E	0528-001	Outdoor, IP66-rated, HDTV, day/night, fixed network camera with varifocal 3-8 mm DC-iris lens and remote back focus. Lightfinder technology. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio. SD/SDHC memory card slot for optional local video storage. Operation in -30°C to +50°C when powered by IEEE 802.3af midspan or -40°C to +50°C with AXIS T8123 High PoE Midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66 rated cable glands. Midspan not included.	\$ 930
AXIS P1354 BULK 10PCS	0524-021	AXIS P1354 in 10-pack. Cannot be sold separately as single packs. No power supplies.	\$ 6,761
AXIS P1354 BAREBONE	0524-041	AXIS P1354 Barebone. No lens. No power supply.	\$ 587
AXIS P1354 BAREB BULK 10PCS	0524-051	AXIS P1354 Barebone in 10-pack. Cannot be sold separately as single packs. No lenses. No power supplies.	\$ 5,869

AXIS P1355	0525-001	1080p HDTV resolution, day/night, fixed camera with varifocal 2.8-8 mm P-iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Power over Ethernet. Power supply not included.	\$ 881
AXIS P1355-E	0529-001	Outdoor, IP66-rated, 1080p HDTV, day/night, fixed network camera with varifocal 2.8-8 mm P-iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. WDR- dynamics contrast. Video motion detection and active tampering alarm. Two-way audio. MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Operation in -30°C to +50°C when powered by IEEE 802.3af midspan or -40°C to +50°C with AXIS T8123/-E High PoE Midspans. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66 rated cable glands. Midspan not included.	\$ 1,126
AXIS P1355 BULK 10PCS	0525-021	AXIS P1355 in 10-pack. Cannot be sold separately as single packs. No power supplies.	\$ 8,721
AXIS P1355 BAREBONE	0525-041	AXIS P1355 Barebone. No lens. No power supply.	\$ 783
AXIS P1355 BAREB BULK 10PCS	0525-051	AXIS P1355 Barebone in 10-pack. Cannot be sold separately as single packs. No lenses. No power supplies.	\$ 7,829

AXIS P1365	0690-001	HDTV 1080p resolution, day/night, fixed camera with CS-mount varifocal 2.8-8 mm P-iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 60 fps. WDR – Forensic Capture, Lightfinder and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Power over Ethernet. Includes stand with cable management. Power supply not included.	\$ 734
AXIS P1365-E	0740-001	Outdoor, NEMA 4X, IP66/67 and IK10-rated, lightweight, HDTV 1080p, day/night, fixed network camera with CS-mount varifocal 2.8-8 mm P-iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 60 fps. WDR- Forensic Capture Lightfinder and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio. MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Operation in -40°C to +50°C. Powered by IEEE 802.3af midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan not included.	\$ 979
AXIS P1365 BULK 10PCS	0690-021	AXIS P1365 in 10-pack. Cannot be sold separately as single packs. No power supplies.	\$ 7,251
AXIS P1365 BAREBONE	0690-041	AXIS P1365 Barebone. No lens. No power supply.	\$ 636
AXIS P1365 BAREB BULK 10PCS	0690-051	AXIS P1365 Barebone in 10-pack. Cannot be sold separately as single packs. No lenses. No power supplies.	\$ 6,359

AXIS P1357	0526-001	5MP resolution, day/night, fixed camera with varifocal 2.8-8 mm P-iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP at 12 fps, 3MP resolution at 20 fps, or HDTV 1080p at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Power over Ethernet. Power supply not included.	\$ 881
AXIS P1357-E	0530-001	Outdoor, IP66-rated, 5MP, day/night, fixed network camera with varifocal 2.8-8 mm P-iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps, 3MP resolution at 20 fps, or HDTV 1080p at 30 fps. WDR-dynamics contrast. Video motion detection and active tampering alarm. Two-way audio. MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Operation in -30°C to +50°C when powered by IEEE 802.3af midspan or -40°C to +50°C with AXIS T8123/-E High PoE Midspans. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66 rated cable glands. Midspan not included.	\$ 1,126
AXIS P1357 BULK 10PCS	0526-021	AXIS P1357 in 10-pack. Cannot be sold separately as single packs. No power supplies.	\$ 8,721
AXIS P1357 BAREBONE	0526-041	AXIS P1357 Barebone. No lens. No power supply.	\$ 783
AXIS P1357 BAREB BULK 10PCS	0526-051	AXIS P1357 Barebone in 10-pack. Cannot be sold separately as single packs. No lenses. No power supplies.	\$ 7,829

AXIS P1405-E	0620-001	Compact and outdoor-ready HDTV camera for day and night surveillance, IP66-rated, varifocal 2.8-10 mm P-iris lens . Remote 3.5 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 30 fps.Video motion detection, active tampering alarm, corridor format and WDR – Dynamic Contrast. microSD/SDHC memory card slot for edge storage. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -10 °C to 50 °C (14 °F to 122 °F).	\$ 587
AXIS P1405-LE	0621-001	Compact and outdoor-ready HDTV camera for day and night surveillance, IP66-rated, varifocal 2.8-10 mm P-iris lens . Remote 3.5 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 30 fps.Video motion detection, active tampering alarm, corridor format and WDR – Dynamic Contrast. Built-in IR illumination covering up to 10 meters (33 feet). microSD/SDHC memory card slot for edge storage. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -10 °C to 50 °C (14 °F to 122 °F).	\$ 636
AXIS P1425-E	0622-001	Compact and outdoor-ready HDTV camera for day and night surveillance, IP66-rated, varifocal 3-10.5 mm P-iris lens . Remote 3.5 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 30 fps.Video motion detection, active tampering alarm, corridor format and WDR – Dynamic Contrast. I/O ports, microSD/SDHC memory card slot for edge storage. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F).	\$ 636

AXIS P1425-LE	0623-001	Compact and outdoor-ready HDTV camera for day and night surveillance, IP66-rated, varifocal 3-10.5 mm P-iris lens . Remote 3.5 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 30 fps.Video motion detection, active tampering alarm, corridor format and WDR – Dynamic Contrast. I/O ports, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 15 meters (50 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F).	\$ 685
AXIS P1427-E	0624-001	Compact and outdoor-ready HDTV camera for day and night surveillance, IP66-rated, varifocal 2.8-9.8 mm P-iris lens . Remote 3.5 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max 5 MP resolution at 12.5 fps.Video motion detection, active tampering alarm, corridor format and WDR – Dynamic Contrast. I/O ports, microSD/SDHC memory card slot for edge storage. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F).	\$ 734
AXIS P1427-LE	0625-001	Compact and outdoor-ready HDTV camera for day and night surveillance, IP66-rated, varifocal 2.8-9.8 mm P-iris lens . Remote 3.5 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max 5 MP resolution at 12.5 fps.Video motion detection, active tampering alarm, corridor format and WDR – Dynamic Contrast. I/O ports, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 15 meters (50 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F).	\$ 783

AXIS P1428-E	0637-001	Compact and outdoor-ready 4K Ultra HD camera for day and night surveillance, IP66-rated, varifocal 3.3-9.8 mm P-iris lens . Remote 3 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max 8.3 MP/4K Ultra HD resolution at 30 fps.Video motion detection, active tampering alarm and WDR – Dynamic Contrast. I/O ports, microSD/SDHC memory card slot for edge storage. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F).	\$ 979
AXIS Q1604	0439-001	HDTV, day/night, fixed camera with varifocal 2.8-8 mm DC-iris lens and remote back focus. Support for P-Iris, Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at full frame rate. WDR-dynamic contrast and WDR-dynamic capture. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Power supply not included.	\$ 979
AXIS Q1604 BULK 10PCS	0439-021	AXIS Q1604 in 10-pack. Cannot be sold separately as single packs. No power supplies.	\$ 9,652
AXIS Q1604-E	0463-001	Outdoor, IP66-rated HDTV, day/night, fixed camera with varifocal 2.8-8 mm DC-iris lens and remote back focus. Support for P-Iris, Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at full frame rate. WDR-dynamic contrast and WDR-dynamic capture. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Arctic Temperature Control, Operation in -30°C to +50°C (-22 °F to 122 °F) when powered by IEEE 802.3af midspan or -40°C to +50°C (-40 °F to 122 °F) with High PoE Midspan. Includes a removable sunshield and wall bracket. Midspan not included.	\$ 1,273
AXIS Q1604 BAREBONE	0439-041	AXIS Q1604 Barebone in single pack. No lens. No power supply.	\$ 881
AXIS Q1604 BAREB BULK 10PCS	0439-031	AXIS Q1604 barebone in 10-pack. Cannot be sold separately as single packs. No lenses. No power supplies.	\$ 8,809

AXIS Q1614	0550-001	HDTV, day/night, fixed camera with varifocal 2.8-8 mm P-Iris lens and remote back focus. Support for DC-iris, multiple, individually configurable H.264 and Motion JPEG streams; HDTV 720p or 1MP resolution at 50/60 frames per second. WDR - dynamic capture and Lightfinder technology for demanding lighting conditions. Video motion detection, active tampering alarm and shock detection. Two-way audio with built-in microphone, audio detection and I/O for alarm/event handling. Serial port for RS422/485 communication. Memory card slot for optional local video storage. Power over Ethernet or 8-28 V DC input. Power supply not included.	\$ 1,077
AXIS Q1614 BULK 10PCS	0550-021	AXIS Q1614 in 10-pack. Cannot be sold separately as single packs. No power supplies.	\$ 10,632
AXIS Q1614 BAREBONE	0550-041	AXIS Q1614 Barebone in single pack. No lens. No power supply.	\$ 979
AXIS Q1614 BAREB BULK 10PCS	0550-051	AXIS Q1614 barebone in 10-pack. Cannot be sold separately as single packs. No lenses. No power supplies.	\$ 9,789
AXIS Q1614-E	0551-001	Outdoor, IP66-rated HDTV, day/night, fixed camera with varifocal 2.8-8 mm P-Iris lens and remote back focus. Support for DC-iris, multiple, individually configurable H.264 and Motion JPEG streams; HDTV 720p or 1MP resolution at 50/60 frames per second. WDR - dynamic capture and Lightfinder technology for demanding lighting conditions Video motion detection, active tampering alarm and shock detection. Two-way audio, audio detection and I/O for alarm/event handling. Serial port for RS422/485 communication. Memory card slot for optional local video storage. Arctic Temperature Control, operation in -30°C to +50°C (-22 °F to 122 °F) when powered by IEEE 802.3af midspan or -40°C to +50°C (-40 °F to 122 °F) with PoE+ Midspan. Includes a removable sunshield and wall bracket. Midspan not included.	\$ 1,371

AXIS Q1615	0629-001	HDTV, day/night, fixed camera with varifocal 2.8-8 mm P-Iris lens and remote back focus. Support for DC-iris, multiple, individually configurable H.264 and Motion JPEG streams; HDTV 1080p or 2 MP resolution at 50/60 frames per second. WDR - Forensic Capture and Lightfinder technology for demanding lighting conditions. Electronic image stabilization to improve video quality when the camera is subject to vibration. Video motion detection, active tampering alarm and shock detection. Two-way audio with built-in microphone, audio detection and I/O for alarm/event handling. Serial port for RS485/RS422 communication. Memory card slot for optional local video storage. Power over Ethernet or 8-28 V DC input. Power supply not included.	\$ 1,077
AXIS Q1615 BULK 10PCS	0629-021	AXIS Q1615 in 10-pack. Cannot be sold separately as single packs. No power supplies.	\$ 10,632
AXIS Q1615 BAREBONE	0629-041	AXIS Q1615 Barebone in single pack. No lens. No power supply.	\$ 979
AXIS Q1615 BAREB BULK 10PCS	0629-031	AXIS Q1615 barebone in 10-pack. Cannot be sold separately as single packs. No lenses. No power supplies.	\$ 9,789
AXIS Q1615-E	0630-001	Outdoor, IP66-rated HDTV, day/night, fixed camera with varifocal 2.8-8 mm P-Iris lens and remote back focus. Support for DC-iris, multiple, individually configurable H.264 and Motion JPEG streams; HDTV 1080p or 2 MP resolution at 50/60 frames per second. WDR - Forensic Capture and Lightfinder technology for demanding lighting conditions. Electronic image stabilization to improve video quality when the camera is subject to vibration. Video motion detection, active tampering alarm and shock detection. Two-way audio, audio detection and I/O for alarm/event handling. Serial port for RS485/RS422 communication. Memory card slot for optional local video storage. Arctic Temperature Control, operation in -30°C to 50°C (-22 °F to 122 °F) when powered by IEEE 802.3af midspan or -40°C to 50°C (-40 °F to 122 °F) with PoE+ Midspan. Includes a removable sunshield and wall bracket. Midspan not included.	\$ 1,371

AXIS Q1635	0661-001	1/2" sensor, day/night, fixed camera with varifocal DC-iris lens and remote back focus, support for P-Iris lenses. Support for multiple, individually configurable H.264 and Motion JPEG streams; HDTV 1080p or 2 MP resolution at 50/60 frames per second. WDR-Forensic Capture and Lightfinder technology for demanding lighting conditions. Electronic image stabilization and a defogging functionality to improve video quality. Video motion detection, active tampering alarm and shock detection. Two-way audio with built-in microphone, audio detection and I/O for alarm/event handling. Serial port for RS485/RS422 communication. Memory card slot for optional local video storage. Power over Ethernet or 8-28 V DC input. Power supply not included.	\$ 1,420
AXIS Q1635 BULK 10PCS	0661-021	AXIS Q1635 in 10-pack. Cannot be sold separately as single packs. No power supplies.	\$ 14,062
AXIS Q1635 BAREBONE	0661-031	AXIS Q1635 Barebone in single pack. No lens. No power supply.	\$ 1,224
AXIS Q1635 BAREB BULK 10PCS	0661-041	AXIS Q1635 barebone in 10-pack. Cannot be sold separately as single packs. No lenses. No power supplies.	\$ 12,239
AXIS Q1755 60HZ	0304-001	2.0 Megapixel HDTV camera with 10x zoom, auto focus and day/night mode. Complying with SMPTE standards for HDTV 1080i and 720P. 25/30 in all resolutions in H.264 or Motion JPEG. Video motion detection and active tampering alarm. Gatekeeper functionality. I/O for alarm/event handling. Two-way audio with audio detection alarm. Power over Ethernet. Power supply not included.	\$ 1,469
AXIS Q1755 60HZ BULK 10PCS	0304-021	AXIS Q1755 60Hz in 10-pack. Cannot be sold separately as single packs. No midspan.	\$ 14,552

AXIS Q1755 60HZ POE	0304-034	2.0 Megapixel HDTV camera with 10x zoom, auto focus and day/night mode. Complying with SMPTE standards for HDTV 1080i and 720P. 25/30 in all resolutions in H.264 or Motion JPEG. Video motion detection and active tampering alarm. Gatekeeper functionality. I/O for alarm/event handling. Two-way audio with audio detection alarm. Power over Ethernet. Includes one-port Midspan.	\$ 1,518
AXIS Q1755-E 60HZ	0348-001	Outdoor, IP66-rated, 2.0 Megapixel HDTV camera with 10x zoom, auto focus and day/night mode. Complying with SMPTE standards for HDTV 1080i and 720P. 25/30 in all resolutions in H.264 or Motion JPEG. Video motion detection and active tampering alarm. Gatekeeper functionality. Two-way audio. Arctic Temperature Control. Operation in -30 °C to 45 °C (-22 °F to 113 °F) when powered by IEEE 802.3af midspan or down to -40 °C (-40 °F) with AXIS T8123 High PoE Midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66 rated cable glands. Midspan not included.	\$ 1,763
AXIS Q1765-LE	0509-001	Outdoor, IP66 and NEMA 4X-rated, 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Integrated IR LED illumination. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. WDR-dynamic contrast. Video motion detection and active tampering alarm. Two way audio and I/O with multi-connector cable (not included). MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -40°C to +50°C. Powered by PoE (IEEE 802-3af), 8-28 V DC or 20-24 V AC. Includes a removable sunshield, integrated wall/ceiling mount. Power supply or midspan not included.	\$ 1,371

AXIS Q1765-LE PTMOUNT	0644-001	Outdoor, IP66 and NEMA 4X-rated, 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Integrated IR LED illumination. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. WDR-dynamic contrast. Video motion detection and active tampering alarm. Serial port supporting RS422/485 communication for connection to a pan-tilt motor. MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -40°C to +50°C. Powered by PoE (IEEE 802-3af), 8-28 V DC or 20-24 V AC. Includes a removable sunshield. Power supply, midspan or pan-tilt motor not included.	\$ 1,371
AXIS Q1775	0751-001	1080p HDTV camera with 10x zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max. HDTV 1080p resolution at 50/60 fps. WDR-Dynamic Capture (130dB@ 30 fps and 90dB@ 60 fps). Video motion detection, Gatekeeper functionality and active tampering alarm. Two way audio in 48KHz, I/O and serial port for RS485/RS422 communication. SDHC/SDXC memory card slot for optional local video storage. Operation in 0 °C to +50 °C. Powered by PoE (IEEE 802-3af), 8-28 V DC or 20-24 V AC. Includes stand for wall or ceiling mount. Power supply not included.	\$ 1,273
AXIS Q1775-E	0752-001	Outdoor, IP66- and NEMA 4X-rated, 1080p HDTV camera with 10x zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max. HDTV 1080p resolution at 50/60 fps. WDR-Dynamic Capture (130dB@ 30 fps and 90dB@ 60 fps). Video motion detection, Gatekeeper functionality and active tampering alarm. Two way audio in 48KHz, I/O and serial port for RS485/RS422 communication. SD/SDHC/SDXC memory card slot for optional local video storage. Arctic Temperature Control, operation in -30°C to 50°C (-22 °F to 122 °F) when powered by IEEE 802.3af midspan or -40 °C to 50 °C (-40 °F to 122 °F) with PoE+ Midspan. Includes a removable sunshield and wall bracket. Midspan not included.	\$ 1,567

AXIS Q1910	0334-001	Indoor Thermal Network Camera, 160x128 resolution, 8.33 fps, and 17° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	\$ 2,939
AXIS Q1910-E	0335-001	Outdoor ready Thermal Network Camera, IP66-rated, 160x128 resolution, 8.33 fps, and 17° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	\$ 3,429
AXIS Q1931-E 7MM 30 FPS	0600-001	Outdoor Thermal Network Camera for wall and ceiling mount, IP66 and IP67-rated, 384x288 resolution, 30 fps, and 50° angle of view. It supports ONVIF, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 3,429
AXIS Q1931-E PT MOUNT 7MM 30 FPS	0683-001	Outdoor Thermal Network Camera for pan/tilt motor head, IP66-rated, 384x288 resolution, 30 fps, and 50° angle of view. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 3,429
AXIS Q1931-E 13MM 30 FPS	0601-001	Outdoor Thermal Network Camera for wall and ceiling mount, IP66 and IP67-rated, 384x288 resolution, 30 fps, and 28° angle of view. It supports ONVIF, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 3,429
AXIS Q1931-E PT MOUNT 13MM 30 FPS	0684-001	Outdoor Thermal Network Camera for pan/tilt motor head, IP66-rated, 384x288 resolution, 30 fps, and 28° angle of view. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 3,429
AXIS Q1931-E 35MM 30 FPS	0602-001	Outdoor Thermal Network Camera for wall and ceiling mount, IP66 and IP67-rated, 384x288 resolution, 30 fps, and 10° angle of view. It supports ONVIF, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 4,115

AXIS Q1931-E PT MOUNT 35MM 30 FPS	0685-001	Outdoor Thermal Network Camera for pan/tilt motor head, IP66-rated, 384x288 resolution, 30 fps, and 10° angle of view. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 4,115
AXIS Q1931-E 60MM 30 FPS	0603-001	Outdoor Thermal Network Camera for wall and ceiling mount, IP66 and IP67-rated, 384x288 resolution, 30 fps, and 6° angle of view. It supports ONVIF, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 6,075
AXIS Q1931-E PT MOUNT 60MM 30 FPS	0686-001	Outdoor Thermal Network Camera for pan/tilt motor head, IP66-rated, 384x288 resolution, 30 fps, and 6° angle of view. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 6,075
AXIS Q1932-E 10MM 30 FPS	0608-001	Outdoor Thermal Network Camera for wall and ceiling mount, IP66 and IP67-rated, 640x480 resolution, 30 fps, 57° angle of view. It supports ONVIF, H.264, audio, local storage, I/O, PoE, tampering alarm, motion and audio detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 6,859
AXIS Q1932-E PT MOUNT 10MM 30 FPS	0704-001	Outdoor Thermal Network Camera for pan/tilt motor head, IP66-rated, 640x480 resolution, 30 fps and 57° angle of view. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 6,859
AXIS Q1932-E 19MM 30 FPS	0609-001	Outdoor Thermal Network Camera for wall and ceiling mount, IP66 and IP67-rated, 640x480 resolution, 30 fps and 32° angle of view. It supports ONVIF, H.264, audio, local storage, I/O, PoE, tampering alarm, motion and audio detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 6,859

AXIS Q1932-E PT MOUNT 19MM 30 FPS	0705-001	Outdoor Thermal Network Camera for pan/tilt motor head, IP66-rated, 640x480 resolution, 30 fps and 32° angle of view. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 6,859
AXIS Q1932-E 35MM 30 FPS	0610-001	Outdoor Thermal Network Camera for wall and ceiling mount, IP66 and IP67-rated, 640x480 resolution, 30 fps and 18° angle of view. It supports ONVIF, H.264, audio, local storage, I/O, PoE, tampering alarm, motion and audio detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 7,839
AXIS Q1932-E PT MOUNT 35MM 30 FPS	0706-001	Outdoor Thermal Network Camera for pan/tilt motor head, IP66-rated, 640x480 resolution, 30 fps and 18° angle of view. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 7,839
AXIS Q1932-E 60MM 30 FPS	0611-001	Outdoor Thermal Network Camera for wall and ceiling mount, IP66 and IP67-rated, 640x480 resolution, 30 fps and 10° angle of view. It supports ONVIF, H.264, audio, local storage, I/O, PoE, tampering alarm, motion and audio detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 9,799
AXIS Q1932-E PT MOUNT 60MM 30 FPS	0707-001	Outdoor Thermal Network Camera for pan/tilt motor head, IP66-rated, 640x480 resolution, 30 fps and 10° angle of view. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform. Shipped with AXIS ACAP VMD 3.0 and CLD (license included).	\$ 9,799
AXIS F34 MAIN UNIT	0778-001	AXIS F34 Main Unit. 4-channel main unit to be used with any of AXIS F Sensor Units. Supports 1080p in 15/12.5 fps or 720p in full frame rate. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Supports edge storage through NAS or SD cards (optional). Two SD card slots. Power over Ethernet or 8-28 V DC input. Power supply not included.	\$ 391

AXIS F34 SURVEILLANCE SYSTEM	0779-004	AXIS F34 Surveillance System. Includes one AXIS F34 Main Unit, 4 x AXIS F1004 Sensor Units, 4 x AXIS F8214 Dome Accessory, 4 x AXIS F8224 Recessed Mount, 4 x AXIS F7315 Cable White 15 m (49 ft) for connecting sensor units to the main unit and 2 x AXIS Surveillance microSDXC card 64 GB. Comes with a power supply.	\$ 783
AXIS F41 MAIN UNIT	0658-001	AXIS F41 Main Unit. To be used with any of AXIS F Series Sensor Units. Supports full HDTV 1080p and WDR - Forensic Capture. Two way audio, 4 configurable I/Os with 12 V output and RS232. Supports Edge Storage through NAS or SD card (optional). PoE and 8-28 V DC support.	\$ 440
AXIS F44 MAIN UNIT	0659-001	AXIS F44 Main Unit. 4-channel main unit to be used with any of AXIS F Series Sensor Units. Supports 1080p in 15/12.5 fps or 720p in full frame rate. Two way audio, 4 configurable I/Os with 12 V output and RS232. Supports Edge Storage through NAS or SD cards (optional). Two SD card slots. PoE and 8-28 V DC support.	\$ 538
AXIS F1004 SENSOR UNIT	0765-001	AXIS F1004 Sensor Unit with a fixed lens. Provides HDTV 720p and 102° horizontal FOV. Pigtail for a detachable 8-m (26-ft.) cable for connecting to an AXIS F Main Unit. A flush ceiling/wall mount kit is included.	\$ 97
AXIS F1005-E SENSOR UNIT 3M	0675-001	AXIS F1005-E Sensor Unit with a 3 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fixed lens that provides 113° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	\$ 244
AXIS F1005-E SENSOR UNIT 12M	0676-001	AXIS F1005-E Sensor Unit with a 12 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fixed lens that provides 113° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	\$ 264
AXIS F1015 SENSOR UNIT 3M	0677-001	AXIS F1015 Sensor Unit with a 3 meter cable to the main unit. To be used with AXIS F Series Main Units. Vari-focal lens that provides 53° - 108° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	\$ 273

AXIS F1015 SENSOR UNIT 12M	0678-001	AXIS F1015 Sensor Unit with a 12 meter cable to the main unit. To be used with AXIS F Series Main Units. Vari-focal lens that provides 53° - 108° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	\$ 293
AXIS F1025 SENSOR UNIT 3M	0735-001	AXIS F1025 Sensor Unit with a 3 meter cable to the main unit. To be used with AXIS F Series Main Units. Pinhole lens that provides 92° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8202 Straight Mounting Bracket.	\$ 244
AXIS F1025 SENSOR UNIT 12M	0734-001	AXIS F1025 Sensor Unit with a 12 meter cable to the main unit. To be used with AXIS F Series Main Units. Pinhole lens that provides 92° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8202 Straight Mounting Bracket.	\$ 264
AXIS F1035-E SENSOR UNIT 3M	0737-001	AXIS F1035-E Sensor Unit with a 3 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fisheye lens that provides 194° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	\$ 244
AXIS F1035-E SENSOR UNIT 12M	0736-001	AXIS F1035-E Sensor Unit with a 12 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fisheye lens that provides 194° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	\$ 264
AXIS F4005 DOME SENSOR UNIT	0798-001	AXIS F4005 Dome Sensor Unit with a 12-meter (39-feet) cable to an AXIS F Series Main Unit. Recessed dome without a clear dome cover. Fixed lens that provides 113° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit.	\$ 273

AXIS F4005-E DOME SENSOR UNIT	0775-001	AXIS F4005-E Dome Sensor Unit with a 12-meter (39-foot) cable to an AXIS F Series Main Unit. Comes with a clear dome cover and damask at the back that makes it IK09 and IP66 rated. Fixed lens that provides 110° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit.	\$ 283
AXIS M3004-V	0516-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. MicroSD/microSDHC memory card slot for optional local video storage. Video motion detection and active tampering alarm. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	\$ 224
AXIS M3004-V SURVEILLANCE KIT	0516-041	Bundle with four units of AXIS M3004-V Fixed Dome Network Camera. The cameras feature 1 megapixel/ HDTV 720p resolution and MicroSD/MicroSDHC card slot. Includes a CD with AXIS Camera Companion video management software with support for up to 16 cameras. The cameras are powered using Power over Ethernet. Midspan and SD cards are not included.	\$ 881
AXIS M3014	0285-001	Ultra-discreet fixed dome camera for recessed mounting in drop ceilings. Fixed lens, progressive scan CMOS sensor. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. Video motion detection. Power over Ethernet. Midspan not included.	\$ 342
AXIS M3014 BULK 10PCS	0285-021	AXIS M3014 in 10-pack. Cannot be sold separately as single packs. No Midspans	\$ 3,370
AXIS M3005-V	0517-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. MicroSD/microSDHC memory card slot for optional local video storage. Video motion detection and active tampering alarm. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	\$ 293

AXIS M3006-V	0514-001	Compact, indoor fixed mini dome with dust- and vandal-resistant casing. Easy mounting on wall or ceiling. Fixed, 134° lens, and digital PTZ can be used as digital varifocal to set the angle of view. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps or 3 MP resolution at 20 fps. MicroSD/microSDHC memory card slot for optional local video storage. Video motion detection and active tampering alarm. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	\$ 440
AXIS M3007-P	0543-001	Ultra-discreet, smoke detector-like indoor fixed mini dome with tamper-resistant casing, offering 360°/180° panoramic views as well as quad and digital PTZ views. Multiple, individually configurable H.264 and Motion JPEG streams in up to 5MP resolution at 12 fps. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. The camera comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet for easy installation. Midspan not included.	\$ 538
AXIS M3007-PV	0515-001	Compact, indoor fixed mini dome with dust- and vandal-resistant casing, offering 360°/180° panoramic views as well as quad and digital PTZ views. Easy mounting on wall or ceiling. Multiple, individually configurable H.264 and Motion JPEG streams in up to 5MP resolution at 12 fps. MicroSD/microSDHC memory card slot for optional local video storage. Video motion detection and active tampering alarm. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	\$ 538
AXIS M3024-LVE	0535-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation. Fixed lens and built-in IR illumination. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included	\$ 538

AXIS M3025-VE	0536-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	\$ 538
AXIS M3026-VE	0547-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation. Fixed, 106° lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps or 3 MP resolution at 20 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	\$ 636
AXIS M3027-PVE	0556-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation, offering 360°/180° panoramic views as well as quad and digital PTZ views. Multiple, individually configurable H.264 and Motion JPEG streams in up to 5MP resolution at 12 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) cable with a male RJ-45 network connector and is powered using Power over Ethernet. Midspan not included.	\$ 734
AXIS M3037-PVE	0548-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation, offering 360°/270°/180° panoramic views as well as quad and digital PTZ views. Multiple, individually configurable H.264 and Motion JPEG streams in up to 5MP resolution at 12 fps. Two-way, echo-free audio communication with built-in microphone and speaker. SIP support for IP phone system integration. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) cable with a male RJ-45 network connector and is powered using Power over Ethernet. Midspan not included.	\$ 783

AXIS M3113-R	0330-001	Fixed dome camera with rugged design, adapted for mobile video surveillance. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Rugged RJ-45 network connector, Power over Ethernet. Includes lens tool, top cover tool and mounting adapters. Midspan not included.	\$ 440
AXIS M3113-R BULK 10PCS	0330-021	AXIS M3113-R in 10-pack/bulk. No midspans, no mounting adapters.	\$ 4,331
AXIS M3113-R BULK 50PCS	0330-031	AXIS M3113-R in 50-pack/bulk. No midspans, no mounting adapters.	\$ 21,608
AXIS M3113-R M12	0358-001	Fixed dome camera with rugged design, adapted for mobile video surveillance. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Rugged M12 network connector, Power over Ethernet. Includes lens tool, top cover tool and mounting adapters. Midspan not included.	\$ 440
AXIS M3113-R M12 BULK 10PCS	0358-021	AXIS M3113-R M12 in 10-pack/bulk. No midspans, no mounting adapters.	\$ 4,331
AXIS M3113-R M12 BULK 50PCS	0358-031	AXIS M3113-R M12 in 50-pack/bulk. No midspans, no mounting adapters.	\$ 21,608
AXIS M3114-R	0342-001	Fixed dome camera with rugged design, adapted for mobile video surveillance. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Rugged RJ-45 network connector, Power over Ethernet. Includes lens tool, top cover tool and mounting adapters. Midspan not included.	\$ 538
AXIS M3114-R BULK 10PCS	0342-021	AXIS M3114-R in 10-pack/bulk. No midspans, no mounting adapters.	\$ 5,291
AXIS M3114-R BULK 50PCS	0342-031	AXIS M3114-R in 50-pack/bulk. No midspans, no mounting adapters.	\$ 26,420

AXIS M3114-R M12	0359-001	Fixed dome camera with rugged design, adapted for mobile video surveillance. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Rugged M12 network connector, Power over Ethernet. Includes lens tool, top cover tool and mounting adapters. Midspan not included.	\$ 538
AXIS M3114-R M12 BULK 10PCS	0359-021	AXIS M3114-R M12 in 10-pack/bulk. No midspans, no mounting adapters.	\$ 5,291
AXIS M3114-R M12 BULK 50PCS	0359-031	AXIS M3114-R M12 in 50-pack/bulk. No midspans, no mounting adapters.	\$ 26,420
AXIS M3114-R M12 2MM	0448-001	Fixed dome camera with rugged design, adapted for mobile video surveillance. Fixed, wide angle lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Rugged M12 network connector, Power over Ethernet. Includes lens tool, top cover tool and mounting adapters. Midspan not included.	\$ 587
AXIS M3114-R M12 2MM BULK 10PCS	0448-021	AXIS M3114-R M12 2mm in 10-pack/bulk. No midspans, no mounting adapters.	\$ 5,752
AXIS M3114-R M12 2MM BULK 50PCS	0448-031	AXIS M3114-R M12 2mm in 50-pack/bulk. No midspans, no mounting adapters.	\$ 28,762
AXIS P3214-V	0612-001	Day/night fixed dome with a discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 2.8-10 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 489

AXIS P3214-VE	0613-001	Day/night fixed dome with an IK10 vandal-resistant outdoor casing. Varifocal 2.8-10 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Operation in -30°C to +50°C (-22°F to 122°F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and weather shield against sun, rain or snow.	\$ 636
AXIS P3215-V	0614-001	Day/night fixed dome with a discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max full HDTV 1080p/2MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 587
AXIS P3215-VE	0615-001	Day/night fixed dome with an IK10 vandal-resistant outdoor casing. Varifocal 3-10.5 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max full HDTV 1080p/2MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Operation in -30°C to +50°C (-22°F to 122°F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and weather shield against sun, rain or snow.	\$ 734

AXIS P3224-LV	0759-001	Day/night fixed dome with support for OptimizedIR with built-in adaptable IR illuminators, and WDR – Forensic Capture. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 2.8-10 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 60 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 587
AXIS P3224-LVE	0758-001	Day/night fixed dome with support for OptimizedIR with built-in adaptable IR illuminators, and WDR – Forensic Capture. IK10 vandal-resistant outdoor casing. Varifocal 2.8-10 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 60 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Operation in -30°C to +50°C (-22°F to 122°F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes.	\$ 734
AXIS P3225-LV	0761-001	Day/night fixed dome with support for OptimizedIR with built-in, adaptable IR illuminators, and WDR – Forensic Capture. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max full HDTV 1080p/2MP resolution at 60 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 685

AXIS P3225-LVE	0760-001	Day/night fixed dome with support for OptimizedIR with built-in adaptable IR illuminators, and WDR – Forensic Capture. IK10 vandal-resistant outdoor casing. Varifocal 3-10.5 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max full HDTV 1080p/2MP resolution at 60 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Operation in -30°C to +50°C (-22°F to 122°F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes.	\$ 832
AXIS P3304	0352-001	Fixed dome with discreet and tamper-resistant casing. Varifocal 2.8-10 mm lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone, and audio detection. I/O for alarm/event handling. Power over Ethernet. Power supply not included.	\$ 587
AXIS P3304 BULK 10PCS	0352-021	AXIS P3304 in 10-pack. Cannot be sold separately as single packs. No power supplies. Wall screws and plugs removed.	\$ 5,771
AXIS P3354 12MM	0467-001	Light-sensitive, day/night fixed dome with Lightfinder in a discreet, tamper-resistant indoor casing. Varifocal 3.3-12 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	\$ 587

AXIS P3354 6MM	0465-001	Light-sensitive, day/night fixed dome with Lightfinder in a discreet, tamper-resistant indoor casing. Varifocal 2.5-6 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	\$ 587
AXIS P3364-V 12MM	0471-001	Light-sensitive, day/night fixed dome with Lightfinder in a discreet, vandal-resistant indoor casing. Varifocal 3.3-12 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	\$ 685
AXIS P3364-V 6MM	0481-001	Light-sensitive, day/night fixed dome with Lightfinder in a discreet, vandal-resistant indoor casing. Varifocal 2.5-6 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	\$ 685

AXIS P3364-LV 12MM	0486-001	Light-sensitive, day/night fixed dome in a discreet, vandal-resistant indoor casing. Built-in, automatically or manually adjustable IR illumination. Varifocal 3.3-12 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included.	\$ 783
AXIS P3364-LV 6MM	0485-001	Light-sensitive, day/night fixed dome in a discreet, vandal-resistant indoor casing. Built-in, automatically or manually adjustable IR illumination. Varifocal 2.5-6 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included.	\$ 783
AXIS P3384-V	0511-001	Day/night fixed dome with support for WDR – dynamic capture in a discreet, vandal-resistant indoor casing. Varifocal 3-9 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. Light sensitivity with Lightfinder. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	\$ 881

AXIS P3364-VE 12MM	0484-001	Light-sensitive, day/night fixed dome with Lightfinder in a vandal-resistant, outdoor casing. Varifocal 3.3-12 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Operation in -40°C to 55°C (-40°F to 131°F) powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m (16 ft.) Ethernet cable with mounted gasket.	\$ 881
AXIS P3364-VE 6MM	0482-001	Light-sensitive, day/night fixed dome with Lightfinder in a vandal-resistant, outdoor casing. Varifocal 2.5-6 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Operation in -40°C to 55°C (-40°F to 131°F) powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m (16 ft.) Ethernet cable with mounted gasket.	\$ 881
AXIS P3364-LVE 12MM	0473-001	Light-sensitive, day/night fixed dome in a vandal-resistant, outdoor casing. Built-in, automatically or manually adjustable IR illumination. Varifocal 3.3-12 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes 5m Ethernet cable with mounted gasket.	\$ 979

AXIS P3364-LVE 6MM	0476-001	Light-sensitive, day/night fixed dome in a vandal-resistant, outdoor casing. Built-in, automatically or manually adjustable IR illumination. Varifocal 2.5-6 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes 5m Ethernet cable with mounted gasket.	\$ 979
AXIS P3384-VE	0512-001	Day/night fixed dome with support for WDR – dynamic capture in a vandal-resistant outdoor casing. Varifocal 3-9 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. Light sensitivity with Lightfinder. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Operation in -40°C to 55°C (-40°F to 131°F) powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m (16 ft.) Ethernet cable with mounted gasket.	\$ 1,077
AXIS P3346	0369-001	3 MP, day/night fixed dome with discreet, tamper-resistant indoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 3MP resolution at 20 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	\$ 940

AXIS P3346-V	0370-001	3MP, day/night fixed dome with discreet, vandal-resistant indoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 3MP resolution at 20 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	\$ 979
AXIS P3346-VE	0371-001	3MP, day/night fixed dome with vandal-resistant, IP66-rated outdoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 3MP resolution at 20 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m Ethernet cable with mounted gasket.	\$ 1,136
AXIS P3365-V	0586-001	Day/night fixed dome with discreet, vandal-resistant indoor casing. Varifocal 3-9 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max full HDTV 1080p/2MP resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	\$ 783

AXIS P3365-VE	0587-001	Day/night fixed dome with vandal-resistant, IP66-rated outdoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max full HDTV 1080p / 2MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m Ethernet cable with mounted gasket.	\$ 979
AXIS P3367-V	0406-001	5MP, day/night, fixed dome with discreet, vandal-resistant indoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	\$ 979
AXIS P3367-VE	0407-001	5MP, day/night, fixed dome with vandal-resistant, IP66-rated outdoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m Ethernet cable with mounted gasket.	\$ 1,175

AXIS P3904-R	0640-001	Fixed dome mobile surveillance camera with rugged design. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max 720p resolution at 30/25 fps. Video motion detection and active tampering alarm. Male RJ-45 network connector, Power over Ethernet. microSD card slot for Edge storage support. Includes lens tool and top cover tool. Midspan not included.	\$ 440
AXIS P3904-R BULK 10 PCS	0640-021	AXIS P3904-R (RJ45) in 10-pack/bulk. No midspans or mounting adapters included.	\$ 4,180
AXIS P3904-R BULK 50 PCS	0640-031	AXIS P3904-R (RJ45) in 50-pack/bulk. No midspans or mounting adapters included.	\$ 20,873
AXIS P3904-R M12	0638-001	Fixed dome mobile surveillance camera with rugged design. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max 720p resolution at 30/25 fps. Video motion detection and active tampering alarm. M12 network connector, Power over Ethernet. microSD card slot for Edge storage support. Includes lens tool and top cover tool. Midspan not included.	\$ 440
AXIS P3904-R M12 BULK 10 PCS	0638-021	AXIS P3904-R (M12) in 10-pack/bulk. No midspans or mounting adapters included.	\$ 4,180
AXIS P3904-R M12 BULK 50 PCS	0638-031	AXIS P3904-R (M12) in 50-pack/bulk. No midspans or mounting adapters included.	\$ 20,873
AXIS P3905-R	0641-001	Fixed dome mobile surveillance camera with rugged design. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max 1080p resolution at 30/25 fps. Video motion detection and active tampering alarm. Male RJ-45 network connector, Power over Ethernet. microSD card slot for Edge storage support. Includes lens tool and top cover tool. Midspan not included.	\$ 538
AXIS P3905-R BULK 10 PCS	0641-021	AXIS P3905-R (RJ-45) in 10-pack/bulk. No midspans or mounting adapters included.	\$ 5,111
AXIS P3905-R BULK 50 PCS	0641-031	AXIS P3905-R (RJ-45) in 50-pack/bulk. No midspans or mounting adapters included.	\$ 25,479
AXIS P3905-R M12	0639-001	Fixed dome mobile surveillance camera with rugged design. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max 1080p resolution at 30/25 fps. Video motion detection and active tampering alarm. M12 network connector, Power over Ethernet. microSD card slot for Edge storage support. Includes lens tool and top cover tool. Midspan not included.	\$ 538

AXIS P3905-R M12 BULK 10 PCS	0639-021	AXIS P3905-R (M12) in 10-pack/bulk. No midspans or mounting adapters included.	\$ 5,111
AXIS P3905-R M12 BULK 50 PCS	0639-031	AXIS P3905-R (M12) in 50-pack/bulk. No midspans or mounting adapters included.	\$ 25,479
AXIS P3915-R	0643-001	Fixed dome mobile surveillance camera with rugged design. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max 1080p resolution at 30/25 fps. Video motion detection and active tampering alarm. Male RJ-45 network connector, Power over Ethernet. Audio-in and I/O. microSD card slot for Edge storage support. Includes lens tool and top cover tool. Midspan not included.	\$ 587
AXIS P3915-R BULK 10 PCS	0643-021	AXIS P3915-R (RJ-45) in 10-pack/bulk. No midspans or mounting adapters included.	\$ 5,576
AXIS P3915-R BULK 50 PCS	0643-031	AXIS P3915-R (RJ-45) in 50-pack/bulk. No midspans or mounting adapters included.	\$ 27,831
AXIS P3915-R M12	0642-001	Fixed dome mobile surveillance camera with rugged design. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max 1080p resolution at 30/25 fps. Video motion detection and active tampering alarm. M12 network connector, Power over Ethernet. Audio-in and I/O. microSD card slot for Edge storage support. Includes lens tool and top cover tool. Midspan not included.	\$ 587
AXIS P3915-R M12 BULK 10 PCS	0642-021	AXIS P3915-R (M12) in 10-pack/bulk. No midspans or mounting adapters included.	\$ 5,576
AXIS P3915-R M12 BULK 50 PCS	0642-031	AXIS P3915-R (M12) in 50-pack/bulk. No midspans or mounting adapters included.	\$ 27,831
AXIS P3905-RE	0662-001	Fixed dome mobile surveillance camera for outdoors use on buses, trams, trucks and emergency vehicles. IP69K and IK09 rated. Fixed 6 mm lens providing 55° horizontal FOV. Flat, discreet and tamper-resistant casing. Supports H.264 and Motion JPEG streams; max 1080p resolution at 30/25 fps. Video motion detection and active tampering alarm. Male RJ-45 network connector, Power over Ethernet. microSD card slot for Edge storage support. Includes lens tool and top cover tool.	\$ 636

AXIS P3905-RE BULK 10PCS	0662-021	Fixed dome mobile surveillance camera for outdoors use on buses, trams, trucks and emergency vehicles. IP69K and IK09 rated. Fixed 6 mm lens providing 55° horizontal FOV. Flat, discreet and tamper-resistant casing. Supports H.264 and Motion JPEG streams; max 1080p resolution at 30/25 fps. Video motion detection and active tampering alarm. Male RJ-45 network connector, Power over Ethernet. microSD card slot for Edge storage support. Includes lens tool and top cover tool. 10 PCS.	\$ 6,173
AXIS P3905-RE M12	0663-001	Fixed dome mobile surveillance camera for outdoors use on buses, trams, trucks and emergency vehicles. IP69K and IK09 rated. Fixed 6 mm lens providing 55° horizontal FOV. Flat, discreet and tamper-resistant casing. Supports H.264 and Motion JPEG streams; max 1080p resolution at 30/25 fps. Video motion detection and active tampering alarm. M12 network connector, Power over Ethernet. microSD card slot for Edge storage support. Includes lens tool and top cover tool.	\$ 636
AXIS P3905-RE M12 BULK 10PCS	0663-021	Fixed dome mobile surveillance camera for outdoors use on buses, trams, trucks and emergency vehicles. IP69K and IK09 rated. Fixed 6 mm lens providing 55° horizontal FOV. Flat, discreet and tamper-resistant casing. Supports H.264 and Motion JPEG streams; max 1080p resolution at 30/25 fps. Video motion detection and active tampering alarm. M12 network connector, Power over Ethernet. microSD card slot for Edge storage support. Includes lens tool and top cover tool. 10 PCS.	\$ 6,173
AXIS Q3505-V 9MM	0616-001	Day/night fixed dome with support for WDR – Forensic Capture in a discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 3-9 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution at up to 60 fps. Electronic image stabilization. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 979

AXIS Q3505-V 22MM	0617-001	Day/night fixed dome with support for WDR – Forensic Capture in a discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution at up to 60 fps. Electronic image stabilization. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 1,077
AXIS Q3505-VE 9MM	0618-001	Day/night fixed dome with support for WDR – Forensic Capture in an IK10+ vandal-resistant outdoor casing. Varifocal 3-9 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution at up to 60 fps. Electronic image stabilization. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Operation in wide temperature range powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and weather shield against sun, rain or snow.	\$ 1,126
AXIS Q3505-VE 22MM	0619-001	Day/night fixed dome with support for WDR – Forensic Capture in an IK10+ vandal-resistant outdoor casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution at up to 60 fps. Electronic image stabilization. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Operation in wide temperature range powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and weather shield against sun, rain or snow.	\$ 1,224

AXIS Q3709-PVE	0664-001	Multi-sensor, day/night fixed dome in an IK10 vandal-resistant outdoor casing. Fixed focal, multi-megapixel lenses, focused from factory. Multiple, individually configurable H.264 and Motion JPEG streams; high-quality 4K video in 30 fps from each of 3 sensors and up to 33 MP resolution in total, together providing a 180° view. Video motion detection and active tampering alarm. Operation in wide temperature range powered by standard Power over Ethernet Plus. Midspan not included. Designed for pendant or wall mount arm with same bayonet joint interface as Axis' PTZ domes. Includes weather shield against sun, rain or snow, easily repaintable to blend in with the environment.	\$ 2,351
AXIS Q8414-LVS METAL	0709-001	AXIS Q8414-LVS Network Camera Metal is a brushed stainless steel indoor corner camera with an anti-grip/anti-ligature design to prevent self-harm. Ideal for correctional facilities and psychiatric wards. It supports IK10+ 50 joules impact rating. It is IP66- and NEMA 4X-rated for easy and safe cleaning. Superb images day and night with Lightfinder technology and has built-in invisible IR LED (940 nm). It delivers HDTV 720p or 1.3 Megapixel video, supporting a lens with: P-Iris, varifocal 2.5–6 mm, 105°–49° horizontal angle of view, F1.2. It offers 3 masks and I/O ports. Built-in surface mounted high quality microphone.	\$ 1,273
AXIS Q8414-LVS WHITE	0710-001	AXIS Q8414-LVS Network Camera White is a powder coated stainless steel indoor corner camera with an anti-grip/anti-ligature design to prevent self-harm. Ideal for correctional facilities and psychiatric wards. It supports IK10+ 50 joules impact rating. It is IP66- and NEMA 4X-rated for easy and safe cleaning. Superb images day and night with Lightfinder technology and has built-in invisible IR LED (940 nm). It delivers HDTV 720p or 1.3 Megapixel video, supporting a lens with: P-Iris, varifocal 2.5–6 mm, 105°–49° horizontal angle of view, F1.2. It offers 3 masks and I/O ports. Built-in surface mounted high quality microphone.	\$ 1,273

AXIS 214 PTZ 60HZ	0246-004	Pan/tilt/zoom (x18) camera. Auto-iris, automatic day/night, and auto-focus zoom lens. Up to 4CIF resolution at 30 fps frame rate. Simultaneous MPEG-4 and Motion JPEG. I/O for alarm/event handling. Two-way Audio full duplex. Includes ceiling mount kit and power supply.	\$ 1,273
AXIS Q8665-E 24V AC	0715-001	High speed and precision PT-head design PTZ camera with integrated wiper. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 100°/s, tilt speed: 0.02°/s to 40°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 24V AC.	\$ 4,899
AXIS Q8665-E 120V AC	0717-001	High speed and precision PT-head design PTZ camera with integrated wiper. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 100°/s, tilt speed: 0.02°/s to 40°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 120V AC.	\$ 4,899
AXIS Q8665-LE 24V AC	0718-001	High precision PT-head design PTZ camera with integrated wiper and IR illuminators enabling a viewing range in darkness up to 150m. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 40°/s, tilt speed: 0.02°/s to 30°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 24V AC.	\$ 5,879
AXIS Q8665-LE 120V AC	0720-001	High precision PT-head design PTZ camera with integrated wiper and IR illuminators enabling a viewing range in darkness up to 150m. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 40°/s, tilt speed: 0.02°/s to 30°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). External power supply with power input 120V AC and integrated light sensor for IR illuminator control included.	\$ 6,369

AXIS Q8631-E 24V AC 35MM 30 FPS	0725-001	High speed and precision PT-head design thermal PT camera with 384x288 thermal imaging resolution. Pan speed: 0.02°/s to 100°/s, tilt speed: 0.02°/s to 40°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 24V AC.	\$ 6,859
AXIS Q8631-E 120V AC 35MM 30 FPS	0727-001	High speed and precision PT-head design thermal PT camera with 384x288 thermal imaging resolution. Pan speed: 0.02°/s to 100°/s, tilt speed: 0.02°/s to 40°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 120V AC.	\$ 6,859
AXIS Q8632-E 120V AC 35MM 30 FPS	0733-001	High speed and precision PT-head design thermal PT camera with 640x480 thermal imaging resolution. Pan speed: 0.02°/s to 100°/s, tilt speed: 0.02°/s to 40°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 120V AC.	\$ 10,779
AXIS Q8632-E 24V AC 35MM 30 FPS	0731-001	High speed and precision PT-head design thermal PT camera with 640x480 thermal imaging resolution. Pan speed: 0.02°/s to 100°/s, tilt speed: 0.02°/s to 40°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 24V AC.	\$ 10,779
AXIS M5013	0398-001	Ceiling-mount mini PTZ dome camera with SVGA resolution and 3x digital zoom. 800x600 @ 30fps in H.264 and Motion JPEG. IP51 protection against dust and water. Only PoE, midspan not included. Hard and soft ceiling mounting brackets included.	\$ 489
AXIS M5013-V	0552-001	Vandal resistant IP66- and IK10-rated. Hard ceiling-mount PTZ dome camera with SVGA resolution and 3x digital zoom. 800x600 @ 30fps in H.264 and Motion JPEG. Only PoE, midspan not included.	\$ 587
AXIS M5014	0399-001	Ceiling-mount mini PTZ dome camera with HDTV 720p resolution, 16:9 format and 3x digital zoom. 1280x720 @ 30fps in H.264 and Motion JPEG. IP51 protection against dust and water. Only PoE, midspan not included. Hard and soft ceiling mounting brackets included.	\$ 587

AXIS M5014-V	0553-001	Vandal resistant IP66- and IK10-rated. Hard ceiling-mount PTZ dome camera with HDTV 720p resolution and 3x digital zoom. 1280x720 @ 30fps in H.264 and Motion JPEG. Only PoE, midspan not included.	\$ 685
AXIS P5414-E 60HZ	0588-001	Intelligent Direct Drive PTZ camera with HDTV 720p, day/night and 18x zoom, designed for mounting on a wall or building. No extra bracket are needed, build in junction box. Audio In/Out, full size SD card, 24 V DC, 4 configurable I/Os and Ethernet connector with PoE. Repaintable sunshield covering the entire unit. Power supply not included.	\$ 1,567
AXIS P5415-E 60HZ	0589-001	Intelligent Direct Drive PTZ camera with HDTV 1080p, day/night and 18x zoom, designed for mounting on a wall or building. No extra bracket are needed, build in junction box. Audio In/Out, full size SD card, 24 V DC, 4 configurable I/Os and Ethernet connector with PoE. Repaintable sunshield covering the entire unit. Power supply not included.	\$ 1,959
AXIS P5512 60HZ	0409-001	Compact pan/tilt/zoom (12x) camera including auto-iris, automatic day/night, and autofocus zoom lens. Up to 4CIF resolution at 30 fps frame rate. Simultaneous H.264 and Motion JPEG, standard IEEE 802.3af PoE (midspan not included), mounting kit for hard and drop ceiling and transparent cover smoked and clear. I/O connections for alarm/event handling. Two-way, full duplex audio requires multi connection cable (not included)	\$ 1,077
AXIS P5512-E 60HZ	0411-001	Outdoor, IP66-rated pan/tilt/zoom (12x) camera including auto-iris, automatic day/night, and autofocus zoom lens. Up to 4CIF resolution at 30 fps. Simultaneous H.264 and Motion JPEG. Power over Ethernet IEEE 802.3af, (midspan not included), clear and smoked dome bubble included. Brackets AXIS T91A are sold separately.	\$ 1,469
AXIS P5514 60HZ	0769-001	Compact PTZ camera, 360° pan with auto-flip, HDTV camera including 12x optical zoom, auto-iris, automatic day/night, and autofocus zoom lens. Up to 720P (1280x720) resolution at 60 fps frame rate. Simultaneous H.264 and Motion JPEG, standard IEEE 802.3af PoE (midspan not included), mounting kit for hard and drop ceiling, smoked and clear transparent cover. IP51 protection SD-card slot, 4 I/O connections for alarm/event handling. Two-way, full duplex audio requires multi connection cable (not included)	\$ 979

AXIS P5514-E 60HZ	0771-001	Compact outdoor PTZ camera, 360° pan with auto-flip, HDTV camera including 12x optical zoom, auto-iris, automatic day/night, and autofocus zoom lens. Up to 720P (1280x720) resolution at 60 fps frame rate. Simultaneous H.264 and Motion JPEG, standard IEEE 802.3af PoE. SD-card slot, IP66, Advanced Gatekeeper. Midspan and mounting brackets are not included	\$ 1,175
AXIS P5515 60HZ	0770-001	Compact PTZ camera, 360° pan with auto-flip, HDTV camera including 12x optical zoom, auto-iris, automatic day/night, and autofocus zoom lens. Up to 1080P (1920x1080) resolution at 30 fps frame rate. Simultaneous H.264 and Motion JPEG, standard IEEE 802.3af PoE (midspan not included), mounting kit for hard and drop ceiling, smoked and clear transparent cover. IP51 protection, SD-card slot, 4 I/O connections for alarm/event handling. Two-way, full duplex audio requires multi connection cable (not included)	\$ 1,175
AXIS P5515-E 60HZ	0772-001	Compact outdoor PTZ camera, 360° pan with auto flip, HDTV camera including 12x optical zoom, auto-iris, automatic day/night, and autofocus zoom lens. Up to 1080P (1920x1080) resolution at 30 fps frame rate. Simultaneous H.264 and Motion JPEG, standard IEEE 802.3af PoE. SD-card slot, IP66, Advanced Gatekeeper. Midspan and mounting brackets are not included	\$ 1,371
AXIS P5522 60 Hz	0420-004	PTZ camera with 18x optical zoom, D1 resolution (720x480) and IP51 classification in H.264 and Motion JPEG, Day & Night. Two way audio, four I/O and external power with multi-connector cable (not included) Includes High PoE midspan, smoked and clear dome covers, and mounting kit for hard and drop ceilings.	\$ 1,469
AXIS P5522-E 60 Hz	0422-004	Outdoor PTZ camera with 18x zoom, D1 resolution (720x480) and IP66 classification in H.264 and Motion JPEG, Day & Night. Includes High PoE midspan, smoked and clear dome covers. Brackets are sold separately	\$ 1,861

AXIS P5532 60HZ	0310-004	PTZ camera with 29x optical zoom, D1 resolution (720x480) and IP51 classification. H.264 and Motion JPEG, Day & Night, WDR, EIS. Two way audio, four I/O and external power with multi-connector cable (not included) Includes High PoE midspan, smoked and clear dome covers, and mounting kit for hard and drop ceilings.	\$ 1,763
AXIS P5532-E 60HZ	0312-004	Outdoor ready PTZ camera with 29x optical zoom, D1 resolution (720x480), IP66 and NEMA 4X classification. H.264 and Motion JPEG, Day & Night, WDR, Electronic Imaging Stabilization. Includes High PoE midspan, smoked and clear dome covers. Mounting brackets are not included.	\$ 2,155
AXIS P5534 60HZ	0314-004	HDTV 720p compliant PTZ camera with 18x optical zoom for indoor use. HDTV 720p @ 30fps (1280x720) in H.264 and Motion JPEG, Day & Night, two-way audio, I/O, IP51. Two way audio, four I/O and external power with multi-connector cable (not included) Includes HiPoE midspan, smoked and clear dome covers and mounting kit for hard and drop ceilings	\$ 1,959
AXIS P5534-E 60HZ	0316-004	HDTV 720p compliant outdoor-ready, PTZ camera with 18x optical zoom. HDTV 720p @ 30fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper. Includes High PoE 30 W midspan, smoked and clear dome. Mounting brackets are not included.	\$ 2,351
AXIS P5544 60HZ	0443-004	PTZ dome camera with 360-degree panoramic view, 18x optical zoom for indoor use. HDTV 720p @ 25/30fps (1280x720) in H.264 and Motion JPEG, Day & Night, two-way audio, I/O, IP51. Includes PoE+ midspan, clear dome covers and mounting kit for hard and drop ceilings	\$ 2,939
AXIS P5624-E 60HZ	0671-001	PTZ camera with continues 360° pan for both indoor and outdoor with 18x optical zoom. HDTV 720p @ 30fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot, smoked and clear dome. Mounting brackets and Midspan are not included.	\$ 1,567

AXIS P5635-E 60HZ	0670-001	PTZ camera with continues 360° pan for both indoor and outdoor with 30x optical zoom. HDTV 1080p @30fps (1920x1080) in H.264 and Motion JPEG, Two-way audio, 4xI/O, 24V and PoE, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot. Mounting brackets, Midspan/Power supply and connector or cable for audio, I/O and 24V are not included.	\$ 1,959
AXIS Q6000-E 60HZ	0636-001	Outdoor-ready 360° situational awareness camera, comprising 4x2MP sensors, up to 4x720p @ 30fps (1280x720) in H.264 and Motion JPEG. Designed to be integrated with any AXIS Q60-E series camera for large area coverage and simultaneous zoomed-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q60-E.	\$ 1,567
AXIS Q6000-E 60HZ SOLO	0781-004	Outdoor-ready 360° situational awareness camera, comprising 4x2MP sensors, up to 4x720p @ 30fps (1280x720) in H.264 and Motion JPEG. Full size SD-card slot. It uses the same brackets as AXIS Q60-E. Can be used stand-alone or integrated with any AXIS Q60xx-E. AXIS T8133 midspan included	\$ 1,763
AXIS Q6042 60HZ	0558-004	IP52, PTZ dome camera with 36x optical zoom. WDR, EIS. Auto day/night functionality; min. illumination down to 0.5 lux in color and 0.008 in black/white. Continuous 360° rotation and 180° tilt with E-flip. Progressive scan, extended D1 resolution (752x480) @ 30 fps in H.264 and Motion JPEG. Shock detection, autotracking, tour recording. Full size SD slot. Two way audio, four I/Os and external power with multi-connector cable (not included). Includes High PoE midspan, smoked and clear dome covers, and mounting kits for hard and drop ceilings	\$ 2,400

AXIS Q6042-E 60HZ	0560-004	Outdoor-ready, IP66, IK10 and NEMA 4X classification, PTZ dome camera with 36x optical zoom. Arctic Temperature Control enables operation and start up from -50 °C to +50 °C (-58 °F to 122 °F). WDR, EIS. Auto day/night functionality; min. illumination down to 0.5 lux in color and 0.008 in black/white. Continuous 360° rotation and 220° tilt with E-flip. Progressive scan, extended D1 resolution (752x480) @ 30fps in H.264 and Motion JPEG. Shock detection, Autotracking, Active Gatekeeper, tour recording. Full size SD slot. Power through High PoE only. Includes clear transparent dome cover and High PoE midspan. No mounting bracket included (several different accessories available).	\$ 2,939
AXIS Q6042-C 60HZ	0562-001	Actively cooled, outdoor-ready high-speed PTZ dome camera with 36x optical zoom. IP66-, MIL-, IK10 and NEMA 4X-rated. Temperature range -20 °C to +75 °C. WDR, Active Gatekeeper, Tour recording and autotracking, EIS, Auto day/night mode down to 0.5 lux in color and 0.008 lux in night mode. Continuous 360° rotation and 220° tilt with E-flip. Progressive scan, Extended D1 resolution (752x480) @ 30 fps in H.264 and Motion JPEG. Including 5 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 12 V in. Power supply and brackets are not included. (several different accessories available).	\$ 3,429
AXIS Q6042-S 60HZ	0579-001	Stainless steel, (SS-316L) pressurized (5psi) High performance PTZ dome camera with 36x optical zoom. with IP66, IK10 and NEMA 4X classification. WDR, EIS. Auto day/night functionality; min. illumination down to 0.5 lux in color and 0.008 in black/white. Continuous 360° rotation and 220° tilt with E-flip. Progressive scan, extended D1 resolution (752x480) @ 30 fps in H.264 and Motion JPEG. Shock detection, Autotracking, Active Gatekeeper, tour recording. Full size SD slot. Including 7 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 12 V in. Mounting brackets and power adapter are not included (several different accessories available).	\$ 5,389

AXIS Q6044 60HZ	0570-004	HDTV 720p compliant, high-speed PTZ dome camera with 30x optical zoom for indoor use. HDTV 720p @ 30 fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP52. Continuous 360° rotation and 220° tilt with E-flip. WDR, EIS, Automatic Defogging, shock detection. Full-size SD slot. Two-way audio, four I/Os and external power with multi-connector cable (not included). Includes High PoE midspan, smoked and clear dome covers, and mounting kits for hard and drop ceilings.	\$ 2,792
AXIS Q6044-E 60HZ	0572-004	HDTV 720p compliant, outdoor-ready, high-speed PTZ dome camera with 30x optical zoom. HDTV 720p @ 30fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP66, IK10 and NEMA 4X classification. Continuous 360° rotation and 220° tilt with E-flip. WDR, EIS, automatic defogging, shock detection, Arctic Temperature Control enables operation and start up from from -50 °C to +50 °C (-58 °F to 122 °F). Active Gatekeeper, tour recording and autotracking. Includes High PoE midspan and clear dome cover. Mounting brackets are not included (several different accessories available)	\$ 3,331
AXIS Q6044-E 60HZ BLACK < US >	0572-034	Only for special approved projects HDTV 720p compliant, outdoor-ready, high-speed PTZ dome camera with 30x optical zoom. HDTV 720p @ 30fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP66, IK10 and NEMA 4X classification. Continuous 360° rotation and 220° tilt with E-flip. WDR, EIS, automatic defogging, shock detection, Arctic Temperature Control enables operation and start up from from -50 °C to +50 °C (-58 °F to 122 °F). Active Gatekeeper, tour recording and autotracking. Includes High PoE midspan and clear dome cover. Mounting brackets are not included (several different accessories available)	\$ 3,331

AXIS Q6044-C 60HZ	0574-001	Actively cooled, outdoor-ready high-speed PTZ dome camera with 30x optical zoom. IP66-, MIL-, IK10 and NEMA 4X-rated. Temperature range -20 °C to +75 °C HDTV 720p compliant @ 30fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP66, IK10 and NEMA 4X classification. Continuous 360° rotation and 220° tilt with E-flip. WDR, EIS, automatic defogging, shock detection. Active Gatekeeper, tour recording and autotracking. Including 5 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 12 V in. Power supply and brackets are not included. (several different accessories available).	\$ 3,821
AXIS Q6044-S 60HZ	0581-001	Stainless steel, (SS-316L) pressurized (5psi) HDTV 720p compliant, outdoor-ready, high-speed PTZ dome camera with 30x optical zoom. HDTV 720p @ 30fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP66, IK10 and NEMA 4X classification. Continuous 360° rotation and 220° tilt with E-flip. WDR, EIS, automatic defogging, shock detection. Active Gatekeeper, tour recording and autotracking. Including 7 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 12 V in. Mounting brackets and power adapter are not included (several different accessories available).	\$ 5,683
AXIS Q6045 MkII 60HZ < US >	0692-004	HDTV 1080p compliant, high-speed PTZ dome camera with 32x optical zoom for indoor use. HDTV 1080p (1920x1080)@30fps 720p@60fps. Continuous 360° rotation and 220° tilt with E-flip. Day & Night, IP52. Shock detection, autotracking, tour recording and Active Gatekeeper. Two-way audio, I/O and external power with multi-connector cable (not included). Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection Includes High PoE midspan, smoked and clear dome covers, and mounting kits for hard and drop ceilings	\$ 2,988

<p>AXIS Q6045-E MkII 60HZ < US ></p>	<p>0694-004</p>	<p>Top performance HDTV 1080p compliant, outdoor-ready, IP66, IK09 and NEMA 4X-rated PTZ dome camera with 32x optical zoom. Arctic Temperature Control enables operation and start up from -50 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080)@30fps, 720P60fps. Shock detection, autotracking, tour recording and Active Gatekeeper. Power through High PoE only. Highlight compensation. Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan are included. Brackets are not included (several different accessories available).</p>	<p>\$ 3,527</p>
<p>AXIS Q6045-C Mk II 60HZ</p>	<p>0696-001</p>	<p>Actively cooled, outdoor-ready high-speed PTZ dome camera with 32x optical zoom. IP66-, MIL-, IK10 and NEMA 4X-rated. Temperature range -20 °C to +75 °C. Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080) @ 30 fps, 720p@60fps. Shock detection, autotracking, tour recording and Active Gatekeeper. Highlight compensation. Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection. Including 5 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 12 V in. Power supply and brackets are not included. (several different accessories available).</p>	<p>\$ 4,017</p>
<p>AXIS Q6045-S Mk II 60HZ</p>	<p>0698-001</p>	<p>Stainless steel, (SS-316L) pressurized (5psi) Top performance HDTV 1080p compliant, outdoor-ready, IP66, IK10 and NEMA 4X-rated PTZ dome camera with 32x optical zoom. Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080) @ 30 fps, 720@60 fps. Shock detection, autotracking, tour recording and Active Gatekeeper. Highlight compensation. Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection. Including 7 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 12 V in. Brackets and power adapter are not included (several different accessories available).</p>	<p>\$ 5,879</p>

AXIS Q6114-E 60HZ < US >	0650-004	Lightfinder HDTV PTZ for outdoor as well as indoor use. HDTV 720p resolution in 60fps with 30x zoom and top performance. Perfect image quality in all directions, without distortion. 130db WDR, EIS, automatic defog, Advanced gate keeper. With its compact size and repaintable surface, it will easily blend into the surroundings. Midspan included.	\$ 2,645
AXIS Q6115-E 60HZ < US >	0652-004	Top of the line PTZ with HDTV PTZ for outdoor as well as indoor use. HDTV 1080p resolution in 60fps with 30x zoom and top performance. Perfect image quality in all directions without distortion. 115dbWDR, EIS, automatic defog, Advanced gate keeper. With its compact size and repaintable surface, it will easily blend into the surroundings. Midspan included.	\$ 2,939
AXIS Q8721-E 35MM 30 fps	0489-001	IP66-rated outdoor-ready pan tilt network camera for visual and thermal imaging is comprised of an AXIS Q1755 visual 10x optical zoom- and autofocus camera that delivers video in HDTV 1080i or 720p and an AXIS Q1921 thermal camera with 35mm lens that delivers 384x288 resolution in 30 fps. Preset accuracy of 0.02° and continues pan 360° endless. Temp spec. -30 °C to 45 °C (-22 °F to 113 °F). Requires: Power supply AXIS Q872X-E and wall- or column mount bracket.	\$ 18,354
AXIS Q8721-E 60MM 30 fps	0491-001	IP66-rated outdoor-ready pan tilt network camera for visual and thermal imaging is comprised of an AXIS Q1755 visual 10x optical zoom- and autofocus camera that delivers video in HDTV 1080i or 720p and an AXIS Q1921 thermal camera with 60mm lens that delivers 384x288 resolution in 30 fps. Preset accuracy of 0.02° and continues pan 360° endless. Temp spec. -30 °C to 45 °C (-22 °F to 113 °F). Requires: Power supply AXIS Q872X-E and wall- or column mount bracket.	\$ 20,510

AXIS Q8722-E 35MM 30 fps	0493-001	IP66-rated outdoor-ready pan tilt network camera for visual and thermal imaging is comprised of an AXIS Q1755 visual 10x optical zoom- and autofocus camera that delivers video in HDTV 1080i or 720p and an AXIS Q1922 thermal camera with 35mm lens that delivers 640x480 resolution in 30 fps. Preset accuracy of 0.02° and continues pan 360° endless. Temp spec. -30 °C to 45 °C (-22 °F to 113 °F). Requires: AXIS Q872X-E Power Supply and AXIS Wall Bracket K or AXIS Column Bracket K.	\$ 22,764
AXIS Q8722-E 60MM 30 fps	0495-001	IP66-rated outdoor-ready pan tilt network camera for visual and thermal imaging is comprised of an AXIS Q1755 visual 10x optical zoom- and autofocus camera that delivers video in HDTV 1080i or 720p and an AXIS Q1922 thermal camera with 60mm lens that delivers 640x480 resolution in 30 fps. Preset accuracy of 0.02° and continues pan 360° endless. Temp spec. -30 °C to 45 °C (-22 °F to 113 °F). Requires: Power supply AXIS Q872X-E and wall- or column mount bracket.	\$ 24,920
AXIS V5914 60HZ < US >	0632-004	Generic PTZ camera with 30x zoom, autofocus and HDTV 720p resolution at 60/fps for live streaming of video and audio. "Video conference" design, smooth pan and tilt, WDR, EIS. HDMI, 3G-SDI, XLR-3 for studio connectivity. CD-audio quality in stereo. Compliance with SMPTE 296M Power supply and wall mount bracket are included.	\$ 1,959
AXIS V5915 60HZ < US >	0634-004	Generic PTZ camera with 30x zoom, autofocus and HDTV 1080p resolution at 60/fps for live streaming of video and audio. "Video conference" design, smooth pan and tilt, WDR, EIS. HDMI, 3G-SDI, XLR-3 for studio connectivity. CD-audio quality in stereo. Compliance with SMPTE 274M Power supply and wall mount bracket are included.	\$ 2,547
AXIS P7701	0319-004	1 channel network video decoder. Decodes H.264 and MPEG-4 Part 2 in max. D1 resolution at 30/25 (NTSC/PAL) fps and 720p in Motion JPEG. Decodes AAC, G726 and G.711 audio streams in mono. Supports video source sequencing. Power over Ethernet enabled. Includes power supply.	\$ 489

AXIS P7701 VIDEO DEC BB BULK 20PCS	0319-051	AXIS P7701 BARE BOARD in 20-pack. Cannot be sold separately as single packs. No power supplies.	\$ 9,780
AXIS P7701 VIDEO DECODER BARE BONE	0319-041	Bare board 1 channel video decoder. Decodes H.264 and MPEG-4 Part 2 in max. D1 resolution at 30/25 (NTSC/PAL) fps and 720p in Motion JPEG. Decodes AAC, G726 and G.711 audio streams in mono. Supports video source sequencing. Power over Ethernet enabled. No power supply.	\$ 489
AXIS M7001	0298-001	1-channel video encoder. Dual streaming in H.264 and Motion JPEG; max. D1 resolution at 30/25 fps. Video motion detection. Power over Ethernet (IEEE 802.3af) only. NO midspan	\$ 244
AXIS M7001 BULK 10PCS	0298-021	AXIS M7001 in 10-pack/bulk. Cannot be sold separately as single packs. NO midspans	\$ 2,440
AXIS M7011 Video Encoder	0764-001	Single channel video encoder with H.264 (High, Main and Base profile) and Motion JPEG support. Power over Ethernet (IEEE 802.3af). Edge storage using microSDHC card or NAS. AVHS and ACAP support. No midspan included.	\$ 195
AXIS M7011 BULK 10PCS	0764-021	10-pack of AXIS M7011 Video Encoder. Comes without midspan.	\$ 1,852
AXIS M7014 Video Encoder	0415-004	Four-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 15 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Power over Ethernet (IEEE 802.3af). Local storage using microSDHC card. PTZ support. Includes power supply.	\$ 293
AXIS M7014 VIDEO ENCODER BULK 10PCS	0415-021	AXIS M7014 in 10-pack. Power supply not included. Cannot be sold separately as single packs.	\$ 2,841
AXIS M7014 SURVEILLANCE KIT	0415-044	Bundle with 1 unit of AXIS M7014 Video Encoder and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 100 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	\$ 391

AXIS M7016 ACS KIT	0541-044	Bundle with 1 unit of AXIS M7016 Video Encoder and a 16-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 100 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	\$ 1,175
AXIS M7016 VIDEO ENCODER	0541-004	Sixteen-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Unit includes 4 x micro SD card slots for edge storage. PTZ support. Unit has 4 x ARTPEC chips and 4 x IP addresses. Includes power supply.	\$ 979
AXIS P7214 Video Encoder	0417-004	Four-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. Power over Ethernet (IEEE 802.3af). Local storage using microSDHC card. PTZ support. Includes power supply.	\$ 391
AXIS P7214 VIDEO ENCODER BULK 10PCS	0417-021	AXIS P7214 in 10-pack. Power supply not included. Cannot be sold separately as single packs.	\$ 3,792
AXIS P7214 VIDEO ENC BARE BONE	0417-031	Four-channel bare bone video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. Power over Ethernet (IEEE 802.3af). Local storage using microSDHC card. PTZ support. No power supply included.	\$ 391
AXIS P7214 SURVEILLANCE KIT	0417-044	Bundle with 1 unit of AXIS P7214 Video Encoder and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 100 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	\$ 489

AXIS P7224 Video Encoder Blade	0418-001	AXIS P7224: Four-channel video encoder blade. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. PTZ support. COMPATIBLE WITH AXIS Q7900 RACK AND AXIS 291 1U VIDEO SERVER RACK.	\$ 391
AXIS P7216 VIDEO ENCODER	0542-004	Sixteen-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. SFP slot for optional fiber connection and/or network redundancy. Unit includes 4 x micro SD card slots for edge storage. PTZ support. Unit has 4 x ARTPEC chips and 4 x IP addresses. Includes power supply.	\$ 1,273
AXIS P7216 ACS KIT	0542-044	Bundle with 1 unit of AXIS P7216 Video Encoder and a 16-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 100 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	\$ 1,469
AXIS P7224 VID ENC BLADE BULK 10PCS	0418-021	AXIS P7224 in 10-pack. Cannot be sold separately as single packs.	\$ 3,792
AXIS Q7401 VIDEO ENCODER	0288-004	1 channel video encoder. Multiple, individually configurable H.264 and Motion JPEG streams; max. D1 resolution at 30/25 fps. Video motion detection. Active tampering alarm. Two-way audio and audio detection. Power over Ethernet (IEEE 802.3af) with power out for the analog camera. SD/SDHC memory card slot for local storage.. Includes power supply.	\$ 391
AXIS Q7401 VIDEO ENCODER BARE BONE	0288-041	Bare board 1 channel video encoder. Multiple, individually configurable H.264 and Motion JPEG streams; max. D1 resolution at 30/25 fps. Video motion detection. Active tampering alarm. Two-way audio and audio detection. Power over Ethernet (IEEE 802.3af) with power out for the analog camera. SD/SDHC memory card slot for local storage.. No power supply.	\$ 391

AXIS Q7401 VIDEO ENCODER BARE BONE BULK 20PCS	0288-051	AXIS Q7401 BARE BONE in 20-pack. Cannot be sold separately as single packs. No power supplies.	\$ 7,820
AXIS Q7401 VIDEO ENCODER BULK 10PCS	0288-021	AXIS Q7401 in 10-pack. Power supply not included. Cannot be sold separately as single packs	\$ 3,910
AXIS Q7404 VIDEO ENCODER	0291-004	Four-channel video encoder. Multiple, individually configurable H.264 and Motion JPEG streams per channel;max. D1 resolution at 30/25 (NTSC/PAL) fps. Video motion detection. Active tampering alarm. Two-way audio and audio detection on one channel. PTZ support. Includes power supply.	\$ 881
AXIS Q7404 BULK 10PCS	0291-024	AXIS Q7404 in 10-pack. Cannot be sold separately as single packs. Power supplies included.	\$ 8,369
AXIS Q7411 VIDEO ENCODER	0518-004	Video Encoder with H.264 (Main and Base profile) and Motion JPEG support. Supports 60/50 frames per second. Coax PTZ Control, video motion detection, two-way audio, configurable I/O connectors and ACAP support. 8-28 VD and Power over Ethernet (IEEE 802.3af). Edge storage using microSDHC card or NAS.	\$ 391
AXIS Q7411 VIDEO ENCODER BULK 10PCS	0518-021	AXIS Q7411 in 10-pack. Power supply not included. Cannot be sold separately as single packs.	\$ 3,792
AXIS Q7414 VIDEO ENCODER BLADE	0354-001	Four channel video encoder blade. Multiple, individually configurable H.264 and Motion JPEG streams; max. D1 resolution at 30/25 fps per channel. Four bi-directional audio channels with AAC encoding. Video motion detection. Active tampering alarm. COMPATIBLE WITH AXIS Q7900 RACK AND AXIS 291 1U VIDEO SERVER RACK.	\$ 979
AXIS Q7414 VIDEO ENCODER BULK 10PCS	0354-021	AXIS Q7414 in 10-pack. Cannot be sold separately as single packs.	\$ 9,301

AXIS Q7424-R MKII VIDEO ENCODER	0742-001	Rugged Video Encoder with H.264 and Motion JPEG support. 1-4 video channels. Video motion detection. Two-way audio with audio detection. ACAP support on one channel. Ethernet port and SFP slot for fiber connection. Support for Power over Ethernet (IEEE 802.3af) and Power Supply (optional). Edge storage using SDHC card or NAS. PTZ support and configurable I/O connectors. AXIS Q7424-R MkII is an update to the original AXIS Q7424-R. The addition of 100 Mbps on the SFP slot is the only difference. The original product only has support for 1 Gbps.	\$ 881
AXIS Q7424-R MKII VID ENC BULK 10P	0742-021	Rugged Video Encoder with H.264 and Motion JPEG support. 1-4 video channels. Video motion detection. Two-way audio with audio detection. ACAP support on one channel. Ethernet port and SFP slot for fiber connection. Support for Power over Ethernet (IEEE 802.3af) and Power Supply (optional). Edge storage using SDHC card or NAS. PTZ support and configurable I/O connectors. AXIS Q7424-R MkII is an update to the original AXIS Q7424-R. The addition of 100 Mbps on the SFP slot is the only difference. The original product only has support for 1 Gbps. 10 PCS.	\$ 8,370
AXIS Q7436 VIDEO ENCODER BLADE	0584-001	6 channel video encoder blade. Multiple, individually configurable H.264 (Base, Main and High profile) and Motion JPEG streams; max. D1 resolution at 60/50 fps per channel. Video motion detection. Active tampering alarm. Coax PTZ Control (Coaxitron). Compatible with the following video encoder chassis:AXIS Q7920, AXIS Q7900 and AXIS 291 1U	\$ 1,175
AXIS Q7436 VIDEO ENCODER BLADE BULK 10 PCS	0584-021	AXIS Q7436 in 10-pack. Cannot be sold separately as single packs.	\$ 11,171
AXIS Q7436/Q7920 KIT	0656-004	14 x AXIS Q7436 Video Encoder Blade mounted in an AXIS Q7920 Video Encoder Chassis. Country specific power cable.	\$ 18,227
AXIS 291 1U VIDEO SERV RACK	0267-004	1U 19" rack unit with three expansions slots, compatible with all Axis Blade video servers. Universal built-in power supply. One 10/100/1000Base-T output.	\$ 391
AXIS 291 1U VIDEO SERVER RACK < GENERIC >	0267-001	1U 19" rack unit with three expansions slots, compatible with all Axis Blade video servers. Universal built-in power supply. One 10/100/1000Base-T output. No power cable.	\$ 391

AXIS Q7920 VIDEO ENCODER CHASSIS	0575-004	5 U rack-mount video encoder chassis, providing an expandable solution for migrating large-scale analog installations to network video. Holds up to 14 hot-swappable video encoder blades supporting up to 84 analog cameras.	\$ 2,547
AXIS A8004 JUNCTION BOX	5801-131	AXIS A8004 Junction box offers neat and easy recessed installations of the AXIS A8004-VE Network video door station. Multiple mounting and wiring options along with a robust steel construction makes it suitable for most situations and wall types.	\$ 68
AXIS A9801 SECURITY RELAY	5801-141	AXIS A9801 Security relay box offer an easy and cost efficient way to improve security for doors controlled by an Axis network video door station. The product bridges the connection between door station and door lock and is placed on the secure side of the door. If an intruder attempt to tamper with the door station to access the door lock wires, AXIS A9801 Security relay will cut the connection and ensure that the door remains securely locked.	\$ 97
AXIS A1001 Network Door Controller	0540-001	AXIS A1001 Network Door Controller is an open, non-proprietary platform for access management. The controller is installed by each door and data is automatically synchronized between the controllers in the system. The controller supports most Wiegand and RS 485 OSDP readers. The unit comes with a built-in software for basic access management for up to 33 controllers as well as an open API to meet the requirements for larger and more advanced installations. The plenum rated controller is designed for wall or ceiling mount indoors and supports Power over Ethernet IEEE 802.3af Class 3. It is fitted with 14 configurable input/outputs and 5 power outputs for door accessories including fault/tamper detection and support for Uninterruptible Power Supply (UPS).	\$ 587

AXIS A1001 BULK 10PCS Network Door Controller	0540-021	AXIS A1001 Network Door Controller is an open, non-proprietary platform for access management. The controller is installed by each door and data is automatically synchronized between the controllers in the system. The controller supports most Wiegand and RS 485 OSDP readers. The unit comes with a built-in software for basic access management for up to 33 controllers as well as an open API to meet the requirements for larger and more advanced installations. The plenum rated controller is designed for wall or ceiling mount indoors and supports Power over Ethernet IEEE 802.3af Class 3. It is fitted with 14 configurable input/outputs and 5 power outputs for door accessories including fault/tamper detection and support for Uninterruptible Power Supply (UPS).	\$ 5,879
AXIS A8004-VE	0673-001	AXIS A8004-VE Network Video Door Station is an open, IP-based door station for two-way communication, video and remote entry control. By combining exceptional audio capabilities, including a high performing solution for echo cancellation and noise suppression, with an integrated HDTV camera with WDR and excellent low-light performance, the unit offers reliable 24/7 identification and remote entry control also in the most demanding situations. Based on open IP standards and interfaces such as Onvif, PoE and SIP, AXIS A8004-VE Network Video Door Station offers great integration possibilities and is a perfect complement to any video surveillance system.	\$ 1,224
AXIS A4011-E READER	0745-001	AXIS A4011-E Reader is a generic touch-free reader with keypad and illuminated symbols. It is a perfect match to the Network Door Controller A1001. The reader is intended for both indoor and outdoor use and it supports most smart card formats with 13.56 MHz.	\$ 362
ACC CABLE I/O AUDIO 5M P3343-VE	5502-331	Audio and I/O extension cable for AXIS P33 Series. Includes 4 pin terminal connector 2.5mm Female to Male, 2 x stereo plug 3.5mm Male to Female. 5 meter.	\$ 38
ACC EXTENSION CABLE PS-H 1.8M	5500-141	1.8 meter extension Cable for PS-H and PS-L products	\$ 7

USB POWER CABLE 1M	5505-661	USB power cable to power our M10 cameras. Perfect to use with AXIS M1025 as PVM. Connect camera to a TV through HDMI and use this cable to the USB port on the TV to power the camera, no need for external power supply. DC plug 1.35x3.5mm. Length 1M (3.3 ft). White color.	\$ 14
AXIS P55/Q60 MULTI CONN CABLE 5M	5502-491	Multi-connector cable for power, audio and I/O. Used for Indoor AXIS P55-series and Indoor Q60-series PTZ Dome Network Camera.	\$ 107
AXIS Q603X-E CABLE RJ45 OUTDOOR 5M	5502-731	Outdoor CAT6 Ethernet cable. IP66 rated male push pull connector for AXIS Q603X-E and AXIS P55-E, IP20 rated male RJ45 connector for midspan. Length: 5 meters. Color: black.	\$ 77
AXIS Q603X-E CABLE RJ45 OUTDOOR 15M	5504-731	Outdoor CAT6 Ethernet cable. IP66 rated male push pull connector for AXIS Q603X-E and AXIS P55-E, IP20 rated male RJ45 connector for midspan. Length:15 meters. Color: black.	\$ 146
AXIS Q60XX-C MULTI CONNECT CABLE 12M	5504-651	Cable between AXIS Q60XX-C and connection box AXIS T8605. Length: 12m (39ft).	\$ 244
ACC Y/C TO BNC CABLE < US >	21832	Cabel adapter to connect a Y/C (S-Video) cable to the Axis 241S Video Server. Same as 21833 but for US	\$ 17
NETWORK CABLE COUPLER INDOOR	5503-771	Female/female RJ45 coupler. For indoor use. Perfect when you need to extend a pre-terminated cable.	\$ 11
NETWORK CABLE COUPLER INDOOR SLIM	5503-272	Female/female RJ45 coupler. Slim and compact size. For indoor use. Perfect when you need to extend a pre-terminated cable.	\$ 19
NETWORK CABLE COUPLER IP66	5503-431	Compact IP66-rated female/female RJ45 cable coupler. Perfect when you need to extend a pre-terminated outdoor cable.	\$ 28
ACC OUTDOOR ANTENNA KIT 211W	5500-311	External antenna for AXIS 211W. Includes 3 m cable.	\$ 126
GASKET A CABLE 3,5- 7MM 10PCS	5503-741	M20 Gasket for cable diameter 3,5mm to 7mm. 10 pcs.	\$ 9
GASKET B M20 CABLE 6-13MM 10PCS	5503-751	M20 Gasket for cable diameter 6-13mm, 10 pcs.	\$ 9
GASKET C M25 CABLE 8-17MM 10PCS	5503-791	M20 Gasket for cable 8-17mm, 10 pcs.	\$ 9
CABLE GLAND A M16 5PCS	5800-961	M16 cable gland for cable diameter of 4.5 to 10mm. IP68. 5 pcs.	\$ 19
CABLE GLAND A M20 5PCS	5503-761	M20 cable gland, 5 pcs.	\$ 9

GASKET C M20 10PCS	5505-941	This gasket is specially made for flexible and easy installation. By using the included CONNECTOR GUARD A over the RJ45 connector, you do not need to re-terminate the network cable which gives a much faster and more secure installation. Made for M20 holes and cables from 5 to 15mm in outer diameter. 10 pcs.	\$ 9
CABLE GASKET M20 3MM 10PCS	5506-421	M20 gasket for small cables like I/O and audio cables. 10 pcs	\$ 9
CABLE GLAND A M25 5PCS	5503-831	M25 Cable gland, 5 pcs.	\$ 19
CABLE GLAND M20x1.5 RJ45 5PCS	5503-951	M20 cable gland for RJ45. Ease of installation, no need of cutting the cable.	\$ 19
CABLE SEALING IP65 FOR Q8108-R	5502-711	Accessory cable sealing to meet IP65 rating for Q8108-R.	\$ 244
ACC LIGHTNING PROTECTOR 211W	5500-321	Lightning protector for AXIS 211W when used outdoors with external antenna	\$ 87
ACC MAINS ADAP PS-K TERM-CONN	5503-681	Power supply for AXIS P1311/43/44 and AXIS Q7401 as a spare part.	\$ 38
ACC MAINS ADAP PS-P T-C	5502-261	Power supply PS-P T-C for AXIS Q1755 and AXIS Q7404	\$ 38
AXIS T8007 PS24	5503-104	Indoor mains power supply. Output 24V DC 1.5A.	\$ 68
ACC MAINS ADAPTOR AXIS PS24	5000-001	24VAC power adapter for outdoor use. Output max 63VA.	\$ 146
POWER SUPPLY AXIS Q872X-E 120V	5503-461	IP66 rated power supply for AXIS Q872X-E with 120 V AC input.	\$ 371
POWER SUPPLY AXIS Q872X-E 230V	5503-451	IP66 rated power supply for AXIS Q872X-E with 230 V AC input.	\$ 371
AXIS T8003 PS57	5029-034	Power supply for the AXIS T8640 Coax Over Ethernet Adapter. If connected to the base end COAX adapter part, it powers up the connection, the device end unit and the PoE camera and thereby removes the need for a separate midspan. Can also be connected to the device end, to secure enough power (max 30W) to the connected PoE camera (COAX cable quality/long distance).	\$ 53
AXIS T8006 PS12	5030-064	Power supply with extended temperature specification -40°C to +75°C (-40°F to +167°F) providing 12 V DC to units such as AXIS T8604 and AXIS Q7424-R.	\$ 87
AXIS T8008 PS12	5503-661	Power supply for AXIS Q60XX-C series -40 to +75C (-40 to 167F). In 90-264V AC 47-63Hz. Out 12,5V DC 85W.	\$ 391
AXIS T8051 Power Converter AC/DC to DC	5505-051	AC/DC to DC power converter for AXIS Q35-VE, 24 V AC or 12/24 V DC input. Backbox designed to match perfectly with camera.	\$ 195
AXIS T8081 PS57 MODULE 1000W	5504-804	Power Supply module (1KW) for use with AXIS T8082 PS57 CHASSIS 2KW 1U	\$ 979

AXIS T8082 PS57 CHASSIS 2KW 1U	5504-844	19" rack power supply solution consisting of a power supply chassis (T8080), 2x1 KW power supply modules (AXIS T8081) and one power distribution board (T8088) for use with AXIS T8646 POE+ OVER COAX BLADE.	\$ 2,939
AXIS T8085 PS57 500W 1U	5504-864	Power supply 500W for use with AXIS T8646 POE+ OVER COAX BLADE in a 1U rack.	\$ 1,273
MAINS ADAPTER AXIS Q8108-R	5502-071	Indoor mains adapter for powering an AXIS Q8108-R when not installed in a vehicle	\$ 69
POWER SUPPLY DIN CP-D 12/2.1 25W	5505-731	DIN power supply. 12V DC, 2.1 A. For use in T98A to power cameras, media converters etc.	\$ 97
CONNECTOR M12 FEMALE 4P 10PCS	5502-141	Rugged, female D-coded M12 connector compatible with Connector M12 male 4P, 209FD-R M12 /209MFD-R M12. Field installable with screw-in contacts. 10 pcs	\$ 146
CONNECTOR M12 MALE 4P 10PCS	5502-131	Rugged, male D-coded M12 connector compatible with AXIS M31XX-R M12 and Connector M12 Female 4P . Field installable with screw-in contacts. 10 pcs	\$ 146
AXIS 10-PIN PUSH- PULL SYSTEM CONN	5506-251	10-pin system connector for power, audio and I/O.	\$ 38
AXIS T8414 INSTALLATION DISPLAY	5900-144	AXIS T8414 is a battery-powered, PoE enabled handheld device that displays live view from Axis cameras and encoders for easy angle of view- and focus setting. You can take snapshots and record/view video clips, make image settings and more. It can also show analog video via BNC input. Includes carrying case with sunshield, battery, mains charger, car charger, cable tester connector, protective rubber gasket, Ethernet cable and analog BNC cable.	\$ 636
AXIS T8414 POWER EXTENSION KIT	5504-831	A high capacity battery for AXIS T8414 Installation Display. By upgrading AXIS T8414 with the latest firmware, a camera using PoE 802.3af/802.3at Type 1 Class 3 can now be powered from the battery. Included in the kit is also a matching battery cover lid.	\$ 87
AXIS T90C10 FIXED DOME IR-LED	5024-101	IR-illuminator for AXIS P334X-VE cameras. 18-56 VDC input. Operating temperature -40 °C to 55 °C (-40 °F to 131 °F). IP66-, Nema 4X rated, vandal resistant. Premounted 5m power cable cable with gaskets.	\$ 342
AXIS T90C20 FIXED DOME IR-LED	5024-201	IR-illuminator for AXIS P334X-VE cameras. PoE IEEE802.3af compliant. Operating temperature -40 °C to 55 °C (-40 °F to 131 °F). IP66-, Nema 4X rated, vandal resistant. Premounted 5m network cable cable with gaskets.	\$ 342

AXIS T90A32 IR-LED 30-60 DEG	5013-321	IR LED illuminator for use with the Axis Day/Night network cameras. 850 nm semi-covert. Adjustable angle between 30 to 60 degrees. Range 53 meters in 60 degrees and 80 meters in 30 degrees. Includes power supply with photocell and wall / ceiling bracket. Input 100-240 VAC. Consumption 50 W. Cable length 2.5m. Outdoor	\$ 979
AXIS T90B15 W-LED	5505-481	White LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 10 m to 50 m (33 ft to 164 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50 °C to 50°C (-58 °F to 122 °F).	\$ 314
AXIS T90B20 IR-LED	5505-451	IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 20 m to 120 m (66 ft to 394 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F).	\$ 440
AXIS T90B25 W-LED	5505-491	White LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 15 m to 90 m (49 ft to 295 ft). Made of IK09 impact resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F).	\$ 440
AXIS T90B30 IR-LED	5505-461	IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 30 m to 220 m (98 ft to 722 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F).	\$ 783
AXIS T90B35 W-LED	5505-501	White LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 20 m to 150 m (66 ft to 492 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F).	\$ 783

AXIS T90B40 IR-LED	5505-471	Two panel IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°-140° beam angles. Beam distance ranges 45 m to 310 m (148 ft to 1010 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F).	\$ 1,567
AXIS WL LENS A 120 DEG	5505-671	Accessory lens providing 120° beam angle, beam distance 10 m (33 ft). Compatible with AXIS T90B15 W-LED.	\$ 25
AXIS WL LENS B 120 DEG	5505-681	Accessory lens providing 120° beam angle, beam distance is 15 m (49 ft). Compatible with AXIS T90B25 W-LED.	\$ 28
AXIS IR LENS B 120 DEG	5505-701	Accessory lens providing 120° beam angle, beam distance 20 m (66 ft). Compatible with AXIS T90B20 IR-LED.	\$ 28
AXIS WL LENS C 120 DEG	5505-691	Accessory lens providing 120° beam angle, beam distance 20 m (66 ft). Compatible with AXIS T90B35 W-LED.	\$ 33
AXIS IR LENS C 120 DEG	5505-711	Accessory lens compatible with AXIS T90B30 IR-LED providing 120° beam angle, beam distance 30 m (98 ft). Also compatible with AXIS T90B40 IR-LED (two lenses are required as the illuminator has two panels). The beam angle can be adjusted between 120° and 180°, with a beam distance stretching from 65 m to 45 m (213 ft to 148 ft). This sales part includes one lens.	\$ 33
AXIS T90B REMOTE CONTROL	5800-931	The remote control is compatible with all Axis T90B illuminators and provides the possibility to adjust settings of light intensity, photocell sensitivity and more conveniently from the ground level. No lift or ladder required. The remote control feature can be disabled after the installation is finalized to avoid tampering.	\$ 38
PT IR ILLUMINATOR KIT A	5503-441	Infra red illuminator kit compatible with AXIS Q87-E. Kit contents: One 50 degree and one 10 degree illuminator that together cover the field of view of the camera when zoomed in or out. Range aprox. 100 meters. IR mount brackets for the positioning unit.	\$ 1,645
AXIS CONVERSION LENS 0.3X	5507-301	Wide angle conversion lens for AXIS Q1755 and Q1775.	\$ 215
ACC LENS CONVERTER 0.5X FOR Q1755	5500-501	Super wide angle conversion lens for AXIS Q1755. Converts AXIS Q1755PTZ lens to 2.55mm -25.5mm	\$ 215
ACC LENS CONVERTER 2.2X FOR Q1755	5500-511	Super telephoto conversion lens for AXIS Q1755. 2.2X. Converts AXIS Q1755PTZ lens to 102mm. For use in full focal length.	\$ 244

AXIS M3004-V/05-V LENS M12 6MM	5503-651	Optional lens, 6mm for M3004-V/M3005-V	\$ 48
AXIS M3006-V LENS M12 2.0MM	5503-941	Optional lens for AXIS M3006-V, 2.0mm, HFOV: 105°. Including lens tool.	\$ 97
AXIS M3006-V LENS M12 2.8MM	5503-981	Optional lens for AXIS M3006-V, 2.8mm. Including lens tool.	\$ 77
AXIS M3025-VE LENS M12 6MM	5504-551	Optional lens for AXIS M3025-VE, 6mm. Including focus ring.	\$ 48
ACC LENS M12 MEGAPIXEL 16MM 10PCS	5502-161	Megapixel lens 16mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs	\$ 146
ACC LENS M12 MEGAPIXEL 2.8MM 10PCS	5502-101	Megapixel lens 2.8mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs	\$ 195
ACC LENS M12 MEGAPIXEL 3.6MM 10PCS	5502-151	Megapixel lens 3.6mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter 10pcs	\$ 146
ACC LENS M12 MEGAPIXEL 6MM 10PCS	5502-111	Megapixel lens 6mm lens with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter 10pcs	\$ 146
ACC LENS M12 2.8MM F2.0 10 PCS	5504-951	Megapixel lens 2.8 mm, F2.0 with M12 thread for AXIS P39-R Series that provides 115° horizontal FOV with these cameras. With IR filter. 10 pieces.	\$ 195
ACC LENS M12 6MM F1.6 10 PCS	5504-961	Megapixel lens 6 mm, F1.6 with M12 thread for AXIS P39-R Series that provides 52° horizontal FOV with these cameras. With IR filter. 10 pieces.	\$ 195
ACC LENS M12 8MM F1.6 10 PCS	5504-971	Megapixel lens 8 mm, F1.6 with M12 thread for AXIS P39-R Series that provides 40° horizontal FOV with these cameras. With IR filter. 10 pieces.	\$ 195
ACC LENS M12 3.6MM F2.0 10PCS	5506-011	Megapixel lens 3.6 mm, F2.0 with M12 thread for AXIS P39-R Series that provides 87° horizontal FOV with these cameras. With IR filter. 10 pieces. Can be used as a spare part for AXIS P39-R or as a wider FOV option for P3905-RE.	\$ 195
ACC LENS M12 MEGAPIXEL 6PCS	5506-431	2 pieces each of 2.8 mm (F2.0), 6 mm (F1.6) and 8 mm (F1.6) Megapixel lenses with M12 thread. For use with AXIS P39-R cameras. Includes lens tools.	\$ 146
ACC LENS M12 MEGAPIXEL 8MM 10PCS	5502-411	Megapixel lens 8mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs	\$ 146

LENS M12 MEGAPIXEL 10PCS	5502-421	Mixed pack of M12 Megapixel lenses. Focal length: 2.8mm, 3.6mm, 6mm, 8mm and 16mm for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs=2 pcs of each lens.	\$ 146
Theia Fixedfocal Megapixel 1.7MM	5502-451	Wideangle lens without barrel distortion. CS mount Fixedfocal Lens 1.7 mm DC-Iris for AXIS P1343 and AXIS P1344.	\$ 243
THEIA LENS CS VARIF 1.8-3MM DC-IRIS	5503-161	Barrel distortion corrected and IR corrected wideangle lens for cameras up to 5 mega pixel resolution. Compatible with e.g. AXIS M1114/-E, AXIS P1353/-E, P1354/-E, P1355/-E, P1357/-E, AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E.	\$ 293
LENS CS VF 2.2-6MM F1.3 DC-I MP	5502-751	Varifocal 2.2-6mm DC-Iris Megapixel Lens, F1.3, CS mount for AXIS M1113/4	\$ 146
LENS CS 2.4-6MM MANUAL IRIS	5503-181	Manual iris lens, varifocal 2.4-6MM compatible with AXIS M1103 and M1104.	\$ 77
LENS FUJINON CS 2.2- 6MM DC-IRIS B	5800-781	Varifocal IR-corrected lens with DC-Iris. Compatible with e.g. AXIS P1353/-E, P1354/-E, P1355/-E, P1357/-E, AXIS Q1602/-E, Q1604/-E.	\$ 146
Varifocal MegaPixel Lens 2.4-6mm	5500-871	CS mount Varifocal Megapixel Lens 2.4-6mm DC Iris for AXIS P1344 and AXIS 211M/223M. Includes CS mount ring for AXIS 223M.	\$ 195
LENS CS 16MM F1.8 MP	5502-741	Fixed Iris Megapixel Lens 16mm, F1.8, CS mount for AXIS M1103/4	\$ 48
ACC LENS CS 9-20MM F=1.6 P-IRIS 5MP	5502-801	Varifocal 5 Mega Pixel P-Iris Lens 9-20mm, F1.6, CS mount, IR-corrected, for AXIS P1347 and AXIS P1346 firmware release 5.20 (or later)	\$ 342
LENS CS VARIF 9- 40MM DC-IRIS D/N	5503-171	Varifocal IR-corrected lens for cameras up to 5 mega pixel resolution. Compatible with e.g. AXIS M1114/-E, P1354/-E, P1355/-E, P1357/-E, Q1602/-E, Q1604/-E.	\$ 264
LENS CS VARIF 9- 40MM P-IRIS D/N	5504-901	Varifocal IR-corrected P-iris tele lens compatible with AXIS P1355/-E, P1357/-E, AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E.	\$ 264
Varifocal MegaPixel Lens 5-50mm	5502-221	CS mount Varifocal Megapixel Lens 5-50mm DC Iris for AXIS P1344 and AXIS 211M.	\$ 244
LENS COMPUTAR CS 12.5-50MM DC-IRIS	5800-791	Varifocal IR-corrected lens with DC-Iris. Compatible with e.g. AXIS P1353/-E, P1354/-E. Axis Q1602/-E, Q1604/-E.	\$ 244
LENS COMPUTAR CS 12.5-50MM P-IRIS	5800-801	Varifocal IR-corrected lens with P-Iris. Compatible with e.g. AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E, AXIS P1355/-E, P1357/-E.	\$ 244
LENS CS VF 15-50MM F1.5 DC-I MP	5502-761	Varifocal Mega Pixel DC-Iris Lens 15-50mm, F1.5, CS mount, for AXIS M1113/14	\$ 195
LENS CS 15-50MM F1.5 DC-I MP D/N	5503-421	Varifocal Megapixel DC-Iris Lens 15-50mm, F1.5, CS mount, Day/Night for AXIS Q1602.	\$ 195

LENS FUJINON C CS 8-80MM DC	5506-991	Varifocal IR-corrected lens with DC-Iris. For use with both C-mount and CS-mount cameras thanks to the included adapter. Compatible with e.g. AXIS Q1635.	\$ 342
AXIS LENS CLOTH 10PCS	5502-661	Axis accessory lens cloth. 10 pack	\$ 38
AXIS LENS CLOTH 50PCS	5502-721	Axis accessory lens cloth. 50 pack	\$ 166
LENS TOOL AXIS M311X 4PCS	5502-771	Tool kit for simplifying adjustment of viewing direction and focus setting. Compatible with AXIS M311X (except 2mm lens version). Content: Lens tool and Opening tool 4 pcs of each.	\$ 24
YP3040 PAN-TILT MOTOR	5502-461	YP3040 PAN TILT MOTOR is a compact PT motor for use with AXIS Q1755 Network Cameras and AXIS Q19 Series Network Thermal Cameras. Indoor and outdoor use. IP66-rated. 24VAC input. Compatible with AXIS T92A Housing and AXIS T92E Housing. YP3040 Wall bracket required. AXIS PS24 recommended.	\$ 489
INSTALLATION KIT AXIS P55XX/T95A	5502-991	All required parts for installing an AXIS P553X into an AXIS T95A housing. Kit contents: Bracket, connector, I/O and audio cable, network cable and screws.	\$ 87
LENS TOOL KIT AXIS M311X 2MM 4PCS	5503-561	Tool kit for simplifying adjustment of viewing direction and focus setting. Compatible with AXIS M311X cameras with 2mm lens. Content: Lens tool and Opening tool 4 pcs of each.	\$ 24
LENS TOOLKIT P39XX-R 4 PCS	5506-441	Tool kit for simplifying adjustment of viewing direction and focus setting. Compatible with AXIS P39xx-R cameras with the standard lens and the 2.8 mm accessory lens. Content: Lens tool, Allen key and Opening tool. 4 pcs of each.	\$ 19
AXIS T8605 MEDIA CONVERTER SWITCH	5028-051	Original Media converter switch for AXIS Q60-C series. 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not included). Two I/O ports (only active when connected to an AXIS Q60-C camera) and a combined communication and powering port for the camera. Temp spec. -40 °C to 75 °C (-40 °F to 167 °F). 12 V DC power input. Shelf or DIN-rail mount	\$ 440
ELECTRICAL SAFETY KIT A 120VAC	5503-521	Electrical safety kit for AXIS T98A in countries where the mains power is 120 V DC. Included products: Surge protector class 2, Fuse/main switch, terminal blocks and an intrusion door switch.	\$ 195

AXIS CABINET LOCK A	5505-651	Door lock for AXIS T98A surveillance cabinet. Uses a generic key but it is possible to change locking cylinder to a unique key solution (not supplied from Axis)	\$ 58
AXIS DOOR SWITCH A	5503-841	Intrusion door switch for AXIS T98A, connection to I/O port.	\$ 28
AXIS DOME INTRUSION SWITCH B	5505-071	Intrusion switch for AXIS Q35-V and -VE as well as P33-VE cameras. Connects to camera I/O connector.	\$ 19
CORRIDOR FORMAT BRACKET A	5504-931	The corridor format bracket makes it possible to mount a camera rotated 90 degrees inside the AXIS T93F05 and AXIS T93F20 housings to enable a vertically oriented, "portrait"-shaped video stream from the camera. Integrated camera heater (only applicable when mounted in AXIS T93F20). Not for use with AXIS Q1635.	\$ 38
CORRIDOR FORMAT BRACKET B	5506-381	The corridor format bracket makes it possible to mount a camera rotated 90 degrees inside the AXIS T93F10 housing to enable a vertically oriented, "portrait"-shaped video stream from the camera. Integrated camera heater. Not for use with AXIS Q1635.	\$ 38
SURVEILLANCE STICKER ENG 10PCS	5502-811	Axis branded sticker showing a Camera. Text: Video surveillance in operation	\$ 8
SURVEILLANCE STICKER ENG 50PCS	5502-821	Axis branded sticker showing a Camera. Text: Video surveillance in operation	\$ 18
PL ADAPTER FLAT L GREY M311X 10 PCS	5503-071	Optional light grey plastic adapter for mounting AXIS M311X on flat surfaces. Used when the cable must enter from the side. 10 pack	\$ 28
AXIS T94D01S MT BRACKET FL WT 10PCS	5504-911	White plastic adapter for mounting AXIS P3904-R and AXIS P3905-R on flat surfaces. Does not fit with AXIS P3915-R. Used when the cable must enter from the side. 10 pack.	\$ 28
AXIS T94D02S MT BRACKET CU WT 10PCS	5504-921	White plastic adapter for mounting AXIS P3904-R, AXIS P3905-R and AXIS P3915-R on curved surfaces. 10 pack.	\$ 28
AXIS WEATHERSHIELD KIT C	5504-881	Heavy duty weathershield for wall mounted AXIS M3024-LVE/25-VE/26-VE and AXIS P32-VE fixed dome cameras.	\$ 33
AXIS RACK SLIDE RAILS A	5504-781	Rack slides for AXIS Q7920 Video Encoder Chassis	\$ 68
AXIS Q1765 FOOT CHASSIS	5506-091	Sparepart foot chassis for AXIS Q1765-LE and AXIS Q193X-E. Note. This sales part does not include the mounting bracket (5506-081 AXIS T94G01S Mounting plate)	\$ 38
AXIS Q1765-LE FRONT KIT	5801-101	Sparepart front window for AXIS Q1765-LE	\$ 28

MAINS CABLE ANGL C13-OPN 0.5M	5506-244	Angled C13 mains cable for use when limited space. Open ends for installation in terminal blocks etc. Use when installing midspan into AXIS T98A Surveillance cabinet.	\$ 14
AXIS T93G TOP COVER	5506-971	Spare part top part of the AXIS T93G housing including window.	\$ 48
AXIS T96B05 FRONT KIT 5 PCS	5506-851	Spare part window and window holder for AXIS T96B05 Outdoor Housing and AXIS P3905-RE. 5 Pcs. Includes screws.	\$ 166
AXIS WASHER KIT A	5505-921	Washer kit for spraying cleaning fluid on the windows of AXIS Q8631-E/Q8632-E and AXIS Q8665-E/Q8665-LE. The kit contains a 23 liter tank, pump for delivery up to 11m (36ft), tube, nozzle and mounting bracket for attaching the nozzle to the PT-head.	\$ 460
AXIS ADAPTER RJ45 MALE TO MALE	5506-891	Adapter for connecting Q6000-E to PTZ camera	\$ 15
AXIS BIRD CONTROL SPIKE 10P	5801-121	Bird control spikes made of flexible UV-resistant polymer preventing birds from landing on cameras or mounts. Each module has five spikes and can be mounted on flat or curved surfaces using the pre-mounted adhesive or cable ties (not included). The modules can be connected lengthwise and/or widthwise to cover a larger area. 10 pcs.	\$ 24
AXIS T8414 INSTALLATION DISPLAY	5900-144	AXIS T8414 is a battery-powered, PoE enabled handheld device that displays live view from Axis cameras and encoders for easy angle of view- and focus setting. You can take snapshots and record/view video clips, make image settings and more. It can also show analog video via BNC input. Includes carrying case with sunshield, battery, mains charger, car charger, cable tester connector, protective rubber gasket, Ethernet cable and analog BNC cable.	\$ 636
AXIS T8414 POWER EXTENSION KIT	5504-831	A high capacity battery for AXIS T8414 Installation Display. By upgrading AXIS T8414 with the latest firmware, a camera using PoE 802.3af/802.3at Type 1 Class 3 can now be powered from the battery. Included in the kit is also a matching battery cover lid.	\$ 87
ACC LENS CONVERTER 0.5X FOR Q1755	5500-501	Super wide angle conversion lens for AXIS Q1755. Converts AXIS Q1755PTZ lens to 2.55mm -25.5mm	\$ 215
ACC LENS CS 9-20MM F=1.6 P-IRIS 5MP	5502-801	Varifocal 5 Mega Pixel P-Iris Lens 9-20mm, F1.6, CS mount, IR-corrected, for AXIS P1347 and AXIS P1346 firmware release 5.20 (or later)	\$ 342

AXIS T91A21 STAND BLACK	5022-211	Metal stand for wall or hard ceiling mount. Compatible with all standard tripod thread cameras e.g. AXIS Q17/19 series and AXIS P13 series.	\$ 28
AXIS T91A21 STAND WHITE	5017-211	Metal stand for wall or hard ceiling mount. Compatible with all standard tripod thread cameras e.g. AXIS Q17/19 series and AXIS P13 series.	\$ 28
AXIS T8412/T8414 CARRYING CASE	5800-331	Sparepart carrying case for the AXIS T8412 and T8414 installation displays, with included sunshield, velcro wrist strap and lanyard.	\$ 28
AXIS T92A10 HOUSING	5015-101	Outdoor IP66 rated housing for AXIS 210/210A, 211/211A/211M/211W, 221/223M, Q1755 and P13 Series. Made of die-cast aluminum, the sunshield of ABS material. Includes UL certified 110VAC power supply, heater and wall bracket with internal cable channel. Built in 12VDC camera power supply. Only for US	\$ 293
AXIS T92A20 HOUSING	5015-204	Outdoor High PoE powered IP66 rated housing for AXIS 210/210A, 211/211A/211M/211W, 221/223M, Q1755 and P13 Series. Made of die-cast aluminum, the sunshield of ABS material. Also includes heater, wall bracket with internal cable channel and AXIS T8121 single port High PoE midspan. Country Specific	\$ 440
AXIS T92E05 PROTECTIVE HOUSING	0344-001	Protective camera housing for P13XX, M11XX, Q16XX and Q1755. Die cast aluminum casing and wallbracket, polycarbonate sunshield. The housing is IP66-, Nema 4X rated and IK10 impact-resistant. Sunshield, wallbracket and screwdriver included.	\$ 195
AXIS T92E20 OUTDOOR HOUSING	0433-001	Outdoor PoE camera housing with window-/camera heaters and fan for P13XX, M11XX, Q16XX and Q1755. Die cast aluminum casing and wallbracket, polycarbonate sunshield. The housing is IP66-, Nema 4X-, Vibration 4M3 rated and IK10 impact-resistant. Sunshield, wallbracket and screwdriver included.	\$ 322
AXIS T93E05 PROTECTIVE HOUSING	5502-871	The protective housing, AXIS T93E05, is compatible with the AXIS M11 series. Made of ASA polymer, it is IP66-rated and the operating temperature ranges between -20 °C to +50 °C (-4 °F to 122 °F). Wall bracket and sun shield are included.	\$ 118

AXIS T93F05 PROTECTIVE HOUSING	5900-261	Fixed box protective camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Compatible with AXIS P13 Series and AXIS Q16 Series. AXIS T94Q01A Wall mount included.	\$ 156
AXIS T93F10 OUTDOOR HOUSING 24VAC/12-24VDC	5900-271	Fixed box outdoor camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Powered by 24 V AC or 12-24 V DC. Temperature range -40C to -45C (-40F to 113F). Compatible with AXIS P13 Series and AXIS Q16 Series. AXIS T94Q01A Wall mount included.	\$ 234
AXIS T93F20 OUTDOOR HOUSING POE	5900-281	Fixed box outdoor camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Powered by PoE IEEE802.3af. Temperature range -40C to -45C (-40F to 113F). Compatible with AXIS P13 Series and AXIS Q16 Series. AXIS T94Q01A Wall mount included.	\$ 234
AXIS T93G05 PROTECTIVE HOUSING	5506-491	Tailor-made light weight IP66- and IK10-rated housing for AXIS M1124/M1125. Operating temperature: -20 °C to 50 °C (-4 °F to 122 °F). Material: IK10 impact-resistant polymer. Wallmount included.	\$ 117
AXIS SUNSHIELD A	5504-941	Accessory sunshield and weather protection for AXIS T93F Housing Series	\$ 33
AXIS T95A00 DOME HOUSING	5010-001	Dome housing for AXIS 213, 214, 215 PTZ Network Cameras and AXIS 231D+, 232D+, 233D Dome Network Cameras. Includes clear and smoked bubble, heater with fan, power supply for network cameras. 100-240 VAC input.	\$ 636
AXIS T95A10 DOME HOUSING	5010-101	Dome housing for AXIS 213, 214, 215 PTZ Network Cameras and AXIS 231D+, 232D+, 233D Dome Network Cameras. Includes clear and smoked bubble, heater with fan, power supply for network cameras 24VAC input. (Recommended power supply PS24)	\$ 587
AXIS T96A05-V DOME HOUSING BLACK	5032-061	Black vandal resistant housing for AXIS M50 series. IK10 and IP66 rated.	\$ 126
AXIS T96A05-V DOME HOUSING WHITE	5032-051	White vandal resistant housing for AXIS M50 series. IK10 and IP66 rated.	\$ 126
AXIS T96B05 OUTDOOR HOUSING	5505-911	Outdoor housing for AXIS P39-R cameras. Enables P39-R cameras to be mounted outside vehicles such as buses, trams, trucks and emergency vehicles. Includes lens tool and top cover tool.	\$ 97

AXIS INDOOR FIXED CEILING HOUSING	24888	AXIS Vandal Resistant Housings deliver maximum protection for Axis fixed network cameras in three different mounting configurations. Depending on the model, these heavy-duty all steel housings can be mounted directly to wall, in the corner of a room or on a surface mount ceiling.	\$ 195
AXIS INDOOR FIXED CORNER HOUSING	24887	AXIS Vandal Resistant Housings deliver maximum protection for Axis fixed network cameras in three different mounting configurations. Depending on the model, these heavy-duty all steel housings can be mounted directly to wall, in the corner of a room or on a surface mount ceiling.	\$ 293
AXIS INDOOR FIXED WALL HOUSING	24886	AXIS Vandal Resistant Housings deliver maximum protection for Axis fixed network cameras in three different mounting configurations. Depending on the model, these heavy-duty all steel housings can be mounted directly to wall, in the corner of a room or on a surface mount ceiling.	\$ 293
AXIS PENDANT DOME OUTDOOR	25733	Outdoor housing with clear dome for the AXIS 213, 231 & 232 PTZ Network Camera (Heater and Blower) Pendant Mount	\$ 587
AXIS ACH12 INDOOR HOUSING	21899	Camera protection you can rely on. The AXIS ACH13 Indoor Housing is an IP65 classified housing from Axis that offers a convenient and tailor-made solution for mounting the AXIS 210, AXIS 211, AXIS 2120, AXIS 2420 and AXIS 230 Network Camera indoors. Tamper-proof your cameras and protect them against dust and jet spray.	\$ 146
AXIS ACH13B OUTDOOR HOUSING	24889	The AXIS ACH13HB Outdoor Housing combines the proven protection of an outdoor housing with a heater and blower to keep your Axis Network Camera within normal operating temperatures in either hot or cold climates.	\$ 342
AXIS T97A10 ENCLOSURE	5021-101	IP66-rated enclosure for AXIS Q7401, AXIS P8221 and AXIS P7701. Operating temperature ranges between 0 °C to 45 °C (32 °F to 113 °F). Optional accessories for impact resistance and polemount are available.	\$ 82
AXIS T98A15-VE SURVEILLANCE CABINET	5900-151	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included.	\$ 264

AXIS T98A15-VE MEDIA CONVERTER CABINET A (120 V AC)	5505-351	Pre-assembled T98A Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	\$ 881
AXIS T98A16-VE SURVEILLANCE CABINET	5900-161	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible cameras: AXIS M111X-E, P13XX-E, Q16XX-E, Q1755-E, Q191X-E Q192X-E.	\$ 264
AXIS T98A16-VE MEDIA CONVERTER CABINET A (120 V AC)	5505-361	Pre-assembled T98A Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	\$ 881
AXIS T98A17-VE SURVEILLANCE CABINET	5900-171	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible cameras: AXIS P33-VE/-LVE.	\$ 264
AXIS T98A17-VE MEDIA CONVERTER CABINET A (120 V AC)	5505-371	Pre-assembled T98A Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	\$ 881
AXIS T98A18-VE SURVEILLANCE CABINET	5900-181	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible products: AXIS T91A61 Wall bracket for use with AXIS P55 and Q60-series or fixed dome pendant kits.	\$ 264

AXIS T98A18-VE MEDIA CONVERTER CABINET A (120 V AC)	5505-381	Pre-assembled T98A18-VE Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3) AXIS T8604 Media Converter, (4) Power cable and DIN clip for midspan AXIS T8124, (5) Internal cables and mounts. Tested and verified with Axis cameras.	\$ 881
AXIS T98A19-VE SURVEILLANCE CABINET	5900-321	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible products: AXIS P5414-E/15-E.	\$ 264
AXIS T98A19-VE MEDIA CONVERTER CABINET A (120 V AC)	5505-391	Pre-assembled T98A Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	\$ 881
AXIS T98A SUNSHIELD	5503-551	Metal sunshield for AXIS T98A-VE Surveillance Cabinet series. Reduces the temperature inside the cabinet, caused by sun radiation, with up to 15°C (27°F).	\$ 73
COVER AXIS M301X WHITE 10PCS	5502-171	White cover with clear bubble for AXIS M3011 and AXIS M3014. 10 pack. Sparepart	\$ 146
ACC CVER DME AXIS M301X BLCK 10PCS	5502-181	Black cover with clear bubble for AXIS M3011 and AXIS M3014. 10 pack	\$ 146
ACC CVER DME AXIS M301X SIL 10PCS	5502-191	Silver cover with clear bubble for AXIS M3011 and AXIS M3014 Network Cameras. 10 pack.	\$ 146
ACC CVER DME AXIS M301X GOLD 10PCS	5502-201	Gold cover with clear bubble for AXIS M3011 and AXIS M3014 Network Cameras. 10 pack.	\$ 146
ACC CVER DME AXIS M301X MIX 10PCS	5502-341	Mixed covers with clear bubble for AXIS M3011 and AXIS M3014 Network Cameras. Includes 3 black, 3 silver, 3 gold and 1 white cover.	\$ 146
AXIS M3004-V/05-V BLACK COVER 10PCS	5503-591	Clip on black cover for AXIS M3004-V and AXIS M3005-V.	\$ 97
AXIS M3004-V/05-V WHITE COVER 10PCS	5503-601	Clip on white cover for AXIS M3004-V and AXIS M3005-V.	\$ 97
AXIS M3006-V/07-PV COVER BLACK 10PCS	5503-611	Clip on black cover for AXIS M3006-V and AXIS M3007-PV. 10 pcs.	\$ 97
AXIS M3006-V/07-PV COVER WHITE 10PCS	5503-621	Clip on white cover for AXIS M3006-V and AXIS M3007-PV. 10 pcs.	\$ 97

AXIS SKIN COVER A BLACK 5P	5505-121	Skin covers compatible with AXIS Q3505-V for changing the appearance of the camera, simplify re-painting or covering screws. Black color. 5 pcs	\$ 77
AXIS SKIN COVER B BLACK 5P	5505-201	Skin covers compatible with AXIS Q3505-VE for changing the appearance of the camera, simplify re-painting and covering screws. Black color. 5 pcs	\$ 77
AXIS SKIN COVER C BLACK 5P	5506-031	Skin covers compatible with AXIS P32-V cameras for changing the appearance of the camera, simplify re-painting or covering screws. Black color. 5 pcs	\$ 77
AXIS SKIN COVER D 5PCS	5506-161	Spare part skin covers for the AXIS P56 Series. Both the camera cover and the ring around the dome are included. 5 pcs.	\$ 126
AXIS P39-R SKIN COVER WHITE 10P	5505-991	Skin covers compatible with AXIS P39-R cameras for changing the appearance of the camera, simplify re-painting or covering screws. White color. 10 pcs.	\$ 146
AXIS P39-R SKIN COVER BLACK 10P	5506-001	Skin covers compatible with AXIS P39-R cameras for changing the appearance of the camera, simplify re-painting or covering screws. Black color. 10 pcs.	\$ 146
AXIS SMOKED DOME M3004/05 5PCS	5504-031	Smoked domes for AXIS M3004-V and and M3005-V. 5pcs.	\$ 224
AXIS M3006 SMOKED DOME 5PCS	5504-011	Original white top cover with smoked dome for AXIS M3006, 5pcs.	\$ 244
AXIS M3007 SMOKED DOME 5PCS	5504-021	Original white top cover with smoked dome for AXIS M3007, 5pcs.	\$ 244
AXIS M320X DOME KIT SM BLK	5503-191	Interchangeable black casing with smoked dome for AXIS 216FD, AXIS M32 Series, AXIS P3301 and P3304.	\$ 28
AXIS P32-V CLEAR DOME A 5P	5506-131	Standard clear dome for AXIS P32-V Series, 5 pcs	\$ 166
AXIS P32-V SMOKED DOME A 5P	5506-021	Smoked domes for AXIS P32-V Series, 5 pcs	\$ 166
AXIS P32-VE CLEAR DOME A 5P	5506-121	Standard clear dome for AXIS P32-VE Series, 5 pcs	\$ 166
AXIS P32-VE SMOKED DOME A 5P	5506-461	Smoked dome for AXIS P32-VE Series, 5 pcs	\$ 166
AXIS P3353/54 DOME KIT CL BLACK	5503-141	Black cover with clear dome for the AXIS P3343, P3344, P3353, P3354.	\$ 28
AXIS P3346 DOME KIT CL BLACK	5503-151	Black cover with clear dome for AXIS P3346.	\$ 28
AXIS P3364-LV DOME KIT BLACK	5504-401	Dome kit for AXIS P3364-LV. The dome is pre-mounted in a black top cover casing.	\$ 73
AXIS Q3505-V SMOKED DOME 5P	5505-601	Smoked dome for AXIS Q3505-V. 5 pcs	\$ 175
AXIS Q3505-VE SMOKED DOME 5P	5505-621	Smoked dome for AXIS Q3505-VE. 5pcs	\$ 195

AXIS Q603X-E CLEAR DOME	5503-001	Stand alone clear dome for the AXIS Q603X-E with slightly decreased optical quality compared to the HD dome version, but with the line higher up to enable greater tilt without distortion.	\$ 38
AXIS Q6114-E/15-E CLEAR DOME	5507-281	Standard clear dome for AXIS Q61 Series.	\$ 58
AXIS Q6114-E/15-E CLEAR DOME 5P	5506-521	Standard clear dome for AXIS Q61 Series, 5 pcs	\$ 264
ACC DOME AXIS 212PTZ-V GLASS CLEAR	5502-091	Vandal-resistant casing with clear transparent cover as a spare part for AXIS 212PTZ-V.	\$ 68
ACC DOME AXIS 216FD-V GLASS CLEAR	5005-051	Vandal-resistant casing with clear transparent cover. Can also upgrade an AXIS 216FD/216MFD/P330X/M320X to an AXIS 216FD-V/216MFD-V/P330X-V/M320X-V.	\$ 68
ACC TOP CLEAR ASS 216FD BLACK	5500-821	Interchangeable black casing for AXIS 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras with transparent cover.	\$ 28
ACC TOP CLEAR ASS 216FD BLACK 10PCS	5500-771	Interchangeable black casing for AXIS 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras with transparent cover. 10-pack.	\$ 273
ACC DOME AXIS 23XD+ CLEAR COVER	5500-191	Clear plastic dome for AXIS 231/232D+ dome cameras	\$ 27
ACC DOME AXIS 23XD+ SMOKED COVER	5500-201	Smoked plastic dome for AXIS 231/232D+ dome cameras	\$ 27
ACC DOME UPGR KIT AXIS 233D CL/SM	5500-601	Clear and Smoked plastic dome for AXIS 233D dome cameras	\$ 68
AXIS INDOOR FIXED CAMERA DOME	22870	The AXIS Indoor Fixed Camera Dome is a low profile indoor ceiling mount housing. A tinted lower dome enables discreet operation of the camera. This accessory is a professional housing option for indoor surveillance. It is tailor-made for the AXIS 210, AXIS 211, AXIS 2120, AXIS 2420, AXIS 2100, AXIS 2110, and AXIS 230 Network Cameras.	\$ 195
CLEAR BUBBLE FUSIONDOMES	25741	Clear Bubble for AXIS Pendant Fusion Dome (Spare Part)	\$ 68
SMOKED BUBBLE FUSIONDOMES	25740	Smoked Bubble for AXIS Pendant Fusion Domes (Spare Part)	\$ 68
AXIS PENDANT DOME INDOOR	25735	Indoor housing with clear dome for the AXIS 213 PTZ, 231D, 232D Network Camera (No Electronics)	\$ 293
ACC PL ADAPTER FLAT AXIS M311X 10PCS	5502-541	Optional plastic adapter for mounting AXIS M311X on flat surfaces. Used when the cable must enter from the side. 10 pack	\$ 28
ADAPTER CURV L GREY M311X 10PCS	5503-061	Optional light grey adapter for mounting AXIS M311X on curved surfaces. 10 pack	\$ 28

ACC AL MOUNT BRACKET AXIS 212 PTZ	5502-041	AXIS 212 PTZ-V aluminum side wall bracket as spare part.	\$ 58
ACC MOUNT BRACKET DOWN 212PTZ-V	5500-791	AXIS 212PTZ-V vertical tilt mount bracket. For AXIS 212PTZ network cameras. Powder coated aluminum. 37.7 degree downward angle.	\$ 48
ACC AXIS 213 WALL BRACKET	5500-071	AXIS 213 WALL BRACKET allows mounting the AXIS 213 PTZ Network Camera on a wall, or other vertical surface.	\$ 48
ACC DROP CEILING MOUNT AXIS 215 PTZ	5500-681	Drop ceiling mount kit for AXIS 215 PTZ as spare part	\$ 29
MOUNT CLAMP AXIS M10	5502-381	Clamp to mount AXIS M10 series. 1 pcs.	\$ 4
MOUNT CLAMP AXIS M10 10PCS	5502-391	Clamp to mount AXIS M10 series. 10 pack.	\$ 28
M10 STAND EXTENSION 10CM 10PCS	5502-701	AXIS M10-series 10 cm stand extension. 10 pcs. Cable clip included.	\$ 28
ACC RACK HOLDER 2400/2401 EUR	19273	19" Rack mount holder for up to 8 2401/2400 Video Servers.	\$ 440
ACC AXIS 225FD DROP CEILING MOUNT	5003-001	Drop ceiling mount for AXIS 225FD.	\$ 97
AXIS 225FD PENDANT BLK	5500-381	With AXIS 225FD PENDANT KIT it is possible to mount the AXIS 225FD Network Camera on AXIS T91A Brackets, VT Dome mounts and on 1,5"NPT threaded brackets. Includes 1.5 inch to M30 Male adapter. Black	\$ 77
AXIS 225FD PENDANT BLK 1,5"NPT	5502-001	With AXIS 225FD PENDANT KIT 1,5"NPT it is possible to mount the AXIS 225FD Network Camera on AXIS T91A Brackets and on 1,5" NPT threaded brackets. Black	\$ 68
AXIS M32/P3301/4 J-BOX ADAPTER PLATE	30337	Bracket for mounting a 216FD, 216MFD, P3301,P3304,M3203,M3204 or 212PTZ on a US junction box (4 11/16 switchbox or 4" squarebox).	\$ 43
AXIS P851X WALLBRACKET KIT BLACK	5503-511	Black telescopic wallbracket kit for the AXIS P85-series. Kit content: two wallbrackets and one floor bracket	\$ 68
AXIS P851X WALLBRACKET KIT WHITE	5503-501	White telescopic wallbracket kit for the AXIS P85-series. Kit content: two wallbrackets and one floor bracket	\$ 68
AXIS T8640 WALL MOUNT BRACKET	5026-411	Wall mount bracket for AXIS T8640 Ethernet over Coax adapter base or device unit.	\$ 13
AXIS T8640 DIN RAIL CLIP	5026-431	DIN rail clip for AXIS 8640 Ethernet over Coax adapter.	\$ 22
AXIS T8642 MOUNTING KIT A	5506-291	Kit for mounting an AXIS T8642 e.g. inside an AXIS Q8414-LVS. Kit contents: cable tie 432mm (17 in) long, BNC male to female angled adapter and network cable 135 mm (5.3 in) long.	\$ 14

AXIS T8640 RACK MOUNT BRACKET	5026-421	Rack mount bracket for AXIS T8640 Ethernet over Coax adapter (8 units in 1U).	\$ 61
AXIS T90A61 BRACKET SINGLE	5013-611	Mounting bracket for one AXIS T90A illuminator.	\$ 48
AXIS T90A62 BRACKET TWIN	5013-621	Mounting bracket for two AXIS T90A illuminators.	\$ 64
AXIS T90A63 BRACKET WALL L MOUNT	5013-631	L shaped wall bracket which provides up/down and left/right adjustment when used with the standard bracketry on AXIS T90A series illuminators.	\$ 38
AXIS T90A66 BRACKET POLE CLAMP	5013-661	Pole bracket for AXIS T90A illuminators.	\$ 87
AXIS T91A02 DIN RAIL CLIP 77MM	5017-027	DIN rail clip for AXIS Q7401, AXIS P8221 and AXIS 7701.	\$ 12
AXIS T91A02 DIN RAIL CLIP 86MM	5017-028	DIN rail clip for AXIS M7014 and AXIS P7214	\$ 12
AXIS T91A03 DIN RAIL MOUNT	5503-194	DIN rail clip for AXIS Q7424-R.	\$ 19
AXIS T91A04 CAMERA HOLDER ¾" NPS	5017-041	Holding device for pendant mounted cameras. For use with ¾" pipes with NPS or NPT threading. Compatible with all cameras with standard tripod threading.	\$ 28
AXIS T91A05 CAMERA HOLDER 1.5" NPS	5017-051	Holding device for pendant mounted cameras. For use with 1.5" pipes with NPS or NPT threading. Compatible with all cameras with standard tripod threading.	\$ 28
AXIS T91A06 PIPE ADAPTER ¾-1.5"	5503-091	Pipe adapter step up from ¾" NPT thread to 1.5" NPS thread. Compatible with all pendant kits that are made for the AXIS T91A range of brackets.	\$ 12
AXIS T91A11 STAND WHITE	5017-111	Plastic camera stand. Original stand for the AXIS M11-series.	\$ 15
AXIS T91A21 STAND BLACK	5022-211	Metal stand for wall or hard ceiling mount. Compatible with all standard tripod thread cameras e.g. AXIS Q17/19 series and AXIS P13 series.	\$ 28
AXIS T91A21 STAND WHITE	5017-211	Metal stand for wall or hard ceiling mount. Compatible with all standard tripod thread cameras e.g. AXIS Q17/19 series and AXIS P13 series.	\$ 28
AXIS T91B21 STAND WHITE	5506-611	White aluminum stand for wall or hard ceiling mount. A cable hole in the base of the stand makes it possible to hide the hole in the wall out of which the cable is routed. A snap on cover gives a clean look without visible screws. Compatible with all standard tripod thread cameras e.g. AXIS M11, P13, Q16 series.	\$ 28

AXIS T91B21 STAND BLACK	5506-621	Black aluminum stand for wall or hard ceiling mount. A cable hole in the base of the stand makes it possible to hide the hole in the wall out of which the cable is routed. A snap on cover gives a clean look without visible screws. Compatible with all standard tripod thread cameras e.g. AXIS M11, P13, Q16 series.	\$ 28
AXIS T91A27 POLE MOUNT 10PCS	5503-971	Pole mount bracket compatible with all cameras with standard tripod threading (1/4"-20 UNC)	\$ 28
AXIS T91A47 POLE MOUNT 60-110MM	5504-701	AXIS T91A47 Pole Mount for Indoor and outdoor installations, for poles between 60-110 mm (2.4"-4.3") in diameter. AXIS T91A47 is compatible with all outdoor fixed and thermal cameras and most fixed outdoor dome cameras such as the AXIS P33-VE.	\$ 68
AXIS T91A47 POLE MOUNT 110-400MM	5504-581	AXIS T91A47 Pole Mount for Indoor and outdoor installations, for poles between 110-400 mm (2.4"-4.3") in diameter. AXIS T91A47 is compatible with all outdoor fixed and thermal cameras and most fixed outdoor dome cameras such as the AXIS P33-VE.	\$ 77
AXIS T91A50 TELESCOPIC CEIL MNT	5504-501	Indoor telescopic ceiling mount. Expands between 1 m (39") and 2 m (79"). Features a swivel action to prevent breaking if hit by forklifts or high vehicles. Can be mounted on a sloped ceiling. Accessory extension pipes (Not included) for a maximum length of 5 m (197"). Compatible with all Axis pendant kits featuring a 1,5" NPS thread and the AXIS T91A05 Camera holder for fixed cameras.	\$ 195
AXIS T91A51 CEILING MOUNT	5504-511	The indoor ceiling mount is ideal for low ceiling installations such as parking houses, with swivel action to prevent breaking if hit. Can be mounted in a sloped ceilings to compensate angles up to 45 degrees. Available accessory extension pipes (Not included) of 30 cm (12") or 1 meter (39") to enable correct camera height for the specific environment. Compatible with all Axis pendant kits featuring a 1,5" NPS thread and the AXIS T91A05 Camera holder for fixed cameras.	\$ 117
AXIS T91A52 EXTENSION PIPE 30 CM	5504-252	Extension pipe for AXIS T91A50 and AXIS T91A51. Length 30 cm (12").	\$ 33
AXIS T91A52 EXTENSION PIPE 100 CM	5504-152	Extension pipe for AXIS T91A50 and AXIS T91A51. Length 100 cm (39").	\$ 48

AXIS T91B61 WALL MOUNT	5504-621	Chromated and powder coated aluminum wall mount for AXIS P55-series and AXIS Q60-series PTZ dome cameras. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal, conduit hole cover and AXIS T94A01D Pendant Kit for PTZ dome cameras. Color: White	\$ 97
AXIS T91C61 WALL MOUNT STAINLESS STEEL	5504-691	Stainless steel wall mount bracket for AXIS Q60-S. AXIS T94S01D pendant kit is included.	\$ 440
AXIS T91D61 WALL MOUNT	5504-821	Chromated and powder coated aluminum wall mount with 1.5" NPS thread for fixed dome pendant kits. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal and conduit hole cover. Color: White	\$ 82
AXIS T91E61 WALL MOUNT	5506-481	Wall mount with internal cable canal for dome cameras with 1.5" NPS thread, compatible with Axis pendant kits. IK10 and NEMA 4X rated. Powder coated aluminum for indoor and outdoor installations.	\$ 38
AXIS T91B62 PARAPET MOUNT	5504-631	Chromated and powder coated aluminum parapet mount compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60-series PTZ dome cameras. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal, conduit hole cover and AXIS T94A01D Pendant Kit for PTZ dome cameras. Color: White	\$ 185
AXIS T91A63 BRACKET CEILING	5017-631	Ceiling Bracket. 70 cm / 28 inch. For use with AXIS P55-series, AXIS Q60-series PTZ Dome Network Cameras, AXIS P33 Series Pendant kit, AXIS P33-VE Series Pendant kit, AXIS 225 Pendant kit and AXIS 216/P3301 Pendant kit. White.	\$ 117
AXIS T91B63 CEILING MOUNT	5504-641	Chromated and powder coated aluminum ceiling mount 75 cm / 29.5 inch compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60-series PTZ dome cameras. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal, conduit hole cover and AXIS T94A01D Pendant Kit for PTZ dome cameras. Color: White	\$ 117
AXIS T91A64 BRACKET CORNER	5017-641	Corner Bracket. Requires AXIS T91A61 Wall Bracket. AXIS P55-series, AXIS Q60-series PTZ Dome Network Cameras, AXIS P33 Series Pendant kit, AXIS P33-VE Series Pendant kit, AXIS 225 Pendant kit and AXIS 216/P3301 Pendant kit. White.	\$ 77

AXIS T91A67 MOUNT POLE	5017-671	Pole Bracket. AXIS P55-series, AXIS Q60-series PTZ Dome Network Cameras, AXIS P33 Series Pendant kit, AXIS P33-VE Series Pendant kit, AXIS 225 Pendant kit and AXIS 216/P3301 Pendant kit. Includes steel pole straps. White. Requires mounting tool Part no: 21776	\$ 97
AXIS T91C67 POLE BRACKET STAINLESS STEEL	5505-001	Stainless steel pole mount for AXIS Q60-S	\$ 146
AXIS T91A6 PIPE SEAL 1PCS	5503-781	Pipe seal for AXIS T91A6, to protect from dust, water and bugs.	\$ 11
ACC TOOL STEEL STRAP	21776	Tool for steel strap tensioning. For use with 21764 and AXIS T91A67	\$ 142
AXIS T94A01D PENDANT KIT	5502-431	Pendant kit for the AXIS Q60-series and AXIS P55-series PTZ Network Cameras, enables mount on standard '1,5" NPT threaded brackets. White.	\$ 48
AXIS T94A01F CEILING BRACKET	5506-181	Bracket for mounting an AXIS P56 Series camera in a hard ceiling. For indoor and outdoor installations. 3/4" conduit hole, compatible with ACI adapters.	\$ 28
AXIS T94A01L RECESSED MOUNT	5505-721	Outdoor recessed mount for AXIS Q60-E cameras. Can be mounted in panels, wood or pre-made holes solid concrete. The mount is very sturdy and made of aluminum and stainless steel. It supports the IK10 impact rating of the camera and has two 3/4" conduit holes for a plenum rated and rodent safe installation.	\$ 244
AXIS T94A02L RECESSED MOUNT	5506-171	Outdoor recessed mount for AXIS P56 cameras. Also suitable indoor for recessed camera installations in plenum as the back box is made of metal and has a 3/4" hole for cable protection conduits.	\$ 136
AXIS T94A03L RECESSED MOUNT	5506-841	Recessed mount for AXIS P5514/-E and P5515/-E cameras. Also suitable indoor for recessed camera installations in plenum as the back box is made of metal and has a 3/4" hole for cable protection conduits.	\$ 136
AXIS T94B01D PENDANT KIT	5503-871	Pendant kit for AXIS M3004-V/M3005-V to enable use of AXIS T91A Brackets or 1.5"(NPT or NPS threaded) pipes. The camera network cable fits into the product and a RJ45 network cable coupler is included.	\$ 34
AXIS T94B01L RECESSED MOUNT	5503-891	Indoor recessed mount for drop ceiling installations. RJ45 network cable coupler included. Compatible with AXIS M3004-V/5-V	\$ 68
AXIS T94B01M J-BOX/GANG BOX PLATE	5503-861	Bracket for mounting on 4" square, 4" octagon, single or double-gang junction box. RJ45 network cable coupler included. Compatible with AXIS M3004-V/5-V.	\$ 28

AXIS T94B01S MNT BRACKET BLACK 10PCS	5504-531	Black mount bracket for mounting on standard tripod threading (1/4"-20 UNC) or single-gang junction box. Compatible with AXIS M3004-V/5-V.	\$ 48
AXIS T94B01S MNT BRACKET WHITE 10PCS	5503-911	White mount bracket for mounting on standard tripod threading (1/4"-20 UNC) or single-gang junction box. Compatible with AXIS M3004-V/5-V.	\$ 48
AXIS T94F01D PENDANT KIT	5503-881	Indoor pendant kit for AXIS M3006/7, AXIS M3024-LVE/3025-VE/3026-VE. to enable use of AXIS T91A Brackets or 1.5"(NPT or NPS threaded) pipes. The camera network cable fits into the product and a RJ45 network cable coupler is included.	\$ 38
AXIS T94F02D PENDANT KIT	5900-021	Outdoor pendant kit for M3024-LVE/M3025-VE to enable use of AXIS T91A Brackets or 1.5"(NPT or NPS threaded) pipes.	\$ 38
AXIS T94F01L RECESSED MOUNT	5503-901	Indoor recessed mount for drop ceiling installations. RJ45 network cable coupler included. Compatible with AXIS M3006-V/M3007-PV,AXIS M3024-LVE/M3025-VE/M3026-VE.	\$ 87
AXIS T94F02L RECESSED MOUNT	5504-871	Indoor recessed mount for drop ceiling installations. RJ45 network cable coupler included. Compatible with AXIS M3007-P	\$ 87
AXIS T94F01M J-BOX/GANG BOX PLATE	5503-921	Bracket for mounting on 4" square, 4" octagon, single or double-gang junction box. RJ45 network cable coupler included. Compatible with. Compatible with AXIS M3006/7, AXIS M3024-LVE/3025-VE/3026-VE.	\$ 28
AXIS T94F01P CONDUIT BACK BOX	5504-041	Backbox for AXIS M3006-V, AXIS M3007-P/-PV, AXIS M3024-LVE/3025-VE/3026-VE/3027-PVE which enables safe cabling through 1/2" (M20) conduits.	\$ 28
AXIS T94F01S MOUNTING BRACKET	5505-171	Standard mount bracket for AXIS M3006-V, AXIS M3007-P/-PV, AXIS M3024-LVE/3025-VE/3026-VE	\$ 19
AXIS T94F02S MOUNTING BRACKET	5507-131	Standard plastic mounting bracket for AXIS P1405, P1425, P1427, P1428.	\$ 19
AXIS T94G01P CONDUIT BACK BOX	5505-181	Back box for 3/4" (M25) conduits/cable protection pipes. Compatible with AXIS Q1765-LE and AXIS Q1931-E.	\$ 28
AXIS T94G01S MOUNTING PLATE	5506-081	Sparepart mounting bracket for AXIS Q1765-LE, Q1931-E, Q1932-E	\$ 28
AXIS T94H05L RECESS MOUNT-L	5504-051	Recessed mount for AXIS P3364-L. For indoor use in drop ceilings installations.	\$ 68
AXIS T94H01P CONDUIT BACKBOX	5034-111	Vandal resistant aluminum back box accessory for AXIS P33-/V series indoor cameras (except P3301/04) which enables safe cabling through 3/4" conduits.	\$ 38

AXIS T94K01D PENDANT KIT	5505-081	Indoor pendant kit for AXIS P32-V Series- AXIS P33/-V and AXIS Q3505-V, compatible with Axis ceiling-/wall mounts, AXIS T91A67 Pole mount and 1.5" NPS threaded pipes.	\$ 38
AXIS T94K01L RECESSED MOUNT	5505-571	Indoor recessed mount compatible with AXIS P32-V Series, AXIS P33/-V Series and AXIS Q3505-V.	\$ 77
AXIS T94K01S MOUNTING BRACKET 4P	5505-551	Sparepart mounting bracket for AXIS Q3505- V. 4 pcs	\$ 117
AXIS T94M01D PENDANT KIT	5505-091	Outdoor pendant kit for AXIS Q3505-VE compatible with Axis ceiling-/wall mounts, AXIS T91A67 Pole mount and 1.5" NPS threaded pipes.	\$ 58
AXIS T94M01L RECESSED MOUNT	5505-581	Outdoor recessed mount for AXIS P32-VE Series, P33-VE Series and Q3505-VE	\$ 107
AXIS T94M01S MOUNTING BRACKET 4P	5505-561	Sparepart mounting bracket for AXIS Q3505- VE. 4 pcs	\$ 136
AXIS T94P01B CORNER BRACKET	5504-711	Corner mount for AXIS P5414-E/15-E, AXIS Q1765-LE, AXIS Q1931-E and AXIS P33-VE series.	\$ 77
AXIS T94R01P CONDUIT BACK BOX	5505-141	Back box to enable external cable entry or use of cable protection equipment. Hole for 3/4 inch conduits or M25 cable protection pipes. Compatible with AXIS T94Q01A Wall mount, all AXIS M11-E/P13-E/Q16-E/Q1755- E/Q1910-E/21-E/22-E outdoor fixed box camera wall mounts and AXIS T92E Series and AXIS T93E05 Fixed camera housings.	\$ 33
AXIS T94S01D PENDANT KIT STAINLESS STEEL	5504-681	Stainless steel pendant kit for AXIS Q60-S with 1.5" NPT female thread.	\$ 126
AXIS T94S01S MOUNTING BRACKET 4P	5506-061	Sparepart mounting bracket for AXIS P32-V Series. 4 pcs	\$ 68
AXIS T94T01D PENDANT KIT	5505-871	Outdoor pendant kit for AXIS P32-VE Series, compatible with Axis ceiling-/wall mounts, AXIS T91A67 Pole mount and 1.5" NPS threaded pipes.	\$ 48
AXIS T94T01S MOUNTING BRACKET 4P	5506-071	Sparepart mounting bracket for AXIS P32-VE Series. 4 pcs	\$ 87
AXIS T94Q01A WALL MOUNT	5505-241	Wall mount compatible with all Axis outdoor fixed box cameras and housings. Corrosion tested according to NEMA 4X, UL listed and IK10 rated.	\$ 43
AXIS T95A61 BRACKET WALL	5010-611	Wall bracket for AXIS T95A00 and T95A10 dome housing.	\$ 97

AXIS T95A64 BRACKET CORNER	5010-641	Corner bracket for AXIS T98A-VE Surveillance Cabinet and AXIS T95A00/T95A10 Dome Housings. When used with the AXIS T95 Dome Housings the wall bracket AXIS T95A61 is required.	\$ 87
AXIS T95A67 BRACKET POLE	5010-671	Pole bracket for AXIS T98A-VE Surveillance Cabinet and AXIS T95A00/T95A10 Dome Housings. When used with the AXIS T95 Dome Housings the wall bracket AXIS T95A61 is required.	\$ 126
CORNER MOUNT	22059	Corner mount adaptor for the Axis Indoor, Outdoor and Vandal Fusion Dome housings, for use with the AXIS 213	\$ 87
GOOSENECK WALL MOUNT	25736	Gooseneck Wall mount for the Axis Pendant Fusion Dome Line	\$ 97
PARAPET MOUNT	25738	Parapet Mount for the AXIS Pendant Fusion Dome line.	\$ 391
POLE MOUNT	21896	Pole mount adaptor for the Axis Indoor, Outdoor and Vandal Fusion Dome housings, for use with the AXIS 213	\$ 58
VT CEILING BRACKET BALL JOINT WCM5A	0217-061	Stylish round tubing ceiling bracket with ball joint. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	\$ 117
VT CEILING BRACKET INT CABLE WCM4A	0217-051	Stylish round tubing ceiling bracket with internal cable channel. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	\$ 107
VT COLUMN MOUNT BALL JOINT WFWCA	0217-071	Column mount with ball joint. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	\$ 97
VT CORNER MOUNT WCWA	0217-101	Corner mount. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	\$ 58
VT WALLBRACKET BALLJOINT WBJA	0217-021	Wall bracket with ball joint. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	\$ 24
VT WALLBRACKET INTERNA CABLE WBOVA1	0217-031	Wall bracket with internal cable channel. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	\$ 35
WALL MOUNT AXIS PS24	5000-011	Metal box to mount AXIS PS24 to a wall.	\$ 48
AXIS PS-24 Pole bracket	21764	Outdoor pole mount bracket for PS-24 and AXIS T97A10. Requires the Wall Mount AXIS PS-24 (5000-011) and a mounting tool for straps (21776 or similar).	\$ 44
YP3040 WALL BRACKET	5502-471	Wall bracket for YP3040 Pan Tilt Motor. White	\$ 48
AXIS WALL BRACKET K	5503-491	Bracket for mounting an AXIS Q87-E on a wall.	\$ 117
AXIS COLUMN BRACKET K	5506-411	New improved bracket for mounting an AXIS Q87-E on top of a column/pole or parapet.	\$ 117

AXIS T91A03 DIN RAIL CLIP 5PCS	5800-511	The clip, made of steel, enables mounting on a standard 35mm DIN rail. It includes 2 cable ties. Compatible with AXIS T8120/T8133 midspans and AXIS T8604 / T8605 converters. Weight: 17 g (0.6 oz.). 5-pack.	\$ 19
AXIS MIDSPAN DIN CLIP A	5503-931	Din clip for AXIS midspan T8123, T8124 and T8125	\$ 19
P1204 MOUNTING KIT 5-P	5800-421	Original mounting kit for AXIS P1204. Kit contents: Sensor unit cover skin, bracket, angled bracket and camera holder. 5 pack.	\$ 48
P1214/-E MOUNT KIT INC HOUS 5-P	5800-431	Original mounting kit for AXIS P1214/-E. Kit contents: sensor unit housing, flush wall mount bracket. 5 pack.	\$ 97
P1214/-E MOUNT KIT EXC HOUS 5-P	5800-461	Mounting kit for AXIS P1204/E. Kit contents: Flush mount wall bracket. 5 pack.	\$ 28
DROP CEILING AXIS 216FD/P3301 CL	5005-031	Drop ceiling mount kit for AXIS 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras including clear transparent cover	\$ 58
AXIS 216FD/P3301 PENDANT WHT	5500-891	With AXIS 216FD PENDANT KIT it is possible to mount AXIS 212PTZ, 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras on AXIS T91A Brackets, VT Dome Brackets and on 1,5"NPT threaded brackets. Includes 1.5 inch to M30 Male adapter. White	\$ 48
AXIS 216FD/P3301 PENDANT WHT 1.5NPT	5502-021	With AXIS 216FD PENDANT KIT it is possible to mount AXIS 212PTZ, 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras on AXIS T91A Brackets and on 1,5"NPT threaded brackets. White	\$ 38
STAND M10 SERIES 7CM	5700-481	Plastic stand for the AXIS M10-series	\$ 13
AXIS 216FD/P3301 PENDANT BLK 1,5NPT	5502-011	With AXIS 216FD PENDANT KIT it is possible to mount AXIS 212PTZ, 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras on AXIS T91A Brackets and on 1,5"NPT threaded brackets. Black	\$ 38
AXIS 216FD/P3301 PENDANT BLK	5500-881	With AXIS 216FD PENDANT KIT it is possible to mount AXIS 212PTZ, 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras on AXIS T91A Brackets, VT Dome Brackets and on 1,5"NPT threaded brackets. Includes 1.5 inch to M30 Male adapter. Black	\$ 48
DROP CEILING KIT CL AXIS P3346	5502-781	Drop ceiling mount for AXIS P3346, AXIS P3367-V and AXIS P3384-V including clear bubble. For indoor use	\$ 68
DROP CEILING KIT SM AXIS P3346	5502-791	Drop ceiling mount for AXIS P3346, AXIS P3367-V and AXIS P3384-V including smoked bubble. For indoor use	\$ 68

DROP CEILING KIT CL AXIS P3343/4	5502-361	Drop ceiling mount for AXIS P3343, AXIS P3344, AXIS P3353 and AXIS P3354 including clear transparent bubble. For indoor use	\$ 68
DROP CEILING KIT SM AXIS P3343/4	5502-371	Drop ceiling mount for AXIS P3343, AXIS P3344, AXIS P3353 and AXIS P3354 including smoked transparent bubble. For indoor use	\$ 68
PENDANT KIT AXIS P334X	5502-351	With AXIS P33 Series PENDANT KIT it is possible to mount the AXIS P3343/-V, AXIS P3344/-V, AXIS P3346/-V, AXIS P3353, AXIS P3354, AXIS P3363-V, AXIS P3364-V, AXIS P3367/-V and AXIS P3384-V Fixed Dome Network Cameras on AXIS T91A Brackets or on standard 1.5" NPT threaded brackets. White	\$ 38
ACC MOUNTING BRACKET AXIS P3343	5502-401	Mounting plate for AXIS P3343/-V, AXIS P3344/-V, AXIS P3353, AXIS P3354, AXIS P3363-V and AXIS P3364-V. Used when mounted on a single or double gang box.	\$ 28
MOUNTING BRACKET AXIS P33XX-VE	5700-691	Original AXIS P33XX-VE mounting bracket for wall or hard ceiling.	\$ 28
AXIS P33XX-VE 3/4" □ NPS CONDUIT ADAPTER	5503-711	Aluminum cable cover with stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection.	\$ 38
AXIS P33XX-VE 3/4" □ NPS COND ADPT 4P	5503-721	Aluminum cable cover with stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection. Four complete units.	\$ 141
AXIS P33XX-VE 3/4" NPS ADAPT	5503-131	Stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection.	\$ 28
PENDANT KIT AXIS P334X-VE	5502-321	With AXIS P33-VE Series PENDANT KIT it is possible to mount the AXIS P3343-VE, AXIS P3344-VE, AXIS P3346-VE, AXIS P3363-VE and AXIS P3364-VE, AXIS P3367-VE, AXIS P3384-VE Fixed Dome Network Cameras on AXIS T91A Brackets or on standard 1.5" NPT threaded brackets. White	\$ 48
POLE MOUNT BRACKET F	5503-631	Polemount bracket for AXIS T8123-E and AXIS T8124-E outdoor midspans.	\$ 58
ADAPTER AXIS 209 TO M31/P39 50 PCS	5503-192	Adapter plate for mounting an AXIS M31 using the same foot print as the AXIS 209. 50 PCS	\$ 244
ACC CORNER MOUNT AXIS 215PTZ-E	5502-291	Corner bracket for AXIS 215 PTZ-E.	\$ 68
AXIS P33XX-VE CABLE COVER 4 PCS	5503-731	Aluminum cable cover for AXIS P33XX-VE cameras. 4 pcs.	\$ 58
ACC POLE MOUNT AXIS 215PTZ-E	5502-301	Pole bracket for AXIS 215 PTZ-E.	\$ 68

1.5 inch to M30 Male adapter	5502-441	Adapter to convert M30 to 1.5" thread. Used to convert VT Dome mounts to 1.5" NPT thread. Black color.	\$ 19
MOUNT BRACKET M311X 10 PCS	5503-081	Original mount bracket for hard ceiling AXIS M311X, 10 pcs	\$ 38
AXIS ACI COND ADAP 3/4" U-SHAPE 30MM 5PCS	5505-191	Mechanical adapter that provides a U-shaped 30mm wide cable entry for use when a U-shape cable protection is required. The adapter is compatible with AXIS P54-series, AXIS P32-VE Series (requires AXIS ACI Mounting Bracket A), AXIS Q3505-VE, AXIS T91B6X mounts and AXIS AXIS T94R01P Conduit Back Box. 5 pcs.	\$ 24
AXIS ACI CONDUIT BRACKET A 5P	5505-971	Cable protection attachment bracket for AXIS P32-VE Series. Compatible with 3/4" Conduits, M25 pipes and AXIS ACI adapters. 5pcs.	\$ 38
AXIS ACI CONDUIT BRACKET B 5P	5506-041	Cable protection attachment bracket for AXIS P32-V Series. Compatible with 1/2" Conduits, M20 pipes and AXIS ACI adapters. 5pcs.	\$ 19
AXIS ACI CONDUIT ADAPTER 1/2"-3/4" A 2P	5505-541	Step up ACI adapter for attaching 3/4" conduits or M25 pipes to AXIS products with a 1/2" conduit interface such as AXIS P32-V series (requires AXIS ACI conduit bracket B) and AXIS Q3505-V. 2 pcs	\$ 38
AXIS ACI COND ADAP 1/2 " U-SHAPE 20MM 5P	5505-521	Mechanical adapter that provides a U-shaped 20mm wide cable entry for use when a U-shape cable protection is required. The adapter is compatible with AXIS products with a 1/2" conduit interface such as AXIS P32 V series (requires AXIS ACI conduit bracket B) and AXIS Q3505-V. 5 pcs	\$ 19
AXIS ACI COND ADAP 1/2"-3/4" NPS 2P	5505-591	Threaded stainless steel step up ACI adapter for attaching 3/4" NPS conduits to AXIS products with a 1/2" conduit interface such as AXIS P35-V series. 2 pcs	\$ 68
AXIS ACI CONDUIT ADAPTER 3/4" NPS 2P	5505-641	Threaded stainless steel step up ACI adapter for attaching 3/4" NPS conduits to AXIS products with a 3/4" conduit interface such as AXIS P35-V series. 2 pcs	\$ 97
AXIS T92E CAMERA HOLDER PLATE C	5505-331	Camera holder plate for mounting an AXIS Q1614 in a AXIS T92E05 and AXIS T92E20 housing. Or change the camera unit inside an AXIS P135X-E outdoor camera.	\$ 19
AXIS T92E CAMERA CHANGE KIT A	5505-341	Kit for mounting an AXIS Q1614 in a AXIS T92E05/AXIS T92E20 housing produced before 2014. Or change the camera unit inside an AXIS P134X-E outdoor camera.	\$ 38
AXIS F8001 SURFACE MOUNT	5505-791	Bracket to mount and secure an F Series main unit onto a surface. Withstands vibrations and secures all cables to/from the main unit.	\$ 38

ACC PL ADAPTER CURVED AXIS M311X 10PCS	5502-551	Optional adapter for mounting AXIS M311X on curved surfaces. 10 pack	\$ 28
AXIS F7315 CABLE WHITE 15M 4PCS	5506-821	AXIS F7315 comes in packs of four. 15-m (49 ft.) white cable with an RJ12 contact for connection to an AXIS F1004 Sensor Unit.	\$ 97
AXIS F7308 CABLE BLACK 8M 4PCS	5506-921	AXIS F7308 comes in packs of four. 8-m (26 ft.) black cable with an RJ12 contact for connection to an AXIS F1004 Sensor Unit. Used as a spare part for the original cable that comes with AXIS F1004 Sensor Unit.	\$ 38
AXIS F8002 DIN RAIL CLIP	5505-801	DIN clip + angled mounting bracket. Allows an AXIS F Series main unit to be mounted on a DIN rail with the short side against the rail to minimize used space. Main unit can be mounted with cables going in any of three directions (up, down or out from the rail).	\$ 38
AXIS F8401 CLEAR LENS PROTECTOR 5PCS	5505-841	Lens protection for AXIS F1005-E. The lens protector is screwed onto the threaded front part of the sensor unit to protect the lens. Comes in pack of 5 units.	\$ 77
AXIS F8201 VARI- ANGLE MT BRACK 5PCS	5505-811	Mounting bracket for AXIS F1005-E, AXIS F1015 and AXIS 1035-E. Allows the sensor unit to be fixed and angled into various directions to get the desired view. Comes in pack of 5 pcs.	\$ 28
AXIS F8202 STRAIGHT MT BRACKET 5PCS	5505-821	Mounting bracket that allows the pinhole sensor unit of AXIS F1025 to be mounted onto a flat surface with the cone being flush with opposite surface. Comes in pack of 5 pcs.	\$ 28
AXIS F8203 FIXED MT BRACKET 5PCS	5505-831	Metal bracket for stable mounting of AXIS F1005-E, F1015 and F1035-E. Variety of holes for screws for flexible mounting. Comes in pack of 5 units.	\$ 146
AXIS F8204 MOUNTING BAND 10 PCS	5506-571	Stainless steel band for flexible mounting of AXIS F Series Sensor units and AXIS P12 sensor units. Sold in 10-pack. 10 x M20 x 1.5 nuts to lock the band to the sensor unit are included. Works with all AXIS P12 Sensor Units and all AXIS F Series Sensor units except AXIS F1015.	\$ 38
AXIS F8211 PINHOLE TRIM RING 10PCS	5507-101	Trim ring for discreet mounting of AXIS F1025 Sensor Unit behind a thin surface. 10 PCS.	\$ 58
AXIS F8212 TRIM RING 10PCS	5507-111	Trim ring for discreet mounting of AXIS F1005-E, F1035-E, P1214-E and P1224-E behind a surface. 10 PCS.	\$ 97
AXIS F8214 DOME ACC 4PCS	5506-501	AXIS F8214 Dome Accessory (4 pieces). Dome accessory for use with AXIS F1004 Sensor Unit. Can be mounted on walls and ceilings. Can be used with or without bubble.	\$ 58

AXIS F8224 RECESSED MOUNT 4PCS	5506-511	AXIS F8224 Recessed Mount (4 pieces). Recessed mount accessory for use with AXIS F1004 Sensor Unit. Can be mounted in a ceiling.	\$ 58
AXIS F8205 BULLET ACCESSORY	5506-211	Bullet-style camera accessory for AXIS F1005-E. AXIS F1005-E provides 113° horizontal FOV. Comes with c-clamp and a stand.	\$ 24
AXIS F8215 VARIFOCAL BULLET ACC	5506-221	Varifocal bullet-style camera accessory for AXIS F1015. AXIS F1015 provides 58-108° horizontal FOV. Comes with c-clamp and a stand.	\$ 24
AXIS F8225 PINHOLE ACCESSORY	5506-531	Discreet accessory for ceiling mount of AXIS F1025 (pinhole). AXIS F1025 provides 92° horizontal FOV. Used to get overview of rooms or of a door. Can easily be repainted to fit ceiling color.	\$ 38
AXIS F8235 FISHEYE ACCESSORY	5506-541	Discreet accessory to mount a AXIS F1035-E in a ceiling. Perfect for overview in small rooms or in parts of a larger room. Can easily be repainted to fit ceiling color.	\$ 38
AXIS F9201 SILVER HEIGHT S. HOUSING	5506-271	Height strip housing for use with an AXIS F Series Main Unit and AXIS F1025 Sensor Unit. Can also be used with AXIS P1204. Comes with both a metric and an imperial height strip. Silver aluminium housing.	\$ 97
AXIS F9201 BLACK HEIGHT S. HOUSING	5506-261	Height strip housing for use with an AXIS F Series Main Unit and AXIS F1025 Sensor Unit. Can also be used with AXIS P1204. Comes with both a metric and an imperial height strip. Black aluminium housing.	\$ 97
AXIS S1016	0202-720	Axis Camera Station S1016 Recorder workstation. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. windows. Includes AXIS Camera Station licenses for 16 channels, three year hardware and software support and international keyboard and mouse. Support for multiple screens.	\$ 3,919
AXIS S1032	0202-730	Axis Camera Station S1032 Recorder rack server. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. windows. Includes AXIS Camera Station licenses for 32 channels and three year hardware and software support.	\$ 10,779

AXIS S1048	0202-750	Axis Camera Station S1048 Recorder rack server. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. windows. Includes AXIS Camera Station licenses for 48 channels and three year hardware and software support.	\$ 15,679
AXIS S9001	0202-770	Desktop Terminal to be used with Axis S1032 or Axis S1048 recording servers. The terminal is preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. windows. Includes three year hardware and software support and international keyboard and mouse. Support for multiple screens.	\$ 1,959
AXIS C3003-E NETWORK HORN SPEAKER	0767-001	AXIS C3003-E delivers high sound pressure and clear voice in demanding outdoor environments. The self-contained network speaker installs and powers with a single network cable. It integrates in your video management or VoIP system (SIP) and ensures reliability through the Auto Speaker Test.	\$ 489
Axis Cross Line Detection	0333-011	Single unit license for AXIS Cross Line Detection, a basic cross line video analytic. Visit www.axis.com for supported products and application download.	\$ 28
Axis Cross Line Detection 10-pack	0333-031	Ten (10) unit license for AXIS Cross Line Detection, a basic cross line video analytic. Visit www.axis.com for supported products and application download.	\$ 273
Axis Cross Line Detection 50-pack	0333-051	Fifty (50) unit license for AXIS Cross Line Detection, a basic cross line video analytic. Visit www.axis.com for supported products and application download.	\$ 1,332
AXIS H. 264 50-user decoder license pack	0160-050	A license document that grants installation of AXIS AVC/H.264 decoder onto 50 separate computers. Applicable for all AXIS products that supports H.264 but does not have support for audio.	\$ 44
AXIS H.264 +AAC decoder 50-user decoder license pack	0160-060	A license document that grants installation of AXIS AVC/H.264 and ACC decoder onto 50 separate computers. Applicable for all AXIS products that supports H.264 that also have support for audio.	\$ 54

AXIS MPEG-4 +AAC decoder 50-user license	0160-040	A license document that grants installation of AXIS MPEG-4 and AAC decoder onto 50 separate computers. Applicable for all Axis products that supports MPEG-4. Required for models that supports AAC audio encoding (e.g. models: 207, 207W, 207MW, 212PTZ, 216FD, 223M)	\$ 68
AXIS MPEG-4 Decoder 50-user license pack	0160-030	A license document that grants installation of AXIS MPEG-4 decoder onto 50 separate computers. Applicable for all Axis MPEG-4 products that does not support AAC audio encoding. (e.g. models: 210, 211, 210A, 211A, 213, 214, 221, 225FD, 231D+, 232D+, 241S,241Q, 241SA, 241QA, 242SIV, 243SA, 282, 282A)	\$ 48
ACAP AXIS MOTION GUARD 1 LICENSE	0333-061	Single unit license for AXIS Motion Guard, a robust, installer-friendly motion detection video analytic. Visit www.axis.com for supported products and application download.	\$ 146
ACAP AXIS MOTION GUARD 10 LICENSE	0333-071	Ten (10) unit license for AXIS Motion Guard, a robust, installer-friendly motion detection video analytic. Visit www.axis.com for supported products and application download.	\$ 1,459
ACAP AXIS LOITERING GUARD 1 LICENSE	0333-081	Single unit license for AXIS Loitering Guard, a robust, installer-friendly loitering detection video analytic. Visit www.axis.com for supported products and application download.	\$ 146
ACAP AXIS LOITERING GUARD 10 LICENSE	0333-091	Ten (10) unit license for AXIS Fence Guard, a robust, installer-friendly loitering detection video analytic. Visit www.axis.com for supported products and application download.	\$ 1,459
ACAP AXIS FENCE GUARD 1 LICENSE	0333-101	Single unit license for AXIS Fence Guard, a robust, installer-friendly perimeter protection video analytic. Visit www.axis.com for supported products and application download.	\$ 146
ACAP AXIS FENCE GUARD 10 LICENSE	0333-111	Ten (10) unit license for AXIS Fence Guard, a robust, installer-friendly perimeter protection video analytic. Visit www.axis.com for supported products and application download.	\$ 1,459
AXIS Camera Station 1 license add-on	0202-034	License for 1 additional Axis network video channel to AXIS Camera Station 4 or 10 license base pack. Requires the base pack to be pre-installed. Delivered as a license code in an envelope.	\$ 97

AXIS Camera Station 10 license base pack EN	0202-004	In English. AXIS Camera Station is a monitoring and recording system for small and midsize installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. Base pack with a license for 10 Axis network video channels. Delivered in a box with CD-ROM and QIG.	\$ 979
AXIS Camera Station 4 license base pack EN	0202-054	In English. AXIS Camera Station is a monitoring and recording system for small and midsize installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. Base pack with a license for 4 Axis network video channels. Delivered in a box with CD-ROM and QIG.	\$ 391
AXIS Camera Station 5 license add-on	0202-014	License for 5 additional Axis network video channel to AXIS Camera Station 4 or 10 license base pack. Requires the base pack to be pre-installed. Delivered as a license code in an envelope.	\$ 489
AXIS Camera Station 20 license add-on	0202-264	License for 20 additional Axis network video channel to AXIS Camera Station 4 or 10 license base pack. Requires the base pack to be pre-installed. Delivered as a license code in an envelope.	\$ 1,939
AXIS Camera Station 4 license base pack eLicense	0202-600	AXIS Camera Station is a monitoring and recording system for small and midsize installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. Base pack with a license for 4 Axis network video channels. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	\$ 391
AXIS Camera Station 10 license base pack eLicense	0202-601	AXIS Camera Station is a monitoring and recording system for small and midsize installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. Base pack with a license for 10 Axis network video channels. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	\$ 979

AXIS Camera Station 1 license add-on eLicense	0202-602	License for 1 additional Axis network video channel to AXIS Camera Station 4 or 10 license base pack. Requires the base pack to be pre-installed. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	\$ 97
AXIS Camera Station 5 license add-on eLicense	0202-603	License for 5 additional Axis network video channel to AXIS Camera Station 4 or 10 license base pack. Requires the base pack to be pre-installed. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	\$ 489
AXIS Camera Station 20 license add-on eLicense	0202-607	License for 20 additional Axis network video channel to AXIS Camera Station 4 or 10 license base pack. Requires the base pack to be pre-installed. eLicense. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	\$ 1,939
AXIS M3024/25/26/27 COVER WHT 10PCS	5504-071	White cover skins compatible with AXIS M3024/M3025/M3026/M3027 for covering screws or simplify the painting process.	\$ 126
AXIS M3024/25/26/27 COVER BLK 10PCS	5504-061	Black cover skins compatible with AXIS M3024/M3025/M3026/M3027 for covering screws or simplify the painting process.	\$ 126
ACC TOP COVER AXIS 209FD-R 10PCS	5500-301	Replaceable cover for AXIS 209FD-R, 10 pcs. Includes dry bags	\$ 244
ACC DOME KIT AXIS 215 PTZ	5500-671	Smoked and clear dome kit for AXIS 215 PTZ as spare part	\$ 68
SPR DOME CLEAR AXIS 215 PTZ-E	5700-291	Spare clear dome for AXIS 215-PTZ-E. Includes mounting ring, clear bubble, rubber gasket and 4 screws.	\$ 97
ACC DOME AXIS 216FD GLASS SMOKED	5005-001	Casing with smoked transparent cover for AXIS 216FD/216MFD/P3301	\$ 28
ACC DOME AXIS 216FD GLASS CLEAR	5005-011	Casing with clear transparent cover for AXIS 216FD/216MFD/P3301	\$ 28
ACC DOME AXIS 216FD-V GLASS SMOKED	5005-061	Vandal-resistant casing with smoked transparent cover. Can also upgrade an AXIS 216FD/216MFD/P330X/M320X to an AXIS 216FD-V/216MFD-V/P330X-V/M320X-V	\$ 68
ACC DOME AXIS 225FD GLASS SMOKED	5003-011	Smoked dome glass for AXIS 225FD	\$ 58
ACC CABLE GLAND KIT AXIS 225FD	5500-241	Cable gland for AXIS 225FD	\$ 25
ACC MOUNT KIT 23XD DOME IN SMOKE	21774	Smoked dome, indoor for AXIS 231/232D.	\$ 27
ACC DOME 23XD INDOOR PLASTIC CLEAR	21777	Clear dome, indoor for AXIS 231/232D (included with AXIS 231D/232D), available as spare part.	\$ 27

AXIS M3004-V/05-V CLEAR DOME	5800-631	Original top cover with clear dome for AXIS M3004-V/05-V	\$ 19
AXIS M3006 CLEAR DOME 5PCS	5800-731	Original white top cover with clear dome for AXIS M3006, 5pcs.	\$ 244
AXIS M3007 CLEAR DOME 5PCS	5800-741	Original white top cover with clear dome for AXIS M3007, 5pcs.	\$ 244
AXIS M3024 CLEAR DOME 5PCS	5800-711	Standard clear domes for AXIS M3024, 5 pcs	\$ 244
AXIS Q3505-V CLEAR DOME 5P	5505-611	Standard clear domes for AXIS Q35-V Series, 5 pcs	\$ 175
AXIS M3025/26 CLEAR DOME 5PCS	5800-721	Standard clear domes for AXIS M3025, M3026. 5 pcs	\$ 244
AXIS M3025/26 SMOKED DOME 5PCS	5505-861	Smoked domes for AXIS M3025-VE, M3026-VE. 5 pcs.	\$ 244
AXIS Q3505-VE CLEAR DOME 5P	5505-631	Standard clear dome for AXIS Q3505-VE. 5pcs	\$ 195
AXIS M3027 CLEAR DOME 5PCS	5800-751	Standard clear domes for AXIS M3027, 5 pcs	\$ 244
TOP COVER AXIS M311X-R BL 10PCS	5700-661	Black top cover including dome and screws for AXIS M311X-R. 10 pcs. Approved for use in buses and trams. Not for trains.	\$ 244
AXIS Q8414-LVS SMOKED DOME 5P	5506-301	Smoked dome for hiding the direction of the camera. Compatible with AXIS Q8414-LVS. 5 pcs.	\$ 97
TOP COVER AXIS M311X-R 10PCS	5700-641	Original dark grey top cover including dome and screws for AXIS M311X-R. 10 pcs	\$ 244
TOP COVER M311X- VE NOCAP 10 PCS	5800-061	Original top cover including dome and screws for AXIS M311X-VE No Cap. 10 pcs.	\$ 244
TOP COVER M311X- VE 10 PCS	5800-051	Original top cover including dome and screws for AXIS M311X-VE. 10 pcs.	\$ 244
SPR TOP COVER AXIS P39-R 10 PCS	5801-111	Original top cover including dome and screws for AXIS P39-R Series. 10 pieces.	\$ 244
SPR AXIS P3343 DOME KIT	5700-321	Dome Kit for AXIS P3343, AXIS P3344, AXIS P3353 and AXIS P3354 as spare part. Includes a clear bubble, mounted on o plastic dome cover and a separate smoked bubble.	\$ 28
SPR AXIS P3343-V DOME KIT	5700-311	Dome kit for AXIS P3343-V, AXIS P3344-V, AXIS P3363-V and AXIS P3364-V as spare part. Includes a clear bubble, mounted on an aluminium dome cover and a separate smoked bubble.	\$ 68
SPR DOME KIT AXIS P3343-VE	5700-341	Dome Kit for AXIS P3343-VE, P3344-VE, AXIS P3363-VE and AXIS P3364-VE as spare part. Includes a clear bubble, mounted on an aluminium dome cover and a separate smoked bubble.	\$ 68
SPR AXIS P3346 DOME KIT	5700-901	Dome Kit for AXIS P3346 as spare part. Includes a clear bubble, mounted on o plastic dome cover and a separate smoked bubble.	\$ 33

SPR AXIS P3346-V DOME KIT	5700-911	Dome kit for AXIS P3346-V, P3367-V and AXIS P3384-V as spare part. Includes a clear bubble, mounted on a zinc alloy dome cover and a separate smoked bubble.	\$ 73
SPR AXIS P3346-VE DOME KIT	5700-921	Dome Kit for AXIS P3346-VE, P3367-VE, AXIS P3384-VE as spare part. Includes a clear bubble, mounted on an aluminium dome cover and a separate smoked bubble.	\$ 73
AXIS P3364-LV DOME KIT	5800-691	Dome kit for AXIS P3364-LV. The dome is pre-mounted in the standard white top cover casing.	\$ 73
AXIS P3364-LVE DOME KIT	5800-681	Dome kit for AXIS P3364-LVE. The dome is pre-mounted in a standard white top cover casing.	\$ 73
AXIS M501X DOME	5800-111	Spare part AXIS M501X dome, pre-mounted in the white top casing. Opening tool and gasket are included.	\$ 28
AXIS P54 CLEAR DOME	5800-771	Clear dome for AXIS P54-series.	\$ 48
AXIS P54 SMOKED DOME	5800-761	Smoked dome for AXIS P54-series.	\$ 48
AXIS P54-SERIES WEATHER COVER	5505-151	Sparepart weather cover for Axis P54-Series.	\$ 38
AXIS P553X DOME KIT	5700-631	Dome kit for AXIS P5522 and AXIS P553X as spare art. Includes one clear and one smoked bubble.	\$ 58
AXIS DOME CLEAR P5544	5800-391	Sparepart dome for AXIS P5544. Note that this product does not contain the fisheye lens.	\$ 48
AXIS P5624-E/35-E CLEAR DOME	5506-141	Clear dome for AXIS P56 Series cameras.	\$ 48
AXIS P5624-E/35-E SMOKED DOME	5506-151	Smoked dome for AXIS P56 Series cameras.	\$ 48
AXIS T93F TOP COVER	5505-891	Spare part top part of the housing including window.	\$ 58
SPR BUBBLE KIT SMOKED T95A	5700-131	Replacement smoked bubble for AXIS T95A. Includes aluminum ring, rubber gasket and screws.	\$ 128
SPR BUBBLE KIT CLEAR T95A	5700-121	Replacement clear bubble for AXIS T95A. Includes aluminum ring, rubber gasket and screws.	\$ 128
AXIS Q603X HD DOME KIT	5700-811	HD optimized dome kit for AXIS Q603X as spare part. Includes a clear bubble mounted on dome ring and a separate smoked bubble.	\$ 87
AXIS Q603X-E CLEAR DOME C	5800-081	Stand alone HD quality clear dome without line for the AXIS Q603X-E.	\$ 77
AXIS Q603X-E SMOKED DOME C	5800-341	Stand alone HD quality smoked dome without line for the AXIS Q603X-E.	\$ 77
AXIS Q60-E/C CLEAR DOME D	5800-481	Clear dome cover for AXIS Q60XX-E/-C series	\$ 77
AXIS Q60-E/C SMOKED DOME D	5503-961	Stand alone smoked dome for AXIS Q60XX-E/-C series	\$ 77

AXIS Q6000-E CLEAR DOME	5506-641	Clear dome for AXIS Q6000-E	\$ 77
DOME SM INCL WITH Q60xx CAMERAS	5800-411	Smoked dome for AXIS Q60XX-E/-C series free of charge when ordered at the same time as an AXIS Q60XX-E/-C Camera. NOTE: If spare smoked domes are requested part number 5503-961 shall be ordered.	\$ -
AXIS Q604X-S SUNSHIELD	5504-671	Stainless steel sunshield for AXIS Q604X-S	\$ 287
AXIS Q8414-LVS CLEAR DOME 5P	5506-331	Standard clear dome for AXIS Q8414-LVS. 5 pcs.	\$ 97
AXIS Q872x-E SUNSHIELD KIT	5800-321	Sunshield for AXIS Q872x-E as sparepart. Including screws and washer	\$ 293
ACC ALLEN-KEY M3 TAMP PROOF 10PACK	5500-491	Allen-key for AXIS 209FD-R 10-pack	\$ 38
ACC MOUNT CLAMP FOR AXIS 207	5004-001	Clamp to mount AXIS 206 series and AXIS 207 series.	\$ 9
ACC PL MOUNT BRACKET AXIS 212 PTZ	5500-271	AXIS 212 plastic wall bracket as spare part	\$ 19
ACC SCREW KIT AXIS 215 PTZ	5500-691	Screw kit för AXIS 215 PTZ as spare part	\$ 10
DROP CEILING AXIS 216FD/P3301 SM	5005-041	Drop ceiling mount kit for AXIS 216FD/216MFD/P3301 including smoked transparent cover	\$ 58
AXIS Q604X RECESSED MOUNT	5505-161	Spare part indoor recessed mount for mounting AXIS Q60 indoor cameras in drop ceilings.	\$ 87
P1214/P1214-E/P1224-E MOUNT BRACKET 5PCS	5503-991	Mount bracket for AXIS P1214, P1214-E and P1224-E. Allows to mount the sensor unit in different horizontal and vertical angles.	\$ 58
AXIS M501X MOUNTING KIT	5800-121	Original ceiling mount kit for both hard- and drop ceilings for the AXIS M501X.	\$ 15
AXIS Q8414-LVS BACK CHASSIS METAL	5506-321	Spare part brushed stainless steel metal back chassis with gaskets for AXIS Q8414-LVS.	\$ 195
AXIS Q8414-LVS BACK CHASSIS WHITE	5506-311	Spare part powder coated white stainless steel back chassis with gaskets for AXIS Q8414-LVS.	\$ 195
AXIS T98A MOUNTING BRACKET	5800-351	Original stainless steel mounting bracket for AXIS T98A-VE Surveillance Cabinet series.	\$ 58
ACC SCREW KIT AXIS 216FD	5005-021	Spare set of tamper-proof screws for AXIS 216FD/216FD-V/216MFD/216MFD-V/P3301/P3301-V, with Torx screw driver. Mounting screws also included.	\$ 6
STAINLESS STEEL STRAPS 700MM 1 PAIR	5700-981	Original stainless steel straps for AXIS T91A47 60-110 mm and AXIS T91A67. Mouting tool (P/N 21776) is required.	\$ 14

STAINLESS STEEL STRAPS 1450MM 1 PAIR	5800-811	Original stainless steel straps for AXIS T91A47 110-400 mm. The straps also fit the AXIS T91A67. Mounting tool (P/N 21776) is required.	\$ 24
ACC DESSICANT BAG 100PCS	5500-591	Dry bags for AXIS 209FD-R, 100 pcs	\$ 39
ACC LENS 4MM F=1.2 CS MOUNT	5500-161	CS mount 4 mm, for 210/210A, new lens RoHS compatible	\$ 48
ACC LENS CS VARIF 3-8MM DC-IR	5500-051	CS mount Varifocal 3-8 mm DC-Iris for 211	\$ 97
ACC LENS CS VARIF 3-8MM DC-IR D/N	5500-061	CS mount Varifocal 3-8 mm DC-Iris for 221	\$ 123
AXIS P1204 SENSOR UNIT	5503-801	Original sensor unit for AXIS P1204 with premounted cable. Cover skin and mounting kit is included.	\$ 195
AXIS P1214 SENSOR UNIT	5503-811	Original sensor unit for AXIS P1214 with premounted cable. Flush mount bracket included.	\$ 195
AXIS P1214-E SENSOR UNIT	5503-821	Original sensor unit for AXIS P1214-E with premounted cable. Flush mount bracket and sensor unit housing included.	\$ 195
SPR P1224-E SENSOR UNIT	5800-991	Original sensor unit for AXIS P1224-E with premounted cable. Flush mount bracket included.	\$ 195
ACC MAINS ADAPTOR AXIS 214	5500-211	Mains adapter, AXIS 214, spare-part	\$ 38
ACC MAINS ADAPTOR PS-P	5500-704	Power supply PS-P for AXIS 215 PTZ	\$ 38
AXIS Q8414-LVS IR WINDOW B 5P	5506-371	Accessory IR window without microphone hole. 5 pcs.	\$ 117
ACC PS-RACK	22512	Power supply for the Axis Video Server Rack	\$ 489
ACC MALE RJ45 AXIS 209FD-R	5502-061	Vibration resistant male RJ-45 connector suitable for RJ-45 version of AXIS M31XX-R and AXIS 209FD-R/MFD-R Network Cameras.	\$ 15
MAINS CABLE IEC-C13	5800-201	Mains cable for AXIS One-Port Midspan, AXIS T8123/24, AXIS 291, AXIS Q7900, AXIS Video Server Rack, AXIS PoE Midspan 8-Port/16-Port, Power Supply AXIS T8412.	\$ 15
AXIS PATCH CABLE A 200MM 6PCS	5506-451	Set of patch cables for AXIS T8085 PS57 RACK MOUNT 500W 1U to connect AXIS T8646 POE+ OVER COAX BLADE	\$ 77
ACC MALE RJ45 AXIS 209FD-R 10PCS	5502-051	Vibration resistant male RJ-45 connector suitable for AXIS 209FD-R/MFD-R Network Camera. 10 pack	\$ 146
ACC STAND CAMERA METAL US	18618	Metal stand for network cameras AXIS 221, AXIS 230, AXIS 2120, AXIS 2420	\$ 20
ACC STAND PLASTIC AXIS 205/206	22473	Plastic stand for AXIS 205, 206, 206M, 206W, 207, 207W Network Cameras	\$ 14
ACC STAND PLASTIC AXIS 210/211	23452	Plastic stand for AXIS 210 and 211 (A) Network Cameras	\$ 14

AXIS P3367-VE CASING KIT	5800-601	The kit contains a complete AXIS P3367-VE enclosure, heater and cable cover. The kit could also be used for converting an indoor version of AXIS P3346, P3367, P3384 and P3365 to an outdoor VE version.	\$ 211
CONN KIT AXIS P1311	5500-851	Kit for the AXIS P13XX-series. Content: one terminal connector 4P str 250mm BP LF and one 2P STR 3.81MM BP LF.	\$ 9
CONN KIT AXIS Q7404	5700-161	Terminal connectors for AXIS Q7404. Includes 8 pcs 2P 2.50MM, 4 pcs 4P 2.50MM and one 2P 3.81MM. In total 13 connectors.	\$ 34
AXIS M3004 LENS	5800-641	Original M12 lens for AXIS M3004 2.8mm. Focus tool included.	\$ 48
AXIS M3005 LENS	5800-651	Original M12 lens for AXIS M3005 2.8mm. Focus tool included.	\$ 48
LENS 3-8MM 13VG308ASIR	5700-601	Varifocal 3-8mm DC-Iris Lens, CS mount. Original Lens for AXIS P1343	\$ 74
LENS 3-8MM TG3Z0312FCS-MPIR-12	5700-611	Original DC-IRIS IR-corrected Megapixel lens for P1344.	\$ 191
LENS CS 2.8-8MM F1.2 DC-I MP	5700-881	CS mounted Varifocal 2.8-8 mm DC-iris megapixel lens. Original lens for AXIS M1114.	\$ 146
LENS CS VF 2.8-8MM F1.2 P-IRIS	5800-671	Original CS mounted varifocal P-Iris lens 2.8-8mm for AXIS Q1604/14 and AXIS P1355/57	\$ 146
LENS CS VF 2.8-8MM F1.2 DC-IR	5800-661	Original CS mounted varifocal DC-Iris lens 2.8-8mm for AXIS Q1602/04 and AXIS P1354/55	\$ 146
AXIS LENS FUJINON CS 2.8-8MM P-IRIS	5506-721	Standard CS mounted varifocal P-Iris lens 2.8-8mm for AXIS Q1615.	\$ 146
LENS CS 2.8MM M13F02820	5700-821	Fixed Iris Megapixel Lens 2.8mm, F2.0, CS mount. Original Lens for AXIS M1103/4.	\$ 48
LENS CS 2.9-8.2MM F1.4 DC SVGA	5700-871	Varifocal 2.9-8.2mm CS mounted SVGA DC-iris lens. Original lens for AXIS M1113	\$ 68
LENS CS 6.0MM F1.8 MP	5700-861	CS mounted 6.0 mm megapixel lens. Original lens for AXIS M1103/4	\$ 48
AXIS LENS TAMRON C 4-13MM DC-IRIS	5506-731	Standard C mounted varifocal DC-Iris lens 4-13mm for AXIS Q1635.	\$ 391
M3004-V/05-V FOCUS TOOL 2PCS	5503-581	Focus tool for AXIS M3004-V/M3005-V (2pcs)	\$ 11
MAIN BODY CUP M3011/14 10PCS	5700-511	Metal cup for AXIS M3011 and AXIS M3014 Network Cameras. 10 pcs.	\$ 206
POWER SUPPLY AXIS T8412	5700-704	Power supply for AXIS T8412 Installation Display	\$ 58
SPR AXIS P3343-VE SCREW KIT	5700-351	Screw Kit for AXIS P3343-VE and P3344-VE as spare part. Includes mounting screws, plugs and I/O connector.	\$ 5
SPR AXIS P3343/-V SCREW KIT	5700-301	Screw kit för AXIS P3343, P3343-V, P3344 and P3344-V as spare part. Includes mounting screws, plugs and I/O connector.	\$ 4

AXIS P3343-VE/44-VE CASING KIT	5700-841	The kit contains mounting bracket, bottom casing, heater and cable cover required for converting an indoor version of AXIS P3343/P3344 to an outdoor VE version. Note: Dome kit is not included, has to be ordered separately.	\$ 136
AXIS P3364-VE CASING KIT	5506-471	The kit contains mounting bracket, bottom casing, heater and cable cover required for converting an indoor version of AXIS P3364-V to an outdoor VE version. Note: Dome kit is not included, has to be ordered separately.	\$ 136
SPR BRACKET KIT AXIS Q60XX/P55XX	5700-851	Bracket kit for surface mounting a camera on a hard ceiling. Compatible with Q603X and P553X. Content: Bracket, screws with washers and wave springs.	\$ 24
CONN KIT AXIS M7014	5800-621	Terminal connectors for AXIS M7014. Includes 2 pcs TERMINAL CONN 2P STR 2.50MM, rubber feet and mounting screws for the encoder.	\$ 9
SPR CONN KIT AXIS Q7401	5500-831	Connectors for AXIS Q7410 as spare parts. Includes two 2pin STR 2.50MM, one 6pin STR 2.50MM and one 2pin STR 3.81MM. In total 4 connectors.	\$ 19
CONN KIT AXIS P7214/Q7411	5800-611	Terminal connectors for AXIS P7214 and AXIS Q7411. Includes 1 pcs TERMINAL CONN 6P STR 2.50MM, 2 pcs TERMINAL CONN 2P STR 2.50MM, rubber feet and mounting screws for the encoder.	\$ 9
SPR CONN PUSH PULL PLUG IDC-8 IP67	5700-371	Spare RJ45 connector plug for AXIS Q603X-E & AXIS P55XX-E. IP67 rated.	\$ 48
NETWORK CABLE WITH GASKET 5M	5700-331	Shielded outdoor network cable 5 meter. Pre mounted rubber gasket and male RJ45 connectors. For use with AXIS M11-E series, AXIS P13-E series, AXIS Q16-E series, AXIS Q1755-E, AXIS Q19-E series, AXIS P33-VE series and AXIS T92/3-E housings.	\$ 10
AXIS Q60XX-C MULTI CONNECT CABLE 5M	5800-491	Cable between AXIS Q60XX-C and connection box AXIS T8605	\$ 136
AXIS Q60XX-C MULTI CONNECT CABLE 7M	5800-821	Cable between AXIS Q60XX-C and connection box AXIS T8605	\$ 175
SPR COVERT CAMERA M7001	5700-471	Cover Camera for AXIS M7001 as spare part.	\$ 146
AXIS P5512 DOME KIT	5800-141	Dome kit for AXIS P5512. Clear-/smoked dome and ome cover included.	\$ 48
AXIS P5512-E DOME KIT	5800-281	Dome kit for AXIS P5512-E. Clear-/smoked dome and dome cover included.	\$ 48
AXIS P553X CLEAR DOME	5800-251	Original clear dome for AXIS P5522/-E, AXIS P5532/-E, AXIS P5534/-E.	\$ 33
AXIS P553X SMOKED DOME	5800-191	Original smoked dome for AXIS P5522/-E, AXIS P5532/-E, AXIS P5534/-E.	\$ 33
AXIS P5544 LENS KIT	5800-401	Spare part lens kit for AXIS P5544	\$ 391

AXIS Q603X-E DOME COVER RING	5800-101	Dome cover ring for AXIS Q603X-E including screws.	\$ 18
AXIS Q604X-S CLEAR DOME A	5700-751	Original clear dome for AXIS Q604X-S cameras	\$ 68
AXIS Q604X-S SMOKED DOME A	5504-791	Smoked dome for AXIS Q604X-S cameras	\$ 77
SPR ELECTRONIC KIT T95A00	5700-081	Electronic boards for replacement in AXIS T95A00 110-230 VAC. Includes 4 boards.	\$ 211
SPR ELECTRONIC KIT T95A10	5700-091	Electronic boards for replacement in AXIS T95A10 24 VAC. Includes 3 boards.	\$ 128
SPR FAN/HEATER RING AXIS 215 PTZ-E	5700-281	Spare fan and heater ring for AXIS 215-PTZ-E. Includes 2 fans and 2 heaters.	\$ 117
SPR HEATER/FAN KIT T95A00	5700-101	Replacement kit with 3 heaters and fans for AXIS T95A00	\$ 94
SPR HEATER/FAN KIT T95A10	5700-111	Replacement kit with 3 heaters and fans for AXIS T95A10	\$ 97
SPR SCREW AND GLAND KIT T95A	5700-151	Replacement cable gland plate, cable glands and screws for AXIS T95A	\$ 24
AXIS Q60XX-C COOLING MODULE	5800-501	Peltier element, inside and outside fan for AXIS Q60XX-C	\$ 979
SPR LENS 3-8MM M13VG308 AXIS 211M	5700-001	Original lens for AXIS 211M as spare part	\$ 195
SPR MAINS ADAPTOR PS-V EUR	5700-221	Power supply PS-V for AXIS M10 series. White Sparepart	\$ 38
MAINS ADAPTOR PS-H	5500-331	5V DC 2A power supply with 1.35x3.5 plug. Center (+) polarity.	\$ 38
SPR POWER SUPPLY 1U 310W FRONT	5700-071	Replacement power supply for AXIS Q7900 encoder rack	\$ 322
SPR POWER SUPPLY 1U 300W BL. FRONT	5800-861	Replacement power supply for AXIS Q7920 Video Encoder Chassis	\$ 322
SPR POWER SUPPLY AXIS 215 PTZ-E	5700-361	Spare Power supply for AXIS 215PTZ-E. All regions incl. Japan.	\$ 38
SPR SUNSHIELD KIT T95A	5700-141	Replacement sunshield and lid for AXIS T95A	\$ 58
AXIS P5512-E SUNSHIELD	5800-151	Sunshield for AXIS P5512-E.	\$ 24
SUNSHIELD KIT AXIS P553X-E	5700-961	Sunshield for AXIS P553X-E including mounting screws.	\$ 28
SUNSHIELD AXIS Q603X-E	5700-951	Sunshield for AXIS Q603X-E.	\$ 28
AXIS Q60XX-C SUNSHIELD	5800-471	Sunshield for AXIS Q60xx-C series	\$ 38
SUNSHIELD KIT T92E	5700-941	Sunshield for AXIS P134X-E, AXIS Q1755-E and AXIS Q192X-E. Includes mounting screws and Torx key.	\$ 34
FRONT GLASS KIT AXIS T92E20/21	5700-831	Complete Front Kit for AXIS T92E20/21. Content: Front Cover, Front Glass, Gasket & Screws.	\$ 20
ELECTRONIC KIT AXIS T92E20	5700-971	Sparepart including the electronics module of the AXIS T92E20 housing including fan and screws.	\$ 175

FRONT KIT T92E24	5800-041	Front kit including metal frame, window, heater, gasket and screws for AXIS T92E24 Thermal camera housing. Compatible with the 60mm TA-lens.	\$ 930
AXIS SUNSHIELD B	5800-971	Sunshield compatible with AXIS P1765-LE and AXIS Q1931-E	\$ 28
AXIS SUNSHIELD C	5800-981	Sunshield compatible with AXIS Q1765-LE PT Mount	\$ 28
WEATHERSHIELD KIT P3343/44-VE	5800-011	Original weathershield for AXIS P3343, AXIS P3344-VE, AXIS P3363-VE and AXIS P3364-VE. Screws included.	\$ 20
WEATHERSHIELD KIT P3346/67-VE	5800-021	Original weathershield for AXIS P3346, AXIS P3367-VE and AXIS P3384-VE. Screws included.	\$ 20
AXIS WEATHERSHIELD KIT D	5506-761	Weathershield with screws for protecting the dome of an AXIS Q35-VE camera from rain, snow and sun.	\$ 20
AXIS WEATHERSHIELD KIT E	5506-751	Weathershield with screws for protecting the dome of an AXIS P32-VE camera from rain, snow and sun.	\$ 18
DROP CEILING KIT AXIS P553X/4X	5800-131	Original kit for mounting a AXIS P553X/4X pan tilt zoom camera in a soft/drop ceiling	\$ 77
AXIS T8412/T8414 CARRYING CASE	5800-331	Sparepart carrying case for the AXIS T8412 and T8414 installation displays, with included sunshield, velcro wrist strap and lanyard.	\$ 28
SPR FAN CASSETTE AXIS Q7900 E2	5800-271	Original spare part fan cassette for AXIS Q7900 E2.	\$ 195
SPR FAN CASSETTE AXIS Q7920	5800-851	Original spare part fan cassette for AXIS Q7920.	\$ 97
AXIS T98A05 CABINET DOOR	5800-521	Cabinet door for AXIS T98A Surveillance Cabinet. Stand alone. Used in T98A15-VE Cabinets.	\$ 126
AXIS T98A06 CABINET DOOR	5800-531	Cabinet door for AXIS T98A Surveillance Cabinet. Compatible cameras: AXIS M111X-E, AXIS P13XX-E, AXIS Q16XX-E, AXIS Q17XX-E, AXIS Q191X-E, AXIS Q192X-E. Used in T98A16-VE Cabinets.	\$ 126
AXIS T98A07 CABINET DOOR	5800-541	Cabinet door for AXIS T98A Surveillance Cabinet. Compatible cameras: AXIS P33-VE/-LVE and the outdoor bullet-style Q1765 and Q1931 cameras. Used in T98A17-VE Cabinets.	\$ 126
AXIS T98A08 CABINET DOOR	5800-551	Cabinet door for T98A. Compatible products: AXIS T91A61 Wall bracket for use with AXIS P55 and Q60-series or fixed dome pendant kits. Used in T98A18-VE Cabinets.	\$ 126
AXIS T98A09 CABINET DOOR	5800-871	Cabinet door for AXIS T98A. Compatible products: AXIS P54-Series. Used in T98A19-VE Cabinets.	\$ 126

AXIS P135X CONN KIT	5800-381	Terminal connectors for AXIS P135X-series. Includes 1 pcs TERMINAL CONNECTOR 4P STR 2.50MM, 1 pcs TERMINAL CONNECTOR 2P STR 3.81MM, 2 pcs TERMINAL CONNECTOR 2P STR 2.50MM	\$ 9
AXIS T8123/4-E MIDSPAN SPARE KIT	5800-371	2pcs RJ-45 waterproof plugs and 1pcs grounding wire for outdoor midspan T8123/4-E	\$ 28
AXIS M311X-R 2MM M12 LENS	5700-711	Original lens for AXIS M311X-R as spare part	\$ 77
FRONT KIT 60MM AXIS Q872X-E	5800-311	Frontkit for AXIS Q872X-E with 60mm lens as spare part.	\$ 1,469
FRONT KIT 35MM AXIS Q872X-E	5800-301	Frontkit for AXIS Q872X-E with 30mm lens as spare part	\$ 685
PT IR ILLUMINATOR KIT B	5800-921	Spare part illuminator kit for AXIS Q8665-LE. NOTE: it is not possible to upgrade a Q8665-E to become LE version	\$ 1,273
AXIS Q86-E LIGHT SENSOR BOX 120 V	5505-771	Light sensor box with integrated power supply for controlling IR illuminators and power AXIS Q8665-LE. Input power 120V AC.	\$ 627
AXIS Q8721-E/22-E BASE	5800-951	Base assembly for the AXIS Q8721-E/22-E.	\$ 685
AXIS CONNECTOR A 2P2.5 STR 10PCS	5505-261	Axis male connector for legacy IO port . Pitch: 2.50 mm. 2pos terminal block. 10pack.	\$ 19
AXIS CONNECTOR A 4P2.5 STR 10PCS	5800-891	Axis male connector for limited and full IO port . Pitch: 2.50 mm. 4pos terminal block. 10pack.	\$ 19
AXIS CONNECTOR A 6P2.5 STR 10PCS	5505-271	Axis male connector for extended IO port . Pitch: 2.50 mm. 6pos terminal block. 10pack	\$ 58
AXIS CONNECTOR A 2P3.81 STR 10PCS	5800-901	Axis male connector for low voltage power. Pitch: 3.81 mm. 2pos terminal block. 10pack	\$ 19
AXIS CONNECTOR A 3P3.81 STR 10PCS	5505-281	Axis male connector for low voltage power. Pitch: 3.81 mm. 3pos terminal block. 10pack	\$ 28
AXIS CONN A 4P3.81 STR IN/OUT 10P	5505-291	Axis male connector for audio. Pitch: 3.81 mm. 2+2pos terminal block. 10pack	\$ 38
AXIS CONNECTOR A 4P3.81 STR 10PCS	5505-251	Axis male connector for low voltage power. Pitch: 3.81 mm. 4pos terminal block. 10pack	\$ 28
AXIS CONNECTOR A 2P5.08 STR 10PCS	5505-301	Axis male connector for low voltage power. Pitch: 5.08 mm. 2pos terminal block. 10pack	\$ 28
SPR 5 PORT GB ETHERNET SWITCH KIT	5800-881	Spare part internal switch for the AXIS Q8721-E/22-E Dual cameras. Includes brackets, network cable coupler and a short patch cable.	\$ 587
STAINLESS STEEL STRAP 570MM 1 PAIR	5700-701	Stainless steel straps for polemounts, hose clamp type. Compatible with AXIS T91A47, T91A67 and T91C67. Standard straps for AXIS T91C67 Stainless pole mount.	\$ 24
AXIS Q8414-LVS IR WINDOW A 5P	5506-341	Standard IR window with microphone hole and water-stop membrane for AXIS Q8414-LVS. 5 pcs.	\$ 146

AXIS POE ACTIVE SPLITTER 5V AF	5008-001	Power over Ethernet (802.3af) compatible. Use with Power over Ethernet-midspans or PoE-enabled switches to enable Power over Ethernet for AXIS M1011/-W, AXIS M1031-W, AXIS M1043-W and AXIS 1044-W.	\$ 58
AXIS POE MIDSPAN 8-PORT	5012-004	802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length is 328ft/100m. Supporting up to eight Axis Network cameras/video servers. Metal casing.	\$ 587
AXIS POE MIDSPAN 16-PORT	5012-014	802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length is 328ft/100m. Supporting up to sixteen Axis Network cameras/video servers. Metal casing.	\$ 783
AXIS T8120 15W MIDSPAN 1-PORT	5026-204	Provides power over Ethernet to Axis network video products with built-in PoE support. AXIS T8120 is IEEE 802.3af compliant, ensuring compatibility with all Axis PoE Class 1-3 products. The midspan can be installed on a wall or shelf.	\$ 58
AXIS T8120 15W MIDSPAN 10PCS	5026-224	Provides power over Ethernet to Axis network video products with built-in PoE support. AXIS T8120 is IEEE 802.3af compliant, ensuring compatibility with all Axis PoE Class 1-3 products. The midspan can be installed on a wall or shelf. 10 pcs.	\$ 518
AXIS T81B22 DC 30W MIDSPAN	5023-121	PoE midspan for PTZ dome- and fixed outdoor cameras. IEEE802.3af compliant (max. 15W) at 12/24V DC input. IEEE802.3at compliant (max. 30W) at 12V DC input. Temp spec: -20 °C to 65 °C (-4 °F to 149 °F).	\$ 97
AXIS T8123-E OUTDOOR MIDSPAN 30w	5030-234	Outdoor ready IP66-rated midspan compliant with IEEE802.3af and 802.3at. Built in surge protection and IP66-rated male RJ45 connector is included. Delivers up to 30W. Temperature specification: -40°C to 55°C (-40° to 131°F) for 30W and -40°C to 65°C (-40°F to 149°F) for 15.4W.	\$ 244
AXIS T8133 30W MIDSPAN	5900-294	Single port midspan for Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4. Replaces AXIS T8123.	\$ 77
AXIS T8134 MIDSPAN 60W	5900-334	High PoE 1-port midspan 60W. Compliant with 802.3.at and PoE 802.3af.	\$ 146
AXIS T8124-E OUTDOOR MIDSPAN 60W	5031-244	Outdoor ready IP66-rated midspan for AXIS Q60-E. Built in surge protection and IP66-rated male RJ45 connector is included. Delivers up to 60W. Temperature specification: -40°C to 50°C (-40° to 122°F).	\$ 313
AXIS T8125 AC 24V MIDSPAN 60W	5900-251	60W PoE midspan for 24V AC input.	\$ 156

AXIS T8126 HIGH POE SPLITTER 12V	5014-501	12V DC High PoE splitter (802.3.at pre-standard). Requires either a AXIS T8121 midspan (max 24W output) or a 802.3af PoE midspan (max 12W output) Adapter cable for AXIS 210, 213PTZ, 214PTZ, 215PTZ and 225FD is included.	\$ 87
AXIS T8128 HIGH POE SPLITTER 24V	5014-511	24V DC High PoE splitter (802.3.at pre-standard). Requires High PoE midspan (AXIS T8121). Adapter cable for AXIS 231D+, 232D+ and 233D is included.	\$ 87
AXIS T8129 PoE EXTENDER	5025-281	Power over Ethernet extender repeats the data signal and forward the PoE to the camera, PoE+ compliant it is compatible with all Axis cameras. No additional power supply is required. The maximum total distance between switch and camera depends on the power input and the power required by the camera, but all cameras can be at least extended to 200 meter connection.	\$ 195
AXIS T8640 POE+ OVER COAX ADAP	5026-401	Pair of Ethernet over COAX adapters that enable use of COAX cables for PoE applications, supports IEEE802.3af/at. Powered by either PoE or power supply, dependent on power requirement at the device end. Diagnostics LEDs for power and link status in both base and device unit. Connectors: BNC and RJ45 connector and power input (for optional power supply). The package contains one base unit and one device unit.	\$ 406
AXIS T8641 POE+ OVER COAX BASE	5028-411	Single Base unit of Ethernet over COAX adapter. The package contains one base unit.	\$ 203
AXIS T8642 POE+ OVER COAX DEVI	5027-421	Single Device unit of Ethernet over COAX adapter. The package contains one device unit.	\$ 203
AXIS T8646 POE+ OVER COAX BLADE	5026-461	Ethernet over COAX blade (6ch) that enable use of COAX cables for PoE applications, supports IEEE802.3af/at. For use with Axis video encoder chassis together with our AXIS T8082 or AXIS T8085 power supplies. Requires one AXIS T8642 POE+ OVER COAX DEVICE for every channel at the camera end.	\$ 685
AXIS T8646 POE+ OVER COAX BLADE KIT	5026-471	A Kit that contains one (1) AXIS T8646 POE+ OVER COAX BLADE and six (6) AXIS T8642 POE+ OVER COAX DEVICE for a complete 6 channel solution.	\$ 1,665

AXIS T8310 CONTROL BOARD	5020-001	Modular control board for professional camera and video management. AXIS T8310 Control Board is a complete control board solution which includes AXIS T8311 Joystick, AXIS T8312 Keypad and AXIS T8313 Jog Dial. Includes required USB cables inter-connecting the units and a 2 meter USB cable to the workstation. AXIS T8310 Video Surveillance Control Board is supported in ACS ver. 3.3 or later.	\$ 1,126
AXIS T8311 JOYSTICK	5020-101	Professional joystick for accurate control of Axis pan/tilt/zoom and dome network cameras. Connects to the workstation over USB. Features a three-axis joystick with X/Y-axis for positioning and turning knob for zoom and 6 push-buttons. Includes a 2 meter USB cable for connection to the workstation. AXIS T8311 Joystick is supported in ACS ver. 3.3 or later.	\$ 391
AXIS T8312 KEYPAD	5020-201	Professional 22 button keypad for quick navigation between workspaces, camera views and PTZ. Connects to the workstation over USB. Includes a 2 meter USB cable for connection to the workstation. AXIS T8312 Keypad is supported in ACS ver. 3.3 or later.	\$ 440
AXIS T8313 JOG DIAL	5020-301	Professional video surveillance jog dial for high precision playback, facilitating functions such as play, pause, index, image steps and fast search. 6 built-in push buttons additionally simplifies video forensics. AXIS T8313 Jog Dial is supported in ACS ver. 3.3 or later.	\$ 391
AXIS T8604 MEDIA CONVERTER SWITCH	5027-041	Four port media converter switch with 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not included). Shelf or DIN-rail mount. Temp spec: -40°C to +75°C (-40°F to 167°F).	\$ 391
AXIS DOME MICROPHONE A	5505-061	A dynamic microphone for sound pickup . Mounted on the inside of the dome of AXIS Q35-V cameras and plugged into the 3.5 mm microphone jack.	\$ 28
AXIS T8351 MICROPHONE 3.5MM	5031-511	AXIS T8351 Microphone 3.5mm is an omnidirectional microphone with a 3.5mm connector, compatible with all Axis network video products supporting a 3.5mm jack for microphone input. Flexible to install, AXIS T8351 adapts to different installation scenarios thanks to a vast range of included accessories and to its dust-and-water proof casing.	\$ 136

AXIS T8353A MICROPHONE 3.5MM	5032-531	AXIS T8353A Microphone 3.5mm is an omnidirectional microphone with a 3.5mm adaptor, compatible with all Axis network video products supporting a 3.5mm jack for microphone input. AXIS T8353A Microphone offers great details and resolution, the capsule has a neutral sonic character and is very natural sounding. The discreet microphone is very reliable even in demanding environments.	\$ 440
AXIS T8353B MICROPHONE PHANTOM POWER	5033-541	AXIS T8353B Microphone Phantom Power is an omnidirectional microphone with an XLR contact and a pigtail adaptor. Power ranges between 12-48V DC. It is compatible with phantom power devices, such as AXIS P8221 Network I/O Audio Module. AXIS T8353B Microphone offers great details and resolution, the capsule has a neutral sonic character and is very natural sounding. The discreet microphone is very reliable even in demanding environments.	\$ 440
AXIS T8353 MOUNT	5505-041	Mounting accessory for AXIS T8353 Microphones	\$ 19
AXIS AUDIO EXTENSION CABLE A 5M	5505-131	Audio extension cable for Axis 3.5mm mono microphones. Length 5m (197 in)	\$ 19
AXIS MULTICABLE A I/O AUDIO PWR 1M	5505-031	Multi-connector cable for power (12VDC), audio and I/O port. 1m (40 in)	\$ 77
AXIS MULTICABLE A I/O AUDIO PWR 5M	5505-021	Multi-connector cable for power (12VDC), audio and I/O port. 5m (197 in)	\$ 97
AXIS MULTICABLE B I/O AUDIO PWR 2.5M	5505-511	Multi-connector cable for AC/DC power, audio in/out and I/O connectivity. 2.5m (8.2 ft)	\$ 77
AXIS MULTICABLE C I/O AUDIO PWR 1M	5506-201	Multi-connector cable for power, audio and I/O connectivity. 1m (3.3 ft)	\$ 107
AXIS MULTICABLE C I/O AUDIO PWR 5M	5506-191	Multi-connector cable for power, audio and I/O connectivity. 5m (16.4 ft)	\$ 136
AXIS T8415 WIRELESS INSTALLATION TOOL	5506-231	Camera installation made easy. Battery driven Wi-Fi access point with PoE+ to camera for use with AXIS Installation application on your iOS or Android device.	\$ 587
AXIS T8415 INSTALLATION BAG	5506-871	Durable soft bag to carry the AXIS T8415 Wireless Installation Tool, with space for extra battery, charger, network cables etc.	\$ 48
AXIS INSTALLATION TOOL BATTERY 12V3.4Ah	5506-551	Additional battery for AXIS T8415 Wireless Installation Tool.	\$ 97
AXIS INSTALLATION CHARGER ADAPTOR 12V1A	5506-561	Charging adaptor for AXIS T8415 Wireless Installation Tool.	\$ 48

AXIS P8221	0321-004	Network I/O and audio module. Eight digital ports configurable as inputs or outputs. Two-way audio configurable to simplex, half or full duplex. Built-in pre-amp, phantom power and gain control for a balanced microphone. Line and speaker output. Serial port RS-232/422/485. Power over Ethernet enabled. Includes power supply.	\$ 342
AXIS P8221 BULK 10PCS	0321-021	AXIS P8221 in 10-pack/bulk. Cannot be sold separately as single pack. NO midspans. Power supplies not included.	\$ 3,380
AXIS SURVEILLANCE microSDXC Card 64GB	5506-801	SD card optimized for surveillance. 64 GB micro SD card with SD card adapter.	\$ 77
AXIS SURVEILLANCE microSDXC Card 64GB 10P	5506-811	SD card optimized for surveillance. 64 GB micro SD card with SD card adapter. 10 pcs.	\$ 730