

# INVITATION TO BID

State of Ohio  
Department of Administrative Services  
General Services Division  
Office of Procurement Services

The Original Signed Bid must be submitted to the Office of Procurement Services to receive consideration for award.		BIDDER NAME	
BID NUMBER <b>RS900812</b>	OPENING DATE (1:00 p.m.) <b>NOVEMBER 23, 2011</b>	STREET ADDRESS <input type="checkbox"/> Check if remit address is different and list on separate sheet	
General Services Division Office of Procurement Services 4200 Surface Road Columbus, OH 43228-1395 Attn: Bid Desk		CITY STATE ZIP	
		COUNTY	MBE/EDGE CERTIFICATE NUMBER
		TELEPHONE NO. ( )	TOLL FREE NO. 1 - ( )
		CONTACT PERSON	FAX NO. ( )
REQ./INDEX NO. <b>GDC093</b>	BID NOTICE DATE <b>NOVEMBER 18, 2011</b>	CONTRACTOR'S E-MAIL ADDRESS	

SELECT YOUR PREFERRED METHOD OF RECEIVING PURCHASE ORDERS AND ENTER THE E-MAIL OR FAX NUMBER INFORMATION (ONLY SELECT ONE METHOD)

E-Mail  Fax

In addition to the standard terms for payment, the payment terms for state agency(ies) will be 2%, 10 Days, Net 30 Days unless otherwise stated in the following space. If no discount is offered, bidder should circle "Net 30 Days". \_\_\_\_\_%, \_\_\_\_\_ Days, Net 30 Days

**PARTICIPATING AGENCY(IES):** ALL STATE AGENCIES, AND PROPERLY REGISTERED COUNTIES, TOWNSHIPS, MUNICIPAL CORPORATIONS, REGIONAL TRANSIT AUTHORITIES, REGIONAL AIRPORT AUTHORITIES, PORT AUTHORITIES, SCHOOL DISTRICTS CONSERVANCY DISTRICTS, TOWNSHIP PARK DISTRICTS AND PARK DISTRICTS, PURSUANT TO SECTION 125.04(B) OF THE OHIO REVISED CODE, THE COOPERATIVE PURCHASING ACT. STATE UNIVERSITIES, STATE VOCATIONAL SCHOOLS, STATE COMMUNITY COLLEGES OR OTHER INSTITUTIONS OF HIGHER EDUCATION MAY USE THESE CONTRACTS. SUCH USE HOWEVER, IS BASED UPON EACH ENTITY'S PROCUREMENT AUTHORITY.

**ADDENDUM FOR CHANGE  
ADDENDUM NO.: 1  
REVISION DATE: November 18, 2011**

THE DEPARTMENT OF ADMINISTRATIVE SERVICES, OFFICE OF PROCUREMENT SERVICES IS SOLICITING BIDS FOR:  
**NEW, MODEL YEAR 2012 TRUCKS, UTILITY VEHICLES and CARGO VANS**

Attached are pages 12, 28-35, and even pages 72-110 of this Invitation to Bid. Remove the corresponding pages from the existing bid and replace with the attached.

- As indicated herein this addendum is issued to make the following changes;
- To add the "DATA SHEET" language to the Specifications on page 12.
  - To remove the rear window defroster minimum requirement for Items 10AT, 11AT, 12AT, and 13AT. The rear window defroster has been changed to an additional option for these items.
  - To remove the locking tailgate requirement for all Cab and Chassis specifications.

SPECIFICATIONS (Cont'd.)

**\*DATA SHEET:** Shown below are the specification requirements for the vehicles that the State desires to purchase. Any deviations from the specifications are to be outlined on company letterhead and attached to the bid response. Failure to comply may deem the bid not-responsive. The State retains the right to accept or reject variations and / or exceptions to the specifications directly related to model year variations and manufacturer variations that meet or exceed the basic usage requirements as explained in SCOPE AND CLASSIFICATION on page 7.

**Sport Utility Vehicle (SUV) – Compact – Gasoline**

Item Number 2AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	4 / 2.4	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	172		
Automatic Transmission	Automatic		
Locking Differential	NA		
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	5
Fuel Capacity (gals.)	13.5	Front Seat Type	Bucket
Tires	All Season	Seat Covering	Cloth
Spare Tire	Compact	Floor Covering	Carpet
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	103	2 Sets of Keys with FOBS	Required
Head Room (Front/Rear)	40 / 39	Intermittent Windshield Wipers	Required
Leg Room (Front/Rear)	40 / 35	Rear Window Defroster	Required
Shoulder Room (Front/Rear)	54 / 54	Floor Mats	Front/Rear
Hip Room (Front/Rear)	52 / 47	Radio	Std. (No SAT)
Passenger Volume (cu.ft.)	99	Exterior Rear View Mirror	Dual
Base Curb Weight (lbs.)	3,200	Rear Cargo Light	Automatic
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the addition of language to Specifications.

## Pickup – Compact, 2WD, Regular Cab – Gasoline

Item Number 10AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	4 / 2.9	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	185	Rear Door Type	Locking Tailgate
Automatic Transmission	Automatic	Bed Length (ft)	6
Locking Differential	Ltd. Slip – Mfg Std	Rear Step Bumper	Mfg Std
Drivetrain	2WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	3
Fuel Capacity (gals.)	19	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Cloth
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	111	2 Sets of Keys with FOBS	Required
Head Room (Front)	39	Intermittent Windshield Wipers	Required
Leg Room (Front)	40	Rear Window Wiper	NA
Shoulder Room (Front)	57	Rear Window Defroster	*NA
Hip Room (Front)	53	Floor Mats	Front
Cargo Volume (cu.ft.)	44	Radio	Std. (less SAT)
Base Curb Weight (lbs.)	3,365	Exterior Rear View Mirror	Dual
Payload (lbs.)	1,485	Cargo Dome Lighting	Required
Gross Vehicle Weight Rating(GVWR)	4,850		
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the minimum requirement for a rear window defroster.

ITEM – 10AT – Pickup – Compact, 2WD, Regular Cab – Gasoline

DELIVERY: \_\_\_\_\_ DAYS A.R.O. (See IV.A.) INDICATE CITY/STATE OF MANUFACTURER: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_ MFG: \_\_\_\_\_ MODEL: \_\_\_\_\_ MODEL NUMBER: \_\_\_\_\_

Item ID No.: TBD Estimated # of Units: **13** UNIT PRICE: \_\_\_\_\_

List any exceptions to the specifications:  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Delivery charge per mile, per vehicle round trip map mileage for delivery by the contractor: \$0.\_\_\_\_\_. The maximum delivery charge the state will pay is \$.60 or less per mile. The round trip map mileage figure will be multiplied by an estimated figure of 300 miles and added to the base cost of the vehicle for bid evaluation purposes only. If there is no delivery charge per mile round trip map mileage rate supplied or the calculated value of the delivery charge is less than the minimum delivery charge; the minimum delivery charge (Not to exceed \$50.00) will be used for evaluation purposes.

Minimum Delivery Charge, Not to Exceed \$50.00: \_\_\_\_\_

<u>CONTRACTOR'S ORDER NO.</u>	<u>OPTIONS</u>	<u>Units to Eval.</u>	<u>UNIT COST</u>
_____	30 Day Tag		\$ _____
_____	Parts Manual (Bidder to Specify Paper or Electronic)		\$ _____
_____	Shop Manual (Bidder to Specify Paper or Electronic)		\$ _____
_____	Additional Set of Keys	7	\$ _____
_____	Vinyl Seat Covering	6	\$ _____
_____	Bed Liner	2	\$ _____
_____	*Rear Window Defroster		\$ _____
_____	Additional Option Package (Bidder to specify type: _____).		\$ _____
_____	Additional Option Package (Bidder to specify type: _____).		\$ _____

UNSPECIFIED OPTION PRICE: \_\_\_\_\_% above manufacturer invoice (Not to exceed 3.00%)

Any option not specified in the options table on the pricing pages will be made available to the ordering entities, following Contract award, at the Unspecified Option Price. If no Unspecified Option Price is provided by the Bidder, the State will assume that the price will be equal to the manufacture invoice. The Unspecified Option Price and Additional Option Packages specified by the Bidder, will not be used in the vehicle evaluation.

List standard paint colors: \_\_\_\_\_  
\_\_\_\_\_

Contains recycled materials – Y/N: \_\_\_\_\_ if Yes \_\_\_\_\_%. (Will not be part of the evaluation)

\*Indicates the addition of Rear Window Defroster to the Options table.

## Pickup – Compact, 4WD, Regular Cab – Gasoline

Item Number 11AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	4 / 2.9	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	185	Rear Door Type	Locking Tailgate
Automatic Transmission	Automatic	Bed Length (ft)	6
Locking Differential	Locking Differential	Rear Step Bumper	Mfg Std
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	3
Fuel Capacity (gals.)	19	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Cloth
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	111	2 Sets of Keys with FOBS	Required
Head Room (Front)	39	Intermittent Windshield Wipers	Required
Leg Room (Front)	44	Rear Window Wiper	NA
Shoulder Room (Front)	57	Rear Window Defroster	*NA
Hip Room (Front)	53	Floor Mats	Front
Cargo Volume (cu.ft.)	44	Radio	Std. (less SAT)
Base Curb Weight (lbs.)	3,685	Exterior Rear View Mirror	Dual
Payload (lbs.)	1,465	Cargo Dome Lighting	Required
Gross Vehicle Weight Rating(GVWR)	5,150		
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the minimum requirement for a rear window defroster.

ITEM – 11AT – Pickup – Compact, 4WD, Regular Cab – Gasoline

DELIVERY: \_\_\_\_\_ DAYS A.R.O. (See IV.A.) INDICATE CITY/STATE OF MANUFACTURER: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_ MFG: \_\_\_\_\_ MODEL: \_\_\_\_\_ MODEL NUMBER: \_\_\_\_\_

Item ID No.: TBD Estimated # of Units: 2 UNIT PRICE: \_\_\_\_\_

List any exceptions to the specifications:  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Delivery charge per mile, per vehicle round trip map mileage for delivery by the contractor: \$0.\_\_\_\_\_. The maximum delivery charge the state will pay is \$.60 or less per mile. The round trip map mileage figure will be multiplied by an estimated figure of 300 miles and added to the base cost of the vehicle for bid evaluation purposes only. If there is no delivery charge per mile round trip map mileage rate supplied or the calculated value of the delivery charge is less than the minimum delivery charge; the minimum delivery charge (Not to exceed \$50.00) will be used for evaluation purposes.

Minimum Delivery Charge, Not to Exceed \$50.00: \_\_\_\_\_

<u>CONTRACTOR'S ORDER NO.</u>	<u>OPTIONS</u>	<u>Units to Eval.</u>	<u>UNIT COST</u>
_____	30 Day Tag		\$ _____
_____	Parts Manual (Bidder to Specify Paper or Electronic)		\$ _____
_____	Shop Manual (Bidder to Specify Paper or Electronic)		\$ _____
_____	Additional Set of Keys	1	\$ _____
_____	Vinyl Seat Covering	1	\$ _____
_____	Bed Liner	1	\$ _____
_____	Tow Hitch / 7-Pin Plug / Brake Controller	1	\$ _____
_____	All-Terrain Tires	1	\$ _____
_____	*Rear Window Defroster		\$ _____
_____	Additional Option Package (Bidder to specify type: _____).		\$ _____
_____	Additional Option Package (Bidder to specify type: _____).		\$ _____

UNSPECIFIED OPTION PRICE: \_\_\_\_\_% above manufacturer invoice (Not to exceed 3.00%)

Any option not specified in the options table on the pricing pages will be made available to the ordering entities, following Contract award, at the Unspecified Option Price. If no Unspecified Option Price is provided by the Bidder, the State will assume that the price will be equal to the manufacture invoice. The Unspecified Option Price and Additional Option Packages specified by the Bidder, will not be used in the vehicle evaluation.

List standard paint colors: \_\_\_\_\_  
\_\_\_\_\_

Contains recycled materials – Y/N: \_\_\_\_\_ if Yes \_\_\_\_\_%. (Will not be part of the evaluation)

\*Indicates the addition of Rear Window Defroster to the Options table.

**Pickup – Compact, 2WD, Extended Cab – Gasoline**  
Item Number 12AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	5 / 3.7	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	242	Rear Door Type	Locking Tailgate
Automatic Transmission	Automatic	Bed Length (ft)	6
Locking Differential	Ltd. Slip – Mfg Std	Rear Step Bumper	Mfg Std
Drivetrain	2WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	5
Fuel Capacity (gals.)	19	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Cloth
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	126	2 Sets of Keys with FOBS	Required
Head Room (Front / Rear)	39 / 37	Intermittent Windshield Wipers	Required
Leg Room (Front / Rear)	42 / 23	Rear Window Wiper	NA
Shoulder Room (Front / Rear)	57 / 57	Rear Window Defroster	*NA
Hip Room (Front / Rear)	53 / 57	Floor Mats	Front
Cargo Volume (cu.ft.)	44	Radio	Std. (less SAT)
Base Curb Weight (lbs.)	3,560	Exterior Rear View Mirror	Dual
Payload (lbs.)	1,940	Cargo Dome Lighting	Required
Gross Vehicle Weight Rating(GVWR)	5,000		
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the minimum requirement for a rear window defroster.

ITEM – 12AT – Pickup – Compact, 2WD, Extended Cab – Gasoline

DELIVERY: \_\_\_\_\_ DAYS A.R.O. (See IV.A.) INDICATE CITY/STATE OF MANUFACTURER: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_ MFG: \_\_\_\_\_ MODEL: \_\_\_\_\_ MODEL NUMBER: \_\_\_\_\_

Item ID No.: TBD Estimated # of Units: 1 UNIT PRICE: \_\_\_\_\_

List any exceptions to the specifications:  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Delivery charge per mile, per vehicle round trip map mileage for delivery by the contractor: \$0.\_\_\_\_\_. The maximum delivery charge the state will pay is \$.60 or less per mile. The round trip map mileage figure will be multiplied by an estimated figure of 300 miles and added to the base cost of the vehicle for bid evaluation purposes only. If there is no delivery charge per mile round trip map mileage rate supplied or the calculated value of the delivery charge is less than the minimum delivery charge; the minimum delivery charge (Not to exceed \$50.00) will be used for evaluation purposes.

Minimum Delivery Charge, Not to Exceed \$50.00: \_\_\_\_\_

<u>CONTRACTOR'S ORDER NO.</u>	<u>OPTIONS</u>	<u>Units to Eval.</u>	<u>UNIT COST</u>
_____	30 Day Tag		\$ _____
_____	Parts Manual (Bidder to Specify Paper or Electronic)		\$ _____
_____	Shop Manual (Bidder to Specify Paper or Electronic)		\$ _____
_____	Additional Set of Keys	1	\$ _____
_____	Vinyl Seat Covering	1	\$ _____
_____	Bed Liner	1	\$ _____
_____	*Rear Window Defroster		\$ _____
_____	Additional Option Package (Bidder to specify type: _____).		\$ _____
_____	Additional Option Package (Bidder to specify type: _____).		\$ _____

UNSPECIFIED OPTION PRICE: \_\_\_\_\_% above manufacturer invoice (Not to exceed 3.00%)

Any option not specified in the options table on the pricing pages will be made available to the ordering entities, following Contract award, at the Unspecified Option Price. If no Unspecified Option Price is provided by the Bidder, the State will assume that the price will be equal to the manufacture invoice. The Unspecified Option Price and Additional Option Packages specified by the Bidder, will not be used in the vehicle evaluation.

List standard paint colors: \_\_\_\_\_

Contains recycled materials – Y/N: \_\_\_\_\_ if Yes \_\_\_\_\_%. (Will not be part of the evaluation)

\*Indicates the addition of Rear Window Defroster to the Options table.

**Pickup – Compact, 4WD, Extended Cab – Gasoline**  
Item Number 13AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	5 / 3.7	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	242	Rear Door Type	Locking Tailgate
Automatic Transmission	Automatic	Bed Length (ft)	6
Locking Differential	Ltd. Slip – Mfg Std	Rear Step Bumper	Mfg Std
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	5
Fuel Capacity (gals.)	19	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Cloth
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	126	2 Sets of Keys with FOBS	Required
Head Room (Front / Rear)	39 / 37	Intermittent Windshield Wipers	Required
Leg Room (Front / Rear)	42 / 23	Rear Window Wiper	NA
Shoulder Room (Front / Rear)	57 / 57	Rear Window Defroster	*NA
Hip Room (Front / Rear)	53 / 57	Floor Mats	Front
Cargo Volume (cu.ft.)	44	Radio	Std. (less SAT)
Base Curb Weight (lbs.)	3,560	Exterior Rear View Mirror	Dual
Payload (lbs.)	1,940	Cargo Dome Lighting	Required
Gross Vehicle Weight Rating(GVWR)	5,000		
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the minimum requirement for a rear window defroster.

ITEM – 13AT – Pickup – Compact, 4WD, Extended Cab – Gasoline

DELIVERY: \_\_\_\_\_ DAYS A.R.O. (See IV.A.) INDICATE CITY/STATE OF MANUFACTURER: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_ MFG: \_\_\_\_\_ MODEL: \_\_\_\_\_ MODEL NUMBER: \_\_\_\_\_

Item ID No.: TBD Estimated # of Units: 2 UNIT PRICE: \_\_\_\_\_

List any exceptions to the specifications:  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Delivery charge per mile, per vehicle round trip map mileage for delivery by the contractor: \$0.\_\_\_\_\_. The maximum delivery charge the state will pay is \$.60 or less per mile. The round trip map mileage figure will be multiplied by an estimated figure of 300 miles and added to the base cost of the vehicle for bid evaluation purposes only. If there is no delivery charge per mile round trip map mileage rate supplied or the calculated value of the delivery charge is less than the minimum delivery charge; the minimum delivery charge (Not to exceed \$50.00) will be used for evaluation purposes.

Minimum Delivery Charge, Not to Exceed \$50.00: \_\_\_\_\_

<u>CONTRACTOR'S ORDER NO.</u>	<u>OPTIONS</u>	<u>Units to Eval.</u>	<u>UNIT COST</u>
_____	30 Day Tag		\$ _____
_____	Parts Manual (Bidder to Specify Paper or Electronic)		\$ _____
_____	Shop Manual (Bidder to Specify Paper or Electronic)		\$ _____
_____	Additional Set of Keys	1	\$ _____
_____	Vinyl Seat Covering	1	\$ _____
_____	Bed Liner	1	\$ _____
_____	*Rear Window Defroster		\$ _____
_____	Additional Option Package (Bidder to specify type: _____).		\$ _____
_____	Additional Option Package (Bidder to specify type: _____).		\$ _____

UNSPECIFIED OPTION PRICE: \_\_\_\_\_% above manufacturer invoice (Not to exceed 3.00%)

Any option not specified in the options table on the pricing pages will be made available to the ordering entities, following Contract award, at the Unspecified Option Price. If no Unspecified Option Price is provided by the Bidder, the State will assume that the price will be equal to the manufacture invoice. The Unspecified Option Price and Additional Option Packages specified by the Bidder, will not be used in the vehicle evaluation.

List standard paint colors: \_\_\_\_\_

Contains recycled materials – Y/N: \_\_\_\_\_ if Yes \_\_\_\_\_%. (Will not be part of the evaluation)

\*Indicates the addition of Rear Window Defroster to the Options table.

## Cab & Chassis – 12,500 lbs., DRW, 2WD, Reg Cab – Gasoline

Item Number 32AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	8 / 5.7	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	322	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	2WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	137	2 Sets of Keys with FOBS	Required
Head Room (Front)	41	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	65	Rear Window Defroster	Required
Hip Room (Front)	60	Floor Mats	Front
Base Curb Weight (lbs.)	5,980	Radio	Std. (less SAT)
Payload (lbs.)	6,520	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating <sub>(GVWR)</sub>	12,500	Cargo Dome Lighting	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 12,500 lbs., DRW, 2WD, Reg Cab – Diesel

Item Number 32CT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	6 / 6.6	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	300	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	2WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	Biodiesel	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	137	2 Sets of Keys with FOBS	Required
Head Room (Front)	41	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	65	Rear Window Defroster	Required
Hip Room (Front)	60	Floor Mats	Front
Base Curb Weight (lbs.)	7,085	Radio	Std. (less SAT)
Payload (lbs.)	5,915	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating <sub>(GVWR)</sub>	13,000	Cargo Dome Lighting	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 12,500 lbs., DRW, 4WD, Reg Cab – Gasoline

Item Number 33AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	8 / 5.7	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	322	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	137	2 Sets of Keys with FOBS	Required
Head Room (Front)	41	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	65	Rear Window Defroster	Required
Hip Room (Front)	60	Floor Mats	Front
Base Curb Weight (lbs.)	6,250	Radio	Std. (less SAT)
Payload (lbs.)	6,250	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	12,500	Cargo Dome Lighting	Required
		Skid Plate(s)	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 12,500 lbs., DRW, 4WD, Reg Cab – Diesel

Item Number 33CT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	6 / 6.6	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	300	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	Biodiesel	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	137	2 Sets of Keys with FOBS	Required
Head Room (Front)	41	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	65	Rear Window Defroster	Required
Hip Room (Front)	60	Floor Mats	Front
Base Curb Weight (lbs.)	7,280	Radio	Std. (less SAT)
Payload (lbs.)	5,720	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	13,000	Cargo Dome Lighting	Required
		Skid Plate(s)	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 12,500 lbs., DRW, 2WD, Ext Cab – FFV

Item Number 34BT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	8 / 6.2	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	385	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	2WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	E-85	Seating Capacity	6
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	140	2 Sets of Keys with FOBS	Required
Head Room (Front)	40	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	65	Rear Window Defroster	Required
Hip Room (Front)	60	Floor Mats	Front
Base Curb Weight (lbs.)	6,345	Radio	Std. (less SAT)
Payload (lbs.)	6,955	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	13,300	Cargo Dome Lighting	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 12,500 lbs., DRW, 2WD, Ext Cab – Diesel

Item Number 34CT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	6 / 6.7	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	300	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	2WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	Biodiesel	Seating Capacity	6
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	137	2 Sets of Keys with FOBS	Required
Head Room (Front)	41	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	65	Rear Window Defroster	Required
Hip Room (Front)	60	Floor Mats	Front
Base Curb Weight (lbs.)	7,115	Radio	Std. (less SAT)
Payload (lbs.)	5,885	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	13,000	Cargo Dome Lighting	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

**Cab & Chassis – 12,500 lbs., DRW, 4WD, Ext Cab – FFV**  
Item Number 35BT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	8 / 6.2	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	385	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	E-85	Seating Capacity	6
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	140	2 Sets of Keys with FOBS	Required
Head Room (Front)	40	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	65	Rear Window Defroster	Required
Hip Room (Front)	60	Floor Mats	Front
Base Curb Weight (lbs.)	6,850	Radio	Std. (less SAT)
Payload (lbs.)	6,450	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	13,300	Cargo Dome Lighting	Required
		Skid Plate(s)	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 12,500 lbs., DRW, 4WD, Ext Cab – Diesel

Item Number 35CT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	6 / 6.6	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	300	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	Biodiesel	Seating Capacity	6
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	137	2 Sets of Keys with FOBS	Required
Head Room (Front)	40	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	65	Rear Window Defroster	Required
Hip Room (Front)	60	Floor Mats	Front
Base Curb Weight (lbs.)	7,665	Radio	Std. (less SAT)
Payload (lbs.)	5,335	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	13,000	Cargo Dome Lighting	Required
		Skid Plate(s)	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

**Cab & Chassis – 12,500 lbs., DRW, 2WD, Crew Cab – Gasoline**

Item Number 36AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	8 / 5.7	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	322	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	2WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	6
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	171	2 Sets of Keys with FOBS	Required
Head Room (Front / Rear)	41 / 39	Intermittent Windshield Wipers	Required
Leg Room (Front / Rear)	41 / 39	Rear Window Wiper	NA
Shoulder Room (Front / Rear)	65 / 65	Rear Window Defroster	Required
Hip Room (Front / Rear)	60 / 63	Floor Mats	Front
Base Curb Weight (lbs.)	6,475	Radio	Std. (less SAT)
Payload (lbs.)	6,025	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	12,500	Cargo Dome Lighting	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 12,500 lbs., DRW, 2WD, Crew Cab – Diesel

Item Number 36CT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	6 / 6.6	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	300	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	2WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	Biodiesel	Seating Capacity	6
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	171	2 Sets of Keys with FOBS	Required
Head Room (Front / Rear)	40 / 39	Intermittent Windshield Wipers	Required
Leg Room (Front / Rear)	41 / 39	Rear Window Wiper	NA
Shoulder Room (Front / Rear)	65 / 65	Rear Window Defroster	Required
Hip Room (Front / Rear)	60 / 63	Floor Mats	Front
Base Curb Weight (lbs.)	7,585	Radio	Std. (less SAT)
Payload (lbs.)	5,415	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	13,000	Cargo Dome Lighting	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

**Cab & Chassis – 12,500 lbs., DRW, 4WD, Crew Cab – Gasoline**

Item Number 37AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	8 / 5.7	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	322	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	6
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	137	2 Sets of Keys with FOBS	Required
Head Room (Front / Rear)	41 / 39	Intermittent Windshield Wipers	Required
Leg Room (Front / Rear)	40 / 39	Rear Window Wiper	NA
Shoulder Room (Front / Rear)	65 / 65	Rear Window Defroster	Required
Hip Room (Front / Rear)	60 / 63	Floor Mats	Front
Base Curb Weight (lbs.)	6,735	Radio	Std. (less SAT)
Payload (lbs.)	5,765	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	12,500	Cargo Dome Lighting	Required
		Skid Plate(s)	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 12,500 lbs., DRW, 4WD, Crew Cab – Diesel

Item Number 37CT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	6 / 6.6	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	300	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	Biodiesel	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	137	2 Sets of Keys with FOBS	Required
Head Room (Front / Rear)	40 / 39	Intermittent Windshield Wipers	Required
Leg Room (Front / Rear)	41 / 39	Rear Window Wiper	NA
Shoulder Room (Front / Rear)	65 / 65	Rear Window Defroster	Required
Hip Room (Front / Rear)	60 / 63	Floor Mats	Front
Base Curb Weight (lbs.)	7,855	Radio	Std. (less SAT)
Payload (lbs.)	5,145	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	13,000	Cargo Dome Lighting	Required
		Skid Plate(s)	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

**Cab & Chassis – 16,000 lbs., DRW, 2WD, Reg Cab – Gasoline**

Item Number 38AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	10 / 6.8	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	362	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	2WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	140	2 Sets of Keys with FOBS	Required
Head Room (Front)	40	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	68	Rear Window Defroster	Required
Hip Room (Front)	67	Floor Mats	Front
Base Curb Weight (lbs.)	6,525	Radio	Std. (less SAT)
Payload (lbs.)	9,975	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	16,500	Cargo Dome Lighting	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 16,000 lbs., DRW, 2WD, Reg Cab – Diesel

Item Number 38CT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	6 / 6.7	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	300	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	2WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	Biodiesel	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	140	2 Sets of Keys with FOBS	Required
Head Room (Front)	40	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	67	Rear Window Defroster	Required
Hip Room (Front)	65	Floor Mats	Front
Base Curb Weight (lbs.)	7,520	Radio	Std. (less SAT)
Payload (lbs.)	8,480	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	16,000	Cargo Dome Lighting	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 16,000 lbs., DRW, 4WD, Reg Cab – Gasoline

Item Number 39AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	10 / 6.8	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	362	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	140	2 Sets of Keys with FOBS	Required
Head Room (Front)	40	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	68	Rear Window Defroster	Required
Hip Room (Front)	67	Floor Mats	Front
Base Curb Weight (lbs.)	6,945	Radio	Std. (less SAT)
Payload (lbs.)	7,555	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	16,500	Cargo Dome Lighting	Required
		Skid Plate(s)	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 16,000 lbs., DRW, 4WD, Reg Cab – Diesel

Item Number 39CT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	6 / 6.7	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	300	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	Biodiesel	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	140	2 Sets of Keys with FOBS	Required
Head Room (Front)	40	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	67	Rear Window Defroster	Required
Hip Room (Front)	65	Floor Mats	Front
Base Curb Weight (lbs.)	8,025	Radio	Std. (less SAT)
Payload (lbs.)	7,975	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	16,000	Cargo Dome Lighting	Required
		Skid Plate(s)	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

**Cab & Chassis – 18,000 lbs., DRW, 2WD, Reg Cab – Gasoline**

Item Number 40AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	10 / 6.8	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	362	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	2WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	140	2 Sets of Keys with FOBS	Required
Head Room (Front)	40	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	68	Rear Window Defroster	Required
Hip Room (Front)	67	Floor Mats	Front
Base Curb Weight (lbs.)	6,525	Radio	Std. (less SAT)
Payload (lbs.)	11,475	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating <sub>(GVWR)</sub>	18,000	Cargo Dome Lighting	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 18,000 lbs., DRW, 2WD, Reg Cab – Diesel

Item Number 40CT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	6 / 6.7	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	300	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	2WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	Biodiesel	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	140	2 Sets of Keys with FOBS	Required
Head Room (Front)	40	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	67	Rear Window Defroster	Required
Hip Room (Front)	65	Floor Mats	Front
Base Curb Weight (lbs.)	7,260	Radio	Std. (less SAT)
Payload (lbs.)	10,730	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	18,000	Cargo Dome Lighting	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 18,000 lbs., DRW, 4WD, Reg Cab – Gasoline

Item Number 41AT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	10 / 6.8	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	362	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	NA	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	140	2 Sets of Keys with FOBS	Required
Head Room (Front)	40	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	68	Rear Window Defroster	Required
Hip Room (Front)	67	Floor Mats	Front
Base Curb Weight (lbs.)	6,825	Radio	Std. (less SAT)
Payload (lbs.)	11,175	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	18,000	Cargo Dome Lighting	Required
		Skid plate(s)	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.

## Cab & Chassis – 18,000 lbs., DRW, 4WD, Reg Cab – Diesel

Item Number 41CT

Standard Specification Items	Minimum Requirements	Standard Specification Items	Minimum Requirements
<b>FY2012</b>			
<b>Powertrain:</b>		<b>Exterior:</b>	
Engine Type (Cylinder/Liter)	6 / 6.7	Body Side Moldings	Mfg. Std.
Horsepower (Net HP)	300	Rear Door Type	*
Automatic Transmission	Automatic	Rear Step Bumper	Mfg Std
Locking Differential	Locking Differential		
Drivetrain	4WD		
<b>Chassis:</b>		<b>Seating:</b>	
Alternative Fuel (Type)	Biodiesel	Seating Capacity	3
Fuel Capacity (single or dual) (gals.)	40	Front Seat Type	Split Bench
Tires	All Season	Seat Covering	Vinyl
Spare Tire	Full Size	Floor Covering	Vinyl
Cooling System	h.d.a.		
<b>Safety:</b>		<b>Accessories:</b>	
Restraint System (Driver and Passenger)	Required	Air Conditioning	Required
Supplemental Restraint System (Driver and Passenger)	Required	Tilt Wheel & Cruise Control	Required
Power Antilock Brakes (Front and Rear)	Required	Power Windows & Door Locks	Required
<b>Dimensions:</b>		Keyed Door Locks	Required
Wheelbase (in)	140	2 Sets of Keys with FOBS	Required
Head Room (Front)	40	Intermittent Windshield Wipers	Required
Leg Room (Front)	41	Rear Window Wiper	NA
Shoulder Room (Front)	67	Rear Window Defroster	Required
Hip Room (Front)	65	Floor Mats	Front
Base Curb Weight (lbs.)	7,590	Radio	Std. (less SAT)
Payload (lbs.)	10,410	Exterior Rear View Mirror	Dual
Gross Vehicle Weight Rating(GVWR)	18,000	Cargo Dome Lighting	Required
		Skid Plate(s)	Required
<b>Electrical:</b>		<b>Warranty:</b>	
Alternator (amps)	Mfg. Std.	Mfg. Standard Warranty (Min.)	3yr / 36,000 Mile
Battery (CCA)	Mfg. Std.		

\*Indicates the removal of the Locking Tailgate Minimum Requirement for the Rear Door Type.