



**OHIO/DAS**  
**State Term Schedule**  
**Price List**  
**2009**







# Surface Mounted Lifts

SIN #253-20, #253-2

## Conventional / Two-Post / Asymmetric

	MODEL NUMBER	DESCRIPTION	*RISE	CAPACITY	NET STS PRICE
	SPOA10	Surface Mounted, Frame Contact Lift. Electric-Hydraulic Operation. True Asymmetrical Design For Easy Vehicle Entry. Factory Rotated Columns Allow Doors Of Vehicle To Be Fully Opened While Properly Positioned On Lift. Arm Restraints -- All Arms.	78" (1981 mm)	10,000 lbs. (4536 kg)	\$3,500.64
	SPOA10 with 3-stage RA arms	Same as SPOA10 with 3-stage FRONT arms. The NEW 3-stage arms allow for an increase in overall arm sweep and minimum arm reach to precisely lift vehicles that are: • Primarily Uni-body construction; • Visually marked OE designated pick-up points on the vehicle; • Wider stance and lower profile; • Accommodates short and long wheelbase vehicles			\$3,693.77
	SPOA82	Surface Mounted, Fixed Pad Drive Over Type with True Asymmetrical Design for Easy Vehicle Entry. Factory Rotated Columns Allow Doors of Vehicle to be Fully Opened while Properly Positioned on Lift. Overhead Equalization System. Electric-Hydraulic Operation. Includes (4) FJ2428. Polymer Pad Adapters and Hinged Approach Ramps.	74" (1880 mm)	7,000 lbs. (3175 kg)	\$4,244.50

## Conventional / Two-Post / Symmetric

	SPO10	Surface Mounted, Frame-Contact Lift. Overhead Equalization System. Electric-Hydraulic Operation. Arm Restraints -- All Arms.	78" (1981 mm)	10,000 lbs. (4536 kg)	\$3,500.64
	SPO10-RA	Same As SPO10 With Front and Rear 3 Stage Arms with FJ6204 Screw-Up RA Truck Style Adapter			\$3,958.54
	SPO12	Surface Mounted, Frame Contact Lift. Overhead Equalization System, Arm Restraints -- All Arms, Electric-Hydraulic Operation. Comes standard with (4) FJ6143, (2) FJ6144 and (1) FJ6158 Adapters.	81-1/16" (2059 mm)	12,000 lbs. (5443 kg)	\$5,778.33
	SPO12-LC	Same As Above-But For Low Ceiling Application. Total Height 11'8" (2' Lower Than Std)			\$6336.53
	SPO12-RA	Same As SPO12 With Front and Rear 3 Stage Arms with FJ6204 Thread Up Adapter and (4) FJ6171-1 Extensions 3 1/2" Tall and (4) FJ6171-2 Extensions 5" Tall			\$6214.43
	SPO15	Surface Mounted, Frame Contact Lift. Clear Floor, Arm Restraints -- All Arms, Electric-Hydraulic Operation. With Overhead Adjustments of 15 ft., 15 ft. 6 in., 16 ft. and 16 ft. 6 in. Includes Air Operated Single Point Release Locking Latches. Comes with Stack Adapters.	89 1/2" (2273 mm)	15,000 lbs. (6804 kg)	\$10,662.02
	SPO15-LC	Same As Above— With Overhead Adjustments of 13 ft. 6 in. and 14 ft. 6 in.			\$10,662.02
	SPO15-SPRINTER	Same As SPO15 with arms specially designed to pick up Sprinter Vans (derates lift to 11,000 lbs.)	89 1/2" (2273 mm)	11,000 lbs. (4990 kg)	\$11,309.94
	FJ5115	Aircraft Tug Adapters. Converts An SPO15 Lift From A Vehicle Lift Into A 14,000 lbs. Aircraft Tug Lift. Kit Contains Two Cross Beams And Adapters.			\$1,786.76
	SPO18	Surface Mounted, Frame Contact Lift. Overhead Equalization System, Arm Restraints -- All Arms, Electric-Hydraulic Operation. With Overhead Adjustments of 15 ft., 15 ft. 6 in., 16 ft. and 16 ft. 6 in. Includes Air Operated Single Point Release Locking Latches.	89 -1/2" (2273 mm)	18,000 lbs. (8165 kg)	\$14,678.50
SPO18-LC	Same As Above— With Overhead Adjustments of 13 ft. 6 in. and 14 ft. 6 in.	\$14,678.50			

## Technician Productivity Options

	81"-RISE	Additional 3" rise available for SPO10 and S10i models. <b>Specify 81"-RISE when ordering.</b>	\$145.78
	84"-RISE	Additional 3" rise available for SPO12 and S12i models. <b>Specify 84"-RISE when ordering.</b>	\$145.78
	EH1	<b>For 10,000 lb. models:</b> Includes 3" additional rise standard and provides 1 ft. extended height (models SPO10 and S10i).	\$284.71
	EH1	<b>For 12,000 lb. models:</b> Includes 3" additional rise standard and provides 1 ft. extended height (models SPO12 and S12i).	\$312.75
	EH2	<b>For 10,000 lb. models:</b> Includes 3" additional rise standard and provides 2 ft. extended height (models SPO10 and S10i).	\$460.40
	EH2	<b>For 12,000 lb. models:</b> Includes 3" additional rise standard and provides 2 ft. extended height (models SPO12 and S12i).	\$510.86
	EH4	<b>For 10,000 lb. models:</b> Includes 3" additional rise standard and provides 4 ft. extended height (models SPO10 and S10i).	\$810.52

\* NOTE: Lift Rise Is Measured From Floor To Top Of Either Pad, Runway, Or Adapter In The Highest Position.

NOTE: Standard Colors Red And Blue. Gray, Yellow And Black Are Available At No Additional Charge, But Are Considered Non-Standard And Subject To Lead Time Restrictions And Order Cancellation Penalties. Other Non-Standard Colors Or Shade Variations Are Available For An Additional Charge, But Also Subject To Lead Time Restrictions And Cancellation Penalties.

NOTE: All Accessories Shown Above May Be Used With Most Frame Contact Models. See page 5 for all accessories.

Use Of Adapters **Does Not** Change Lift Capacity. Fits any Surface Mounted or Inground, Frame-Engaging Rotary Lift, Manufactured Since October 1973.



# Surface Mounted Lifts

## Two-Post Lifts for Turf Maintenance

SIN #253-20, #253-2

### Conventional / Two-Post / Turf Maintenance

	MODEL NUMBER	DESCRIPTION	*RISE	CAPACITY	NET STS PRICE
	TL07	2-Post Surface Mounted Lift Electric-Hydraulic Operation. Can Accommodate 3 or 4 Wheel Vehicles.	68" (1727 mm)	7,000 lbs. (3175 kg)	\$5,337.24
	TL07-EH2	Same As TL07 Above -- Provides 2' extra height and 3" additional rise.	71" (1803 mm)		\$5,797.02
	TL07-EH4	Same As TL07 Above -- Provides 4' extra height and 3" additional rise.			\$6,147.76
FJ5123 (200-400)	N257	Arm Kit To Convert TL07-200/400 Series To A Lift For Passenger Cars and Light Trucks.			\$745.73
Rail Bolster Kit	N2206	Arm Kit To Convert TL07-500 Series To A Lift For Passenger Cars and Light Trucks.			\$745.73

### Conventional / Two-Post / Wheel Alignment Base Units

	MODEL NUMBER	DESCRIPTION	*RISE	CAPACITY	NET STS PRICE
	SPO10WABU	Surface Mounted, Wheel Alignment Base Unit, Overhead Equalization System. Electric-Hydraulic Operation.	68" (1727 mm)	NET** 7,000 lbs. (3175 kg)	\$3,500.64
	SPO10WABU-EH2	Same As SPO10WABU Above — Provides 2 ft. extra height and 3" additional rise.	71" (1803 mm)		\$3,961.03
	SPO10WABU-EH4	Same As SPO10WABU Above — Provides 4 ft. extra height and 3" additional rise.			\$4,311.16
<b>NOTE:</b> Must Specify Manufacturer Of Alignment Runways. Available For Rotary, Hunter, Bear, And FMC Models. Verify Application With Factory Before Quoting, As Additional Equipment And Cost May Be Required On Rack Models Other Than Rotary. NOTE**: Capacity Of Lift Based On Weight Capacity When Used With Rotary Runways. For Use With Other Manufacturers, Runways Capacity May Vary.					

\*Lift Rise Is Measured From Floor Level To Top Of Runway.

# Surface Mounted VersaLifts

(Lifting Range 22" - 48")

	MODEL NUMBER	DESCRIPTION	*RISE	CAPACITY	Net STS Price
	VLXS7	Surface Mounted, Fixed Pad Contact Lift, Electric-Hydraulic Operation, Power Unit Stand. 115V, 1 Phase, 60 Hz Power Unit. Stand Included. 3 Position Adapters Included.	22" (559 mm)	7,000 lbs. (3175 kg)	\$2119.45
	VLXS10	<b>NOTE:</b> Lift Standard with 18' Hose (5486mm).	22" (559 mm)	10,000 lbs. (4536 kg)	\$3,166.09
	VMR6	Fully Portable Mid-Rise Lift. Space Saving Scissor-Style Design, With Swing Arms And Pad Adapters, 2 Cylinder Design Powers The Lift To Full Height In Less Than 30 Seconds, Multiple Locking Heights, 115v Operation. <b>Available Only In Blue.</b>	48" (1219 mm)	6,000 lbs. (2722 kg)	\$1,879.59

\*Lift Rise Is Measured From Floor Level To Top Of Either Pad Or Adapter In The High Position.

# SmartLifts

Conventional / SmartLift

	MODEL NUMBER*	DESCRIPTION	**RISE	CAPACITY	NET STS PRICE
	SL19	Conventional SmartLift with Single Plunger, Fully Contained Electric-Hydraulic Operation. Integrated Non-Rotator/Locking-Leg. 8 1/2" Diameter Piston. 208-230 Volt, Single Phase Power Unit.	81 3/8" (2067 mm)	9,000 lbs. (4082 kg)	\$4,699.29
	SL210	Conventional SmartLift with Two Plunger, Side by Side, Fully Contained, Electric-Hydraulic Operation. Rigid Equalized. 8 1/2" Plunger Diameter. Drive Thru. Includes Air Actuated, Multi-Position Locks, 208-230 Volt, Single Phase Power Unit. Flip-up Adapters.	81 1/2" (2045 mm)	10,000 lbs. (4536 kg)	\$6,456.77
	SL212	Conventional SmartLift with Two Plunger, Side by Side, Fully Contained, Electric-Hydraulic Operation. Rigid Equalized. 8 1/2" Plunger Diameter. Drive Thru. Includes Air Actuated, Multi-Position Locks, 208-230 Volt, Single Phase Power Unit. Stack Adapters.	84 1/4" (2140 mm)	12,000 lbs. (5443 kg)	\$8,667.18

\*\*NOTE: Lift Rise Is Measured From Floor To Top Of Either Pad, Runway, Or Adapter In The Highest Position, Except For SmartLift In Which Rise Indicates Plunger Stroke From Finished Floor.





# Surface Mounted Lifts

## Four-Post Lifts

SIN #253-20, #253-2

### Conventional Four-Post

	MODEL NUMBER	DESCRIPTION	*RISE	CAPACITY	MAXIMUM WHEELBASE RANGE	NET STS PRICE
	SMO14S	OPEN FRONT or Open Rear Surface Mounted, Runway-Type, Drive-On Lift, With 20" Wide Fixed Runways. Runways and Ramps Have An Oil Resistant, Non-Skid Coating. Includes Dual Function Sentinel Lock System™ (Patented), Filter Lubricator Regulator (Part#S130080). Electric-Hydraulic Operation. Includes Adjustable Latch Bars. Pre-drilled For Internal Airline Kit.	73-3/4" (1873 mm)	14,000 lbs. (6350 kg)	158-1/2" (4025 mm)	\$6,078.61
	SMO14L				192-1/2" (4892 mm)	\$6,078.61
	SMO14EL2				212-1/2" (5400 mm)	\$6,389.49
					SM14S	158" (4013 mm)
	SM14L	Same As Above Except With CLOSED FRONT.	73-3/4" (1873 mm)	14,000 lbs. (6350 kg)	182-1/2" (4636 mm)	\$4,883.70
	SM14EL2				206-1/2" (5245 mm)	\$5,193.33
	FA647	2 ft. runway extension for SM/SMO 12,000 lb. Series.				\$390.62
	S10060	2 ft. runway extension for SM/SMO 14,000 lb. Series.				\$522.70
<b>NOTE:</b> Narrow Bay Models Available For SM/SMO Series (10" Narrow Overall Width For Narrow Bay Application).						
	SM101	Extended Length Is Ideal For Limousines.	73-3/4" (1873 mm)	10,000 lbs. (4536 kg)	245" (6096 mm)	\$6,703.48
	SM18	Heavy Duty Surface Mounted Runway-Type Drive-On Lift Runways and Ramps Have An Oil Resistant, Non-Skid Coating. Includes Air Operated Single Point Release Locking Latches, Filter Lubricator Regulator. Electric-Hydraulic Operation.	68" (1727 mm)	18,000 lbs. (8165 kg)	194" (4928 mm)	\$7,010.62
	SM18-EL2				230" (5842 mm)	\$7,680.97
	SM30 Series	Heavy Duty Surface Mounted Runway-Type Drive-On Lift, With 24" Wide Runway That Can Be Set For Variable Tread Width Setting. Runways and Ramps Have An Oil Resistant, Non-Skid Coating. Includes Air Operated Single Point Release Locking Latches. Internal Air Line with Quick Disconnects, Electric-Hydraulic Operation.	68" (1727 mm)	30,000 lbs. (13,608 kg)	235" (5969 mm)	\$13,091.72
	SM30S	Overall Length 25'-8 1/8".			271" (6883 mm)	\$14,282.90
	SM30L	Overall Length 28'-8 1/8".			307" (7798 mm)	\$15,473.45
	SM30-EL3	Overall Length 31'-8 1/8".				
	S100012	2 ft. runway extension for SM18.				\$304.65
	S100018	3 ft. runway extension for SM300 - 200.				\$1,103.33
	FA641-18	3 ft. runway extension for SM300 - 100.				\$1,492.09
	RFL25	Heavy Duty Surface Mounted Runway-Type Drive-On Lift, With 24" Wide Runway That Can Be Set For Variable Tread Width Setting. Runways and Ramps Have An Oil Resistant, Non-Skid Coating. Includes Air Operated Single Point Release Locking Latches. Internal Air Line with Quick Disconnects. Electric-Hydraulic Operation. For Raising Forklifts.	68" (1727 mm)	25,000 lbs. (11,340 kg)	163" (4140 mm)	\$17,404.75

\*NOTE: Lift rise is measured from floor to top of either pad, runway, or adapter in the highest position.

### Four-Post Wheel Alignment Action Rack Systems with Rolling Jacks

	MODEL NUMBER	DESCRIPTION	*RISE	SYSTEM CAPACITY	Maximum Wheelbase Range	NET STS PRICE
Stainless Steel Gauges and Rolling Jacks Included!	ARO14S	<b>Includes:</b> • Open Front Action Rack • Four-Post Lift • (2) FA5153 Stainless Steel Radius Gauges • (2) 7,000 lb. Cap. Rolling Jacks • (1) Set 4WS Rear Slip Plates • Patented (Dual Protection Sentinel Lock System)™ • (1) FC134-17 Portable Work Step • Level At All Locking Heights • (1) Internal Air Line Kit • (4) Wiring Access Holes • Runways and Ramps have an Oil Resistant Non-skid Coating • Filter Lubricator Regulator	73-3/4" (1873mm)	14,000 lbs. (6350kg)	158-1/2" (4025mm)	\$16,764.31
	ARO14L				192-1/2" (4892mm)	\$16,764.31
	ARO14EL2				212-1/2" (5400mm)	\$17,058.99
	AR14S	<b>Includes:</b> • Closed Front Action Rack • Four-Post Lift • (1) pair FA5153 (CS) Stainless Steel Radius Gauges • (2) 7,000 lb. Cap. Rolling Jacks • (1) Set 4WS Rear Slip Plates • Air Actuated Locking Latches • (1) FC134-17 Portable Work Step • Level At All Locking Heights • (1) Internal Air Line Kit • (4) Wiring Access Holes • Runways and Ramps have an Oil Resistant Non-skid Coating • Filter Lubricator Regulator	73-3/4" (1873mm)	14,000 lbs. (6350kg)	158-1/2" (4025mm)	\$15,570.02
	AR14L				192-1/2" (4892mm)	\$15,570.02
	AR14EL2				212-1/2" (5400mm)	\$15,865.32

### Efficiency Packages

	S100077	Package Includes Two (2) RJ7000 Rolling Bridges And Airline Kit (uninstalled).	\$5,032.59
	S100021	Package Includes Two (2) SJ6000 Swing Air Jacks And Airline Kit (uninstalled).	\$5,588.93
	S100078	Package Includes Two (2) RJ7000 Rolling Bridges, Airline Kit (uninstalled) And S100074 Bolt-On Alignment Package.	\$6,952.68
	S100079	Package Includes Two (2) SJ6000 Swing Air Jacks, Airline Kit (uninstalled) And S100074 Bolt-On Alignment Package.	\$7,599.98

\*NOTE: Lift rise is measured from floor to top of either pad, runway, or adapter in the highest position, except for SmartLift in which rise indicates plunger stroke from finished floor.



# Lift Accessories

SIN #253-20, #253-2

## Frame Engaging Lift Accessories\*\*

	MODEL NUMBER	DESCRIPTION	Net STS Price	
	FJ6115	EH (Extended Height) Auxiliary Adapters For Use When Raising Certain Vans Or Pick-Ups. Maximum Height 14 3/8" (365 mm). Capacity 2,500 lbs. (1,134 kg) Maximum Per Adapter. Fits Any Surface Mount Or Inground, Frame-Engaging, Rotary Lift Manufactured Since October 1973. Includes (4) FJ696 Adapters and 2 Piece Column or Wall-Mounted Adapter Rack FJ6114.	\$229.26	
	FJ6195	NEW extended height auxiliary adapters' version of FJ6115. 3" (76 mm) additional rise for a total 17 3/8" (454 mm). Includes a set of (2) FJ6196 adapters. Capacity is 2,500 lbs. (1,134 kg) per adapter.	\$153.26	
	FJ6133	EH (Extended Height) Required To Lift 1988 Or Newer General Motors GMT400 Pickup Trucks. Maximum Height: 14" (356 mm) Capacity 2,500 lbs. (1,134 kg) Maximum Per Adapter. Fits Any Surface Mount Or Inground, Frame-Engaging, Rotary Lift Manufactured Since October 1973. Includes (4) FJ6101 Adapters and 2 Piece Column or Wall-Mounted Adapter Rack FJ6114.	\$243.59	
	FJ6137	Required For Raising Mini-Vans With Running Boards (i.e. Aerostar, Astro, Caravan, Voyager). Adjustable Range Provides 4 7/8" to 6 3/4" Additional Height. Polymer Contact Surface Protects Undercoated Surfaces. Fits Any Surface Mount Or Inground, Frame-Engaging, Rotary Lift Manufactured Since October 1973. Includes (4) FJ7858 Adapters and 2 Piece Column or Wall-Mounted Adapter Rack FJ6114.	\$266.02	
	FJ6138	Polymer Pad Adapter Provides 1/2" Additional Clearance. Fits Any Frame Engaging Rotary Lift Manufactured Since October 1973. Includes (4) FJ697 Adapters, 2 Piece Column or Wall-Mounted Adapter Rack FJ6142.	\$140.80	
	FJ6190	Step Polymer Pad Adapter Provides 1" Additional Clearance. Fits Any Frame Engaging Rotary Lift Manufactured Since October 1973. Includes (4) FJ6189 Adapters, 2 Piece Column or Wall-Mounted Adapter Rack FJ6142.	\$147.65	
	FJ6139	High Step Polymer Pad Adapter Provides 2 1/2" Additional Clearance. Fits Any Frame Engaging Rotary Lift Manufactured Since October 1973. Includes (4) FJ698 Adapters, 2 Piece Column or Wall-Mounted Adapter Rack FJ6142.	\$147.65	
	FJ6100	Includes (4) FJ696, (4) FJ697 And (4) FJ698 Plus 2 Piece Column or Wall-Mounted Adapter Organizer Rack Part #FJ6108.	\$449.81	
	FJ6104	Includes (4) FJ6101, (4) FJ697 And (4) FJ698 Plus 2 Piece Column or Wall-Mounted Adapter Organizer Rack Part #FJ6108.	\$465.38	
	FJ6105	Includes (2) FJ696, (2) FJ6101, (4) FJ697, (4) FJ698 Plus 2 Piece Column or Wall-Mounted Adapter Organizer Rack Part #FJ6108.	\$457.91	
	FJ6117	Includes (4) FJ7858, (4) FJ697, (4) FJ698 Plus 2 Piece Column Adapter Organizer Rack Part #FJ6108.	\$472.23	
	FJ6197	Set of four (4) FJ6182 rubber adapters. Required for use on 3-stage arms when lifting trucks or other frame vehicles.	\$234.25	
	FJ7880	Adapter Extension Kit For RA SPO/A10 And SL210 Series Lift Models. Provides Additional Lifting Height When Vehicles Require Additional Clearance Or Use On Front Or Rear To Level Vehicle On Lift. Includes (4) FJ6171-1 Extensions 3 1/2" Tall, (4) FJ6171-2 Extensions 5" Tall and FJ6127 Rack Kit With Mounting Hardware.	\$176.93	
	FA5911	Air/Electric Utility Box Includes Filter/Lubricator/Regulator. Mounts Easily On Any 2-Post Surface Lift Except 84 and 74 Series Lift. Provides Easy Access To Both Air And Electrical Outlets Making The Full Rise Lift A Complete Work Station.	\$317.11	
	FA5910	Air/Electric Utility Box Same As Above Excluding Filter/Lubricator/Regulator.	\$199.36	
	FA915	Air/Electric Utility Box Includes Filter/Lubricator/Regulator. Mounts Easily On Any 4-Post Surface Lift (except for SM300). Provides Easy Access To Both Air And Electrical Outlets Making The Full Rise Lift A Complete Work Station.	\$317.11	
	FA916	Air/Electric Utility Box Same As Above Excluding Filter/Lubricator/Regulator.	\$197.49	
	FA5159	Tool Tray Kit For Light Duty 2-Post Models Includes Two (2) Trays, Brackets and Hardware.	\$67.28	
<b>Drive-On Lift Accessories</b>				
	RJ6000	Rolling Jack For SM/SMO14, AR/ARO14.	6,000 lbs. (2722 kg) \$2,244.67	
	RJ7000	Rolling Jack For SM/SMO14, AR/ARO14.	7,000 lbs. (3175 kg) \$2,376.75	
	RJ9000-1	Rolling Jack For SM30 Series Lifts. For Passenger Cars and Light Trucks Only!	9,000 lbs. (4082 kg)	\$2695.10
	RJ9000-2	Rolling Jack For SM181 Only.		\$3,004.11
	RJ9001	Rolling Jack For SM18 Series Lifts.	\$2,695.10	
	FC5710	Heavy Duty Rolling Jack For SM300, Series Lifts. Capacity, Air/Oil Operated. Supplied With FD291 Combination Front Straight Axle/"Flip Up" Rear Axle Support. Will Accommodate All Adapters Typically Used With FD282 Inground Saddle.	15,000 lbs. (6804 kg) \$5,934.70	
	SJ4500	Swing Air Jack For ARO/SMO Series Lifts.	4,500 lbs. (2041 kg) \$2,503.21	
	SJ6000	Swing Air Jack For ARO/SMO Series Lifts.	6,000 lbs. (2722 kg) \$2,798.52	
	FJ2427	Flat Polymer Pad Adapter Adds 1-1/2" Height. Rubber Pad Surface Measures 4-3/4" x 6-5/16". Protects Vehicles With Factory Applied Undercoating. 3,500 lbs. capacity per adapter.	\$8.72 Each (2 required)	
	FJ2428	Flat Polymer Pad Adapter Adds 3" Height. Rubber Pad Surface Measures 4-3/4" x 6-5/16". Protects Vehicles With Factory Applied Undercoating. 3,500 lbs. capacity per adapter.	\$13.71 Each (2 required)	
	FC5378	Bolt On Work Steps For All 4-Post Series Lifts.	\$376.92 (Pair)	
	FC5247	8 Foot Long Oil Drain Hose With Quick Connect Fitting.	\$73.51	
Internal Air Line Kit	FC5760	Internal Air Line Kit (retrofit) For SM/SMO12 and SM18 Series.	\$280.35	
	FC5760-14	Internal Air Line Kit (retrofit) For SM/SMO14L and EL.		

\*NOTE: All Accessories Shown Above May Be Used With Most Frame Contact Models. Use Of Adapters **Does Not** Change Lift Capacity. Fits any Surface Mounted or Inground, Frame-Engaging Rotary Lift, Manufactured Since October 1973.

## Electrical / Power Unit / Overhead Switch Options

Three Phase Power	Optional 4-HP 3kw, 3 Phase, 60 Hz Power Unit For Use With Four-Post Series, SL Series (Both in bay and Non-in bay), Two-Post Overhead Design Lifts Only (Both in bay and Non-in bay). Must Specify When Ordering. Price In Addition To Standard Unit Price. 208/230 or 460 Volt Must Be Specified.	\$199.36
-------------------	--	----------



# Heavy Duty Inground Modular Concept Units Self-Contained

SIN #253-20, #253-2

## Movable Plunger Modular Unit

	***MODEL NUMBER	CAPACITY	DESCRIPTION	RISE	NET STS PRICE
	MOD30M-10	30,000 lbs. (13608 kg)	Modular Movable Jack Unit With** 10' Long Track. (*Unit not equipped with Saddle or Adapters)	70" (1778mm)	\$35,510.38
	MOD30M-18	30,000 lbs. (13608 kg)	Modular Movable Jack Unit With** 18' Long Track. (*Unit not equipped with Saddle or Adapters)	70" (1778mm)	\$35,510.38
	MOD30M-21	30,000 lbs. (13608 kg)	Modular Movable Jack Unit With** 21' Long Track. (*Unit not equipped with Saddle or Adapters)	70" (1778mm)	\$35,510.38
	MOD30M-24	30,000 lbs. (13608 kg)	Modular Movable Jack Unit With **24' Long Track. (*Unit not equipped with Saddle or Adapters)	70" (1778mm)	\$35,510.38

\* See Adapter Kits to select Saddle and Adapters in accordance to lift application.

\*\* See the Wheelbase Chart to select the required frame length.

\*\*\* Wider pocket opening available upon request.

**Standard Equipment:** Specified Track Length, Totally Contained Steel Enclosure Sealed and Protected With Enviroguard, LDS Liquid Detection System, Multi-Stage Piston Assembly, Multi-Position Remote Release Locks, Electronic Jack Spotting Device, Programable Height Positions.

## Stationary Plunger Modular Unit

	**MODEL NUMBER	CAPACITY	DESCRIPTION	RISE	NET STS PRICE
	MOD30S	30,000 lbs. (13608 kg)	Modular Stationary Jack Unit. (*Unit not equipped with Saddle or Adapters)	70" (1778mm)	\$20,421.94

\*See Adapter Kits to select adapters according to lift application.

\*\* Wider pocket opening available upon request.

**Standard Equipment:** Specified Track Length, Totally Contained Steel Enclosure Sealed and Protected With Enviroguard, LDS Liquid Detection System, Multi-Stage Piston Assembly, Multi-Position Remote Release Locks, Programable Height Positions.


## Modular Unit Controls

	**MODEL NUMBER	DESCRIPTION	NET STS PRICE
	MC2	For 2-Post Lift Configuration - Console With VEC Equalized Controls.	\$8,751.90
	MC3	For 3-Post Lift Configuration - Console With VEC Equalized Controls.	\$13,337.18

Note: When ordering controls, place a dash after the model number and add the voltage require.  
**EXAMPLE - (MC2-230V).**

# Adapter Kits

## Adapter Kits for Modular Lift Configurations

	**MODEL NUMBER	DESCRIPTION	NET STS PRICE
	AK-SBA60-2	Saddle and adapter kit for <b>most School Bus</b> applications. For use on (2-Post lift)	\$2,808.48
	AK-TRA60-2	Saddle and adapter kit for <b>most Transit Bus</b> applications. For use on (2-Post lift)	\$2,808.48
	AK-HTA60-2	Saddle and adapter kit for <b>most Heavy Duty Truck</b> applications. For use on (2-Post lift)	\$2,808.48
	AK-TRLP60-2	Saddle and adapter kit for <b>most Low Profile Transit Bus</b> operations. For use on (2-Post lift configuration).	\$2,808.48
	AK-TRA90-3	Saddle and adapter kit for <b>most Transit Bus</b> applications. For use on (3-Post lift)	\$4,212.73
	AK-HTA90-3	Saddle and adapter kit for <b>most Heavy Duty Truck</b> applications. For use on (3-Post lift)	\$4,212.73
	AK-XPAD	Single post frame contact adapter. 9000 lbs. for most passenger cars.	\$4,622.66



# Parallelogram Lifts

SIN #253-20, #253-2

## Rotary Advantage Parallelogram Lifts

	MODEL NUMBER	DESCRIPTION	MAXIMUM WHEELBASE	CAPACITY	RUNWAY LENGTH	NET STS PRICE
	25/26 S	4-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	276 in. (7010 mm)	25,000 lbs. (11340 kg)	26 ft. (7.9m)	\$52,572.48
	36/28 S	4-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	300 in. (7620 mm)	36,000 lbs. (16330 kg)	28 ft. (8.5m)	\$58,422.45
	36/28 F	4-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$66,212.44
	50/26 S	4-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	276 in. (7010 mm)	50,000 lbs. (22680 kg)	26 ft. (7.9m)	\$64,263.07
	50/26 F	4-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$72,053.07
	45/35 S	6-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	384 in. (9754 mm)	45,000 lbs. (20412 kg)	35 ft. (10.6m)	\$77,901.17
	45/35 F	6-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$85,682.44
	50/28 S	6-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift	290 in. (7366 mm)	50,000 lbs. (22680 kg)	28 ft. (8.5m)	\$68,158.69
	50/28 F	6-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$76,132.47
	50/32 S	6-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	348 in. (8839 mm)	50,000 lbs. (22680 kg)	32 ft. (9.7m)	\$72,053.07
	50/32 F	6-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$79,842.43
	75/30 S	6-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	324 in. (8230 mm)	75,000 lbs. (34020 kg)	30 ft. (9.1m)	\$79,842.43
75/30 F	6-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$87,632.43	
	75/48 S	8-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	540 in. (13716 mm)	75,000 lbs. (34020kg)	48 ft. (14.6m)	\$100,447.54
	75/48 F	8-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$110,358.22
	100/42 S	8-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	468 in. (11887 mm)	100,000 lbs. (45360 kg)	42 ft. (12.8m)	\$105,163.02
	100/42 F	8-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$114,901.76

NOTE: Shims, Full Base Plate Shims and Anchors are NOT provided with Rotary Parallelogram Lifts. Consult the Equipment Function Requirements (EFRs) for the specific lift model. EFRs are available through Rotary Lift Customer Service and on the RDW.

## Rotary Advantage Accessories

	MODEL NUMBER	DESCRIPTION	NET STS PRICE	
	RJ25000	25,000 lbs. (11340 kg) Rolling Jack	\$6,437.46	
	RJ50000	50,000 lbs. (22680 kg) Rolling Jack	\$7,032.42	
	APAIKIT	Built-in Air	\$1,686.46	
	8 ft. Drive-thru Ramp	APRAMP8	8 ft. (2.44m) Drive-thru Ramp Kit (with lift)	\$2,913.15
8 ft. Drive-thru Ramp (w/o lift)	APRAMP8DTKIT	8' Drive-Thru Ramp Kit (without lift)	\$3,583.50	
10 ft. Drive-thru Ramp	APRAMP10	10 ft. (3m) Ramps (adder to standard lift cost)	\$598.08	
Air Caster Kit	APAIRCASTER	Air Castor Kit	\$1,686.46	
Light Kit	APLIGHT	Light Kit (pair)	\$564.44	
Descent Alarm	APAUDALARM	Audible Descent Alarm	\$305.27	
Height Limiter	APAUXHT	Height Limiter	\$282.84	
		Inside Tapeswitch (per ft.)	\$64.17	
	AP09525	High Lift Wheel Dolly -- 850 lbs. (386 kg) Capacity	\$2,971.09	
Washbay Kit	Includes zinc galvanized primer with marine grade epoxy top coat, stainless steel baseplate, EnviroGuard coated control panel, stainless steel fittings and tubing.		4-Leg	\$14,313.43
			6-Leg	\$18,303.74
			8-Leg	\$22,289.69


NOTE: Because of the environment of the typical wash bay application for the Rotary Parallelogram Lift, the entire lift is subjected to harsh cleaning chemicals, road chemicals coming off of the vehicles and constant contact with water and moisture. Even though we take extra precautions to assure that the surfaces of the lifts and listed components of the Wash Bay Kit Option are properly prepared, primed and finished, we do not have any control over the environment and we can only guarantee the surface to be free from rust and other corrosion for a period of one year from the date of installation. Any expressed or implied warranty to the contrary, is excluded and is not covered. In all cases, the standard Rotary Limited Warranty applies.



# Hydraulic Portable Lifts




SIN #253-20, #253-2

## Hydraulic Portable Truck And Bus Lifts

	MODEL NUMBER	DESCRIPTION	*RISE	COMBINED TOTAL SYSTEM CAPACITY	NET STS PRICE
	HP415MF	Portable Bus Lift. Wheel Pick-Up, Electro Hydraulic 4-Unit System. 208-230-460 Volt, 3 Phase Operation With Movable Forks.	67" (1702 mm)	60,000 lbs. (27,216 kg)	\$28,667.97
	HP615MF	Portable Bus Lift. Wheel Pick-Up, Electro Hydraulic 6-Unit System. 208-230-460 Volt, 3 Phase Operation With Movable Forks.	67" (1702 mm)	90,000 lbs. (40,824 kg)	\$43,002.58

\*Lift Rise Is Measured From Floor Level To Bottom Of Adapter.

## Hydraulic Portable Truck And Bus Lifts Accessories And Options

	MODEL NUMBER	DESCRIPTION	NET STS PRICE
	ML41	Saddle Cross Beam With Two (2) Support Blocks For Frame Pick-Up.	\$1,261.58
	RS15	Screw-Type Adjustable 56.1"-82.3" (1425mm - 2090mm). 15,000 lbs. (6804 kg) Capacity.	\$510.24
	RS52	Screw-Type Adjustable 34.3 "-55.5" (870mm - 1410mm).	\$510.24
	RS33	Screw-Type Adjustable 55.31"-82.28" (1405mm - 2090mm). 33,000 lbs. (14970 kg) Capacity.	\$996.80
<b>Power Box</b>	HP12-9	Add-On Box To Operate 8-12 Columns In One Set.	\$1,826.01
<b>Start Box</b>	HP12-10	Add-On Box To Make Any Slave Column A Master.	\$1,826.01
<b>Pendant Control</b>	HP12-5	Up/Down Pendant Control With 30'-0" Cable.	\$585.62
<b>Pendant Control</b>	HP12-11	Fine Adjustment Control with 30"-0" Cable.	\$585.62
	HP12-13	Forklift Ramp Kit used with the HP415 series to utilize two HP columns to service forklifts. Easily attaches to the base of the column and provides clearance needed to raise 4-wheeled forklifts with a weight of 10,000 lbs. ( <b>NOTE:</b> Most 6,000 lb. capacity trucks weigh 10,000 lbs. or less; however, the truck weight should be verified <b>before</b> being lifted.) Drive-on Back-off operation is shown.	\$4,499.31
	HP12-14	Same as above for Drive-through operation.	\$4,499.31
	HP12-18	Phase converter.	\$2,964.66



# Warranties

## Limited Warranty

All Rotary lifts are warranted to the original owner for one year from invoice date. Rotary Lift shall replace for the first year those parts returned to the factory which prove upon inspection by Rotary Lift to be defective. Rotary Lift shall pay for reasonable costs of transportation and labor for replacement of said parts for the first 12 months only.

To activate the first year parts and labor warranty on SmartLift® and Inbay® products, installation shall be done by a Rotary Authorized Installer (RAI) and the product installation registered with the factory.

All Rotary Lift accessories are warranted to the original owner for one year from invoice date. Rotary Lift shall replace for the full year those parts returned to the factory which prove upon inspection by Rotary Lift to be defective. Rotary Lift shall pay for reasonable costs of transportation and labor for replacement of said parts for the warranty period.

**This warranty shall not apply unless the product is installed, operated, used and maintained in accordance with Rotary Lift's specifications as set forth in Rotary Lift's installation, operation and maintenance instructions.**

**This warranty does not cover normal maintenance or adjustments, remedies for routine maintenance, damage or malfunction caused by improper handling, installation, abuse, misuse, negligence, carelessness of operation, or normal wear and tear. In addition, this warranty does not cover equipment when unauthorized repairs or alterations have been attempted or made to the product.**

This warranty is exclusive and all other expressed or implied warranties including merchantability or fitness for a particular purpose are hereby expressly excluded.

The remedies described are exclusive and in no event shall Rotary Lift be liable for any special, consequential or incidental damages of any kind including damages for breach of or delay in performance of the warranty.

This warranty shall be governed under the laws of the State of Indiana, and shall be subject to the exclusive jurisdiction of the Court in the State of Indiana in the County of Jefferson.

## Extended Limited Parts Warranty Statement

The extended parts warranty option is exclusive to the sale of lifts installed and used in the United States and is not transferable. All complete lift models in the **Professional Automotive Service Price List** installed by a Rotary Authorized Installer (RAI) are eligible for a second year of parts warranty (transportation and labor not included). Registration of the lift using [www.rotarylif.com](http://www.rotarylif.com) is required for activation of the second year parts warranty.

**If a Rotary Authorized Installer was used to install the lift, the user may elect to purchase three additional years of extended parts warranty. The purchased extended warranty option is available for all complete lift models included in the Professional Automotive Service Price List and begins with the third year of original ownership. Extended warranty may be purchased anytime during the first year of ownership. For customers electing to purchase extended warranty, Rotary Lift shall replace for the extended warranty period, those parts returned to the factory, which prove upon inspection by Rotary Lift to be defective, provided the conditions below are satisfied. Coverage includes electronic components used on inbay models (i.e. switches, membrane touch pads, LCD screen, control boards, etc.). Purchaser will bear costs of transportation and labor after the first year and the remainder of the warranty.**

**Customers shall be responsible for all freight charges for parts returned for inspection.**

This warranty shall not apply unless the product is operated, used and maintained in accordance with Rotary Lift's specifications as set forth in Rotary Lift's installation, operation and maintenance instructions.

This warranty does not cover normal maintenance or adjustments, remedies for routine maintenance, damage or malfunction caused by improper handling, installation, abuse, misuse, negligence, carelessness of operation, or normal wear and tear. In addition, this warranty does not cover equipment when unauthorized repairs or alterations have been attempted or made to the product.

This warranty is exclusive to the United States and all other expressed or implied warranties including merchantability or fitness for a particular purpose are hereby expressly excluded.

The remedies described are exclusive and in no event shall Rotary Lift be liable for any special, consequential or incidental damages of any kind including damages for breach or delay in performance of the warranty.

**This warranty shall be governed under the laws of the State of Indiana, and shall be subject to the exclusive jurisdiction of the Court in the State of Indiana in the County of Jefferson.**

## Optional Extended Parts Warranty

PART NUMBER		NET STS PRICE
#LP20041	An optional extended parts warranty is available for all complete lift models listed in this price sheet (see above). In order to purchase extended warranties, the lifts must have been installed by a Rotary Authorized Installer (RAI). The purchase of the 3 years parts extended warranty must occur within the first 12 months of the original invoice date. The extended warranty covers parts replacement including electronic components used on inbay lifts such as switches, membranes, LCD screens, control boards, etc. The extended warranties are not available for accessories.	<b>\$93.45each Covers 3 years</b>

## Limited Warranty - Parts

All Rotary Lift Replacement Parts are warranted to the original owner for 90 days from invoice date. During this period, Rotary Lift shall replace those parts returned to the factory which prove upon inspection by Rotary Lift to be defective. Transportation and labor costs not included.

**This warranty shall not apply unless the product is installed, operated, used and maintained in accordance with Rotary Lift's specifications as set forth in Rotary Lift's installation, operation and maintenance instructions.**

**This warranty does not cover normal maintenance or adjustments, damage or malfunction caused by improper handling, installation, abuse, misuse, negligence, carelessness of operation, or normal wear and tear. In addition, this warranty does not cover equipment when unauthorized repairs or alterations have been attempted or made to the product.**

This warranty is exclusive and all other expressed or implied warranties including merchantability or fitness for a particular purpose are hereby expressly excluded.

The remedies described are exclusive and in no event shall Rotary Lift be liable for any special, consequential or incidental damages of any kind including damages for breach of or delay in performance of the warranty.

This warranty shall be governed under the laws of the State of Indiana, and shall be subject to the exclusive jurisdiction of the Court in the State of Indiana in the County of Jefferson.