

TELESQURT



AERIAL

A compact rated aerial that operates and responds like a pumper. Provides a versatile first-out unit to handle both rescue and fire suppression operations.

LADDER LENGTH OPTIONS: 50', 65'

- Engine Company operation — With elevated master stream capability
- Equipped with boom mounted rescue ladder — Enables aerial ladder operation
- Short overall length and wheelbase — Highly maneuverable in congested areas
- Short compact boom length — Minimum apparatus length
- Simple reliable design — Proven track record with high number of units in service
- Minimal outrigger spread — Can set-up in tight areas
- High-volume master stream — Fast, efficient, and safe fire suppression
- Minimal space required for installation — Little or no impact on tank or hosebed size
- Multi-function engine/aerial capability — Versatile fireground application
- Available integrated controls at pump panel — Minimal manpower required for operation



TELESQURT



High-volume master stream with numerous tip options



Integrated pump panel controls for easy operation



Minimal outrigger spread



Multiple compartments providing many storage options



Equipment storage and full aerial controls at rear

These are the typical specifications for the American LaFrance TeleSQURT:

AERIAL LADDER / BOOM CONSTRUCTION:

Extruded aluminum box beam sections – two sections (TS 50) or three (TS 65). Integrated aluminum ladder angles down 10° at tip for access/egress.

WATER SYSTEM: Dual external telescoping aluminum waterways rated at 1000 GPM.

HEIGHT: 50' and 65'

HORIZONTAL REACH: 42' and 60'

OPERATING RANGE: -10° to 85° above horizontal

TURNTABLE: Welded steel construction mounted on a shear ball turntable bearing. 360° continuous rotation in either direction.

PERFORMANCE CAPABILITIES:

Up to 45°: 500 lbs. or 1000 lbs. dist. – no water flowing. Above 45°: 750 lbs or 1500 lbs dist. – no water flowing. With water flow, 250 lbs or 500 lbs distributed (above 45° on TS 50; all positions on TS 65).

STABILIZERS: Steel A-frame stabilizers – two (TS 50) or four (TS 65). Maximum spread: 11'-9" (TS 50); 11'-9" (TS 65).

HYDRAULIC MONITOR/ NOZZLE: Elevation, sweep, and stream controls at operator's control panel and aerial tip: Lateral Sweep: 180° total (90° either side of center). Vertical Travel (TS 50): 250° (+85° above horizontal to 165° below). Vertical Travel (TS 65/ 75) 240° (+70° above horizontal to 170° below).

For your nearest American LaFrance dealer, go to www.americanlafrance.com.

Some specifications and features shown or mentioned in this brochure are optional and are available upon request at extra cost. Specifications are subject to change without notice. ©2009, American LaFrance, LLC. All rights reserved.



QUOTATION

American LaFrance

OHIO STS

\$569,246.00

American LaFrance Eagle, 4-Door, Tilt Cab, Formed Aluminum Body, Single Axle
65' Aluminum Rear Mount, Telescoping Ladder
TeleSqrut

08/01/2011

Quote No: ALF AA01-

Page 1

DESCRIPTION

==American LaFrance 65' Tele-Sqrut Telescoping Water Tower =
Eagle 134 (4) Door Tilt Cab Fire Chassis, Formed Alum Body
Custom Cab and Chassis Specifications
Overall Height - 12' - 0" and Overall Length 33' - 6"
NFPA 1901 Certificate of Compliance
Chassis Wheelbase 199"
|-- Frame, 11/32" x 3-1/2" x 10-15/16" Up to 362" Overall Length
|-- Frame Fasteners, Huck Spin
Frame Reinforcement, C-Channel, Up To 374" Over All Length
|-- Engine, Cummins ISX-500 bhp/1645 lb-ft 11.9L - 2010 EPA
|-- Starter, Delco 42MT/OCP w/Thermal Protection
|-- Air Compressor, Wabco 18.7 cfm
|-- Fan Drive - Engine, Horton Drivemaster
|-- Transmission, Allison 4000 EVS-P
|-- Trans Prog, 5 Spd Pumper, Fire & Emg (120)
|-- Transmission Shifter, Touch Pad
|-- Transmission Oil Cooler
|-- Engine Brake, Jake Brk (2) Swtch, DDC-60
|-- Fuel/Water Separator, Racor 490 w/Electric Heater
|-- Exhaust System - RH Horizontal ATD, Horizontal Tailpipe
|-- Alternator, Leece-Neville, 320 Amp
|-- Air Cleaner w/Ember Separator, Frontal Intake
|-- Air Restriction Gauge, Engine Mtd with Dash Light
|-- Radiator, High Capacity Down Flow, 1627
|-- Coolant Hoses, Gates "Blue Stripe" EPDM
|-- Coolant, Engine, Heavy Duty, to -34 Fahrenheit
|-- Engine Protection Alarms
Light, Engine Compartment (1)
Heater Hoses
Engine Stop Control, Ignition Switch
|-- Fuel Tank, 65 Gallon, Rectangular, Steel
|-- Fuel Fill w/Cap and Lanyard, Left
|-- Fuel Lines, High Temp Reinf Nylon, 12V Re-Prime
Front Axle Package, 20,000 lbs, Meritor MFS-133A
|-- Steering Gear 20,000 lb. Cap w/Ram Assist
|-- Power Steering Pump, Vickers V20
|-- Power Steering Reservoir, 4 Quart
|-- Front Suspension 20,000 lb Taperleaf w/Shock
|-- Front Brakes, Meritor EX-225H 17" Air Disc
|-- Frt Tires, Mchl, 385/65R22.5 "J" XZY-3 WB, 20,000#
|-- Alm Hub Plt, 22.5" x 12.25", 22,000#

DESCRIPTION

|-- Polish Outside of Front Aluminum Wheels
 |-- Hub & Lug Nut Covers, S/S, Front Wheels
 Sngl Rear Axle 31,000 lbs, Meritor, RS-30-185
 |-- Tire Inflation Indicators, for Chassis w/Single Rear Axle
 |-- Rear Axle Ratio for 60 MPH Maximum
 |-- Sngl Rear Susp, 31,000#, Reyco 79KB
 |-- Rear Shock Absorbers, Single Axle
 |-- Brakes, "P" Cam, Dbl Anchr, Cst Shoes, 16.5 x 7"
 |-- Air Tanks, Minimum for Spring Suspensions
 |-- Rear Axle Seals
 |-- Rr Tires, Mchl, 315/80R22.5, "L" XDY-3, 33,000#
 |-- AlumHub Plt, Accuride 29730A 22.5" X 9.0"
 |-- Polish Outside of Rear Aluminum Wheels
 |-- Hub & Lug Nut Covers, S/S, Rear, Axle
 Drive Shaft
 Lubricant, Petroleum, Axles
 Air Brake System
 Air Dryer, Bendix AD-9
 Air Tank Pull Cables, Each Tank
 ABS Braking System, Wabco 4S/4M
 Cab, 134" CBC, Four Door, Flat Roof
 |-- Windows, Side Cab, Fixed
 |-- Cab Tilt Mechanism w/Extnl Alarm
 |-- Cab, Mounts, Air, 1" Up, 1" Down 35 Degree Tilt
 |-- Seat, Dvr, H.O. Bostrom, Air Suspension
 |-- Seat, Offcr, H.O. Bostrom, SCBA NonSusp
 |-- Seats, Rear Facing Crew, H.O.Bostrm SCBA Otbrd (2)
 |-- Seats, Forward Facing, SCBA, H.O. Bostrom, Inboard (2)
 |-- Bottle Holder with Restraint, Zico
 |-- Seat Covers, Durawear/Vinyl
 Cab Grab Handle - (4) Ext. Rubber Inserts + (2) Interior
 Mirrors, Cab, Mekra, Chrome, 16" x 7" M2 Style H&R
 |-- Mirrors, Cab, Convex, 7" x 7"
 Fenders, Cab, Polished Stainless Steel
 Mud Flaps,Front
 Antenna, UHF/VHF Mtd LS Cab Roof (136-174 MHz)
 Antenna, UHF/VHF Mtd RS Cab Roof (406-420 MHz)
 Electrical Load Management System
 |-- Battery System - 12V (6) HD Batteries
 |-- Battery Charger, Kussmaul Auto Chg 1200 "Pump +" w/Recept
 |-- Receptacle, Super Auto Eject, 120 VAC, Yellow Cover
 |-- Electrical Load Manager Interlock, Pumper
 Cab Interior Specifications
 Steering Column, Adj Tilt & Telescoping
 Steering Wheel, 18" Four-Spoke Charcoal Gray
 Overhead Console
 Overhead Switch Console, Primary
 Gauges (U.S)
 Lights, Cab Interior, Red/Clear
 Outlets, 12-Volt, Automotive Type (3) Dash Mounted
 Heater/Air Conditioner and Defroster, Primary
 |-- Heater/Air Conditioner, Auxiliary
 |-- Compressor, Refrigerant, A/C, 15.3 cfm
 |-- Air Conditioning Condenser, Radiator Mtd
 |-- HVAC Performance Spec

DESCRIPTION

Interior, Chieftain Shadow Gray Imperial 1200 w/Shadow Trim
 Trim, Door, ABS/Upper, Brushed S/S Lower Kickplate
 |-- Windows, Door Controls, Power Front & Rear
 Map Box - 8"H x 10"W x 13"D w/ (3) 3" Slots
 Vehicle Data Recorder
 Electronic Stability Control
 Seat Belt Warning System
 Helmet Storage, Each Seating Position (6)
 Seat Belts 3Pt Fwd facing, 3Pt Rr facing
 |-- Bumper Extension 18", Polished Stainless Steel
 |-- Diamondplate Deck, 3/16" Bright Finished
 Tow Hooks, Painted, Mtd Bot Frame Ext
 |-- Air Discharge Connector, LS Step Well
 Fuel Fill Door, Cast Products, Diesel Fuel Label
 Plates, Fluid & Seating Capacity
 Plate, Overall Travel Height, Length and Weight
 Tag, Warning, Aerial Devices
 Tag, Warning, Crew Area and Rear Body Step
 Testing, Third Party, Aerial w/Pump
 Pump Enclosure, S/M S/S 50" Wide, Crosslays Only, RM
 |-- Pump Panel, Brushed Stainless Steel, Side Mount
 |-- Crosslays, (2) 200' 1-3/4" & (1) 200' 2-1/2", Sngl Lay
 |-- Outlet, Crosslay, First, 2" Akron, 1-1/2" Swivel Elbw
 |-- Outlet, Crosslay, Second, 2" Akron, 1-1/2" Swvl Elbw
 |-- Outlet, Crosslay, Third, 2-1/2" Akron, 2-1/2" Swvl Elbw
 |-- Crosslay Cover, Vinyl Snap-on Type
 |-- Storage Above Pump, No Cover
 |-- Running Boards, 3/16" Non-Skid Alum Dia Plt
 |-- Platform, Pump Operator, Pullout, W/Grip Strut, LS
 |-- Tags, Color Coded Per NFPA
 |-- Tags, "No Step Surface", Pump Enclosure
 |-- Valve Controls, Locking Push-pull Type
 |-- Engine Monitoring System, Enfo IV, Class 1
 |-- Omit Vernier Throttle
 |-- Gauge, Water Level, Class 1 Intelli-Tank
 |-- Handrails, (2) 18" Mtd Vertically at Pump Enclosure
 |-- Mic Box, Cast Products, Large, ALF Aerials
 |-- Fire Pump - Hale Qmax 1500 GPM Single Stage, RM ALF Aerials
 |-- Installation, Midship Pump
 |-- Anodes, Sacrificial, Pump, LS/RS
 |-- Primer, Hale ESP
 |-- Mechanical Seal, Hale
 |-- Manuals, Pump Operation and Parts, Hale (2) Sets (CD'S)
 |-- Fire Pump Factory Painted Finish
 |-- Governor, FRC PumpBoss
 |-- Piping, Class 1 HP Hose and Stainless Steel Pipe
 |-- Drain, Master, Class 1
 |-- Tank Fill, 1-1/2"
 |-- Tank to Pump Line, Akron 3"
 |-- Pump Cooler, By-pass Aux Pump Cooler Valve
 |-- Valve Package (1500) GPM, Hale RM ALF Aerials
 |-- Inlet, Main, LS 6" Non-gated, Cap
 |-- Inlet, Main, RS 6" Non-gated, Cap
 |-- Inlet, LS Panel Rear 2-1/2" Akron, Swivel, Plug
 |-- Outlet, LS Panel Front (1) 2-1/2" Akron Straight Discharge

DESCRIPTION
-- Outlet, LS Panel Rear (1) 2-1/2" Akron Straight Discharge
-- Outlet, RS Panel Front (1) 2-1/2" Akron Straight Discharge
-- Outlet, RS Panel Rear (1) 2-1/2" Akron Straight Disc
Light Hood for Right Side Pump Panel
Lights, Work, (2) 6" Pump Compartment
Gauges, Master, (2) Class 1, 4-1/2", 30-0-400 PSI
Gauges, 2-1/2" 0-400 Class 1 Line Gauges
Gauge, Discharge, Aerial 2-1/2" 0-400 Class 1
Electrical Interface w/Fast Idle System
Relief Valve, Intake
Pump Shift, Custom RH Side
Drains, Quarter Turn, 3/4" Class 1
Engine Cooler, Custom or FTL Chassis
-- Engine Cooler, Body Facility Finishes Installation
Outlet, Aerial, 4" Valve, Electric Controlled
-- Discharge Material, 4" Stainless Steel
Water Tank-UPF Poly-Basic Construction-TS65/75, SN55
-- Water Tank - Poly-Tank - 500 GALLONS
Body, T23R-65, Rollup Drs, Low Cab, SRA
-- Compts, Driver, SRA, Rescue-Deep, Rollup Drs, Low Cab*
-- Compts, Curb, SRA, Rescue-Shallow, Rollup Drs, Low Cab
-- Aluminum Diamondplate - High Side Both Sides
-- Doors, Rollup, Robinson ROM, Telesqrts
-- Roll-Up Door Finish, Satin
-- Lights - Body Compartment
-- Wheelwells, Poly, Single RA, SS Fenderette
Body Material, Sqrts/Telesqrts, Aluminum
Exhaust Heat Deflector
Compartmentation Detail
Air Cylinder Storage Compts, SA, Telesqrts
-- Air Cylinder Storage Cast Door
-- Air Cyl. Storage-Left Wheelwell 1 Fwd/1 Rear
-- Air Cyl. Storage-Rt Wheelwell 1 Fwd/1 Rear
Fuel Filler w/ Cast Products Door, Telesqurt
Mud Flaps, Rear
Rub Rails, ALF Aluminum Extrusion, Red Reflective Stripe
Handrails, Aluminum, Body, Pumper Style, Telesqrts
Rear Tailboard, Telesqurt/Squrt, Pumper Style
Steps, Corner, Aluminum Diamondplate, T/S Style, Each Side
Rear Step, Auxiliary, Flip Down, Telesqrts
Outrigger Pad Storage Slides (4-Outriggers)
Hose Bed, Rear Mounted Aerials/Towers
-- Hosebed Flooring, Fiberglass
-- Hosebed Capacity, 1000' - 5"
Hosebed Extension Walls
Hosebed Cover, Sqrt/Telesqurt
Mtg, Grd Ladders, RH Body Interior, Telesqrts
Rear Tow Devices (Painted Torque Box Color)
12v Electrical Sys, Body, Single RA Ladders
Lights - Step
ACCESSORIES, RECTANG. or 1/2 T-TANK ALF PUMPER
-- Decking, Turtle Tile, Black, Floors, Multiple Shelves & Tray
-- Shelves, Adj, 3/16" Smooth Alum (3)
-- Adjustable Track in Cmpts for Future Shelf Installation
-- Tray, 250# Floor Mounted, Sliding (1)

DESCRIPTION
-- Tray, 500# Floor Mounted, Sliding (1)
-- Tool Board, 250# Swing Out Hinged (1)
NFPA Optical Warning System
-- Lightbar, Boom Contour, Strobe
-- Front Warning Lights, Fixed, LED
-- Lights, Warning, Front, Inbrd of Turn Signal, LED
-- Lights, Warning, ALF Aerial, Whelen Strobe Pkg
-- Headlights Halogen, 1High & 1Hi/Low Beam Each Side
-- Turn Signals Cornering Lamps, LED, Halogen
-- Horns, Dual Electric
-- Siren, PA 200 Watt w/(1) Speaker, Ctr Bumper
-- Switch, Foot, (1) Siren/RS
-- Air Horns, Dual 21" Grover Stuttertone 1-LH, 1-RH Bumper
-- Switch, Foot, (1) Officer's Side
-- Code 3 Model D50C Constant 97 DB Back Up
Reflectors, NFPA/FMVSS Required Reflectors
Lights, Clearance/Marker Lights (7)
Lights, Pump Running Board and Rear Step (4)
Lights, Underbody (8)
Light, Scene (1) Whelen, 7E Series, Back of Boom Support
Lights, Deck Lights, (2) 6" Unity, Rear Aerial Body
Light & Bracket, License Plate
Lights, Whelen, CAST3 Stop, Turn, Back-Up (3) Lamps
Light, Midship Marker/Directional
Painting, Alum Body, Custom Pmpr/Quint
-- Paint, Custom Cab, Single Color,
-- Paint, Chassis, Black
-- Paint, Color, Body Single Color
-- Finish, Compartment Interior, Zolatone
-- Finish, Hose Bed / Mill
-- Paint, Paint, Factory Std. Finish
Undercoating, Rust Inhibitor, Body
Lettering, (60) Scotchlite, 3" Letters
Lettering, (36) Scotchlite, Red, Letters on Sides of Aerial
Striping, Scotchlite, (1) 4" NFPA Stripe
Reflective Chevron
-- Red and Yellow Reflective
Delivery Prep, Body Facility, Final Insp. at Body Facility
Delivery, Interstate
Telesqurt 65' Water Tower Specifications
-- Performance Capabilities, Telesqurt 65
-- Dimensions, Telesqurt 65'
-- Mainframe, Telesqurt 65'
-- Pedestal Height Installation, For 67" Frame to Top of Cab
-- Turntable, Telesqurt 65'
-- Stabilizers, Four (4), Telesqurt 65'
-- Stabilizer Bearing Pads, Four (4), TS65
-- Boom Construction, Telesqurt 65'
-- Aerial Ladder, Telesqurt 65'
-- Ladder Rails, Fixed, Telesqurt 65'
-- Hydraulic System, TS 65
-- Control Station, Rear Operators, TeleSQURT 65
-- Waterway System, TS65
-- Monitor, Hydraulically Controlled, TS65
-- Finish Paint, Turntable/Booms, TS65

DESCRIPTION

|-- Operation, Maintenance & Parts Manual, TS65
Third Party Test and Certification, Telesqurt & Squrt
Throttle Control Wiring
Communication System, Two-way, TeleSQURT 50/65
Lts, (2), Unity 12 Volt Spotlights, Top of Boom, TeleSQURT
Lts, (2), Unity 12 Volt Spotlights, Base of Boom, TeleSQURT
Electric System, 110 Volt, TS50/65
Water System, Lower, (1) 4" Inlet/Outlet, TS 50/ 65'
|-- Waterway Inlet Accessories, (1) 4"NST x 5"Storz
Automatic Relief Valve
1-1/2" Aerial Drain System
Flowmeter, TELESQURT / SQURT
Finish Paint,Subframe/Pedestal,TS50/65 & 54 Squrt
Delivery Engineer, TeleSQURT/SQURT Three (3) Days
GROUND LADDERS
Ladder, Duo-Safety, Series 1225-A, 35' 3-Sec (1)
Ladder, Duo-Safety, Series 875-A, 16' Roof (1)
Ladder, Duo-Safety, Series 585-A, 10' Folding (1)
Ladder, Duo-Safety, Series 701-A, 14' Attic (1)
Warranty - Refer to FS12-11 FORM G

REAR-MOUNT LADDER METROSTIK 75



AERIAL

A refined version of our proven aerial performers with Heavy-Duty ratings for versatile fire ground performance.

- High tip load rating – 500 lbs
- Pre-piped telescopic water system rated at 1500 GPM
- Retractable Monitor as standard equipment is quick to establish master stream operation or rescue operation
- Maximum lift cylinder elevation range, -7 to +80°
- 14 ft Outrigger spread with deep penetrating jacks
- Open walkway on ladder for easy, safer climbing
- Maximum available compartmentation in Stainless or Aluminum, depths up to 25" – Store large accessories
- Easy payout and reload of hose, up to 1000' of 5" LDH
- Low enclosed ground ladder storage – Promotes safe removal and easier handling of up to 190 ft of ladders
- Numerous aerial tip options available
- Up to 500 gallon water tank capacity



REAR-MOUNT LADDER METROSTIK 75



Clear unobstructed walkway with wider and deeper fly section



Over 190 cu ft of usable space and depths up to 25"



Low ground ladder storage with safe and easy access to hose and equipment



1500 GPM flow capacity



14" "H Style" Outriggers allow aerial operation at full capacity in tight areas

These are the typical specifications for the Metrostik 75:

LADDER: All-steel construction with k-bracing; Dual cylinder extension system.

3 SECTION AERIAL LADDER: 500 lb capacity with full water rating and 100 lbs equipment allowance.

WATERWAY FLOW CAPACITY: 1500 GPM

HORIZONTAL REACH: 66' reach

ANGLE OF ELEVATION: - 7° to + 80°

MONITOR: Retractable with lever connection to ladder fly or outer mid-section for rescue operations; Automatic electrical disconnect for monitor functions. Optional 30° above horizontal monitor range for low-angle, store-front operations.

OUTRIGGERS: Quantity of 2, H-type, out-and-down style, Short-Jacking capability with Rotational Limiting Safety system.

OUTRIGGER SPREAD: 14' with Short-Jacking capability of 11'.

O.A.L.: 36' - 3" to 36' - 6"

O.A.H. RANGE: 11' - 2" to 11' - 7"

WHEELBASE RANGE: 209" to 238"

COMPARTMENTATION: Stainless Steel or Aluminum in Rescue Depth.

CHASSIS: American LaFrance Eagle®

FIRE PUMP: American LaFrance Midship Pump in single and two-stage models, capacities of 1,250 to 2,000 GPM.

WATER/FOAM TANK CAPACITY: 300 to 500 gal Additional foam tank capacity in above pump storage

For your nearest American LaFrance dealer, go to www.americanlafrance.com.

Some specifications and features shown or mentioned in this brochure are optional and are available upon request at extra cost. Specifications are subject to change without notice. ©2009, American LaFrance, LLC. All rights reserved.



QUOTATION

American LaFrance

OHIO STS

\$588,219.00

American LaFrance Eagle, 4 Door, Tilt Cab, Formed Aluminum Body, Single Axle, 75' Rear Mount, Telescoping Ladder, 500lb (Steel)

08/01/2011

Quote No: ALF AA02-

Page 1

DESCRIPTION

== American LaFrance 75' Rearmount S/A Telescoping Ladder, 5 Eagle 134 (4) Door Tilt Cab Fire Chassis, Formed Aluminum B Custom Cab and Chassis Specifications Overall Height - 11' - 2" and Overall Length 36' NFPA 1901 Certificate of Compliance Chassis Wheelbase 209"

- |-- Frame, 11/32" x 3-1/2" x 10-15/16" Up to 362" Overall Length
- |-- Frame Fasteners, Huck Spin

Frame Reinforcement, C-Channel, (375"+) Over All Length

- |-- Engine, Cummins ISX-500, 500 bhp/1645 lb-ft 11.9L - 2010 EPA
 - |-- Starter, Delco 42MT/OCP w/Thermal Protection
 - |-- Air Compressor, Wabco 18.7 cfm
 - |-- Fan Drive - Engine, Horton Drivemaster
 - |-- Coolant Filter, Fleetguard, Spin-on (Cummins)
 - |-- Transmission, Allison 4000 EVS-P
 - |-- Trans Prog, 5 Spd Pumper, Fire & Emg (120)
 - |-- Transmission Shifter, Touch Pad
 - |-- Transmission Oil Cooler
 - |-- Engine Brake, Jacobs w/(2) Switches
 - |-- Fuel/Water Separator, Racor 490 w/Electric Heater
 - |-- Exhaust System - RH Horizontal ATD, Horizontal Tailpipe
 - |-- Alternator, Leece-Neville, 320 Amp
- |-- Air Cleaner w/Ember Separator, Frontal Intake
- |-- Air Restriction Gauge, Engine Mtd with Dash Light
- |-- Radiator, High Capacity Down Flow, 1627
- |-- Coolant Hoses, Gates "Blue Stripe" EPDM
- |-- Coolant, Engine, Heavy Duty, to -34 Fahrenheit
- |-- Engine Protection Alarms

Light, LED Engine Compartment, (1)
Heater Hoses with Shut-Off Ball Valves
Engine Stop Control, Ignition Switch

- |-- Fuel Tank, 54 Gallon, Rectangular, Steel
- |-- Fuel Fill, Rear, 54 Gallon Tank
- |-- Fuel Re-Prime Pump, 12V, Sngl Suct & Rtrn Lines

Front Axle Package, 22,000 lbs, Meritor MFS-133A

- |-- Steering Gear 22,000 lb. Cap w/Ram Assist
- |-- Power Steering Pump, Vickers V20
 - |-- Power Steering Reservoir, 4 Quart
- |-- Front Suspension 23,000 lb Taperleaf w/Shock
- |-- Front Brakes, Meritor EX-225H 17" Air Disc
- |-- Frt Tires, Mchl, 425/65R22.5 "L" XZY-3 WB, 22,800#

DESCRIPTION
-- Alm Hub Plt, 22.5" x 12.25", 22,000#
-- Polish Outside of Front Aluminum Wheels
-- Hub & Lug Nut Covers, S/S, Front Wheels
Sngl Rear Axle 31,000 lbs, Meritor, RS-30-185
-- Tire Inflation Indicators, for Chassis w/Single Rear Axle
-- Rear Axle Ratio for 60 MPH Maximum
-- Sngl Rear Susp, 31,000#, Neway AD-131 W/Shocks
-- Brakes, "P" Cam, Dbl Anchr, Cst Shoes, 16.5 x 7"
-- Air Tanks, Minimum for Air Suspension
-- Rear Axle Seals
-- Rr Tires, Mchl, 315/80R22.5, "L" XDY-3, 33,000#
-- AlumHub Plt, Accuride 29730A 22.5" X 9.0"
-- Polish Outside of Rear Aluminum Wheels
-- Hub & Lug Nut Covers, S/S, Rear, Axle
Drive Shaft
Lubricant, Petroleum, Axles
Air Brake System
Air Dryer, Bendix AD-9
Air Reservoir, Additional, 1730 Cubic Inches w/ PPV
Air Tank Drain Valves, Auto/Pull Cable
ABS Braking System, Wabco 4S/4M w/Traction Ctrl
Brake Lock, All Wheel (Front Axle)
Cab, 134" CBC, Four Door, Aerial Flat Roof
-- Windows, Side Cab, Fixed
-- Stripe, Paint Transition, Cab
-- Cab Tilt System
-- Cab, Mounts, Air, 1" Up, 1" Down 35 Degree Tilt
-- Seat, Dvr, H.O. Bostrom, Air Suspension
-- Seat, Offcr, H.O. Bostrom, SCBA NonSusp
-- Seats, Rear Facing Crew, H.O.Bostrm SCBA Otbrd (2)
-- Seats, Forward Facing, SCBA, H.O. Bostrom, Inboard (2)
-- Bottle Holder with Restraint, Zico
-- Seat Covers, Durawear/Vinyl
Cab Grab Handle - (4) Ext. Knurled SS + (2) Interior Forward
Mirrors, Cab, Mekra, Chrome, 16" x 7" M2 Style H&R
-- Mirrors, Cab, Convex, 7" x 7"
Fenders, Cab, Polished Stainless Steel
Mud Flaps, Front
Antenna, UHF/VHF Mtd LS Cab Roof (162-174 MHz)
Antenna, UHF/VHF Mtd RS Cab Roof (136-174 MHz)
Electrical Load Management System
-- Battery System - 12V (6) HD Batteries
-- Battery Charger, Kussmaul Auto Chg 1200 "Pump +" w/Recept
-- Receptacle, Super Auto Eject, 120 VAC, Yellow Cover
-- Electrical Load Manager Interlock, Pumper
Cab Interior Specifications
Steering Column, Adj Tilt & Telescoping
Steering Wheel, 18" Four-Spoke Charcoal Gray
Overhead Console w/(1) Stg Compt, RH
Overhead Switch Console, Aerial Control (2)
-- Overhead Switch Console, Aerial, PTO Rocker Switch
Gauges (U.S)
Switch, Additional Dash Rocker, (1)
Lights, Cab Interior, Red/Clear, w/ (2) Swivel Map Lights
Outlets, 12-Volt, Automotive Type (3) Dash Mounted

DESCRIPTION
Heater/Air Conditioner and Defroster, Primary
-- Heater/Air Conditioner, Auxiliary
-- Compressor, Refrigerant, A/C, 15.3 cfm
-- Air Conditioning Condenser, Radiator Mtd
-- HVAC Performance Spec
Interior, Chieftain Shadow Gray Imperial 1200 w/Shadow Trim
Trim, Door, ABS/Upper, Brushed S/S Lower Kickplate
-- Windows, Door Controls, Power Front & Rear
Map Box - 8"H x 10"W x 13"D w/ (3) 3" Slots
Vehicle Data Recorder
Electronic Stability Control
Seat Belt Warning System
Helmet Storage, Each Seating Position (6)
Seat Belts 3Pt Fwd facing, 3Pt Rr facing
Bumper Extension 18", Polished Stainless Steel
-- Diamondplate Deck, 3/16" Bright Finished
Tow Hooks, Painted, Mtd Bot Frame Ext
-- Air Discharge Connector, LS Step Well
Plates, Fluid & Seating Capacity
Plate, Overall Travel Height, Length and Weight
Tag, Warning, Aerial Devices
Tag, Warning, Crew Area and Rear Body Step
Testing, Third Party, Aerial w/Pump
Pump Enclosure, S/M S/S 50" Wide, Crosslays Only, RM
-- Pump Panel, Brushed Stainless Steel, Side Mount
-- Crosslays, (2) 200' 1-3/4" & (1) 200' 2-1/2", Sngl Lay
-- Outlet, Crosslay, First, 2" Akron, 1-1/2" Swivel Elbw
-- Outlet, Crosslay, Second, 2" Akron, 1-1/2" Swvl Elbw
-- Outlet, Crosslay, Third, 2-1/2" Akron, 2-1/2" Swvl Elbw
-- Crosslay Cover, Vinyl Snap-on Type
-- Storage Above Pump, No Cover
-- Running Boards, 3/16" Non-Skid Alum Dia Plt
-- Platform, Pump Operator, Pullout, W/Grip Strut, LS
-- Tags, Color Coded Per NFPA
-- Tags, "No Step Surface", Pump Enclosure
-- Valve Controls, Locking Push-pull Type
-- Engine Gauges built-into Pump Governor
-- Omit Vernier Throttle
-- Gauge, Water Level, Class 1 Intelli-Tank
-- Handrails, (2) 18" Mtd Vertically at Pump Enclosure
-- Mic Box, Cast Products, Large, ALF Aerials
-- Fire Pump, Hale Qmax 1500 GPM Single Stage, RM ALF Ae
-- Installation, Midship Pump
-- Anodes, Sacrificial, Pump, LS/RS
-- Primer, Hale ESP
-- Mechanical Seal, Hale
-- Manuals, Pump Operation and Parts, Hale (2) Sets (CD'S)
-- Fire Pump Factory Painted Finish
-- Governor, FRC PumpBoss
-- Piping, Class 1 HP Hose and Stainless Steel Pipe
-- Drain, Master, Class 1
-- Tank Fill, 1-1/2"
-- Tank to Pump Line, Akron 3"
-- Pump Cooler, By-pass Aux Pump Cooler Valve
-- Valve Package (1500) GPM, Hale RM ALF Aerials

DESCRIPTION

-- Inlet, Main, LS 6" Non-gated, Cap
-- Inlet, Main, RS 6" Non-gated, Cap
-- Inlet, LS Panel Rear 2-1/2" Akron, Swivel, Plug
-- Outlet, LS Panel Front (1) 2-1/2" Akron Straight Discharge
-- Outlet, LS Panel Rear (1) 2-1/2" Akron Straight Discharge
-- Outlet, RS Panel Front (1) 2-1/2" Akron Straight Discharge
-- Outlet, RS Panel Rear (1) 2-1/2" Akron Straight Disc
Light Hood for Right Side Pump Panel
Lights, Work, (2) 6" Pump Compartment
Gauges, Master, (2) Class 1, 4-1/2", 30-0-400 PSI
Gauges, 2-1/2" 0-400 Class 1 Line Gauges
Gauge, Discharge, Aerial 2-1/2" 0-400 Class 1
Electrical Interface w/Fast Idle System
Relief Valve, Intake
Pump Shift, Custom RH Side
Pump Shift Override, Manual
Drains, Quarter Turn, 3/4" Class 1
Engine Cooler, Custom or FTL Chassis
-- Engine Cooler, Body Facility Finishes Installation
Outlet, Aerial, 4" Valve, Electric Controlled
-- Discharge Material, 4" Stainless Steel
Body, C23R75, Aluminum, Roll-up Doors, Std Cab, SRA
-- Water Tank - Poly-Tank - 500 GALLONS
-- Water Tank-UPF, C23R75, All Bodies & Cabs, SRA
-- Body Material, Aluminum, Tube, C23R75 RM Aerial
-- Compts, Driver, SA, Rescue, Rollup, Std Cab
-- Compts, Curb, SRA, Hosebed Style, Rollup, Std Cab
-- Hose Bed, Deep, C Series RM 75' Ladder
-- Hosebed Flooring, Fiberglass
-- Hosebed Capacity, MV75, Deep Bed 1000' of 5" LDH
-- Doors, Rollup, Robinson ROM, C23R75, Single RR Axle
-- Roll-Up Door Finish, Satin
-- Lights - Body Compartment, Whelen LED Strip-Lite
-- Air Cylinder Compts, (12), SRA, C Series 75' RM Ladder
-- Wheelwells, Poly, Single RA, SS Fenderette
Exhaust Heat Deflector
Compartmentation Detail
O/R Control Compartment Doors
Fuel Fill Tube, Street Side, C23R75
Ground Ladder Access, (1) Rollup Door
Mud Flaps, Rear
Body Trim, C Series RM 75' Ladder
Rub Rails, ALF Aluminum Extrusion, Red Reflective Stripe
Handrails, Aluminum, Body, 75' RM Ladder
Steps "V" Frame One (1) Each Side, MV
(6) Chrome Plated Folding Steps Front Of Body
Outrigger Covers (2)
Outrigger Pad Storage Slides
Hosebed Cover, Easy-Load, RM Aerial/Towers
Storage, Grd.Ladders, Tube Style, RM 75' Ladders
Storage, Pike Poles (Center Stack, Tube Style)
Rear Tow Devices (Painted Torque Box Color)
12V Electrical Sys, Body, Multiplexed
Lights - Step
ACCESSORIES, AERIALS

DESCRIPTION

-- Decking, Turtle Tile, Black, Floors, Multiple Shelves & Tray
-- Shelves, Adj, 3/16" Smooth Alum (3)
-- Adjustable Track in Cmpts for Future Shelf Installation
-- Tray, 250# Floor Mounted, Sliding (1)
-- Tray, 500# Floor Mounted, Sliding (1)
-- Tool Board, Swing-Out Hinged Tool Panel (1)
NFPA Optical Warning System
-- Lightbar, Aerial Contour, Combo
-- Front Warning Lights, Fixed, LED
-- Lights, Warning, Front, Inbrd of Turn Signal, LED
-- Lights, Warning, ALF Aerial, Whelen LED Pkg
-- Headlights Halogen, 1High & 1Hi/Low Beam Each Side
-- Turn Signals Cornering Lamps, LED, Halogen
-- Horns, Dual Electric
-- Siren, PA 200 Watt w/(1) Speaker, Ctr Bumper
-- Switch, Foot, (1) Siren/RS
-- Air Horns, Dual 21" Grover Stuttertone 1-LH, 1-RH Bumper
-- Switch, Selector, Horn/Air Horn, Cab Dash Mtd
-- Code 3 Model D50C Constant 97 DB Back Up
Lights, ICC Lighting-LED-Body - Single Rear Axle
Lights, Underbody (8)
Lights, Deck Lights, (2) 6" Unity, Rear Aerial Body
Light & Bracket, License Plate
Lights, Whelen, LED Stop, Turn and Halogen Back-Up
Light, Door Ajar, Un-Stowed Indicator, Flashing LED
Painting, Body, ALF AERIALS (ALL)
-- Paint, Custom Cab, Single Color,
-- Paint, Chassis, Black
-- Paint, Color, Body Single Color
-- Finish, Compartment Interior, Zolatone
-- Paint, Paint, Factory Std. Finish
Undercoating, Rust Inhibitor, Body
Lettering, (60) Scotchlite, 3" Letters
Lettering, (36) Scotchlite, Red, Letters on Sides of Aerial
Striping, Scotchlite, (1) 4" NFPA Stripe
Reflective Chevron
-- Red and Fluorescent Yellow Reflective
Aerial Ladder, 75' RM, Three (3) section STEEL (C23R75)
-- Testing & Certifications, C23R75, 500#Dry/500# Wet Tip
-- Torque Box, Welded Tube, (2) Outriggers, 75' RM Ladder
-- Aerial Device Mtg & Travel Support (RM 2 or 4 O/R)
-- Outriggers (2), 14' Stance, 75' RM Ladder
-- Jack Cylinders, Rr, 23-1/4" Stroke, Rd Style
-- Jack Extension, 42" Stroke, 14' Stance
-- Outrigger Pads (2), 154 sq-in
-- (2) Auxiliary Outrigger Pads
-- O/R Warning Lights, Truck-Lite 7" LED w/(2) LED Ground Lite
-- Aerial Ladder Performance C23R-75, 500# dry/500# wet tip loa
-- (1) Folding Step, Bustin, Aerial Ladder Tip,
-- Elevation System, -7 to 78 Degrees, 75' RM Ladder
-- Rotation System, 40.29" Diameter
-- Extension/Retraction System, C Series 3-Section Ladder
-- Ladder Slide Mechanism
-- Ladder Electrical/Air Line Track System
-- Extension Indicators, 5' & 10' Marker Spacing

DESCRIPTION

|-- 4" Swivel Combo, 3-Pt Hyd, Wtr & 26 Ring Elec
|-- Turntable, Treadplate, 68" x 75", 75' RM Ladders
|-- Safety Railing, T/T, Knurled SS, Safety Chain Gate
|-- Cradle Alignment Indicators
|-- (4) Turntable Work Lights, Rear Step Mtd
|-- Inlet, 4" Waterway Auxiliary , Curbside Rear, RM 75' Ladders
|-- Waterway Inlet Accessories, (1) 4"NST x 5"Storz
|-- Rotational Swivel, 4"
|-- Heel Pin Swivel
|-- Water System Friction Loss
|-- Telescopic Waterway, 3 Sect, 4.5"-4"-3.5"
|-- Monitor, Akron 3598, MasterStream XL, Wireless Radio Control
|-- Ladder Egress, Stainless Steel Bolt-on
|-- Akron #5178, 1500 GPM, 3.5" Nozzle, Electric
|-- Wireless Monitor Function Switches, Akron, T/T & Monitor
|-- Retractable Monitor, Mechanical Latch With Auto-Connector
|-- Flowminder Mtd on T/T Console/Class 1 FMS
(2) Aerial Base Sect Nameplates, 14" x 120"
Hydraulic System W/Sight Glass Ind, 40 Gal
|-- 12 Volt Emergency Hydraulic System, All
|-- (2) Emerg Pwr Unit (EPU) Swtchs, LH/RH Otrgr
PTO, Chelsea Model 277 w/"Hot-Shift", Allison HD Trans. AL1
Elect Sys.Components, Non-Multiplex, C Series 75' RM Ladders
|-- Short O/R Jacking System, Manual, C23R75*
|-- (2) Outrigger Leveling Ind, LH/RH Apparatus Sides
|-- Outrigger Deployment Warning Alarm
|-- Ladder/Outrigger Interlock System
|-- Safety Features, Short Jacking, Out & Down O/R, New Version
|-- Rotation Limiting System, Out & Down Outgrs
|-- Aerial Control Console, LH T/T, C Series RM 75' Aerials
|-- Engine, Fast Idle Actuator (With Fire Pump)
|-- Aerial Hour Meter, Wired to PTO
Comm Sys., FireCom pantherC Series, 3-Way, Tip-T/T-Pump Pane
(2) Unity Spotlights, Rear Ladder Base
(2) Unity Spotlights, Aerial Tip
120 Volt Circuit to Ladder Tip
|-- Receptacle, (1) Woodhead L5-20, Ladder Tip
(1) Special Width Roof Ladder Mtg Brckt, Fly, Right Side
(6) Special Retorquing Tools w/Tool Box
Aerial PPG Painting
Reflective Striping, Otrgr Bm Refl
Caution & Warning Sign
On-Site Maintenance & Operational Training (3) Days
Manuals Chassis, Pump; Body; Aerial Device (Two-2)
GROUND LADDERS
Ladder, Duo-Safety, Series 900-A, 24' 2-Sec (1)
Ladder, Duo-Safety, Series 1225-A, 35' 3-Sec (1)
Ladders, Duo-Safety, Series 875-A, 16' Roof (2)
Ladder, Duo-Safety, Series 701-14 Attic (1)
Ladder, Duo-Safety, Series 585-A, 10' Folding (1)
LOOSE EQUIPMENT
Pike Poles, (2) Duo-Safety, 6' Fiberglass 6FP
Pike Poles, (2) Duo-Safety, 8' Fiberglass 8FP
Pike Poles, (2) Duo-Safety, 12' Fiberglass 12FP
Chocks, Wheel, (2) Ziamatic SAC-44 Folding w/Brkt

DESCRIPTION

Purchaser Provides All Other NFPA 1901 Equipment
Warranty - Refer to FS12-11 FORM G

QUOTATION

American LaFrance

OHIO STS
\$637,194.00

American LaFrance Eagle 4 Door Tilt Cab, Formed Aluminum Body, Tandem Axle, 75' Rear-Mount, Telescoping Ladder, 500lb (Steel)

08/01/2011

Quote No: ALF AA04-

Page 1

DESCRIPTION

== American LaFrance 75' Rearmount Telescoping Ladder, 500lb
== Eagle 134 (4) Door Tilt Cab Fire Chassis, Tandem - Formed
Eagle Medium COE (4) Door Fire Chassis
Custom Cab and Chassis Specifications
Overall Height 11' - 2" and Overall Length 38' - 10"
NFPA 1901 Certificate of Compliance
Chassis Wheelbase 209"
|-- Frame, 11/32" x 3-1/2" x 10-15/16" Up to 362" Overall Length
|-- Frame Fasteners, Huck Spin
Frame Reinforcement, C-Channel, (375"+) Over All Length
|-- Engine, Cummins ISX-500, 500 bhp/1645 lb-ft 11.9L 2010 EPA
|-- Starter, Delco 42MT/OCP w/Thermal Protection
|-- Air Compressor, Wabco 18.7 cfm
|-- Fan Drive - Engine, Horton Drivemaster
|-- Coolant Filter, Fleetguard, Spin-on (Cummins)
|-- Transmission, Allison 4000 EVS-P
|-- Trans Prog, 5 Spd Pumper, Fire & Emg (120)
|-- Transmission Shifter, Touch Pad
|-- Transmission Oil Cooler
|-- Engine Brake, Jacobs w/(2) Switches
|-- Fuel/Water Separator, Racor 490 w/Electric Heater
|-- Exhaust System - RH Horizontal ATD, Horizontal Tailpipe
|-- Alternator, Leece-Neville, 320 Amp
|-- Air Cleaner w/Ember Separator, Frontal Intake
|-- Air Restriction Gauge, Engine Mtd with Dash Light
|-- Radiator, High Capacity Down Flow, 1627
|-- Coolant Hoses, Gates "Blue Stripe" EPDM
|-- Coolant, Engine, Heavy Duty, to -34 Fahrenheit
|-- Engine Protection Alarms
Light, Engine Compartment (1)
Heater Hoses
Engine Stop Control, Ignition Switch
|-- Fuel Tank, 54 Gallon, Rectangular, Steel
|-- Fuel Fill, Rear, 54 Gallon Tank
|-- Fuel Lines, Reinforced, Wire Braid
Front Axle Package, 20,000 lbs, Meritor MFS-133A
|-- Steering Gear 20,000 lb. Cap w/Ram Assist
|-- Power Steering Pump, Vickers V20
|-- Power Steering Reservoir, 4 Quart
|-- Front Suspension 20,000 lb Taperleaf w/Shock
|-- Front Brakes, Meritor EX-225H 17" Air Disc
|-- Frt Tires, Mchl, 385/65R22.5 "J" XZY-3 WB, 20,000#

DESCRIPTION
-- Alm Hub Plt, 22.5" x 12.25", 22,000#
-- Polish Outside of Front Aluminum Wheels
-- Hub & Lug Nut Covers, S/S, Front Wheels
Tndm Rr Axle 44,000 lbs, Meritor, RT-44-145
-- Tire Inflation Indicators, for Chassis w/Tandem Rear Axles
-- Rear Axle Ratio for 60 MPH Maximum
-- Tndm Rear Susp, 48,000#, Neway AD-248 W/Shocks
-- Brakes, "Q-Plus" Tndm Rr Axle, 16.5" x 7" Cam
-- Air Tanks, Minimum for Air Suspension
-- Rear Axle Seals
-- Rr Tires, Mchl, 11R22.5, "H", XDN2, 48,000#
-- Alm Hub Plt, 22.5" x 8.25", 58,400#
-- Polish Outside of Rear Aluminum Wheels
-- Hub & Lug Nut Covers, S/S, Rear, Tandem Axle
Drive Shaft
Lubricant, Petroleum, Axles
Air Brake System
Air Dryer, Bendix AD-9
Air Tank Pull Cables, Each Tank
ABS Braking System, Wabco 4S/4M
Brake Lock, All Wheel (Front Axle)
Cab, 134" CBC, Four Door, Flat Roof
-- Windows, Side Cab, Fixed
-- Cab Tilt Mechanism w/Extnl Alarm
-- Cab, Mounts, Air, 1" Up, 1" Down 35 Degree Tilt
-- Seat, Dvr, H.O. Bostrom, Air Suspension
-- Seat, Offcr, H.O. Bostrom, SCBA NonSusp
-- Seats, Rear Facing Crew, H.O.Bostrm SCBA Otbrd (2)
-- Seats, Forward Facing, SCBA, H.O. Bostrom, Inboard (2)
-- Bottle Holder with Restraint, Zico
-- Seat Covers, Durawear/Vinyl
Cab Grab Handle - (4) Ext. Rubber Inserts
Mirrors, Cab, Mekra, Chrome, 16" x 7" M2 Style H&R
-- Mirrors, Cab, Convex, 7" x 7"
Fenders, Cab, Polished Stainless Steel
Mud Flaps, Front
Antenna, UHF/VHF Mtd LS Cab Roof (42-50 MHz)
Antenna, UHF/VHF Mtd RS Cab Roof (42-50 MHz)
Electrical Load Management System
-- Battery System - 12V (6) HD Batteries
-- Battery Charger, Kussmaul Auto Chg 1200 "Pump +" w/Recept
-- Receptacle, Super Auto Eject, 120 VAC, Yellow Cover
-- Electrical Load Manager Interlock, Pumper
Cab Interior Specifications
Steering Column, Adj Tilt & Telescoping
Steering Wheel, 18" Four-Spoke Charcoal Gray
Overhead Console
Overhead Switch Console, Aerial Control (2)
-- Overhead Switch Console, Aerial, PTO Rocker Switch
Gauges (U.S)
Lights, Cab Interior, Red/Clear
Outlets, 12-Volt, Automotive Type (3) Dash Mounted
Heater/Air Conditioner and Defroster, Primary
-- Heater/Air Conditioner, Auxiliary
-- Compressor, Refrigerant, A/C, 15.3 cfm

DESCRIPTION

-- Air Conditioning Condenser, Radiator Mtd
-- HVAC Performance Spec
Interior, Chieftain Shadow Gray Imperial 1200 w/Shadow Trim
Trim, Door, ABS/Upper, Brushed S/S Lower Kickplate
-- Windows, Door Controls, Power Front & Rear
Map Box - 8"H x 10"W x 13"D w/ (3) 3" Slots
Vehicle Data Recorder
Electronic Stability Control
Seat Belt Warning System
Helmet Storage, Each Seating Position (6)
Seat Belts 3Pt Fwd facing, 3Pt Rr facing
Bumper Extension 12", Polished Stainless Steel
-- Diamondplate Deck, 3/16" Bright Finished
Tow Hooks, Painted, Mtd Bot Frame Ext
Plates, Fluid & Seating Capacity
Plate, Overall Travel Height, Length and Weight
Tag, Warning, Aerial Devices
Tag, Warning, Crew Area and Rear Body Step
Testing, Third Party, Aerial w/Pump
Pump Enclosure, S/M S/S 50" Wide, Crosslays Only, RM
-- Pump Panel, Brushed Stainless Steel, Side Mount
-- Crosslays, (2) 200' 1-3/4" & (1) 200' 2-1/2", Sngl Lay
-- Outlet, Crosslay, First, 2" Akron, 1-1/2" Swivel Elbw
-- Outlet, Crosslay, Second, 2" Akron, 1-1/2" Swvl Elbw
-- Outlet, Crosslay, Third, 2-1/2" Akron, 2-1/2" Swvl Elbw
-- Crosslay Cover, Vinyl Snap-on Type
-- Storage Above Pump, No Cover
-- Running Boards, 3/16" Non-Skid Alum Dia Plt
-- Platform, Pump Operator, Pullout, W/Grip Strut, LS
-- Tags, Color Coded Per NFPA
-- Tags, "No Step Surface", Pump Enclosure
-- Valve Controls, Locking Push-pull Type
-- Engine Monitoring System, Enfo IV, Class 1
-- Omit Vernier Throttle
-- Gauge, Water Level, Class 1 Intelli-Tank
-- Handrails, (2) 18" Mtd Vertically at Pump Enclosure
-- Fire Pump, Hale Qmax 1500 GPM Single Stage, RM ALF Aerials
-- No Pump Shaft Mechanical Speed Counter
-- Installation, Midship Pump
-- Anodes, Sacrificial, Pump, LS/RS
-- Primer, Hale ESP
-- Mechanical Seal, Hale
-- Manuals, Pump Operation and Parts, Hale (2) Sets (CD'S)
-- Fire Pump Factory Painted Finish
-- Governor, FRC PumpBoss
-- Piping, Class 1 HP Hose and Stainless Steel Pipe
-- Drain, Master, Class 1
-- Tank Fill, 1-1/2"
-- Tank to Pump Line, Akron 3"
-- Pump Cooler, By-pass Aux Pump Cooler Valve
-- Valve Package (1500) GPM, Hale RM ALF Aerials
-- Inlet, Main, LS 6" Non-gated, Cap
-- Inlet, Main, RS 6" Non-gated, Cap
-- Inlet, LS Panel Rear 2-1/2" Akron, Swivel, Plug
-- Outlet, LS Panel Front (1) 2-1/2" Akron Straight Discharge

DESCRIPTION

-- Outlet, LS Panel Rear (1) 2-1/2" Akron Straight Discharge
-- Outlet, RS Panel Front (1) 2-1/2" Akron Straight Discharge
-- Outlet, RS Panel Rear (1) 2-1/2" Akron Straight Disc
Light Hood for Right Side Pump Panel
Lights, Work, (2) 6" Pump Compartment
Gauges, Master, (2) Class 1, 4-1/2", 30-0-400 PSI
Gauges, 2-1/2" 0-400 Class 1 Line Gauges
Gauge, Discharge, Aerial 2-1/2" 0-400 Class 1
Electrical Interface w/Fast Idle System
Relief Valve, Intake
Pump Shift, Custom RH Side
Drains, Quarter Turn, 3/4" Class 1
Engine Cooler, Custom or FTL Chassis
-- Engine Cooler, Body Facility Finishes Installation
Outlet, Aerial, 3" Valve Push/Pull Control, RM Aerials Only
-- Discharge Material, 4" Stainless Steel
Body, Rescus Style Rollup Doors - Tandem Rear Axle
-- Water Tank - Poly-Tank - 500 GALLONS
-- Water Tank-UPF, C23R75, All Bodies & Cabs, TRA
-- Body Material, Aluminum, Tube, C23R75 RM Aerial
-- Compts, Driver, TRA, Rescue, Rollup, Std Cab
-- Compts,Curb, TRA, Hosebed Style, Rollup, Std Cab
-- Hose Bed, Deep, C Series RM 75' Ladder
-- Hosebed Flooring, Fiberglass
-- Hosebed Capacity, MV75, Deep Bed
-- Doors, Rollup, Robinson ROM, C23R75, Tandem RR Axle
-- Roll-Up Door Finish, Satin
-- Lights - Body Compartment
-- Lights - Body Compartment, 75' RM Ladder
-- Air Cylinder Compts, (6), SRA, C Series 75' RM Ladder
-- Wheelwells, Poly, Tandem RA, SS Fenderette
Exhaust Heat Deflector
Compartmentation Detail
O/R Control Compartment Doors
Fuel Fill Tube, Street Side, C23R75
Ground Ladder Access, (1) Treadplate Lift-UP Door
Mud Flaps, Rear
Body Trim, C Series RM 75' Ladder
Rub Rails, ALF Aluminum Extrusion, Red Reflective Stripe
Handrails, Aluminum, Body, 75' RM Ladder
Steps "V" Frame One (1) Each Side, MV
(6) Chrome Plated Folding Steps Front Of Body
Outrigger Covers (2)
Outrigger Pad Storage Slides
Hosebed Cover, Easy-Load, RM Aerial/Towers
Storage, Grd.Ladders, Tube Style, RM 75' Ladders
Storage, Pike Poles (Center Stack, Tube Style)
Rear Tow Devices (Painted Torque Box Color)
12V Electrical Sys, Body, Multiplexed
Lights - Step
ACCESSORIES, AERIALS (EXCEPT FOR TDA)
-- Decking, Turtle Tile, Black, Floors, Multiple Shelves & Tray
-- Shelves, Adj, 3/16" Smooth Alum (3)
-- Adjustable Track in Cmpts for Future Shelf Installation
-- Tray, 250# Floor Mounted, Sliding (1)

DESCRIPTION
-- Tray, 500# Floor Mounted, Sliding (1)
-- Tool Board, Swing-Out Hinged Tool Panel (1)
NFPA Optical Warning System
-- Lightbar, Aerial Contour, Combo
-- Front Warning Lights, Fixed, LED
-- Lights, Warning, Front, Inbrd of Turn Signal, LED
-- Lights, Warning, ALF Aerial, Whelen LED Pkg
-- Headlights Halogen, 1High & 1Hi/Low Beam Each Side
-- Turn Signals Cornering Lamps, LED, Halogen
-- Horns, Dual Electric
-- Siren, PA 200 Watt w/(1) Speaker, Ctr Bumper
-- Switch, Foot, (1) Siren/RS
-- Air Horns, Dual 21" Grover Stuttertone 1-LH, 1-RH Bumper
-- Switch, Selector, Horn/Air Horn, Cab Dash Mtd
-- Code 3 Model D50C Constant 97 DB Back Up
Lights, ICC Lighting-LED-Body - Single Rear Axle
Lights, Underbody (8)
Lights, Deck Lights, (2) 6" Unity, Rear Aerial Body
Light & Bracket, License Plate
Lights, Whelen, LED Stop, Turn and Halogen Back-Up
Painting, Body, ALF AERIALS (ALL)
-- Paint, Custom Cab, Single Color,
-- Paint, Chassis, Black
-- Paint, Color, Body Single Color
-- Finish, Compartment Interior, Zolatone
-- Paint, Paint, Factory Std. Finish
Undercoating, Rust Inhibitor, Body
Lettering, (60) Scotchlite, 3" Letters
Lettering, (36) Scotchlite, Red, Letters on Sides of Aerial
Striping, Scotchlite, (1) 4" NFPA Stripe
Reflective Chevron
-- Red and Yellow Reflective
Aerial Ladder, 75' Rear Mount - Three (3) section STEEL (C23
-- Testing & Certifications, C23R75, 500#Dry/500# Wet Tip
-- Torque Box, Welded Tube, (2) Outriggers, 75' RM Ladder
-- Aerial Device Mtg & Travel Support (RM 2 or 4 O/R)
-- Outriggers (2), 14' Stance, 75' RM Ladder
-- Jack Cylinders, Rr, 23-1/4" Stroke, Rd Style
-- Jack Extension, 42" Stroke, 14' Stance
-- Outrigger Pads (2), 154 sq-in
-- (2) Auxiliary Outrigger Pads
-- (2) Outrigger Lights, Out/Down O/R w/(2) Grnd Lts
-- Aerial Ladder Comp, C23R-75, 500# Dry/500# WetTip Load
-- (1) Folding Step, Bustin, Aerial Ladder Tip, NFPA Compliant
-- Elevation System, -7 to 78 Degrees, 75' RM Ladder
-- Rotation System, 40.29" Diameter
-- Extension/Retraction System, C Series 3-Section Ladder
-- Ladder Slide Mechanism
-- Ladder Electrical/Air Line Track System
-- Extension Indicators, 5' & 10' Marker Spacing
-- 4" Swivel Combo, 3-Pt Hyd, Wtr & 26 Ring Elec
-- Turntable, Treadplate, 68" x 75", 75' RM Ladders
-- Safety Railing, T/T, Knurled SS, Safety Chain Gate
-- Cradle Alignment Indicators
-- (4) Turntable Work Lights, Rear Step Mtd

DESCRIPTION

|-- Inlet, 4" Waterway Auxiliary , Curbside Rear, RM 75' Ladders
|-- Waterway Inlet Accessories, (1) 4" NST
|-- Rotational Swivel, 4"
|-- Heel Pin Swivel
|-- Water System Friction Loss
|-- Telescopic Waterway, 3 Sect, 4.5"-4"-3.5"
|-- Monitor, Akron 3598, MasterStream XL, Wireless Radio Control
|-- Ladder Egress, Stainless Steel Bolt-on
|-- Ladder Illumination Lighting, Red, C Series 3-Sec Ladders
|-- Akron #5178, 1500 GPM, 3.5" Nozzle, Electric
|-- Wireless Monitor Function Switches, Akron, T/T & Monitor
|-- Retractable Monitor, Mechanical Latch With Auto-Connector
|-- Flowminder Mtd on T/T, Akron
(2) Aerial Base Sect Nameplates, 14" x 120"
Hydraulic System W/Sight Glass Ind, 40 Gal
|-- 12 Volt Emergency Hydraulic System, All
|-- (2) Emerg Pwr Unit (EPU) Swtchs, LH/RH Otrgr
PTO, Chelsea Model 277 w/"Hot-Shift", Allison HD Trans. AL1
Elect Sys.Components, Non-Multiplex, C Series 75' RM Ladders
|-- Short O/R Jacking System, Manual, C23R75*
|-- (2) Outrigger Leveling Ind, LH/RH Apparatus Sides
|-- Outrigger Deployment Warning Alarm
|-- Ladder/Outrigger Interlock System
|-- Safety Features, Short Jacking, Out & Down O/R, New Version
|-- Rotation Limiting System, Out & Down Outgrs
|-- Aerial Control Console, LH T/T, C Series RM 75' Aerials
|-- Engine, Fast Idle Actuator (With Fire Pump)
|-- Aerial Hour Meter, Wired to PTO
Comm Sys, Tip to T/T, Atkinson
(2) Unity Spotlights, Rear Ladder Base
(2) Unity Spotlights, Aerial Tip
120 Volt Circuit to Ladder Tip
|-- Receptacle, (1) Woodhead L5-20, Ladder Tip
(1) Special Width Roof Ladder Mtg Brckt, Fly, Right Side
(6) Special Retorquing Tools w/Tool Box
Aerial PPG Painting
Reflective Striping, Otrgr Bm Refl
Caution & Warning Sign
On-Site Preventative Maintenance & Operational Training (3)
Manuals Chassis; Pump; Body; Aerial Device (Two-2)
GROUND LADDERS
Ladder, Duo-Safety, Series 900-A, 24' 2-Sec (1)
Ladder, Duo-Safety, Series 1225-A, 35' 3-Sec (1)
Ladders, Duo-Safety, Series 875-A, 16' Roof (2)
Ladder, Duo-Safety, Series 701-14 Attic (1)
Ladder, Duo-Safety, Series 585-A, 10' Folding (1)
LOOSE EQUIPMENT
Pike Poles, (2) Duo-Safety, 6' Fiberglass 6FP
Pike Poles, (2) Duo-Safety, 8' Fiberglass 8FP
Pike Poles, (2) Duo-Safety, 12' Fiberglass 12FP
Chocks, Wheel, (2) Ziamatic SAC-44 Folding w/Brkt
Purchaser Provides All Other NFPA 1901 Equipment
Warranty - Refer to FS12-11 FORM G

REAR-MOUNT LADDER HD/XD



AERIAL

A refined version of our proven aerial performers with Heavy-Duty and Xtra-Heavy Duty ratings for versatile fire ground performance.

- High tip load ratings – 500 lbs and 750 lbs
- Pre-piped telescopic water system rated at 1500 GPM
- Retractable Monitor as standard equipment is quick to establish master stream operation or rescue operation
- Maximum lift cylinder elevation range, -7 to +78°
- 14 ft Outrigger spread with deep penetrating jacks allowing full rated operating capacities on a 10.5° slope (18% grade)
- Open, unobstructed walkway on ladder for easy, safer climbing
- Maximum available compartmentation in Stainless or Aluminum, depths up to 25" – Store large accessories
- Easy payout and reload of hose, up to 1000' of 5" LDH
- Low enclosed ground ladder storage – Promotes safe removal and easier handling of up to 190 ft of ladders
- Numerous aerial tip options available



REAR-MOUNT LADDER HD/XD



Unobstructed walkway with wider and deeper fly section and optional ClearPath LED



Unrestricted 1500 GPM monitor with 180° sweep and 165° vertical range



Low ground ladder storage with safe and easy access to hose and equipment



12' or 14' "H Style" Outriggers allow aerial operation at full capacity in tight areas

These are the typical specifications for the 500 lb Rear-Mount Ladder HD and 750 lbs Rear-Mount Ladder XD

LADDER: All-steel construction with k-bracing; Dual cylinder extension system; TLC (Triangulated Lifting Configuration).

4 SECTION AERIAL LADDER:

- HD: 500 lbs capacity - dry;
250 lbs with full water tower rating
- XD: 750 lbs capacity - dry;
500 lbs with full water tower rating

All with 100 lbs equipment allowance

WATERWAY FLOW CAPACITY: 1500 GPM

HORIZONTAL REACH:
110' Aerial - 99' reach

ANGLE OF ELEVATION: - 7° to + 78°

MONITOR: Retractable with lever connection to ladder fly or outer mid-section for rescue operations; Automatic electrical disconnect for monitor functions. Optional 30° above horizontal monitor range for low-angle store front operations.

OUTRIGGERS: Quantity of 4, H-type, out-and-down style, Short-Jacking capability with Rotational Limiting Safety system. Leveling capacity for full capabilities up to 10.5 ° (18% grade); 50% capabilities up to 15 ° (25% grade).

OUTRIGGER SPREAD:

- HD: 12' with Short-Jacking capability of 10'
- XD: 14' with Short-Jacking capability of 11'

O.A.L.: 41' - 2" to 43' - 0"

O.A.H. RANGE: 11' - 5" to 11' - 11"

WHEELBASE RANGE: 222" to 262"

COMPARTMENTATION:

Stainless Steel or Aluminum in 25" Rescue Depth.

CHASSIS: American LaFrance Eagle®

FIRE PUMP: American LaFrance Midship Pump in single and two-stage models, capacities of 1,250 to 2,000 GPM.

WATER/FOAM TANK CAPACITY: 300 to 500 gal Additional foam tank capacity in above pump storage

For your nearest American LaFrance dealer, go to www.americanlafrance.com.

Some specifications and features shown or mentioned in this brochure are optional and are available upon request at extra cost. Specifications are subject to change without notice. ©2009, American LaFrance, LLC. All rights reserved.



QUOTATION

American LaFrance

OHIO STS

\$748,970.00

American LaFrance Eagle 4-Door Tilt Cab, Formed Aluminum Body, Tandem Axle, 100' Rear-Mount Telescoping Ladder, 500lb (Steel)

08/01/2011

Quote No: ALF AA05-

Page 1

DESCRIPTION

== American LaFrance 100' Rearmount Telescoping Ladder 500lb Eagle 134 (4) Door Tilt Cab Fire Chassis, Formed Aluminum Bo Custom Cab and Chassis Specifications Overall Height - 11' - 4" and Overall Length 41' - 6" NFPA 1901 Certificate of Compliance Chassis Wheelbase - 238"

- |-- Frame, 7/16" x 3-11/16" x 11-1/8" (451"+) Overall Length
- |-- Frame Fasteners, Huck Spin

Frame Reinforcement, C-Channel, (375"+) Over All Length
Frame Reinforcement, Partial L Section Outer

- |-- Engine, Cummins ISX-500, 500 bhp/1645 lb-ft 11.9L - 2010 EPA
- |-- Starter, Delco 42MT/OCP w/Thermal Protection
- |-- Air Compressor, Wabco 18.7 cfm
- |-- Fan Drive - Engine, Horton Drivemaster
- |-- Coolant Filter, Fleetguard, Spin-on (Cummins)
- |-- Transmission, Allison 4000 EVS-P
- |-- Trans Prog, 5 Spd Pumper, Fire & Emg (120)
- |-- Transmission Shifter, Touch Pad
- |-- Transmission Oil Cooler
- |-- Engine Brake, Jacobs w/(2) Switches
- |-- Fuel/Water Separator, Racor 490 w/Electric Heater
- |-- Exhaust System - RH Horizontal ATD, Horizontal Tailpipe
- |-- Alternator, Leece-Neville, 320 Amp
- |-- Air Cleaner w/Ember Separator, Frontal Intake
- |-- Air Restriction Gauge, Engine Mtd with Dash Light
- |-- Radiator, High Capacity Down Flow, 1627
- |-- Coolant Hoses, Gates "Blue Stripe" EPDM
- |-- Coolant, Engine, Heavy Duty, to -34 Fahrenheit
- |-- Engine Protection Alarms

Light, LED Engine Compartment, (1)
Heater Hoses
Engine Stop Control, Ignition Switch

- |-- Fuel Tank, 65 Gallon, Rectangular, Steel
- |-- Fuel Fill w/Cap and Lanyard, Left
- |-- Fuel Re-Prime Pump, 12V, Sngl Suct & Rtrn Lines

Front Axle Package, 22,000 lbs, Meritor MFS-133A

- |-- Steering Gear 22,000 lb. Cap w/Ram Assist
- |-- Power Steering Pump, Vickers V20
- |-- Power Steering Reservoir, 4 Quart
- |-- Front Suspension 23,000 lb Taperleaf w/Shock
- |-- Front Brakes, Meritor EX-225H 17" Air Disc

DESCRIPTION

-- Frt Tires, Mchl, 425/65R22.5 "L" XZY-3 WB, 22,800#
-- Alm Hub Plt, 22.5" x 12.25", 22,000#
-- Polish Outside of Front Aluminum Wheels
-- Hub & Lug Nut Covers, S/S, Front Wheels
Tndm Rear Axle 54,000 lbs, Meritor, RT-52-185
-- Tire Inflation Indicators, for Chassis w/Tandem Rear Axles
-- Rear Axle Ratio for 60 MPH Maximum
-- Tndm Rear Susp, 54,000#, Neway AD-254 W/Shocks
-- Brakes, "Q-Plus" HD Tndm Axle, 16.5" x 7" Cam
-- Air Tanks, Minimum for Air Suspension
-- Rear Axle Seals
-- Rr Tires, Mchl, 12R22.5, "H", XZE, 57,760#
-- Alm Hub Plt, 22.5" x 8.25", 58,400#
-- Polish Outside of Rear Aluminum Wheels
-- Hub & Lug Nut Covers, S/S, Rear, Tandem Axle
-- Interaxle Lock, No Differential Traction Lock, Tndm
Drive Shaft
Lubricant, Petroleum, Axles
Air Brake System
Air Dryer, Bendix AD-9
Air Reservoir, Additional, 1730 Cubic Inches w/ PPV
Air Tank Drain Valves, Auto/Pull Cable
ABS Braking System, Wabco 6S/4M
Brake Lock, All Wheel (Front Axle)
Cab, 134" CBC, Four Door, Flat Roof
-- Windows, Side Cab, Fixed
-- Stripe, Paint Transition, Cab
-- Cab Tilt Mechanism w/Extrnl Alarm
-- Cab, Mounts, Air, 1" Up, 1" Down 35 Degree Tilt
-- Seat, Dvr, H.O. Bostrom, Air Suspension
-- Seat, Offcr, H.O. Bostrom, SCBA NonSusp
-- Seats, Rear Facing Crew, H.O.Bostrm SCBA Otbrd (2)
-- Seats, Forward Facing, SCBA, H.O. Bostrom, Inboard (2)
-- Bottle Holder with Restraint, Zico
-- Seat Covers, Durawear/Vinyl
Cab Grab Handle - (4) Ext. Rubber Inserts
Mirrors, Cab, Mekra, Chrome, 16" x 7" M2 Style H&R
-- Mirrors, Cab, Convex, 7" x 7"
Fenders, Cab, Polished Stainless Steel
Mud Flaps, Front
Antenna, UHF/VHF Mtd LS Cab Roof (136-174 MHz)
Antenna, UHF/VHF Mtd RS Cab Roof (806-900 MHz)
Electrical Load Management System
-- Battery System - 12V (6) HD Batteries
-- Battery Charger, Kussmaul Auto Chg 1200 "Pump +" w/Recept
-- Receptacle, Super Auto Eject, 120 VAC, Yellow Cover
-- Electrical Load Manager Interlock, Pumper
Cab Interior Specifications
Steering Column, Adj Tilt & Telescoping
Steering Wheel, 18" Four-Spoke Charcoal Gray
Overhead Console w/(1) Stg Compt, RH
Overhead Switch Console, Primary
Gauges (U.S)
Lights, Cab Interior, Red/Clear, w/ (2) Swivel Map Lights
Outlets, 12-Volt, Automotive Type (3) Dash Mounted

DESCRIPTION
Heater/Air Conditioner and Defroster, Primary
-- Heater/Air Conditioner, Auxiliary
-- Compressor, Refrigerant, A/C, 15.3 cfm
-- Air Conditioning Condenser, Radiator Mtd
-- HVAC Performance Spec
Interior, Chieftain Shadow Gray Imperial 1200 w/Shadow Trim
Trim, Door, ABS/Upper, Brushed S/S Lower Kickplate
-- Windows, Door Controls, Power Front & Rear
Map Box - 8"H x 10"W x 13"D w/ (3) 3" Slots + PLUS
Vehicle Data Recorder
Electronic Stability Control
Seat Belt Warning System
Helmet Storage, Each Seating Position (6)
Seat Belts 3Pt Fwd facing, 3Pt Rr facing
Bumper Extension 18", Polished Stainless Steel
-- Diamondplate Deck, 3/16" Bright Finished
Tow Hooks, Painted, Mtd Bot Frame Ext
-- Air Discharge Connector, LS Step Well
Plates, Fluid & Seating Capacity
Plate, Overall Travel Height, Length and Weight
Tag, Warning, Aerial Devices
Tag, Warning, Crew Area and Rear Body Step
Testing, Third Party, Aerial w/Pump
Pump Enclosure, S/M S/S 50" Wide, Crosslays Only, RM
-- Pump Panel, Brushed Stainless Steel, Side Mount
-- Crosslays, (2) 200' 1-3/4" & (1) 200' 2-1/2", Sngl Lay
-- Outlet, Crosslay, First, 2" Akron, 1-1/2" Swivel Elbw
-- Outlet, Crosslay, Second, 2" Akron, 1-1/2" Swvl Elbw
-- Outlet, Crosslay, Third, 2-1/2" Akron, 2-1/2" Swvl Elbw
-- Crosslay Cover, Hinged Alum D/P, S/M
-- Storage Above Pump, No Cover
-- Running Boards, 3/16" Non-Skid Alum Dia Plt
-- Platform, Pump Operator, Pullout, W/Grip Strut, LS
-- Tags, Color Coded Per NFPA
-- Tags, "No Step Surface", Pump Enclosure
-- Valve Controls, Locking Push-pull Type
-- Engine Gauges built-into Pump Governor
-- Omit Vernier Throttle
-- Gauge, Water Level, Class 1 Intelli-Tank
-- Handrails, (2) 18" Mtd Vertically at Pump Enclosure
-- Mic Box, Cast Products, Large, ALF Aerials
-- Pump, Hale Qmax 1500 GPM Single Stage, RM ALF Aerials
-- Installation, Midship Pump
-- Anodes, Sacrificial, Pump, LS/RS
-- Primer, Hale ESP
-- Mechanical Seal, Hale
-- Manuals, Pump Operation and Parts, Hale (2) Sets (CD'S)
-- Fire Pump Factory Painted Finish
-- Governor, FRC PumpBoss
-- Piping, Class 1 HP Hose and Stainless Steel Pipe
-- Drain, Master, Class 1
-- Tank Fill, 1-1/2"
-- Tank to Pump Line, Akron 3"
-- Pump Cooler, By-pass Aux Pump Cooler Valve
-- Valve Package (1500) GPM, Hale RM ALF Aerials

DESCRIPTION

|-- Inlet, Main, LS 6" Non-gated, Cap
|-- Inlet, Main, RS 6" Non-gated, Cap
|-- Inlet, LS Panel Rear 2-1/2" Akron, Swivel, Plug
|-- Outlet, LS Panel Front (1) 2-1/2" Akron Straight Discharge
|-- Outlet, LS Panel Rear (1) 2-1/2" Akron Straight Discharge
|-- Outlet, RS Panel Front (1) 2-1/2" Akron Straight Discharge
|-- Outlet, RS Panel Rear (1) 2-1/2" Akron Straight Disc
Light Hood for Right Side Pump Panel
Lights, Work, (2) 6" Pump Compartment
Gauges, Master, (2) Class 1, 4-1/2", 30-0-400 PSI
Gauges, 2-1/2" 0-400 Class 1 Line Gauges
Gauge, Discharge, Aerial 2-1/2" 0-400 Class 1
Electrical Interface w/Fast Idle System
Relief Valve, Intake
Pump Shift, Custom RH Side
Pump Shift Override, Manual
Drains, Quarter Turn, 3/4" Class 1
Engine Cooler, Custom or FTL Chassis
|-- Engine Cooler, Body Facility Finishes Installation
Outlet, Aerial, 4" Valve, Electric Controlled
|-- Discharge Material, 4" Stainless Steel
Body, Rescue Style Aerial, Rollup Doors, Quint
|-- Water Tank-UPF Poly-Basic Construction-100'+ RM Ladder
|-- Water Tank - Poly-Tank - 500 GALLONS
|-- Compts, Driver, Rescue, Rollup, Hi Cab, RM Aerial
|-- Compts, Curb, Narrow EZ Load Bed, Rollup, Hi Cab, RMA
|-- Steps, Access, Each Side, Std Cab PR/LR, Low Cab LR
|-- Hose Bed, Curbside, Narrow, RM Aerial
|-- Hosebed Flooring, Fiberglass
|-- Hosebed Capacity, 500' of 5" Hose, Curbside, Narrow, RM AL
|-- Hosebed Cover, Easy-Load, RM Aerial/Towers
|-- L/R -1 Hinged Compt. Doors - 3/16" Flat Overlap Type
|-- Compartment Door Latches
|-- Compartment Door Stay Arms-Gas Cylinder
|-- L/R - 2,3,4,5 Doors, Rollup, Robinson ROM, RM Aerial Quint
|-- Roll-Up Door Finish, Satin
|-- Lights - Body Compartment, New Tower/Aerial Body
Body Material, Aluminum, Tube, RM Aerial
Exhaust Heat Deflector
Compartmentation Detail
O/R Control Compartment Doors
Air Cylinder Storage Compts, Tube Body, RM Aerial/Tower
|-- Air Cylinder Storage Cast Door
|-- Air Cyl. Storage-Left Wheelwell 1 Fwd/2 Centr
|-- Air Cyl.Strge-Rt Wheelwell 1 Fwd/2 Cen/1 Rear
Fuel Filler w/ Cast Products Door
Rear Body Module, Roll-up Door, Tube Body, RM Tower/Aerial
|-- Waterway Inlet With Recessed Box
Alum. Treadplate Deck For Warning Lights
Wheelwells, Poly, Tandem RA, SS Fenderette
Mud Flaps, Rear
Body Trim, RM Aerial Ladder/Tower, Aluminum Diamondplate
Rub Rails, ALF Aluminum Extrusion, Red Reflective Stripe
Handrails, Looped, Aluminum, Both Sides, RM Aerial
Outrigger Covers (4)

DESCRIPTION

Outrigger Pad Storage Slides (4-Outriggers)
 Storage, Grd.Ladders, Tube Style, RM 100'+ Aerial/Tower
 Ladder Lock, Hinged, Single (Interior)
 Storage, Pike Poles (Center Stack, Tube Style)
 Rear Tow Devices (Painted Torque Box Color)
 12v Electrical Sys, Body, Non-Multiplex, RM Ladder/Platform
 Lights - Step

 |-- Decking, Dri-Dek, Black, Floors, Multiple Shelves & Trays
 |-- Shelves, Adj, 3/16" Smooth Alum (3)
 |-- Adjustable Track in Cmpts for Future Shelf Installation
 |-- Tray, 250# Floor Mounted, Sliding (1)
 |-- Tray, 500# Floor Mounted, Sliding (1)
 |-- Tool Board, Swing-Out Hinged Tool Panel (1)
 |-- Shelf Locations Determined at Pre-construction
 NFPA Optical Warning System
 |-- Lightbar, Aerial Contour, Combo w/ Scene
 |-- Front Warning Lights, Fixed, LED
 |-- Lights, Warning, Front, Inbrd of Turn Signal, LED
 |-- Lights, Warring, ALF Aerial, Whelen LED Pkg
 |-- Headlights Halogen, 1High & 1Hi/Low Beam Each Side
 |-- Turn Signals Cornering Lamps, LED, Halogen
 |-- Horns, Dual Electric
 |-- Siren, PA 200 Watt w/(1) Speaker, Ctr Bumper
 |-- Switch, Foot, (1) Siren/RS
 |-- Air Horns, Dual 21" Grover Stuttertone 1-LH, 1-RH Bumper
 |-- Switches, Foot, (2) Total (1) Each, Driver / Officer's Sides
 |-- Code 3 Model D50C Constant 97 DB Back Up
 Lights, ICC Lighting-LED-Body-T/A-MM
 Lights, Underbody (8)
 Lights, Deck Lights, (2) 6" Unity, Rear Aerial Body
 Light & Bracket, License Plate
 Lights, Whelen, Cast4 Tail/Turn/Backup, LED/Halogen (4) Lamp
 Painting, Body, ALF AERIALS (ALL)
 |-- Paint, Custom Cab, Single Color,
 |-- Paint, Chassis, Black
 |-- Paint, Color, Body Single Color
 |-- Finish, Compartment Interior, Zolatone
 |-- Paint, Paint, Factory Std. Finish
 Undercoating, Rust Inhibitor, Body
 Lettering, (60) Scotchlite, 3" Letters
 Striping, Scotchlite, (1) 4" NFPA Stripe
 Reflective Chevron
 |-- Red and Fluorescent Yellow-Green Reflective
 AERIAL LADDER, 110' REAR MOUNT STEEL- 500# Dry/250# Wet Tip
 |-- Testing & Certifications, C24R105/110, 500#Dry/250# Wet Tip
 |-- Torque Box, New Tube, (4) 12' RD O/R, C24R105/110
 |-- Aerial Device Mtg & Travel Support (RM 2 or 4 O/R)
 |-- Outriggers (4), 12' Stance, Pinless Deep Penetrating, C24R
 |-- O/R Warning Lights, Truck-Lite 7" LED w/(4) LED Grd Lig
 |-- Jack Cylinders, Frt & Rr, 36.75" Stroke, New Rd Style
 |-- Jack Extension, (4) Outriggers, 30" Stroke
 |-- (5) Extension Slide Pads, New Rd O/R
 |-- Outrigger Pads (4), 154 sq-in
 |-- Aerial Ladder Comp, C24R-110, 500# Dry/250# Wet Tip Load

DESCRIPTION

|-- (2) Folding Steps With "Bustin" Inserts
 |-- Elevation System, -7 to 78 Degrees
 |-- Rotation System, 40.29" Diameter
 |-- Extension/Retraction System, C Series 4-Section Ladder
 |-- Ladder Slide Mechanism, Nylatron
 |-- Ladder Electrical/Air Line Track System
 |-- Extension Indicators, 5' & 10' Marker Spacing
 |-- 4" Swivel Combo, 3-Pt Hyd, Wtr & 26 Ring Elec
 |-- Turntable Treadplate, 80" x 81" Octagon, Cutoff Hose Bed
 |-- Safety Railing, T/T, Knurled SS, Safety Chain Gate
 |-- Cradle Alignment Indicators
 |-- (4) Turntable Work Lights, Rear Step Mtd
 |-- 4" Waterway Inlet, SS, Rear Only, RM 100'+ Ladders
 |-- Waterway Inlet Accessories, (1) 4"NST x 5"Storz
 |-- Rotational Swivel, 4"
 |-- Heel Pin Swivel
 |-- Water System Friction Loss
 |-- Telescopic Waterway, 4 Sect, 5"-4.5"-4"-3.5"
 |-- Monitor, Akron 3598, MasterStream XL, Wireless Radio Control
 |-- Ladder Bolt-On Egress
 |-- Ladder Illumination Lighting, Red, C Series 4-Sec Ladders
 |-- Akron #5178, 1500 GPM, 3.5" Nozzle, Electric
 |-- Wireless Monitor Function Switches, Akron, T/T & Monitor
 |-- Retractable Monitor, Mechanical Latch With Auto-Connector
 |-- Flowminder Mtd on T/T, Akron
 (4) Auxiliary Outrigger Pads
 (2) Aerial Base Sect Nameplates, 14" x 120"
 Hydraulic System W/Sight Glass Ind, 40 Gal
 |-- 12 Volt Emergency Hydraulic System, All
 |-- (2) Emerg Pwr Unit (EPU) Swtchs, LH/RH Otrgr
 PTO, Chelsea Model 277 w/"Hot-Shift", Allison HD Trans. AL1
 Electrical System Components, Non-Multiplexed, RM Ladders
 |-- Short O/R Jack Sys, Manual, 4-O/R, RM 100' + Ladders*
 |-- (2) Outrigger Leveling Ind, LH/RH Rear, Rr Mt
 |-- Outrigger Deployment Warning Alarm
 |-- Ladder/Outrigger Interlock System
 |-- Safety Features, Short Jacking, Out & Down O/R, New Version
 |-- Rotation Limiting System, Out & Down Outgrs
 |-- Aerial Control Console, LH T/T, All RM Aerials
 |-- T/T Console Cover, Aluminum Treadplate
 |-- Engine, Fast Idle Actuator (With Fire Pump)
 |-- Aerial Hour Meter, Wired to PTO
 Comm Sys, Tip to T/T, Atkinson
 (2) Unity Spotlights, Rear Ladder Base
 (2) Unity Spotlights, Aerial Tip
 (1) Special Width Roof Ladder Mtg Brckt, Fly, Right Side
 (6) Special Retorquing Tools w/Tool Box
 Aerial PPG Painting
 Reflective Striping, Otrgr Bm Refl
 Caution & Warning Sign
 On-Site Preventative Maintenance & Operational Training (3)
 Manuals Chassis; Pump; Body; Aerial Device (2)
GROUND LADDERS
 Ladder, Duo-Safety, Series 900-A, 24' 2-Sec (1)
 Ladder, Duo-Safety, Series 1200-A, 35' 2-Sec (1)

DESCRIPTION

Ladders, Duo-Safety, Series 875-A, 16' Roof (2)

Ladder, Duo-Safety, Series 701-14 Attic (1)

Ladder, Duo-Safety, Series 585-A, 10' Folding (1)

EQUIPMENT ITEMS

Pike Poles, (2) Duo-Safety, 6' Fiberglass 6FP

Pike Poles, (2) Duo-Safety, 8' Fiberglass 8FP

Pike Poles, (2) Duo-Safety, 12' Fiberglass 12FP

Chocks, Wheel, (2) Ziamatic SAC-44 Folding w/Brkt

Purchaser Provides All Other NFPA 1901 Equipment

Warranty - Refer to FS12-11 FORM G

REAR-MOUNT PLATFORM



AERIAL

A fully integrated unit with increased capacity, functionality and a seamless product design to meet today's and tomorrow's department needs.

- More precise incident access — Angled corners
- Exterior deck work area — 10 sq ft
- 360° view of situation — Multiple control mounting locations
- Increased work and storage space — 29 sq ft total workspace and 7.6 cu ft storage
- Ease of service — Modular construction
- Heavy-Duty platform capacities up to 1000 lbs
- Unimpeded ladder walkway
- Oversized telescopic waterway — Up to 2000 GPM
- Oversized body storage — Up to 25" deep compartments
- Unique tubular torque box design with deep penetrating outriggers





Room for 1000 ft of 5" L.D.H.



Easy payout hosebed



Increased work and storage space



Low ground ladder storage compartment for ease of access



Full-height and full-depth body compartments with up to 25" depth

REAR-MOUNT PLATFORM

These are the typical specifications for the Rear-Mount Platform apparatus and the American LaFrance Eagle® chassis:

LADDER: All-steel construction with k-bracing. Dual-rod extension system. TLC (Triangulated Lifting Configuration).

MODULAR AERIAL PLATFORM: 1000 lb capacity

WATERWAY FLOW CAPACITY: 2000 GPM

HORIZONTAL REACH: 91'-0"

ANGLE OF ELEVATION: -6° to +80°

OUTRIGGERS: Quantity of 4, H-type, out-and-down style, Short-Jacking capability with Rotational Limiting Safety System. Leveling capacity for full capabilities up to 10.5° (18% grade); 50% capabilities up to 15° (26% grade).

OUTRIGGER SPREAD: 18' with Short-Jacking capability of 13'

O.A.L.: 47'-7"

O.A.H. RANGE: 11'-9" to 12'-1"

WHEELBASE RANGE: 238" to 262"

CHASSIS: American LaFrance Eagle®

BODY: Available in aluminum or stainless steel.

PUMP MODULE: Independent pump module with patented rubber-isolated mounting system.

FIRE PUMP: American LaFrance Midship Pump in single and two-stage models, capacities of 1250 to 2000 GPM.

WATER/FOAM TANK CAPACITY: 300 to 400 gal. Additional foam tank capacity in above pump storage.

For your nearest American LaFrance dealer, go to www.americanlafrance.com.

Some specifications and features shown or mentioned in this brochure are optional and are available upon request at extra cost. Specifications are subject to change without notice. ©2009, American LaFrance, LLC. All rights reserved.



QUOTATION

American LaFrance

OHIO STS
\$798,430.00

American LaFrance Eagle 4 Door Tilt Cab, Formed Aluminum Body, Tandem Axle, 100' Steel, Rear Mount Telescoping Ladder Platform 1000lb

08/01/2011

Quote No: ALF AA06-

Page 1

DESCRIPTION

== American LaFrance 100' Rear Mount Platform ==
Eagle 134 (4) Door Tilt Cab Fire Chassis, Formed Alum Body
Custom Cab and Chassis Specifications
Overall Height - 11' - 9" and Overall Length 46' - 1"
NFPA 1901 Certificate of Compliance
Chassis Wheelbase - 238"
|-- Frame, 7/16" x 3-11/16" x 11-1/8" (451"+) Overall Length
|-- Frame Fasteners, Huck Spin
Frame Reinforcement, C-Channel, (375"+) Over All Length
Frame Reinforcement, Partial L Section Outer
|-- Engine, Cummins ISX-500, 500 bhp/1645 lb-ft 11.9L - 2010 EPA
|-- Starter, Delco 42MT/OCP w/Thermal Protection
|-- Air Compressor, Wabco 18.7 cfm
|-- Fan Drive - Engine, Horton Drivemaster
|-- Coolant Filter, Fleetguard, Spin-on (Cummins)
|-- Transmission, Allison 4000 EVS-P
|-- Trans Prog, 5 Spd Pumper, Fire & Emg (120)
|-- Transmission Shifter, Touch Pad
|-- Transmission Oil Cooler
|-- Engine Brake, Jacobs w/(2) Switches
|-- Fuel/Water Separator, Racor 490 w/Electric Heater
|-- Exhaust System - RH Horizontal ATD, Horizontal Tailpipe
|-- Alternator, Leece-Neville, 320 Amp
|-- Air Cleaner w/Ember Separator, Frontal Intake
|-- Air Restriction Gauge, Engine Mtd with Dash Light
|-- Radiator, High Capacity Down Flow, 1627
|-- Coolant Hoses, Gates "Blue Stripe" EPDM
|-- Coolant, Engine, Heavy Duty, to -34 Fahrenheit
|-- Engine Protection Alarms
Light, LED Engine Compartment, (1)
Heater Hoses with Shut-Off Ball Valves
Engine Stop Control, Ignition Switch
|-- Fuel Tank, 65 Gallon, Rectangular, Steel
|-- Fuel Fill w/Cap and Lanyard, Left
|-- Fuel Re-Prime Pump, 12V, Sngl Suct & Rtrn Lines
Front Axle Package, 22,000 lbs, Meritor MFS-133A
|-- Steering Gear 22,000 lb. Cap w/Ram Assist
|-- Power Steering Pump, Vickers V20
|-- Power Steering Reservoir, 4 Quart
|-- Front Suspension 23,000 lb Taperleaf w/Shock
|-- Front Brakes, Meritor EX-225H 17" Air Disc
|-- Frt Tires, Mchl, 425/65R22.5 "L" XZY-3 WB, 22,800#

DESCRIPTION
-- Alm Hub Plt, 22.5" x 12.25", 22,000#
-- Polish Outside of Front Aluminum Wheels
-- Hub & Lug Nut Covers, S/S, Front Wheels
Tndm Rear Axle 54,000 lbs, Meritor, RT-52-185
-- Tire Inflation Indicators, for Chassis w/Tandem Rear Axles
-- Rear Axle Ratio for 60 MPH Maximum
-- Tndm Rear Susp, 54,000#, Neway AD-254 W/Shocks
-- Brakes, "Q-Plus" HD Tndm Axle, 16.5" x 7" Cam
-- Air Tanks, Minimum for Air Suspension
-- Rear Axle Seals
-- Rr Tires, Mchl, 12R22.5, "H", XZE, 57,760#
-- Alm Hub Plt, 22.5" x 8.25", 58,400#
-- Polish Outside of Rear Aluminum Wheels
-- Hub & Lug Nut Covers, S/S, Rear, Tandem Axle
Drive Shaft
Lubricant, Petroleum, Axles
Air Brake System
Air Dryer, Bendix AD-9
Air Reservoir, Additional, 1730 Cubic Inches w/ PPV
Air Tank Drain Valves, Auto/Pull Cable
ABS Braking System, Wabco 6S/4M
Brake Lock, All Wheel (Front Axle)
Cab, 134" CBC, Four Door, Flat Roof
-- Windows, Side Cab, Fixed
-- Stripe, Paint Transition, Cab
-- Cab Tilt Mechanism w/Extnl Alarm
-- Cab, Mounts, Air, 1" Up, 1" Down 35 Degree Tilt
-- Seat, Dvr, H.O. Bostrom, Air Suspension
-- Seat, Offcr, H.O. Bostrom, SCBA NonSusp
-- Seats, Rear Facing Crew, H.O.Bostrm SCBA Otbrd (2)
-- Seats, Forward Facing, SCBA, H.O. Bostrom, Inboard (2)
-- Bottle Holder with Restraint, Zico
-- Seat Covers, Durawear/Vinyl
Cab Grab Handle - (4) Ext. Rubber Inserts
Mirrors, Cab, Mekra, Chrome, 16" x 7" M2 Style H&R
-- Mirrors, Cab, Convex, 7" x 7"
Fenders, Cab, Polished Stainless Steel
Mud Flaps, Front
Radio, Rcway, Power & Ground, UHF/VHF Mtd Loc,
Antenna, UHF/VHF Mtd LS Cab Roof (162-174 MHz)
Antenna, UHF/VHF Mtd RS Cab Roof (162-174 MHz)
Electrical Load Management System
-- Battery System - 12V (6) HD Batteries
-- Battery Charger, Kussmaul Auto Chg 1200 "Pump +" w/Recept
-- Receptacle, Super Auto Eject, 120 VAC, Yellow Cover
-- Electrical Load Manager Interlock, Pumper
Cab Interior Specifications
Steering Column, Adj Tilt & Telescoping
Steering Wheel, 18" Four-Spoke Charcoal Gray
Overhead Console w/(1) Stg Compt, RH
Overhead Switch Console, Primary
Overhead Switch Console, Aerial, PTO Rocker Switch
Gauges (U.S)
Switches, Additional Dash Rocker, (Qty)
Lights, Cab Interior, Red/Clear, w/ (2) Swivel Map Lights

DESCRIPTION
Outlets, 12-Volt, Automotive Type (3) Dash Mounted
Heater/Air Conditioner and Defroster, Primary
-- Heater/Air Conditioner, Auxiliary
-- Compressor, Refrigerant, A/C, 15.3 cfm
-- Air Conditioning Condenser, Radiator Mtd
-- HVAC Performance Spec
Interior, Chieftain Shadow Gray Imperial 1200 w/Shadow Trim
Trim, Door, ABS/Upper, Brushed S/S Lower Kickplate
-- Windows, Door Controls, Power Front & Rear
Map Box - 8"H x 10"W x 13"D w/ (3) 3" Slots
Vehicle Data Recorder
Electronic Stability Control
Seat Belt Warning System
Helmet Storage, Each Seating Position
Seat Belts 3Pt Fwd facing, 3Pt Rr facing
Bumper Extension 18", Polished Stainless Steel
-- Diamondplate Deck, 3/16" Bright Finished
Tow Hooks, Painted, Mtd Bot Frame Ext
-- Air Discharge Connector, LS Step Well
Plates, Fluid & Seating Capacity
Plate, Overall Travel Height, Length and Weight
Tag, Warning, Aerial Devices
Tag, Warning, Crew Area and Rear Body Step
Testing, Third Party, Aerial w/Pump
Pump Enclosure, S/M S/S 50" Wide, Crosslays RM
-- Pump Panel, Brushed Stainless Steel, Side Mount
-- Crosslays, (2) 200' 1-3/4" & (1) 200' 2-1/2", Sngl Lay
-- Outlet, Crosslay, First, 2" Akron, 1-1/2" Swivel Elbw
-- Outlet, Crosslay, Second, 2" Akron, 1-1/2" Swvl Elbw
-- Outlet, Crosslay, Third, 2-1/2" Akron, 2-1/2" Swvl Elbw
-- Crosslay Cover, Hinged Alum D/P, S/M
-- Storage Above Pump, No Cover
-- Running Boards, 3/16" Non-Skid Alum Dia Plt
-- Platform, Pump Operator, Pullout, W/Grip Strut, LS
-- Tags, Color Coded Per NFPA
-- Tags, "No Step Surface", Pump Enclosure
-- Valve Controls, Locking Push-pull Type
-- Engine Gauges built-into Pump Governor
-- Omit Vernier Throttle
-- Gauge, Water Level, Class 1 Intelli-Tank
-- Handrails, (2) 18" Mtd Vertically at Pump Enclosure
-- Mic Box, Cast Products, Large, ALF Aerials
-- Pump, Hale Qmax 2000 GPM Single Stage, RM ALF Aerials
-- Installation, Midship Pump
-- Anodes, Sacrificial, Pump, LS/RS
-- Primer, Hale ESP
-- Mechanical Seal, Hale
-- Manuals, Pump Operation and Parts, Hale (2) Sets (CD'S)
-- Fire Pump Factory Painted Finish
-- Governor, FRC PumpBoss
-- Piping, Class 1 HP Hose and Stainless Steel Pipe
-- Drain, Master, Class 1
-- Tank Fill, 1-1/2"
-- Tank to Pump Line, Akron 3"
-- Pump Cooler, By-pass Aux Pump Cooler Valve

DESCRIPTION

-- Valve Package (2000) GPM, Hale RM ALF Aerials
-- Inlet, Main, LS 6" Non-gated, Cap
-- Inlet, Main, RS 6" Non-gated, Cap
-- Inlet, LS Panel Rear 2-1/2" Akron, Swivel, Plug
-- Outlet, LS Panel Front (1) 2-1/2" Akron Straight Discharge
-- Outlet, LS Panel Rear (1) 2-1/2" Akron Straight Discharge
-- Outlet, RS Panel Front (1) 2-1/2" Akron Straight Discharge
-- Outlet, RS Panel Rear (1) 2-1/2" Akron Straight Disc
Light Hood for Right Side Pump Panel
Lights, Work, (2) 6" Pump Compartment
Gauges, Master, (2) Class 1, 6", 30-0-400 PSI
Gauges, 2-1/2" 0-400 Class 1 Line Gauges
Gauge, Discharge, Aerial 2-1/2" 0-400 Class 1
Electrical Interface w/Fast Idle System
Relief Valve, Intake
Pump Shift, Custom RH Side
Pump Shift Override, Manual
Drains, Quarter Turn, 3/4" Class 1
Engine Cooler, Custom or FTL Chassis
-- Engine Cooler, Body Facility Finishes Installation
Outlet, Aerial, 5" Electric Controlled
-- Discharge Material, 5" Black Iron Pipe
Adapter, Elbow, 4" NSTF x 5" Storz, w/Cap, Chain (1)
Body, Rescue style Tower, Rollup Doors, Quint
-- Water Tank-UPF Poly-Basic Const-100'+ RM Towers
-- Water Tank - Poly-Tank - 300 GALLONS
-- Compts, Drivers, Rescue, Rollup, Hi Cab, RM LT
-- Compts, Curb, Easy-Load Hosebed, Rollup, Hi Cab, RM LT
-- Steps, Access, Each Side, Std Cab PR/LR, Low Cab LR
-- Hose Bed, Deep, RM Tower, Std Cab
-- Hosebed Flooring, Fiberglass
-- Hosebed Capacity, 1000 Ft of 5" Hose, RM Tower/Aerial
-- Hosebed Cover, Easy-Load, RM Aerial/Towers
-- L/R - 1 Hinged Compt. Doors - 3/16" Flat Overlap Type
-- Compartment Door Latches
-- Compartment Door Stay Arms-Gas Cylinder
-- L/R 2,3,4,5 Doors, Rollup, Robinson ROM, RM Tower, Quint
-- Roll-Up Door Finish, Satin
-- Lights - Body Compt, ROM LED Strip
-- (8) Chrome Plated Folding Steps, Front Of Body, (4) Ea Side
Body Material, Aluminum, Tube, RM Tower
Exhaust Heat Deflector
Compartmentation Detail
O/R Control Compartment Doors
Air Cylinder Storage Compts, Tube Body, RM Aerial/Tower
-- Air Cylinder Storage Cast Door
-- Air Cyl. Storage-Left Wheelwell 1 Fwd/2 Centr
-- Air Cyl.Strge-Rt Wheelwell 1 Fwd/2 Cen/1 Rear
Fuel Filler w/ Cast Products Door
Rear Body Module, Roll-up Door, Tube Body, RM Tower/Aerial
-- Waterway Inlet With Recessed Box
Alum. Treadplate Deck For Warning Lights
Wheelwells, Poly, Tandem RA, SS Fenderette
Mud Flaps, Rear
Body Trim, RM Aerial Ladder/Tower, Aluminum Diamondplate

DESCRIPTION

Rub Rails, ALF Aluminum Extrusion, Red Reflective Stripe
 Handrails, Looped, Aluminum, Both Sides, RM Tower
 Outrigger Covers (4)
 Outrigger Pad Storage Slides (4-Outriggers)
 Storage, Grd.Ladders, Tube Style, RM 100'+ Aerial/Tower
 Ladder Lock, Hinged, Single (Interior)
 Storage, Pike Poles (Center Stack, Tube Style)
 Rear Tow Devices (Painted Torque Box Color)
 12v Electrical Sys, Body, Non-Multiplex, RM Ladder/Platform
 Lights - Step
ACCESSORIES, AERIALS (EXCEPT FOR TDA)
 |-- Decking, Turtle Tile, Black, Floors, Multiple Shelves & Tray
 |-- Shelves, Adj, 3/16" Smooth Alum (3)
 |-- Adjustable Track in Cmpts for Future Shelf Installation
 |-- Tray, 250# Floor Mounted, Sliding (1)
 |-- Tray, 500# Floor Mounted, Sliding (1)
 |-- Tool Board, Swing-Out Hinged Tool Panel (1)
 |-- Shelf Locations Determined at Pre-construction
NFPA Optical Warning System
 |-- Lightbar, Aerial Contour, Combo w/ Scene
 |-- Front Warning Lights, Fixed, LED
 |-- Lights, Warning, Front, Inbrd of Turn Signal, LED
 |-- Lights, Warring, ALF Aerial, Whelen LED Pkg
 |-- Headlights Halogen, 1High & 1Hi/Low Beam Each Side
 |-- Turn Signals Cornering Lamps, LED, Halogen
 |-- Horns, Dual Electric
 |-- Siren, PA 200 Watt w/(1) Speaker, Ctr Bumper
 |-- Switch, Foot, (1) Siren/RS
 |-- Air Horns, Dual 21" Grover Stuttertone 1-LH, 1-RH Bumper
 |-- Switch, Selector, Horn/Air Horn, Cab Dash Mtd
 |-- Code 3 Model D50C Constant 97 DB Back Up
 Lights, ICC Lighting-LED-Body-T/A-MM
 Lights, Underbody (8)
 Lights, Deck Lights, (2) 6" Unity, Rear Aerial Body
 Light & Bracket, License Plate
 Lights, Whelen, Cast4 Tail/Turn/Backup, LED/Halogen (4) Lamp
Painting, Body, ALF AERIALS (ALL)
 |-- Paint, Custom Cab, Two Colors - STD Break
 |-- Paint, Chassis, Black
 |-- Paint, Color, Body Single Color
 |-- Finish, Compartment Interior, Zolatone
 |-- Paint, Paint, Factory Std. Finish
 Undercoating, Rust Inhibitor, Body
 Lettering, (60) Scotchlite, 3" Letters
 Lettering, (36) Scotchlite, Red, Letters on Sides of Aerial
 Striping, Scotchlite, (1) 4" NFPA Stripe
 Reflective Chevron
 |-- Red and Fluorescent Yellow-Green Reflective
100' PLATFORM REAR MOUNT STEEL,(Tube Torquebox)
 |-- Ldr/Pltfrm Criteria & Standards, P43R-100
 |-- UL Aerial Device, P43R/P45M, 1000# TL
 |-- Torque Box, New Tube, (4) RD O/R, P43R
 |-- Aerial Device Mtg & Travel Support (RM 2 or 4 O/R)
 |-- Outriggers (4), 18' Stance, New Rd O/R
 |-- Jack Cylinders, Frt & Rr, 36.75" Stroke, New Rd Style

DESCRIPTION

|-- Jack Extension, 65.5" Frt/Rr Stroke, P43R
 |-- (5) Extension Slide Pads, New Rd O/R
 |-- Outrigger Pads (4), 154 sq-in
 |-- (4) Auxiliary Outrigger Pads
 |-- O/R Warning Lights, Truck-Lite 7" LED w/(4) LED Grd Lig
 |-- Tower Ladder Components, P43R-100
 |-- Elevation System, -6 to 80 Degrees
 |-- Rotation System, 40.29" Diameter
 |-- Extension/Retraction System, WheelBase 251" Or Less P43R-100
 |-- Ladder Slide Mechanism
 |-- Extension Indicators, 5' & 10' Marker Spacing
 |-- Platform Const, 29.0 Sq Ft, w/ Ext Step
 |-- Platform Floor, 29.0 SqFt w/Ext Step, New Tower
 |-- Platform Handrail, 42" High, 10" Pivot
 |-- Platform/Ladder Access Gate
 |-- Platform Leveling System
 |-- Platform Mounting
 |-- Safety Belt Connections, (4)
 |-- Platform Control Console, Multi-Location, New Tower
 |-- Telescopic Waterway, 3 Sect, 5"-4.5"-4"
 (2) Base Sect Nameplates, 20" x 104", P44M/P45M/P43R
 |-- Lifting Arms
 |-- Rescue Stretcher Holders
 |-- Rescue Ladder Brackets, Both Sides
 Under Platform Steel Lifting Eyes
 Platform Storage Compartments
 (5) Amber Platform LED Clearance Lts, RM Tower
 Hydraulic System W/Sight Glass Ind, 60 Gal
 |-- 12 Volt Emergency Hydraulic System, All
 |-- (2) Emerg Pwr Unit (EPU) Swtchs, LH/RH Otrgr
 5" Combo Hydrlic, Wtr & 26 Ring Elec Swvl
 PTO, Muncie MPM w/"Hot-Shift", Allison HD Trans., AL1
 Turntable, 95" x 78" Wide, Cutoff Over Hosebed, P43R
 |-- Safety Railing, T/T, Knurled SS, Safety Chain Gate
 |-- Cradle Alignment Indicators
 |-- (4) Turntable Work Lights, Rear Step Mtd
 Cradle Alignment Lights, Towers
 Electrical Sys.Components, RM Towers, Non-Multiplexed
 |-- Short O/R Jack Sys, Manual, 4-O/R, RM Platforms*
 |-- (2) Outrigger Leveling Ind, LH/RH Rear, Rr Mt
 |-- Outrigger Deployment Warning Alarm
 |-- Ladder/Outrigger Interlock System
 |-- Safety Features, Outriggers w/ Short Jacking
 |-- Rotation Limiting System, Out & Down Outgrs
 |-- Aerial Cntrl Stn, LH T/T Console, RM Towers
 |-- T/T Console Cover, Black Metal
 |-- Engine, Fast Idle Actuator (With Fire Pump)
 |-- Aerial Hour Meter, Wired to PTO
 |-- Low Air Pressure Warning System, Visual @ T/T Only
 |-- Flowminder Mtd on T/T Console/Class 1 FMS
 Comm Sys., Platform to T/T, Atkinson
 (1) Unity Spotlight, (1) Floodlight, Platform
 (2) Unity Spotlights, Rear Ladder Base
 Ladder Illumination Lighting, 3-Sec Platform Ladders
 Lts, (5) Whelen 700 Series, SuperLED, NFPA Compliant Upper A

MID-MOUNT PLATFORM



AERIAL

The low-angle and near-unit platform access makes this apparatus the ideal fire-fighting vehicle for urban areas with narrow streets.

LADDER LENGTH OPTIONS: 99', 100'

- More precise incident access — Angled corners
- Exterior deck work area — 10 sq ft
- 360° view of situation — Multiple control mounting locations
- Increased work and storage space — 29 sq ft total workspace and 7.6 cu ft storage
- Ease of service — Modular construction
- Unimpeded ladder walkway
- Oversized telescopic waterway — Up to 2000 GPM
- Heavy-Duty platform capacities up to 1000 lbs



MID-MOUNT PLATFORM

These are the typical specifications for the Mid-Mount Platform apparatus and American LaFrance Eagle® chassis:

LADDER: All-steel construction with k-bracing. Dual-cylinder extension system with TLC (Triangulated Lifting Configuration).

MODULAR AERIAL PLATFORM: 1000 lbs capacity.

WATERWAY FLOW CAPACITY: 2000 GPM

HORIZONTAL REACH: 100MM, 93'-2";
93MM, 87'- 2"

ANGLE OF ELEVATION: -13° to +78°

OUTRIGGER CONFIGURATION: H-type, out-and-down style. 100' and 93', quantity of 4. Short-Jacking capability with Rotational Limiting Safety System.

OUTRIGGER SPREAD: 100' and 93'-18'

(mid-position), 16' (rear position); 2 mounted below front bumper.

O.A.L. (TYP.) RANGE: 100MM-47' to 49';
93MM-46' to 48'

O.A.H. (TYP.) RANGE: 10'-2" to 11'-0"

WHEELBASE (TYP.) RANGE: 100MM and
93MM 240" to 268"

CHASSIS: American LaFrance Eagle®

FIRE PUMP: Hale, model 8FG, single stage unit with capacities of 1500 and 2000 GPM.



Clear ladder walkway for easier access



Increased work and storage space



Low ground ladder storage compartment for ease of access



Multiple deep compartments for easy access and equipment storage

For your nearest American LaFrance dealer, go to www.americanlafrance.com.

Some specifications and features shown or mentioned in this brochure are optional and are available upon request at extra cost. Specifications are subject to change without notice. ©2009, American LaFrance, LLC. All rights reserved.



QUOTATION

American LaFrance

OHIO STS

\$890,384.00

American LaFrance Eagle 4-Door Tilt Cab, Formed Aluminum Body Tandem Axle, 100' Mid-Mount Telescoping Ladder Platform 1000lb (Steel)

08/01/2011

Quote No: ALF AA07-

Page 1

DESCRIPTION

== American LaFrance 100' Mid-Mount Platform
Eagle 134 (4) Door Tilt Cab Fire Chassis Formed Alum Body
Custom Cab and Chassis Specifications
Overall Height 11' - 0" and Overall Length 47' - 10"
NFPA 1901 Certificate of Compliance
Chassis Wheelbase - 255"
Torque Box Frame Assembly (7/16" Frame Only)
Frame Fasteners, Huck Spin

- |-- Engine, Cummins ISX- 500 bhp/1645 lb-ft 11.9L - 2010 EPA
- |-- Starter, Delco 42MT/OCP w/Thermal Protection
- |-- Air Compressor, Wabco 18.7 cfm
- |-- Fan Drive - Engine, Horton Drivemaster
- |-- Coolant Filter, Fleetguard, Spin-on (Cummins)
- |-- Transmission, Allison 4000 EVS-P
 - |-- Trans Prog, 5 Spd Pumper, Fire & Emg (120)
 - |-- Transmission Shifter, Touch Pad
 - |-- Transmission Oil Cooler
- |-- Engine Brake, Jacobs w/(2) Switches
- |-- Fuel/Water Separator, Racor 490 w/Electric Heater
- |-- Exhaust System - RH Horizontal ATD, Horizontal Tailpipe
- |-- Alternator, Leece-Neville, 320 Amp
- |-- Air Cleaner w/Ember Separator, Frontal Intake
- |-- Air Restriction Gauge, Engine Mtd with Dash Light
- |-- Radiator, High Capacity Down Flow, 1627
- |-- Coolant Hoses, Gates "Blue Stripe" EPDM
- |-- Coolant, Engine, Heavy Duty, to -34 Fahrenheit
- |-- Engine Protection Alarms

Light, Engine Compartment (1)
Heater Hoses
Engine Stop Control, Ignition Switch

- |-- Fuel Tank, 56 Gallon, Rectangular, Steel
- |-- Fuel Fill w/Cap and Lanyard, Left
- |-- Fuel Lines, Reinforced, Wire Braid

Front Axle Package, 22,000 lbs, Meritor MFS-133A

- |-- Steering Gear 22,000 lb. Cap w/Ram Assist
- |-- Power Steering Pump, Vickers V20
 - |-- Power Steering Reservoir, 4 Quart
- |-- Front Suspension 23,000 lb Taperleaf w/Shock
- |-- Front Brakes, Meritor EX-225H 17" Air Disc
- |-- Frt Tires, Mchl, 425/65R22.5 "L" XZY-3 WB, 22,800#
- |-- Alm Hub Plt, 22.5" x 12.25", 22,000#

DESCRIPTION

|-- Polish Outside of Front Aluminum Wheels
 |-- Hub & Lug Nut Covers, S/S, Front Wheels
 Tndm Rear Axle 58,000 lbs, Meritor, RT-58-185
 |-- Tire Inflation Indicators, for Chassis w/Tandem Rear Axles
 |-- Rear Axle Ratio for 60 MPH Maximum
 |-- Tndm Rear Susp, 60,000#, Raydan AL-60
 |-- Brakes, "P" Cam, Tandem Dbl Anchr, Cst Shoes, 16.5"x 7"
 |-- Air Tanks, Minimum for Air Suspension
 |-- Rear Axle Seals
 |-- Rr Tires, Mchl, 315/80R22.5, "L" XDY-3, 66,000#
 |-- Alm Hub Plt, 22.5" x 9.00", 72,000#
 |-- Polish Outside of Rear Aluminum Wheels
 |-- Hub & Lug Nut Covers, S/S, Rear, Tandem Axle
 Drive Shaft
 Lubricant, Petroleum, Axles
 Air Brake System
 Air Dryer, Bendix AD-9
 Air Reservoir, Additional, 700 Cubic Inches w/ PPV
 Air Tank Pull Cables, Each Tank
 ABS Braking System, Wabco 4S/4M
 Brake Lock, All Wheel (Front Axle)
 Cab, 134" CBC, Four Door, Flat Roof
 |-- Windows, Side Cab, Fixed
 |-- Cab Tilt Mechanism w/Extnl Alarm
 |-- Cab, Mounts, Air, 1" Up, 1" Down 35 Degree Tilt
 |-- Seat, Dvr, H.O. Bostrom, Air Suspension
 |-- Seat, Offcr, H.O. Bostrom, SCBA NonSusp
 |-- Seats, Rear Facing Crew, H.O.Bostrm SCBA Otbrd (2)
 |-- Seats, Forward Facing, SCBA, H.O. Bostrom, Inboard (2)
 |-- Bottle Holder with Restraint, Zico
 |-- Seat Covers, Durawear/Vinyl
 Cab Grab Handle - (4) Ext. Rubber Inserts
 Mirrors, Cab, Mekra, Chrome, 16" x 7" M2 Style H&R
 |-- Mirrors, Cab, Convex, 7" x 7"
 Fenders, Cab, Polished Stainless Steel
 Mud Flaps, Front
 Radio, Rcway, Power & Ground, UHF/VHF Mtd Loc,
 Antenna, UHF/VHF Mtd LS Cab Roof (42-50 MHz)
 Antenna, UHF/VHF Mtd RS Cab Roof (42-50 MHz)
 Electrical Load Management System
 |-- Battery System - 12V (6) HD Batteries
 |-- Battery Charger, Kussmaul Auto Chg 1200 "Pump +" w/Recept
 |-- Receptacle, Super Auto Eject, 120 VAC, Yellow Cover
 |-- Electrical Load Manager Interlock, Pumper
 Cab Interior Specifications
 Steering Column, Adj Tilt & Telescoping
 Steering Wheel, 18" Four-Spoke Charcoal Gray
 Overhead Console
 Overhead Switch Console, Primary
 Overhead Switch Console, Aerial, PTO Rocker Switch
 Gauges (U.S)
 Lights, Cab Interior, Red/Clear
 Outlets, 12-Volt, Automotive Type (3) Dash Mounted
 Heater/Air Conditioner and Defroster, Primary
 |-- Heater/Air Conditioner, Auxiliary

DESCRIPTION

-- Compressor, Refrigerant, A/C, 15.3 cfm
-- Air Conditioning Condenser, Radiator Mtd
-- HVAC Performance Spec
Interior, Chieftain Shadow Gray Imperial 1200 w/Shadow Trim
Trim, Door, ABS/Upper, Brushed S/S Lower Kickplate
-- Windows, Door Controls, Power Front & Rear
Map Box - 8"H x 10"W x 13"D w/ (3) 3" Slots
Vehicle Data Recorder
Electronic Stability Control
Seat Belt Warning System
Helmet Storage, Each Seating Position (6)
Seat Belts 3Pt Fwd facing, 3Pt Rr facing
Bumper Extension 18", Polished Stainless Steel
-- Diamondplate Deck, 3/16" Bright Finished
Tow Hooks, Painted, Mtd Bot Frame Ext
Plates, Fluid & Seating Capacity
Plate, Overall Travel Height, Length and Weight
Tag, Warning, Aerial Devices
Tag, Warning, Crew Area and Rear Body Step
Testing, Third Party, Aerial w/Pump
Pump Enclosure, S/M S/S 40" Wide, Crosslays Only Mid Mount
-- Pump Panel, Brushed Stainless Steel, MM Tower /Ladder
-- Crosslays, P45M (2) 200' 1-3/4", Double Lay
-- Outlet, Crosslay, First, 2" Akron, 1-1/2" Swivel Elbw Elec
-- Outlet, Crosslay, Second, 2" Akron, 1-1/2" Swivel Elbw Elec
-- Crosslay Cover, Vinyl Snap-on Type
-- Running Boards, 3/16" Non-Skid Alum Dia Plt
-- Platform, Pump Operator, Pullout, W/Grip Strut, LS
-- Tags, Color Coded Per NFPA
-- Tags, "No Step Surface", Pump Enclosure
-- Engine Monitoring System, Enfo IV, Class 1
-- Omit Vernier Throttle
-- Gauge, Water Level, Class 1 Intelli-Tank
-- Mic Box, Cast Products, Large, ALF Aerials
-- Pump, Hale 8FG - 2000 GPM Single Stage MM ALF Aerials
-- Installation, Midship Pump
-- Anodes, Sacrificial, Pump, LS/RS
-- Primer, Hale ESP
-- Mechanical Seal, Hale
-- Manuals, Pump Operation and Parts, Hale (2) Sets (CD'S)
-- Fire Pump Factory Painted Finish
-- Governor, FRC PumpBoss
-- Piping, Class 1 HP Hose and Stainless Steel Pipe
-- Drain, Master, Class 1
-- Tank Fill, 2" Electric
-- Tank to Pump Line, Akron 3" Electric
-- Pump Cooler, By-pass Aux Pump Cooler Valve
-- Valve Package (2000) GPM, Hale 8FG MM Tower/Aerial
-- Inlet, Main, LS 6" Non-gated, Cap
-- Inlet, Main, RS 6" Non-gated, Cap
-- Inlet, LS Panel Front 2-1/2" Akron, Swivel, Plug
-- DISCHARGE CONTROLS AND OUTLETS FOR MM TOWER
-- Valve Controllers, Electric, for All Discharges
-- Outlet, LS Panel Front (1) 2-1/2" Akron Straight, Electric
-- Outlet, LS Panel Rear (1) 2-1/2" Akron Straight, Elec

DESCRIPTION
-- Outlet, RS Panel Front (1) 2-1/2" Akron Straight, Elec
-- Outlet, RS Panel Rear (1) 4" Akron Straight, Elec
Lights, Work, (2) 6" Pump Compartment
Gauges, Master, (2) Class 1, 4-1/2", 30-0-400 PSI
Gauges, 2-1/2" 0-400 Class 1 Line Gauges
Gauge, Discharge, Aerial 2-1/2" 0-400 Class 1
Electrical Interface w/Fast Idle System
Relief Valve, Intake
Pump Shift, Custom RH Side
Drains, Quarter Turn, 3/4" Class 1
Engine Cooler, Custom or FTL Chassis
-- Engine Cooler, Body Facility Finishes Installation
Outlet, Aerial, 5" Butterfly, Electric Controlled, MM Tower
Body, Quint, 10' 6" OAH, Rollup Doors, P45M, 194CA, (06 Ver
-- Water Tank-UPF Poly-Basic Construction-MM Tower
-- Water Tank - Poly-Tank - 300 GALLONS
-- Cmpts,Driver,P45M,24"Uppr,Rollup,Quint,10'6",1RRStep,194CA
-- Cmpts,Curb, P45M,13"Uppr,Rollup,Quint,10'6",1RRStep,194CA
-- Doors, Rollup, Robinson ROM, P45M
-- Roll-Up Door Finish, Satin
-- Lights - Body Compartment
-- Storage, Grd Ladders, Center Vert.Stack(MM-LT-75/93)
Body Material, 194" CA, MM Tower, Aluminum
Exhaust Heat Deflector
Compartmentation Detail
Air Cylinder Storage, (6), Cast Door, MM Platform
Fuel Filler w/ Cast Products Door, MM Tower
RR Body Module-Alum T/P -Double Door, MM Tower/Ladder
Wheelwells, Poly, Tandem RA, SS Fenderette
Mud Flaps, Rear
Body Trim, MM Tower, Aluminum Diamondplate
Rub Rails, Alum. Ext.
Steps, Access, "A" Frame Style (2-Front & 2-Rear)
-- Handrails - Body, Forward Access Steps, MM-LT
-- Handrails - Body, (2) RR Access Steps, MM-LT
Outrigger Covers (4)
Hosebed Area, MM Tower
-- Hosebed Flooring, Fiberglass
-- Hosebed Capacity, General
Hose Storage, Center Rear, MM Tower
Hosebed Cover, MM Tower
Storage, Pike Poles (Center Stack, Tube Style)
Rear Tow Devices (Painted Torque Box Color)
12v Electrical Sys, Body, Non-Multiplex, MM Platform
Lights - Step
ACCESSORIES, AERIALS (EXCEPT FOR TDA)
-- Decking, Turtle Tile, Black, Floors, Multiple Shelves & Tray
-- Shelves, Adj, 3/16" Smooth Alum (3)
-- Adjustable Track in Cmpts for Future Shelf Installation
-- Tray, 250# Floor Mounted, Sliding (1)
-- Tray, 500# Floor Mounted, Sliding (1)
-- Tool Board, Swing-Out Hinged Tool Panel (1)
NFPA Optical Warning System
-- Lightbar, Contoured, Standard Configuration
-- Front Warning Lights, Fixed, LED

DESCRIPTION

-- Lights, Warning, Front, Inbrd of Turn Signal, LED
-- Lights, Warning, ALF Aerial, Whelen LED Pkg
-- Headlights Halogen, 1High & 1Hi/Low Beam Each Side
-- Turn Signals Cornering Lamps, LED, Halogen
-- Horns, Dual Electric
-- Siren, PA 200 Watt w/(1) Speaker, Ctr Bumper
-- Switch, Foot, (1) Siren/RS
-- Air Horns, Dual 21" Grover Stuttertone, Center Bumper
-- Switch, Selector, Horn/Air Horn, Cab Dash Mtd
-- Code 3 Model D50C Constant 97 DB Back Up
Lights, ICC Lighting-LED-Body-T/A-MM
Lights, Underbody (8)
Lights, Deck Lights, (2) 6" Unity, Rear Aerial Body
Light & Bracket, License Plate
Lights, Whelen, Cast4 Tail/Turn/Backup, LED/Halogen (4) Lamp
Painting, Body, ALF AERIALS (ALL)
-- Paint, Custom Cab, Single Color,
-- Paint, Chassis, Black
-- Paint, Color, Body Single Color
-- Finish, Compartment Interior, Zolatone
-- Paint, Paint, Factory Std. Finish
Undercoating, Rust Inhibitor, Body
Lettering, (60) Scotchlite, 3" Letters
Lettering, (36) Scotchlite, Red, Letters on Sides of Aerial
Striping, Scotchlite, (1) 4" NFPA Stripe
Reflective Chevron
-- Red and Yellow Reflective
100' PLATFORM MID MOUNT STEEL (Torquebox frame)
-- Testing & Certification, P45M100/93, 1000# TL
-- Tower Ladder Components, P45M-100
-- Elevation System, -10 to 78 Degrees
-- Rotation System, 40.29" Diameter
-- Extension/Retraction System, 03' Version
-- Ladder Slide Mechanism, Nylatron
-- Ladder Lubrication, P45M
-- Ladder Elect/Air/Hyd Line Track System
-- Extension Indicators, 10' Marker Spacing
-- Platform Const, 29.0 Sq Ft, w/ Ext Step
-- Platform Floor, 29.0 SqFt w/Ext Step, New Tower
-- Platform Handrail, 42" High, 10" Pivot
-- Platform/Ladder Access Gate
-- Platform Leveling System
-- Platform Mounting
-- Safety Belt Connections, (4)
-- Platform Control Console, Multi-Location, New Tower
-- Telescopic Wtrwy, 5 Sct, 6.0"-5.5"-5"-4.5"-4"
Torque Box/Frame, Deep Penetration Outriggers, P45M
-- Aerial Device Mtg & Travel Support (MM 4 O/R)
-- Stabilizers, Deep Penetration, Front Mounted
-- Outriggers (4), 18'Frt/16'Rr Stance, Pinless Dp Penetrating
-- Jack Cylinders, Deep Pentetration, P45M
-- Jack Extension, 64.5" Frt, 54" Rr Stroke , P45M
-- (4) Outrigger Pads, 168 sq-in
-- (4) Auxiliary Outrigger Pads
-- (4) Outrigger Lights, Out/Down O/R w/(4) Grnd Lts

DESCRIPTION
(2) Base Sect Nameplates, 20" x 104", P44M/P45M/P43R
-- Lifting Arms
-- Rescue Stretcher Holders
-- Rescue Ladder Brackets, Both Sides
Under Platform Steel Lifting Eyes
Platform Storage Compartments
(5) Red Platform LED Clearance Lts, MM Tower
Hydraulic System W/Sight Glass Ind, 40 Gal
-- 12 Volt Emergency Hydraulic System, All
-- (2) Emerg Pwr Unit (EPU) Swtchs, LH/RH Otrgr
5" Combo Hydrlic, Wtr & 26 Ring Elec Swvl
PTO, Muncie MPM w/"Hot-Shift", Allison HD Trans., AL1
Turntable Treadplate, 96" Dia, P44/45M
-- Safety Railing, T/T, Knurled SS, Safety Chain Gate
-- Cradle Alignment Indicators
-- (4) Turntable Work Lights, Rear Step Mtd
Electrical Sys.Components, P45M Towers, Non-Multiplexed
-- Short O/R Jack Sys, Manual, 4-O/R, MM Platforms
-- (2) Outrigger Leveling Ind, LH/RH Apparatus Sides
-- Outrigger Deployment Warning Alarm
-- Ladder/Outrigger Interlock System
-- Safety Features, Short Jacking, MM Tower, New Version
-- Rotation Limiting System, Out & Down Outgrs
-- Aerial Cntrl Stn, RH T/T Console, MM Towers
-- T/T Console Cover, MM Tower, Black Powder Coated Aluminum
-- Engine, Fast Idle Actuator (With Fire Pump)
-- Aerial Hour Meter, Wired to PTO
-- Low Air Pressure Warning System, Visual @ T/T Only
Comm Sys., Platform to T/T, Atkinson
(1) Unity Spotlight, (1) Floodlight, Platform
(2) Unity Spotlights, Rear Ladder Base
120 Volt Circuit to the Platform
-- Receptacles, (2) Woodhead L5-15, Platform
(2) Fire Research Focus 750W Lights, Rr of Platform
(2) Breathing Air, 2265 PSI LP, Platform Mtd
-- (2) Hansen Breathing Air Outlets, Platform
-- 25' LP Air Cylinder Refill Hose
5" SS Waterway Inlets, Pump & Rgt PpPnl, P45M
-- Waterway Inlet Accessories, (1) 5" NST
-- Rotational Swivel, 5"
-- Heel Pin Swivel
-- Water System Friction Loss
MM Platform Water System, (2) Akron Monitors
-- Akron 3578 Monitor, Remote Control, Platform
-- Akron #5178 3.5" Nozzle, Electric
-- Monitor Function Switches, T/T & Monitor
-- Akron 3570 Monitor, Manual, Frt of Platform
-- Akron #5170 3.5" Nozzle, Manual
-- (2) 2.5" NST Gated Preconnects, Front of Platform, New Tower
-- Relief Valve, 2.5", Aerial Waterway
-- Flowminder Mtd on T/T Console/Class 1 FMS
Axe Mounting Provisions, Platform
(1) Roof Ladder Mtg Brckt, Fly, Right Side
(6) Special Retorquing Tools w/Tool Box
Aerial PPG Painting

DESCRIPTION

Reflective Striping, Otrgr Bm Refl
Caution & Warning Sign
On-Site Preventative Maintenance & Operational Training (3)
Manuals-Chassis; Pump; Body; Aerial Device (2)
GROUND LADDERS
Ladder, Duo-Safety, Series 900-A, 24' 2-Sec (1)
Ladder, Duo-Safety, Series 1200-A, 35' 2-Sec (1)
Ladders, Duo-Safety, Series 875-A, 16' Roof (2)
Ladder, Duo-Safety, Series 701-14 Attic (1)
Ladder, Duo-Safety, Series 585-A, 10' Folding (1)
LOOSE EQUIPMENT ITEMS
Pike Poles, (2) Duo-Safety, 6' Fiberglass 6FP
Pike Poles, (2) Duo-Safety, 8' Fiberglass 8FP
Pike Poles, (2) Duo-Safety, 12' Fiberglass 12FP
Chocks, Wheel, (2) Ziamatic SAC-44 Folding w/Brkt
Purchaser Provides All Other NFPA 1901 Equipment
Warranty - Refer to FS12-11 FORM G

TRACTOR DRAWN AERIAL



AERIAL

Exceptional Aerial capability, with superior maneuverability and control to get the unit into tight fire scenes.

LADDER LENGTH OPTION: 100', 105'

- Fifth wheel articulating design provides short turning radius and high maneuverability
- Rear trailer steering allows tiller driver to negotiate tight corners and congested streets
- Available with fire pump and water tank options, providing a versatile fire scene application
- Ladders with wide steps and high handrails for safer rescue and fire fighting
- Pre-piped telescopic water system for quick master stream operation
- High-volume trailer carries exceptional amount of fire-fighting equipment and ground ladders
- Modular body design enables fast repair and reduced downtime
- Numerous compartment design options can be custom tailored to specific needs
- "Out-and-down" outriggers provide flexible placement and Short-Jacking capability
- Available tip load capacity of 250 and 500 lbs



TRACTOR DRAWN AERIAL



Low ground ladder storage for ease of access



Easy maneuverability by tiller driver



Clear ladder walkway for easier access



Multiple compartments providing many storage options



Out-and-down outriggers for tighter spaces

These are the typical specifications for the Tractor Drawn Aerial Ladder:

LADDER: All-steel construction with k-bracing, dual-rod extension system.

TIP LOAD RATING: 100'/105' available tip load capacity of 250 and 500 lbs.

WATERWAY FLOW RATING: 250 lbs – 1000 GPM; 500 lbs – 1500 GPM.

HORIZONTAL REACH: 100' Mod. – 97'; 105' Mod. – 94.5'

ANGLE OF ELEVATION: 100' Mod. – 2° to 75°; 105' Mod. – 7° to 78°;

MONITOR: Retractable with lever connection to ladder fly or outer-mid for rescue operations, automatic electrical disconnect for monitor functions (ladder is available without a waterway).

OUTRIGGERS: Quantity of 2, H-type, out-and-down style, Short-Jacking capability with Rotational Limiting Safety System.

OUTRIGGER SPREAD: 16' or 14' with lockouts.

O.A.L. (TYP.) RANGE: 55' - 3" to 59' - 7"

O.A.H. (TYP.) RANGE: 11' - 3" to 11' - 11"

WHEELBASE (TYP.) RANGE: 140" to 173"

CHASSIS: American LaFrance Eagle®

AVAILABLE OPTIONS: Fly mounted axes and utility tools. High pressure breathing air system. Three-Way Communication System. Tip preconnects. Body materials include aluminum. Compartment shelving; full suspension pull-out trays and custom-hinged tool boards. Rescue depth compartmentation. Upper and lower full-width compartments; hinged or roll-up doors. Fully rated mid-ship mounted fire pump; watertank and crosslay options, diesel and hydraulic generators. Horizontal or vertical ground ladder storage with various NFPA compliant packages. Air bottle storage in wheel well area.

For your nearest American LaFrance dealer, go to www.americanlafrance.com.

Some specifications and features shown or mentioned in this brochure are optional and are available upon request at extra cost. Specifications are subject to change without notice. ©2009, American LaFrance, LLC. All rights reserved.



QUOTATION

American LaFrance

OHIO STS

\$858,246.00

American LaFrance Eagle 4-Door Tilt Cab, Formed Aluminum Body, Single Axle, 100' Tractor-Drawn Mid-Mount, Telescoping Ladder 500lb (Steel)

08/01/2011

Quote No: ALF AA08-

Page 1

DESCRIPTION

== American LaFrance 100' Tractor Drawn Ladder - 500lb ==
Eagle 134 (4) Door Tilt Cab Fire Chassis, Formed Alum Body
Custom Cab and Chassis Specifications
Overall Height 138" and Overall Length 59' - 6"
NFPA 1901 Certificate of Compliance
Chassis Wheelbase - 159"
|-- Frame, 11/32" x 3-1/2" x 10-15/16" Up to 362" Overall Length
|-- Frame Fasteners, Huck Spin
Frame Reinforcement, C-Channel, Up To 374" Over All Length
|-- Engine, Cummins ISX 500 bhp/1645 lb-ft 11.9L - 2010 EPA
|-- Starter, Delco 42MT/OCP w/Thermal Protection
|-- Air Compressor, Wabco 18.7 cfm
|-- Fan Drive - Engine, Horton Drivemaster
|-- Coolant Filter, Fleetguard, Spin-on (Cummins)
|-- Transmission, Allison 4000 EVS-P
|-- Trans Prog, 5 Spd Pumper, Fire & Emg (120)
|-- Transmission Shifter, Touch Pad
|-- Transmission Oil Cooler
|-- Engine Brake, Jacobs w/(2) Switches
|-- Fuel/Water Separator, Racor 490 w/Electric Heater
|-- Exhaust System - RH Horizontal ATD, Horizontal Tailpipe
|-- Alternator, Leece-Neville, 320 Amp
|-- Air Cleaner w/Ember Separator, Frontal Intake
|-- Air Restriction Gauge, Engine Mtd with Dash Light
|-- Radiator, High Capacity Down Flow, 1627
|-- Coolant Hoses, Gates "Blue Stripe" EPDM
|-- Coolant, Engine, Heavy Duty, to -34 Fahrenheit
|-- Engine Protection Alarms
Light, Engine Compartment (1)
Heater Hoses
Engine Stop Control, Ignition Switch
|-- Fuel Tank, 50 Gallon, Rectangular, Steel
|-- Fuel Fill w/Cap and Lanyard, Left
|-- Fuel Lines, Reinforced, Wire Braid
Front Axle Package, 18,000 lbs, Meritor MFS-133A
|-- Steering Gear 18,000 lb. Cap w/o Ram Ass't TAS-85.
|-- Power Steering Pump
|-- Power Steering Reservoir, 4 Quart
|-- Front Suspension 18,000 lb Taperleaf w/Shock
|-- Front Brakes, Meritor EX-225H 17" Air Disc
|-- Frt Tires, Mchl, 315/80R22.5 "L" XZY-3, 18,000#

DESCRIPTION
-- Alm Hub Plt, 22.5" x 9.00", 18,000#
-- Polish Outside of Front Aluminum Wheels
-- Hub & Lug Nut Covers, S/S, Front Wheels
Tire Inflation Indicators, Tiller Axle
Sngl Rear Axle 27,000 lbs, Meritor, RS-26-185
-- Tire Inflation Indicators, for Chassis w/Single Rear Axle
-- Rear Axle Ratio for 60 MPH Maximum
-- Sngl Rear Susp, 27,000#, Neway AD-127 W/Shocks
-- Brakes, "Q-Plus" HD Rear Axle, 16.5" x 7" Cam
-- Air Tanks, Minimum for Air Suspension
-- Rear Axle Seals
-- Rr Tires, Mchl, 12R22.5, "H", XDN2, 28,880#
-- AlumHub Plt, Accuride 29644 22.5" X 8.25"
-- Polish Outside of Rear Aluminum Wheels
-- Hub & Lug Nut Covers, S/S, Rear, Axle
Drive Shaft
Lubricant, Petroleum, Axles
Air Brake System
Air Dryer, Bendix AD-9
Air Reservoir, Additional, 1730 Cubic Inches w/ PPV
Air Tank Pull Cables, Each Tank
ABS Braking System, Wabco 4S/4M
Brake Lock, All Wheel (Front Axle)
Cab, 134" CBC, Four Door, Flat Roof
-- Windows, Side Cab, Fixed
-- Cab Tilt Mechanism w/Extnl Alarm
-- Cab, Mounts, Air, 1" Up, 1" Down 35 Degree Tilt
-- Seat, Dvr, H.O. Bostrom, Air Suspension
-- Seat, Offcr, H.O. Bostrom, SCBA NonSusp
-- Seats, Rear Facing Crew, H.O.Bostrm SCBA Otbrd (2)
-- Seats, Forward Facing, SCBA, H.O. Bostrom, Inboard (2)
-- Bottle Holder with Restraint, Zico
-- Seat Covers, Durawear/Vinyl
Cab Grab Handle - (4) Ext. Rubber Inserts
Mirrors, Cab, Mekra, Chrome, 16" x 7" M2 Style H&R
-- Mirrors, Cab, Convex, 7" x 7"
Fenders, Cab, Polished Stainless Steel
Mud Flaps, Front
Radio, Rcway, Power & Ground, UHF/VHF Mtd Loc,
Antenna, UHF/VHF Mtd LS Cab Roof (42-50 MHz)
Antenna, UHF/VHF Mtd RS Cab Roof (42-50 MHz)
Electrical Load Management System
-- Battery System - 12V (6) HD Batteries
-- Battery Charger, Kussmaul Auto Chg 1200 "Pump +" w/Recept
-- Receptacle, Super Auto Eject, 120 VAC, Yellow Cover
-- Electrical Load Manager Interlock, Pumper
Cab Interior Specifications
Steering Column, Adj Tilt & Telescoping
Steering Wheel, 18" Four-Spoke Charcoal Gray
Overhead Console
Overhead Switch Console, Aerial Control (2)
-- Overhead Switch Console, Tiller, PTO Rocker Switch w/Ind
Gauges (U.S)
Lights, Cab Interior, Red/Clear
Outlets, 12-Volt, Automotive Type (3) Dash Mounted

DESCRIPTION

Heater/Air Conditioner and Defroster, Primary
 |-- Heater/Air Conditioner, Auxiliary
 |-- Compressor, Refrigerant, A/C, 15.3 cfm
 |-- Air Conditioning Condenser, Radiator Mtd
 |-- HVAC Performance Spec
 Interior, Chieftain Shadow Gray Imperial 1200 w/Shadow Trim
 Trim, Door, ABS/Upper, Brushed S/S Lower Kickplate
 |-- Windows, Door Controls, Power Front & Rear
 Map Box - 8"H x 10"W x 13"D w/ (3) 3" Slots
 Vehicle Data Recorder
 Electronic Stability Control
 Seat Belt Warning System
 Helmet Storage, Each Seating Position (6)
 Seat Belts 3Pt Fwd facing, 3Pt Rr facing
 Bumper Extension 4", Polished Stainless Steel
 Tow Hooks, Painted, Mtd Bot Frame Ext
 Plates, Fluid & Seating Capacity
 Plate, Overall Travel Height, Length and Weight
 Tag, Warning, Aerial Devices
 Tag, Warning, Crew Area and Rear Body Step
 Testing, Third Party, Aerial
 == NO FIRE PUMP ==
 Body, Tractor Drawn Aerial, Long Trailer, Roll-up Doors
 |-- Compt, Tractor, Driver, L"1" 42"W, Rollup Doors
 |-- Compt, Tractor, Curb, R "1", 42"W, Rollup Doors
 |-- Compt, Transverse, Gooseneck, L/R "2", Rollup Doors
 |-- Compt, TDA, Rescue L/R "3", Transverse Upper, Rollup Doors
 |-- Body Trim, Aluminum Diamondplate (Base TDA)
 |-- Body Trim, AL DP, Vert Surface, Hi Side, Grd Ladder Struct.
 |-- Compt, TDA, Rescue L/R "4", 26" Dp Both Upper, Rollup Doors
 |-- Compt, TDA, Rescue L/R "5" 26" Dp Driver's Upper, Rollup Do
 |-- Compt, TDA, Low L/R "6" Transverse, Rollup Doors
 |-- Compt, TDA, Low L/R "7". Transverse, Rollup Doors
 |-- Doors, Roll-up, Robinson, TDA Long Trailer
 |-- Roll-Up Door Finish, Satin
 |-- Lights - Body Compartment - TDA
 |-- Fender/Wheelwell, TDA, Trailer, SA, Painted Fenderette
 |-- Outrigger Covers (2)
 |-- Storage, Grd Ladders(Left/Right In)Horz, TDA-346WB
 |-- Storage, Pike Poles -Trailer Frame-Max 12 Feet
 Body Material, TDA, Aluminum
 Exhaust Heat Deflector
 Compartmentation Detail
 O/R Control Compartment Doors
 Air Cylinder Storage Compts, Trailer Fender
 |-- Air Cylinder Storage Cast Door
 |-- Air Cyl. Storage-LT, Wheelwell 1 Rear, TDA
 |-- Air Cyl. Storage-Rt Wheelwell 1 Rear, TDA
 Fuel Fill Tube (Drivers Side) TDA
 Rear Body Module-(1)Alum Treadplate Door RR, TDA
 Wheelwell/Fenders, TDA, Tractor, SA., Painted Fenderette
 Mud Flaps, Rear & Tiller
 Rub Rails, ALF Aluminum Extrusion, Red Reflective Stripe
 Handrails Body - TDA
 Steps (Alum. Diamondplate 3/16")

DESCRIPTION
Outrigger Pad Storage Slides (2-Outriggers)
Rear Tow Devices (Painted Torque Box Color)
Tiller Cab, LA Style, General
-- Tiller Seat Belt
-- Tilt and Telescopic Steering Column
-- Tiller Cab Doors, Hinged
-- Rear Window, Tiller Cab
-- Handrails, Tiller Cab
-- Tiller Cab Wiper/Mirrors
-- Sun Visor, Tiller
-- Safety Start System
-- Comm. System Tiller Cab
-- Tiller Seat - Bostrom Sierra -Gray
-- Heater/Defroster, Tiller Cab
12v Electrical Sys, Body, Non-Multiplex, TDA
Buzzer Warning System - TDA
Lights - Step
ACCESSORIES, TRACTOR DRAWN AERIALS (TDA)
-- Decking, Turtle Tile, Black, Floors, Multiple Shelves & Tray
-- Shelves, Adj, 3/16" Smooth Alum (4)
-- Trays, 250# Floor Mounted, Sliding (2)
-- Trays, 500# Floor Mounted, Sliding (2)
-- Tray, 1000# Dual-Direction Tray, Approx 96" L, Transverse (1)
NFPA Optical Warning System
-- Lightbar, Contoured, Standard Configuration
-- Front Warning Lights, Fixed, LED
-- Lights, Warning, Front, Inbrd of Turn Signal, LED
-- Lights, Warning, ALF Aerial, Whelen LED Pkg
-- Headlights Halogen, 1High & 1Hi/Low Beam Each Side
-- Turn Signals Cornering Lamps, LED, Halogen
-- Horns, Dual Electric
-- Siren, PA 200 Watt w/(1) Speaker, Ctr Bumper
-- Switch, Foot, (1) Siren/RS
-- Air Horns, Dual 21" Grover Stuttertone 1-LH, 1-RH Bumper
-- Switch, Selector, Horn/Air Horn, Cab Dash Mtd
-- Code 3 Model D50C Constant 97 DB Back Up
Lights, ICC Lighting-LED-Body - Single Rear Axle
Lights, Underbody (8)
Lights, Deck Lights, (2) 6" Unity, Rear Aerial Body
Light & Bracket, License Plate
Lights, Whelen, Cast4 Tail/Turn/Backup, LED/Halogen (4) Lamp
Painting, Body, ALF AERIALS (ALL)
-- Paint, Custom Cab, Single Color,
-- Paint, Chassis, Black
-- Paint, Color, Body Single Color
-- Finish, Compartment Interior, Zolatone
-- Paint, Paint, Factory Std. Finish
Undercoating, Rust Inhibitor, Body
Lettering, (60) Scotchlite, 3" Letters
Striping, Scotchlite, (1) 4" NFPA Stripe
Reflective Chevron
-- Red and Yellow Reflective
100' TRACTOR DRAWN AERIAL STEEL (w/ Waterway)
-- Testing & Certifications, C24R105/110, 500#Dry/250# Wet Tip
-- Trailer Frame/Torque Box, 346" WB, (2) O/D Outriggers

DESCRIPTION

|-- Aerial Device Mtg & Travel Support (TDA)
|-- Trailer Fifth Wheel Assembly
|-- Trailer Axle, MFS-20-133A, 21,500# Fire Service Rating
|-- Oil Seals, Tiller Axle
|-- Trailer Steering System
|-- Trailer Suspension, Air Ride w/Shock Absrbrs
|-- Trailer Brake System
|-- Trailer Brakes, Disc, Meritor EX-225-H4
|-- Trailer Brake Chambers, Meritor
|-- Trailer ABS Braking System
|-- Braking Control System
|-- Trailer Brake Reservoirs
|-- Trailer Brake Reservoir Drains, Manual
|-- Outriggers (2), Out & Down, 16' Stance, TDA
|-- Jack Cylinders, RM Rear / MM Front
|-- Jack Extension, 54" Stroke, Rr RM / Frt MM
|-- (4) Extension Slide Pads Per Outrigger Asmbly
|-- (2) Outrigger Pads, 168 sq-in
|-- (2) Auxiliary Outrigger Pads
|-- (2) Outrigger Lights, Out/Down O/R w/(2) Grnd Lts
|-- Tractor Lockout System, Out/Down Outriggers
|-- Aerial Ladder Comp, C24T-105, 500# Dry/250# Wet Tip Load
|-- (2) Folding Steps With "Bustin" Inserts
|-- Elevation System, -7 to 78 Degrees
|-- Rotation System, 40.29" Diameter
|-- Extension/Retraction System, C Series 4-Section Ladder
|-- Ladder Slide Mechanism, Nylatron
|-- Ladder Electrical/Air Line Track System
|-- Extension Indicators, 5' & 10' Marker Spacing
|-- Turntable, Semicircular, 88" x 95" Wide, Full, C24T/L34T
|-- Safety Railing, T/T, Knurled SS, Safety Chain Gate
|-- Cradle Alignment Indicators
|-- (4) Turntable Work Lights, Rear Step Mtd
|-- (2) 4" Wtrwy Inlts, LH/RH, Goosneck
|-- Waterway Inlet Accessories, (2) 4" NST
|-- Rotational Swivel, 4"
|-- Heel Pin Swivel
|-- Water System Friction Loss
|-- Telescopic Waterway, 4 Sect, 5"-4.5"-4"-3.5"
|-- Monitor, Akron 3578, Wireless Radio Controlled, Tip of Fly
|-- Ladder Bolt-On Egress
|-- Ladder Illumination Lighting, Red, C Series 4-Sec Ladders
|-- Akron #5178, 1500 GPM, 3.5" Nozzle, Electric
|-- Wireless Monitor Function Switches, Akron, T/T & Monitor
|-- Retractable Monitor, Mechanical Latch With Auto-Connector
|-- Flowminder Mtd on T/T, Akron
Trailer Wheels, Polished Aluminum Disc
Stainless Steel Lug Nut Covers
Trailer Tires, Mchl, 425/65R22.5, 22,800#, XZY3-WB
(2) Aerial Base Sect Nameplates, 14" x 120"
Hydraulic System W/Sight Glass Ind, 40 Gal
|-- 12 Volt Emergency Hydraulic System, All
|-- (2) Emerg Pwr Unit (EPU) Swtchs, LH/RH Otrgr
4" Swivel Combo, 3-Pt Hyd, Wtr & 26 Ring Elec
PTO, Chelsea Model 277 w/"Hot-Shift", Allison HD Trans. AL1

DESCRIPTION

Electrical System, TDA Ladders W/ Waterway, Non-Multiplexed

- |-- Short O/R Jack Sys, Manual, 2-O/R, L14T/L24T*
- |-- (2) Outrigger Leveling Ind, LH/RH Apparatus Sides
- |-- Outrigger Deployment Warning Alarm
- |-- Ladder/Outrigger Interlock System
- |-- Safety Features, Out & Down Outriggers
- |-- Rotation Limiting System, Out & Down Outgrs
- |-- Aerial Control Console, RH T/T, TDA Aerials
- |-- T/T Console Cover, Aluminum Treadplate
- |-- Engine, Fast Idle Actuator (With Fire Pump)
- |-- Aerial Hour Meter, Wired to PTO

Comm Sys, Tip to T/T, Atkinson

(2) Unity Spotlights, Rear Ladder Base

(2) Unity Spotlights, Aerial Tip

120 Volt Circuit to Ladder Tip

- |-- Receptacle, (1) Woodhead L5-15, Ladder Tip

(1) Special Width Roof Ladder Mtg Brckt, Fly, Right Side

(6) Special Retorquing Tools w/Tool Box

Aerial PPG Painting

Reflective Striping, Otrgr Bm Refl

Caution & Warning Sign

On-Site Preventative Maintenance & Operational Training (3)

Manuals Chassis; Body; Aerial Device (2)

GROUND LADDERS

Ladder, Duo-Safety, Series 900-A, 24' 2-Sec (1)

Ladder, Duo-Safety, Series 1200-A, 35' 2-Sec (1)

Ladders, Duo-Safety, Series 875-A, 16' Roof (2)

Ladder, Duo-Safety, Series 701-14 Attic (1)

Ladder, Duo-Safety, Series 585-A, 10' Folding (1)

LOOSE EQUIPMENT ITEMS

Pike Poles, (2) Duo-Safety, 6' Fiberglass 6FP

Pike Poles, (2) Duo-Safety, 8' Fiberglass 8FP

Pike Poles, (2) Duo-Safety, 12' Fiberglass 12FP

Chocks, Wheel, (2) Ziamatic SAC-44 Folding w/Brkt

Purchaser Provides All Other NFPA 1901 Equipment

Warranty - refer to FS12-11 FORM G

ALUMINUM



PUMPER

This new monolithic integral sub-frame design provides superior performance and reliability.

PUMPER, RESCUE-PUMPER

- Aluminum formed body
 - Aluminum formed from 3/16" 5052 sheet with aluminum sub-frame
 - 150% stronger and 230% more resistant to bending than 1/8" sheet
- Fully modular body with integrated sub-frame and American LaFrance proprietary FMS™ mounting system to reduce shock and torsional loading
- Traditional aluminum framed pumphouse with stainless panels or optional stainless frame pumphouse with classic American LaFrance inset panels
- Multiple body configurations
- 15-step PPG paint on body with durable, high luster finish
- VMUX solid state electronics for maximum programmable flexibility for strong system reliability with advanced full-service harness network
- Multiple pump configurations including American LaFrance pumps with capacities up to 2000 GPM
- Industry first independent UL welder certification
- Full-body durability testing by American LaFrance at independent proving grounds



ALUMINUM



Self-supporting integral sub-frame for maximum strength



Versatility - multiple body configurations with up to 1000 gal tank capacity

These are the typical specifications for the American LaFrance Aluminum Pumper Bodies:

MODEL: American LaFrance Aluminum Pumper Bodies.

CONSTRUCTION: 5052-H32 3/16" formed body panels with integral 6063-T52 sub-frame.

MOUNT SYSTEM: American LaFrance proprietary Flexible Mount System (FMS™).

BODY STYLES: Multiple body configurations available including traditional high/low pumpers and three to five compartment Rescue-Pumpers.

DOORS: Roll-up doors standard with optional hinged overlap doors.

WATER CAPACITY: Polypropylene tanks from 750 to 1500 gal.

PUMPS: Multiple pumps available including American LaFrance Twin Flow split-shaft pumps with capacities from 1000 to 2000 GPM.

PUMP HOUSE: Traditional aluminum or stainless steel pump house and overlap panel with optional stainless steel frame upgrade in both side mount and top mount configurations.

FOAM SYSTEMS: Single or dual tank systems available with foam cells integral to the water tank.

LADDER STORAGE: Standard side wall storage brackets with optional internal ladder storage or optional single and dual overhead electric/hydraulic racks for maximum compartment availability.

GENERATORS: PTO driven hydraulic generators with capacities up to 15 KW or compartment mounted gasoline generators with capacities up to 5 KW. Additional options available upon request.

SCENE LIGHTING: Multiple truck mounted scene lighting available, including folding light towers, telescoping lights on the back of cab and body, or removable tripod lighting in 500W, 1000W, or 1500W light heads.



Threaded inserts provide maximum reliability



Transverse rear compartment with bolt-in divider option



FMS mounting system extends service life of the body

For your nearest American LaFrance dealer, go to www.americanlafrance.com.

Some specifications and features shown or mentioned in this brochure are optional and are available upon request at extra cost. Specifications are subject to change without notice. ©2009, American LaFrance, LLC. All rights reserved.



QUOTATION

American LaFrance

OHIO STS
\$210,606.00

American LaFrance 2 Door Freightliner Pumper
Side Mount Hale QFLO 1250 Pump
Formed Aluminum Pumper Body

07/26/2011

Quote No: ALF AC01-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==
== Chassis M2 2-D Pumper - 1001.001 01/19/10 ==
Certificate of Compliance, NFPA 1901
Chassis, Freightliner M2 106 2-Door

Engine, Cummins ISC8.3 300HP

Standard Engine Protection W/O De-rate

Front Axle, 12,000#, Package

Rear Axle, Single, 23000#, Package
|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Painted Plastic Hood Mounted
Mirrors, Dual Painted West Coast

Steering Column, Fixed
Seat, Non-Suspended Driver's
Seat, Non-Suspended High Back Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder
Rollover Stability, Commercial Chassis
Seatbelt Warning System
Helmet Storage, Each Seating Position
Tire Inflation Indicators, for Chassis w/Single Rear Axle
== Bumper Package / M2 - 1001.001 01/19/10 ==
Bumper, Front, Painted
|-- Air Horns, Hood Mounted
|-- Lanyard Control
|-- Siren, Electronic w/100 Watt Speaker

DESCRIPTION

== Chassis Mods M2 - 1001.001 01/19/10 ==
 Light, Engine Compartment
 Battery "On" Light, Green
 Receptacle, 12V for Fire House Charging System
 |-- Air Charging Connector, LS
 Label, Fluid & Seating Capacity, Cab
 Label, Overall Travel Height, Cab
 Labels, Crew Area and Rear Body Step
 == Pump / Enclosure / Commercial - 1001.001 01/19/10 ==

Testing, Third Party, Pumpers
 Pump, Hale Qflo Plus1250 GPM, Single Stage
 |-- Cooler, Engine, Custom or Commercial Chassis
 |-- Cooler, Pump, Bypass Tank Fill
 Pump Enclosure, S/M w/ Crosslays
 |-- Crosslay Cover, Vinyl
 |-- Running Boards, Non-Skid Aluminum Diamondplate
 |-- Gauges, Master, 4-1/2", 30-0-600 PSI
 |-- Gauge, Discharge 2-1/2" 30-0-600 Class 1
 |-- Elec Interface w/Fast Idle System
 |-- Piping, Class 1 HP Hose and Stainless Steel Pipe

|-- Inlet, Left Panel 2-1/2"

|-- Discharge, LS Panel (2) 2-1/2"
 |-- Discharge, RS Panel (2) 2-1/2"
 |-- Discharge, Crosslays, (2) 1-1/2"
 |-- Discharge, Deck Gun, 3" Centered
 |-- Deck Gun Outlet Capped, Customer Supplies Gun
 |-- Discharge, Rear of Body Left Side (1) 2-1/2"

Tank to Pump Line, 3"
 Tank Fill, 2"
 == Body / Pumper - 1001.001 01/19/10 ==

Water Tank 1000 Gallon, 20 Gallon Foam Cell
 |-- Warranty, Water/Foam Tank Lifetime
 |-- Gauge, Water Tank Level Indicator

Subframe- Aluminum / Pumper Body
 |-- Body Construction / Material / Aluminum
 Body, 35/35 FHRD-L / L-R w/ External Equip. Storage
 |-- Doors, Roll-Up 35/35

|-- Ladder Brackets, Side Mtd, Above Cmpt.s RS
 |-- Ladder Folding, Storage, Top of Cmpt.s RS
 |-- Hose, Soft Suction, 6" NST x 15' Couplings
 Hose Bed Divider, (1)
 Hose Bed Cover, Red w/Weighted Flap and Snaps

Tailboard, 12" Deep
 Body Trim, Aluminum Diamondplate, Pumpers
 Rubrail, with Reflective Stripe
 Vent, Compartment

DESCRIPTION

Hand Rails, Body
 Steps, Folding (4)
 Tow Eyes, Rear
 Mud Flaps, Rear Axle (2)
 == Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Pumper / Commercial - 1001.001 01/19/10 ==

- |-- Electrical, 12 Volt Description
- |-- Warning Light System, NFPA
- |-- Warning Lights, Whelen Halogen Pkg, Commercial
 - |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
- |-- Reflectors NFPA/FMVSS Compliant
- |-- Lights, Clearance & Marker (7)
- |-- Lights, Side Running Board and Rear Step
- |-- Lights, Underbody
- |-- Light, Open Door Indicator, Flashing LED
- |-- Lights, Rear Deck Unity AG-S, 6"
- |-- Lights, Body Compartments
- |-- Lights, Midship Directional , 30'+ OAL
- |-- Light Bracket, License Plate
- |-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

- |-- Paint, Cab, Single Color 2-Door Cab
- |-- Paint, Chassis, Black
- |-- Paint, Body, Single Color
- |-- Finish, Compartment Interior, Zolatone Finish
- |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

- |-- Ladder, 14' Roof
- |-- Ladder, 24'-2 Section
- |-- Ladder, 10' Folding Attic

QUOTATION

American LaFrance

OHIO STS
\$216,482.00

American LaFrance 2 Door Freightliner Pumper
Top Mount Hale QFLO 1250 Pumper
Formed Aluminum Pumper Body

07/26/2011

Quote No: ALF AC02-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==
== Chassis M2 2-D Pumper - 1001.001 01/19/10 ==
Certificate of Compliance, NFPA 1901
Chassis, Freightliner M2 106 2-Door

Engine, Cummins ISC8.3-300HP

Standard Engine Protection W/O De-rate

Front Axle, 12,000#, Package

Rear Axle, Single, 24,000#, Package
|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control

Wheels, Standard Steel Disc

Grille, Painted Plastic Hood Mounted
Mirrors, Dual Painted West Coast

Steering Column, Fixed
"Select" 12VDC Power Supplies
Seat, Non-Suspended Driver's
Seat, Two-Man Mid-Back Bench

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder
Rollover Stability, Commercial Chassis
Seatbelt Warning System
Helmet Storage, Each Seating Position
Tire Inflation Indicators, for Chassis w/Single Rear Axle
== Bumper Package / M2 - 1001.001 01/19/10 ==
Bumper, Front, Painted
|-- Air Horns, Hood Mounted
|-- Lanyard Control

DESCRIPTION

|-- Siren, Electronic w/100 Watt Speaker
 == Chassis Mods M2 - 1001.001 01/19/10 ==
 Light, Engine Compartment
 Battery "On" Light, Green
 Receptacle, 12V for Fire House Charging System
 |-- Air Charging Connector, LS
 Label, Fluid & Seating Capacity, Cab
 Label, Overall Travel Height, Cab
 Labels, Crew Area and Rear Body Step
 == Pump / Enclosure / Commercial - 1001.001 01/19/10 ==
 Testing, Third Party, Pumpers
 Pump, Hale Qflo Plus1250 GPM, Single Stage
 |-- Cooler, Engine, Custom or Commercial Chassis
 |-- Cooler, Pump, Bypass Tank Fill
 Pump Enclosure, T/M w/ Crosslays
 |-- Crosslay Cover, Vinyl
 |-- Running Boards, Non-Skid Aluminum Diamondplate
 |-- Gauges, Master, 4-1/2", 30-0-600 PSI
 |-- Gauge, Discharge 2-1/2" 30-0-600 Class 1
 |-- Elec Interface w/Fast Idle System
 |-- Piping, Class 1 HP Hose and Stainless Steel Pipe

 |-- Inlet, Left Panel 2-1/2"

 |-- Discharge, LS Panel (2) 2-1/2"
 |-- Discharge, RS Panel (2) 2-1/2"
 |-- Discharge, Crosslays, (2) 1-1/2"
 |-- Discharge, Deck Gun, 3" Centered
 |-- Deck Gun Outlet Capped, Customer Supplies Gun
 |-- Discharge, Rear of Body Left Side (1) 2-1/2"

 Tank to Pump Line, 3"
 Tank Fill, 2"
 == Body / Pumper - 1001.001 01/19/10 ==

 Water Tank 1000 Gallon, 20 Gallon Foam Cell
 |-- Warranty, Water/Foam Tank Lifetime
 |-- Gauge, Water Tank Level Indicator

 Subframe- Aluminum / Pumper Body
 |-- Body Construction / Material / Aluminum
 Body, 35/35 FHRD-L / L-R w/ External Equip. Storage
 |-- Doors, Roll-Up 35/35

 |-- Ladder Brackets, Side Mtd, Above Cmpt.s RS
 |-- Ladder Folding, Storage, Top of Cmpt.s RS
 |-- Hose, Soft Suction, 6" NST x 15' Couplings
 Hose Bed Divider, (1)
 Hose Bed Cover, Red w/Weighted Flap and Snaps

 Tailboard, 12" Deep
 Body Trim, Aluminum Diamondplate, Pumpers
 Rubrail, with Reflective Stripe
 Vent, Compartment

DESCRIPTION

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Pumper / Commercial - 1001.001 01/19/10 ==

- |-- Electrical, 12 Volt Description
- |-- Warning Light System, NFPA
- |-- Warning Lights, Whelen Halogen Pkg, Commercial
 - |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
- |-- Reflectors NFPA/FMVSS Compliant
- |-- Lights, Clearance & Marker (7)
- |-- Lights, Side Running Board and Rear Step
- |-- Lights, Underbody
- |-- Light, Open Door Indicator, Flashing LED
- |-- Lights, Rear Deck Unity AG-S, 6"
- |-- Lights, Body Compartments
- |-- Lights, Midship Directional , 30'+ OAL
- |-- Light Bracket, License Plate
- |-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

- |-- Paint, Cab, Single Color 2-Door Cab
- |-- Paint, Chassis, Black
- |-- Paint, Body, Single Color
- |-- Finish, Compartment Interior, Zolatone Finish
- |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

- |-- Ladder, 14' Roof
- |-- Ladder, 24'-2 Section
- |-- Ladder, 10' Folding Attic

QUOTATION

American LaFrance

OHIO STS

\$214,119.00

American LaFrance 2 Dr Freightliner Rescue Pumper
Side Mount Hale QFLO 1250 Pump
Formed Aluminum Rescue Pumper Body

07/26/2011

Quote No: ALF AC03-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

== Chassis M2 2-D Pumper - 1001.001 01/19/10 ==

Certificate of Compliance, NFPA 1901

Chassis, Freightliner M2 106 2-Door

Chassis Surcharge (ALF)

Engine, Cummins ISC8.4-300HP / 800 LB/FT Torque

Standard Engine Protection W/O De-rate

Front Axle, AAC 12,000#, Package

Rear Axle, Single, AAC 24,000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control

Wheels, Standard Steel Disc

Grille, Painted Plastic Hood Mounted

Mirrors, Dual Bright Heated West Coast, LH/RH Remote

Steering Column, Fixed

"Select" 12VDC Power Supplies

Seat, Air Ride Driver's

Seat, Non-Suspension Officers seat

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder

Rollover Stability, Commercial Chassis

Seatbelt Warning System

Helmet Storage, Each Seating Position

Tire Inflation Indicators, for Chassis w/Single Rear Axle

== Bumper Package / M2 - 1001.001 01/19/10 ==

Bumper, Front, Painted

|-- Air Horns, Hood Mounted

DESCRIPTION

|-- Lanyard Control
 |-- Siren, Electronic w/100 Watt Speaker
 == Chassis Mods M2 - 1001.001 01/19/10 ==
 Light, Engine Compartment
 Battery "On" Light, Green
 Receptacle, 12V for Fire House Charging System
 |-- Air Charging Connector, LS
 Label, Fluid & Seating Capacity, Cab
 Label, Overall Travel Height, Cab
 Labels, Crew Area and Rear Body Step
 == Pump / Enclosure / Commercial - 1001.001 01/19/10 ==
 Testing, Third Party, Pumpers
 Pump, Hale Qflo Plus1250 GPM, Single Stage
 |-- Cooler, Engine, Custom or Commercial Chassis
 |-- Cooler, Pump, Bypass Tank Fill
 Pump Enclosure, S/M w/ Crosslays
 |-- Crosslay Cover, Vinyl
 |-- Running Boards, Non-Skid Aluminum Diamondplate
 |-- Gauges, Master, 4-1/2", 30-0-600 PSI
 |-- Gauge, Discharge 2-1/2" 30-0-600 Class 1
 |-- Elec Interface w/Fast Idle System
 |-- Piping, Class 1 HP Hose and Stainless Steel Pipe

 |-- Inlet, Left Panel 2-1/2"

 |-- Discharge, LS Panel (2) 2-1/2"
 |-- Discharge, RS Panel (2) 2-1/2"
 |-- Discharge, Crosslays, (2) 1-1/2"
 |-- Discharge, Deck Gun, 3" Centered
 |-- Deck Gun Outlet Capped, Customer Supplies Gun
 |-- Discharge, Rear of Body Left Side (1) 2-1/2"

 Tank to Pump Line, 3"
 Tank Fill, 2"
 == Body / Rescue Pumper - 1001.001 01/19/10 ==

 Water Tank 1000 Gallon, 20 Gallon Foam Cell
 |-- Warranty, Water/Foam Tank Lifetime
 |-- Gauge, Water Tank Level Indicator

 Subframe- Aluminum / Pumper Body
 |-- Body Construction / Material / Aluminum
 Body, 44/44 FHRD-L/FHRD-R w/ Internal Equip. Storage
 |-- Doors, Roll-Up 44/44

 |-- Ladder Bracket / Folding Tank / Hard Suction Hose
 |-- Ladder Pocket, Vertical Cmpt. Rear of Body RS
 |-- Ladder Folding, Storage, Vertical Rear Cmpt. RS
 |-- Pike Pole Tubes, (2) In Ladder Compartment
 |-- Hose Trays, Vertical Rear Cmpt. LS
 Hose Bed Dividers, Rescue Pumper (1)
 Hose Bed Cover, Red w/Weighted Flap and Snaps

 Tailboard, 12" Deep

DESCRIPTION

Body Trim, Aluminum Diamondplate, Pumpers
 Rubrail, with Reflective Stripe
 Vent, Compartment

Hand Rails, Body
 Steps, Folding (4)
 Tow Eyes, Rear
 Mud Flaps, Rear Axle (2)
 == Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Resc. Pumper / Commercial - 1001.001 01/19/

|-- Electrical, 12 Volt Description
 |-- Warning Light System, NFPA
 |-- Warning Lights, Whelen Halogen Pkg, Commercial
 |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
 |-- Reflectors NFPA/FMVSS Compliant
 |-- Lights, Clearance & Marker (7)
 |-- Lights, Side Running Board and Rear Step
 |-- Lights, Underbody
 |-- Light, Open Door Indicator, Flashing LED
 |-- Lights, Rear Deck Unity AG-S, 6"
 |-- Lights, Body Compartments
 |-- Lights, Midship Directional , 30'+ OAL
 |-- Light Bracket, License Plate
 |-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

|-- Paint, Cab, Single Color 2-Door Cab
 |-- Paint, Chassis, Black
 |-- Paint, Body, Single Color
 |-- Finish, Compartment Interior, Zolatone Finish
 |-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"
 |-- Striping, Reflective 4" NFPA
 |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

|-- Ladder, 14' Roof
 |-- Ladder, 24'-2 Section
 |-- Ladder, 10' Folding Attic

QUOTATION

American LaFrance

OHIO STS
\$220,091.00

American LaFrance 2 Dr Freightliner Rescue Pumper
Top Mount Hale QFLO 1250 Pump
Formed Aluminum Rescue Pumper Body

07/26/2011

Quote No: ALF AC04-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==
== Chassis M2 2-D Pumper - 1001.001 01/19/10 ==
Certificate of Compliance, NFPA 1901
Chassis, Freightliner M2 106 2-Door

Engine, Cummins ISC8.3-300HP

Standard Engine Protection W/O De-rate

Front Axle, AAC 12,000#, Package

Rear Axle, Single, AAC 24,000#, Package
|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control

Wheels, Standard Steel Disc

Grille, Painted Plastic Hood Mounted
Mirrors, Dual Painted West Coast

Steering Column, Fixed
"Select" 12VDC Power Supplies
Seat, Non-Suspended Driver's
Seat, Two-Man Mid-Back Bench

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder
Rollover Stability, Commercial Chassis
Seatbelt Warning System
Helmet Storage, Each Seating Position
Tire Inflation Indicators, for Chassis w/Single Rear Axle
== Bumper Package / M2 - 1001.001 01/19/10 ==
Bumper, Front, Painted
|-- Air Horns, Hood Mounted
|-- Lanyard Control

DESCRIPTION

|-- Siren, Electronic w/100 Watt Speaker
== Chassis Mods M2 - 1001.001 01/19/10 ==
Light, Engine Compartment
Battery "On" Light, Green
Receptacle, 12V for Fire House Charging System
|-- Air Charging Connector, LS
Label, Fluid & Seating Capacity, Cab
Label, Overall Travel Height, Cab
Labels, Crew Area and Rear Body Step
== Pump / Enclosure / Commercial - 1001.001 01/19/10 ==
Testing, Third Party, Pumpers
Pump, Hale Qflo Plus1250 GPM, Single Stage
|-- Cooler, Engine, Custom or Commercial Chassis
|-- Cooler, Pump, Bypass Tank Fill
Pump Enclosure, T/M w/ Crosslays
|-- Crosslay Cover, Vinyl
|-- Running Boards, Non-Skid Aluminum Diamondplate
|-- Gauges, Master, 4-1/2", 30-0-600 PSI
|-- Gauge, Discharge 2-1/2" 30-0-600 Class 1
|-- Elec Interface w/Fast Idle System
|-- Piping, Class 1 HP Hose and Stainless Steel Pipe

|-- Inlet, Left Panel 2-1/2"

|-- Discharge, LS Panel (2) 2-1/2"
|-- Discharge, RS Panel (2) 2-1/2"
|-- Discharge, Crosslays, (2) 1-1/2"
|-- Discharge, Deck Gun, 3" Centered
|-- Deck Gun Outlet Capped, Customer Supplies Gun
|-- Discharge, Rear of Body Left Side (1) 2-1/2"

Tank to Pump Line, 3"
Tank Fill, 2"
== Body / Rescue Pumper - 1001.001 01/19/10 ==

Water Tank 1000 Gallon, 20 Gallon Foam Cell
|-- Warranty, Water/Foam Tank Lifetime
|-- Gauge, Water Tank Level Indicator

Subframe- Aluminum / Pumper Body
|-- Body Construction / Material / Aluminum
Body, 44/44 FHRD-L/FHRD-R w/ Internal Equip. Storage
|-- Doors, Roll-Up 44/44

|-- Ladder Bracket / Folding Tank / Hard Suction Hose
|-- Ladder Pocket, Vertical Cmpt. Rear of Body RS
|-- Ladder Folding, Storage, Vertical Rear Cmpt. RS
|-- Pike Pole Tubes, (2) In Ladder Compartment
|-- Hose Trays, Vertical Rear Cmpt. LS
Hose Bed Dividers, Rescue Pumper (1)
Hose Bed Cover, Red w/Weighted Flap and Snaps

Tailboard, 12" Deep
Body Trim, Aluminum Diamondplate, Pumpers

DESCRIPTION

Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Resc. Pumper / Commercial - 1001.001 01/19/

|-- Electrical, 12 Volt Description
|-- Warning Light System, NFPA
|-- Warning Lights, Whelen Halogen Pkg, Commercial
|-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
|-- Reflectors NFPA/FMVSS Compliant
|-- Lights, Clearance & Marker (7)
|-- Lights, Side Running Board and Rear Step
|-- Lights, Underbody
|-- Light, Open Door Indicator, Flashing LED
|-- Lights, Rear Deck Unity AG-S, 6"
|-- Lights, Body Compartments
|-- Lights, Midship Directional , 30'+ OAL
|-- Light Bracket, License Plate
|-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

|-- Paint, Cab, Single Color 2-Door Cab
|-- Paint, Chassis, Black
|-- Paint, Body, Single Color
|-- Finish, Compartment Interior, Zolatone Finish
|-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"
|-- Striping, Reflective 4" NFPA
|-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

|-- Ladder, 14' Roof
|-- Ladder, 24'-2 Section
|-- Ladder, 10' Folding Attic

QUOTATION

American LaFrance

OHIO STS

\$294,221.00

American LaFrance Custom Pumper
Side Mount Hale QFLO 1250 Pump
Formed Aluminum Pumper Body

07/26/2011

Quote No: ALF AC05-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

== 07 Metropolitan Pumper for Liberty - 1001.001 01/19/10 =

Certificate of Compliance, NFPA 1901

Chassis, Metropolitan Custom Crew, Flat Roof

Engine, 2010 EPA Cummins ISC8.3 330HP

|-- Engine Brake, Cummins C-Brake , (1) Switch

Alternator, 270 Amp

Standard Engine Protection W/O De-rate

Front Axle, Meritor 18,000#, Package

Rear Axle, Single, Meritor 24,000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control

Wheels, Standard Steel Disc

Fenderette, Standard

Mirrors, Mekra, Black, 16" x 7" M2 Style

Steering Column, Tilt & Telescoping Adjustable

Air Conditioning Front and Rear

"Select" 12VDC Power Supplies

Seat, Air Ride Driver's

Seat, Non-Suspended High Back Officer's

Seats, Rear Facing SCBA, (2)

Seats, Forward Facing (2) ABTS SCBA, Rear Wall

SAFETY SYSTEMS, CUSTOM CHASSIS

Vehicle Data Recorder

Rollover Stability (Electronic Stability Control)

Seat Belt Warning System

Helmet Storage, Each Seating Position

DESCRIPTION

Tire Inflation Indicators, for Chassis w/Single Rear Axle

== Bumper Package / Custom - 1001.001 01/19/10 ==

Bumper, Front, Polished Stainless Steel

|-- Air Horns, Thru the Bumper Mtd. (2)

|-- Switch, Horn/Air Horn Selector, Cab Dash Mtd

|-- Siren, Electronic w/100 Watt Speaker

== Chassis Mods Custom - 1001.001 01/19/10 ==

Receptacle, 12V for Fire House Charging System

|-- Air Charging Connector, LS

Fuel Fill, Custom Chassis

Label, Fluid & Seating Capacity, Cab

Label, Overall Travel Height, Cab

Labels, Crew Area and Rear Body Step

== Pump / Enclosure / Custom - 1001.001 01/19/10 ==

Testing, Third Party, Pumpers

Pump, Hale Qflo Plus1250 GPM, Single Stage

|-- Cooler, Engine, Custom or Commercial Chassis

|-- Cooler, Pump, Bypass Tank Fill

Pump Enclosure, S/M w/ Crosslays

|-- Crosslay Cover, Vinyl

|-- Running Boards, Non-Skid Aluminum Diamondplate

|-- Gauges, Master, 4-1/2", 30-0-600 PSI

|-- Gauge, Discharge 2-1/2" 30-0-600 Class 1

|-- Elec Interface w/Fast Idle System

|-- Piping, Class 1 HP Hose and Stainless Steel Pipe

|-- Inlet, Left Panel 2-1/2"

|-- Discharge, LS Panel (2) 2-1/2"

|-- Discharge, RS Panel (2) 2-1/2"

|-- Discharge, Crosslays, (2) 1-1/2"

|-- Discharge, Deck Gun, 3" Centered

|-- Deck Gun Outlet Capped, Customer Supplies Gun

|-- Discharge, Rear of Body Left Side (1) 2-1/2"

Tank to Pump Line, 3"

Tank Fill, 2"

== Body / Pumper - 1001.001 01/19/10 ==

Water Tank 1000 Gallon, 20 Gallon Foam Cell

|-- Warranty, Water/Foam Tank Lifetime

|-- Gauge, Water Tank Level Indicator

Subframe- Aluminum / Pumper Body

|-- Body Construction / Material / Aluminum

Body, 35/35 FHRD-L / L-R w/ External Equip. Storage

|-- Doors, Roll-Up 35/35

|-- Ladder Brackets, Side Mtd, Above Cmpt.s RS

|-- Ladder Folding, Storage, Top of Cmpt.s RS

|-- Hose, Soft Suction, 6" NST x 15' Couplings

Hose Bed Divider, (1)

Hose Bed Cover, Red w/Weighted Flap and Snaps

DESCRIPTION

Tailboard, 12" Deep
 Body Trim, Aluminum Diamondplate, Pumpers
 Rubrail, with Reflective Stripe
 Vent, Compartment

Hand Rails, Body
 Steps, Folding (4)
 Tow Eyes, Rear
 Mud Flaps, Rear Axle (2)
 == Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Pumpers / Custom - 1001.001 01/19/10 ==

|-- Electrical, 12 Volt Description
 |-- Warning Light System, NFPA
 |-- Warning Lights, Liberty Pumper, Whelen Halo Pkg
 |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
 |-- Reflectors NFPA/FMVSS Compliant
 |-- Lights, Clearance & Marker (7)
 |-- Lights, Side Running Board and Rear Step
 |-- Lights, Underbody
 |-- Light, Open Door Indicator, Flashing LED
 |-- Lights, Rear Deck Unity AG-S, 6"
 |-- Lights, Body Compartments
 |-- Lights, Midship Directional , 30'+ OAL
 |-- Light Bracket, License Plate
 |-- Back-Up Alarm, Liberty

|-- Painting, Alm Body, Pumper/Rescue/Tanker Custom
 |-- Paint, Cab, Single Color 4-Door Cab (Liberty Standard Color)
 |-- Paint, Chassis, Black
 |-- Paint, Body, Single Color
 |-- Finish, Compartment Interior, Zolatone Finish
 |-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"
 |-- Striping, Reflective 4" NFPA
 |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

|-- Ladder, 14' Roof
 |-- Ladder, 24'-2 Section
 |-- Ladder, 10' Folding Attic

QUOTATION

American LaFrance

OHIO STS

\$300,098.00

American LaFrance Custom Top Mount Pumper
Top Mount Hale QFLO 1250 Pump
Formed Aluminum Pumper Body

07/26/2011

Quote No: ALF AC06-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

== 07 Metropolitan Pumper for Liberty - 1001.001 01/19/10 =

Certificate of Compliance, NFPA 1901

Chassis, Metropolitan Custom Crew, Flat Roof

Engine, 2010 EPA Cummins ISC8.3 330HP

|-- Engine Brake, Cummins C-Brake , (1) Switch

Alternator, 270 Amp

Standard Engine Protection W/O De-rate

Front Axle, Meritor 18,000#, Package

Rear Axle, Single, Meritor 24,000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control

Wheels, Standard Steel Disc

Fenderette, Standard

Mirrors, Mekra, Black, 16" x 7" M2 Style

Steering Column, Tilt & Telescoping Adjustable

Air Conditioning Front and Rear

"Select" 12VDC Power Supplies

Seat, Air Ride Driver's

Seat, Non-Suspended High Back Officer's

Seats, Rear Facing SCBA, (2)

Seats, Forward Facing (2) ABTS SCBA, Rear Wall

SAFETY SYSTEMS, CUSTOM CHASSIS

Vehicle Data Recorder

Rollover Stability (Electronic Stability Control)

Seat Belt Warning System

Helmet Storage, Each Seating Position

DESCRIPTION

Tire Inflation Indicators, for Chassis w/Single Rear Axle

== Bumper Package / Custom - 1001.001 01/19/10 ==

Bumper, Front, Polished Stainless Steel

|-- Air Horns, Thru the Bumper Mtd. (2)

|-- Switch, Horn/Air Horn Selector, Cab Dash Mtd

|-- Siren, Electronic w/100 Watt Speaker

== Chassis Mods Custom - 1001.001 01/19/10 ==

Receptacle, 12V for Fire House Charging System

|-- Air Charging Connector, LS

Fuel Fill, Custom Chassis

Label, Fluid & Seating Capacity, Cab

Label, Overall Travel Height, Cab

Labels, Crew Area and Rear Body Step

== Pump / Enclosure / Custom - 1001.001 01/19/10 ==

Testing, Third Party, Pumpers

Pump, Hale Qflo Plus1250 GPM, Single Stage

|-- Cooler, Engine, Custom or Commercial Chassis

|-- Cooler, Pump, Bypass Tank Fill

Pump Enclosure, T/M w/ Crosslays

|-- Crosslay Cover, Vinyl

|-- Running Boards, Non-Skid Aluminum Diamondplate

|-- Gauges, Master, 4-1/2", 30-0-600 PSI

|-- Gauge, Discharge 2-1/2" 30-0-600 Class 1

|-- Elec Interface w/Fast Idle System

|-- Piping, Class 1 HP Hose and Stainless Steel Pipe

|-- Inlet, Left Panel 2-1/2"

|-- Discharge, LS Panel (2) 2-1/2"

|-- Discharge, RS Panel (2) 2-1/2"

|-- Discharge, Crosslays, (2) 1-1/2"

|-- Discharge, Deck Gun, 3" Centered

|-- Deck Gun Outlet Capped, Customer Supplies Gun

|-- Discharge, Rear of Body Left Side (1) 2-1/2"

Tank to Pump Line, 3"

Tank Fill, 2"

== Body / Pumper - 1001.001 01/19/10 ==

Water Tank 1000 Gallon, 20 Gallon Foam Cell

|-- Warranty, Water/Foam Tank Lifetime

|-- Gauge, Water Tank Level Indicator

Subframe- Aluminum / Pumper Body

|-- Body Construction / Material / Aluminum

Body, 35/35 FHRD-L / L-R w/ External Equip. Storage

|-- Doors, Roll-Up 35/35

|-- Ladder Brackets, Side Mtd, Above Cmpt.s RS

|-- Ladder Folding, Storage, Top of Cmpt.s RS

|-- Hose, Soft Suction, 6" NST x 15' Couplings

Hose Bed Divider, (1)

Hose Bed Cover, Red w/Weighted Flap and Snaps

DESCRIPTION

Tailboard, 12" Deep
 Body Trim, Aluminum Diamondplate, Pumpers
 Rubrail, with Reflective Stripe
 Vent, Compartment

Hand Rails, Body
 Steps, Folding (4)
 Tow Eyes, Rear
 Mud Flaps, Rear Axle (2)
 == Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Pumpers / Custom - 1001.001 01/19/10 ==

|-- Electrical, 12 Volt Description
 |-- Warning Light System, NFPA
 |-- Warning Lights, Liberty Pumper, Whelen Halo Pkg
 |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
 |-- Reflectors NFPA/FMVSS Compliant
 |-- Lights, Clearance & Marker (7)
 |-- Lights, Side Running Board and Rear Step
 |-- Lights, Underbody
 |-- Light, Open Door Indicator, Flashing LED
 |-- Lights, Rear Deck Unity AG-S, 6"
 |-- Lights, Body Compartments
 |-- Lights, Midship Directional , 30'+ OAL
 |-- Light Bracket, License Plate
 |-- Back-Up Alarm, Liberty

|-- Painting, Alm Body, Pumper/Rescue/Tanker Custom
 |-- Paint, Cab, Single Color 4-Door Cab (Liberty Standard Color)
 |-- Paint, Chassis, Black
 |-- Paint, Body, Single Color
 |-- Finish, Compartment Interior, Zolatone Finish
 |-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"
 |-- Striping, Reflective 4" NFPA
 |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

|-- Ladder, 14' Roof
 |-- Ladder, 24'-2 Section
 |-- Ladder, 10' Folding Attic

QUOTATION

American LaFrance

OHIO STS
\$297,735.00

American LaFrance Custom Rescue Pumper
Side Mount Hale QFLO 1250 Pump
Formed Aluminum Rescue Body

07/26/2011

Quote No: ALF AC07-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

== 07 Metropolitan Pumper for Liberty - 1001.001 01/19/10 =

Certificate of Compliance, NFPA 1901

Chassis, Metropolitan Custom Crew, Flat Roof

Engine, 2010 EPA Cummins ISC8.3 - 330

|-- Engine Brake, Cummins C-Brake , (1) Switch

Alternator, 270 Amp

Standard Engine Protection W/O De-rate

Front Axle, Meritor 18,000#, Package

Rear Axle, Single, Meritor 24,000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Out Traction Control

Wheels, Standard Steel Disc

Fenderette, Standard

Mirrors, Mekra, Black, 16" x 7" M2 Style

Steering Column, Tilt & Telescoping Adjustable

"Select" 12VDC Power Supplies

Seat, Air Ride Driver's

Seat, Non-Suspended High Back Officer's

Seats, Rear Facing SCBA, (2)

Seats, Forward Facing (2) ABTS SCBA, Rear Wall

SAFETY SYSTEMS, CUSTOM CHASSIS

Vehicle Data Recorder

Rollover Stability (Electronic Stability Control)

Seat Belt Warning System

Helmet Storage, Each Seating Position

Tire Inflation Indicators, for Chassis w/Single Rear Axle

DESCRIPTION

== Bumper Package / Custom - 1001.001 01/19/10 ==

Bumper, Front, Polished Stainless Steel

- |-- Air Horns, Thru the Bumper Mtd. (2)
- |-- Switch, Horn/Air Horn Selector, Cab Dash Mtd
- |-- Siren, Electronic w/100 Watt Speaker

== Chassis Mods Custom - 1001.001 01/19/10 ==

Receptacle, 12V for Fire House Charging System

- |-- Air Charging Connector, LS

Fuel Fill, Custom Chassis

Label, Fluid & Seating Capacity, Cab

Label, Overall Travel Height, Cab

Labels, Crew Area and Rear Body Step

== Pump / Enclosure / Custom - 1001.001 01/19/10 ==

Testing, Third Party, Pumpers

Pump, Hale Qflo Plus1250 GPM, Single Stage

- |-- Cooler, Engine, Custom or Commercial Chassis
- |-- Cooler, Pump, Bypass Tank Fill

Pump Enclosure, S/M w/ Crosslays

- |-- Crosslay Cover, Vinyl
- |-- Running Boards, Non-Skid Aluminum Diamondplate
- |-- Gauges, Master, 4-1/2", 30-0-600 PSI
- |-- Gauge, Discharge 2-1/2" 30-0-600 Class 1
- |-- Elec Interface w/Fast Idle System
- |-- Piping, Class 1 HP Hose and Stainless Steel Pipe

- |-- Inlet, Left Panel 2-1/2"

- |-- Discharge, LS Panel (2) 2-1/2"
- |-- Discharge, RS Panel (2) 2-1/2"
- |-- Discharge, Crosslays, (2) 1-1/2"
- |-- Discharge, Deck Gun, 3" Centered
- |-- Deck Gun Outlet Capped, Customer Supplies Gun
- |-- Discharge, Rear of Body Left Side (1) 2-1/2"

Tank to Pump Line, 3"

Tank Fill, 2"

== Body / Rescue Pumper - 1001.001 01/19/10 ==

Water Tank 1000 Gallon, 20 Gallon Foam Cell

- |-- Warranty, Water/Foam Tank Lifetime
- |-- Gauge, Water Tank Level Indicator

Subframe- Aluminum / Pumper Body

- |-- Body Construction / Material / Aluminum

Body, 44/44 FHRD-L/FHRD-R w/ Internal Equip. Storage

- |-- Doors, Roll-Up 44/44

- |-- Ladder Bracket / Folding Tank / Hard Suction Hose
- |-- Ladder Pocket, Vertical Cmpt. Rear of Body RS
- |-- Ladder Folding, Storage, Vertical Rear Cmpt. RS
- |-- Pike Pole Tubes, (2) In Ladder Compartment
- |-- Hose Trays, Vertical Rear Cmpt. LS

Hose Bed Dividers, Rescue Pumper (1)

Hose Bed Cover, Red w/Weighted Flap and Snaps

DESCRIPTION

Tailboard, 12" Deep
 Body Trim, Aluminum Diamondplate, Pumpers
 Rubrail, with Reflective Stripe
 Vent, Compartment

Hand Rails, Body
 Steps, Folding (4)
 Tow Eyes, Rear
 Mud Flaps, Rear Axle (2)
 == Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Resc. Pumper / Custom - 1001.001 01/19/10 =

|-- Electrical, 12 Volt Description
 |-- Warning Light System, NFPA
 |-- Warning Lights, Liberty Pumper, Whelen Halo Pkg
 |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
 |-- Reflectors NFPA/FMVSS Compliant
 |-- Lights, Clearance & Marker (7)
 |-- Lights, Side Running Board and Rear Step
 |-- Lights, Underbody
 |-- Light, Open Door Indicator, Flashing LED
 |-- Lights, Rear Deck Unity AG-S, 6"
 |-- Lights, Body Compartments
 |-- Lights, Midship Directional , 30'+ OAL
 |-- Light Bracket, License Plate
 |-- Back-Up Alarm, Liberty

|-- Painting, Alm Body, Pumper/Rescue/Tanker Custom
 |-- Paint, Cab, Single Color 4-Door Cab (Liberty Standard Color)
 |-- Paint, Chassis, Black
 |-- Paint, Body, Single Color
 |-- Finish, Compartment Interior, Zolatone Finish
 |-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"
 |-- Striping, Reflective 4" NFPA
 |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

|-- Ladder, 14' Roof
 |-- Ladder, 24'-2 Section
 |-- Ladder, 10' Folding Attic

QUOTATION

American LaFrance

OHIO STS

\$303,086.00

American LaFrance Custom Rescue Pumper
Top Mount Hale QFLO 1250 Pump
Formed Aluminum Rescue Body

07/26/2011

Quote No: ALF AC08-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

== 07 Metropolitan Pumper for Liberty - 1001.001 01/19/10 =

Certificate of Compliance, NFPA 1901

Chassis, Metropolitan Custom Crew, Flat Roof

Engine, 2010 EPA Cummins ISC8.3 - 330

|-- Engine Brake, Cummins C-Brake , (1) Switch

Alternator, 270 Amp

Standard Engine Protection W/O De-rate

Front Axle, Meritor 18,000#, Package

Rear Axle, Single, Meritor 24,000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Out Traction Control

Wheels, Standard Steel Disc

Fenderette, Standard

Mirrors, Mekra, Black, 16" x 7" M2 Style

Steering Column, Tilt & Telescoping Adjustable

"Select" 12VDC Power Supplies

Seat, Air Ride Driver's

Seat, Non-Suspended High Back Officer's

Seats, Rear Facing SCBA, (2)

Seats, Forward Facing (2) ABTS SCBA, Rear Wall

SAFETY SYSTEMS, CUSTOM CHASSIS

Vehicle Data Recorder

Rollover Stability (Electronic Stability Control)

Seat Belt Warning System

Helmet Storage, Each Seating Position

Tire Inflation Indicators, for Chassis w/Single Rear Axle

DESCRIPTION

== Bumper Package / Custom - 1001.001 01/19/10 ==

Bumper, Front, Polished Stainless Steel

|-- Air Horns, Thru the Bumper Mtd. (2)

|-- Switch, Horn/Air Horn Selector, Cab Dash Mtd

|-- Siren, Electronic w/100 Watt Speaker

== Chassis Mods Custom - 1001.001 01/19/10 ==

Receptacle, 12V for Fire House Charging System

|-- Air Charging Connector, LS

Fuel Fill, Custom Chassis

Label, Fluid & Seating Capacity, Cab

Label, Overall Travel Height, Cab

Labels, Crew Area and Rear Body Step

== Pump / Enclosure / Custom - 1001.001 01/19/10 ==

Testing, Third Party, Pumpers

Pump, Hale Qflo Plus1250 GPM, Single Stage

|-- Cooler, Engine, Custom or Commercial Chassis

|-- Cooler, Pump, Bypass Tank Fill

Pump Enclosure, T/M w/ Crosslays

|-- Crosslay Cover, Vinyl

|-- Running Boards, Non-Skid Aluminum Diamondplate

|-- Gauges, Master, 4-1/2", 30-0-600 PSI

|-- Gauge, Discharge 2-1/2" 30-0-600 Class 1

|-- Elec Interface w/Fast Idle System

|-- Piping, Class 1 HP Hose and Stainless Steel Pipe

|-- Inlet, Left Panel 2-1/2"

|-- Discharge, LS Panel (2) 2-1/2"

|-- Discharge, RS Panel (2) 2-1/2"

|-- Discharge, Crosslays, (2) 1-1/2"

|-- Discharge, Deck Gun, 3" Centered

|-- Deck Gun Outlet Capped, Customer Supplies Gun

|-- Discharge, Rear of Body Left Side (1) 2-1/2"

Tank to Pump Line, 3"

Tank Fill, 2"

== Body / Rescue Pumper - 1001.001 01/19/10 ==

Water Tank 1000 Gallon, 20 Gallon Foam Cell

|-- Warranty, Water/Foam Tank Lifetime

|-- Gauge, Water Tank Level Indicator

Subframe- Aluminum / Pumper Body

|-- Body Construction / Material / Aluminum

Body, 44/44 FHRD-L/FHRD-R w/ Internal Equip. Storage

|-- Doors, Roll-Up 44/44

|-- Ladder Bracket / Folding Tank / Hard Suction Hose

|-- Ladder Pocket, Vertical Cmpt. Rear of Body RS

|-- Ladder Folding, Storage, Vertical Rear Cmpt. RS

|-- Pike Pole Tubes, (2) In Ladder Compartment

|-- Hose Trays, Vertical Rear Cmpt. LS

Hose Bed Dividers, Rescue Pumper (1)

Hose Bed Cover, Red w/Weighted Flap and Snaps

DESCRIPTION

Tailboard, 12" Deep
 Body Trim, Aluminum Diamondplate, Pumpers
 Rubrail, with Reflective Stripe
 Vent, Compartment

Hand Rails, Body
 Steps, Folding (4)
 Tow Eyes, Rear
 Mud Flaps, Rear Axle (2)
 == Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Resc. Pumper / Custom - 1001.001 01/19/10 =

|-- Electrical, 12 Volt Description
 |-- Warning Light System, NFPA
 |-- Warning Lights, Liberty Pumper, Whelen Halo Pkg
 |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
 |-- Reflectors NFPA/FMVSS Compliant
 |-- Lights, Clearance & Marker (7)
 |-- Lights, Side Running Board and Rear Step
 |-- Lights, Underbody
 |-- Light, Open Door Indicator, Flashing LED
 |-- Lights, Rear Deck Unity AG-S, 6"
 |-- Lights, Body Compartments
 |-- Lights, Midship Directional , 30'+ OAL
 |-- Light Bracket, License Plate
 |-- Back-Up Alarm, Liberty

|-- Painting, Alm Body, Pumper/Rescue/Tanker Custom
 |-- Paint, Cab, Single Color 4-Door Cab (Liberty Standard Color)
 |-- Paint, Chassis, Black
 |-- Paint, Body, Single Color
 |-- Finish, Compartment Interior, Zolatone Finish
 |-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"
 |-- Striping, Reflective 4" NFPA
 |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

|-- Ladder, 14' Roof
 |-- Ladder, 24'-2 Section
 |-- Ladder, 10' Folding Attic

QUOTATION

American LaFrance

OHIO STS

\$220,319.00

American LaFrance 2 Door Navistar Pumper
Side Mount Hale QFLO 1250 Pump
Formed Aluminum Pumper Body

07/26/2011

Quote No: ALF AC09-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

Certificate of Compliance, NFPA 1901

Chassis, Navistar 2 Door DuraStar, 4400 Series

Engine, MaxxForce DT 300HP

Standard Engine Protection W/O De-rate

Front Axle, 12,000#, Package

Rear Axle, Single, 23000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 68 MPH Maximum

Dust Shields, Single Axle, Front and Rear Brakes

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Painted Plastic Hood Mounted

Mirrors, Dual Bright Heated West Coast, LH/RH Remote

Steering Column, Tilt & Telescoping Adjustable

Daytime Running Lights

Power Supply 12VDC (1)

Seat, Air Ride Driver's

Seat, Non-Suspended High Back Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder

Rollover Stability, Commercial Chassis

Seatbelt Warning System

Helmet Storage, Each Seating Position

Tire Inflation Indicators, for Chassis w/Single Rear Axle

== Bumper Package / M2 - 1001.001 01/19/10 ==

Bumper, Front, Chrome

|-- Air Horns, Hood Mounted

DESCRIPTION

|-- Switches, Air Horn (1) Driver / (1) Officer
 |-- Siren, Electronic w/100 Watt Speaker
 == Chassis Mods M2 - 1001.001 01/19/10 ==
 Light, Engine Compartment
 Battery "On" Light, Green
 Receptacle, 12V for Fire House Charging System
 |-- Air Charging Connector, LS
 Label, Fluid & Seating Capacity, Cab
 Label, Overall Travel Height, Cab
 Labels, Crew Area and Rear Body Step
 == Pump / Enclosure / Commercial - 1001.001 01/19/10 ==
 Testing, Third Party, Pumpers
 Pump, Hale Qflo Plus1250 GPM, Single Stage
 |-- Cooler, Engine, Custom or Commercial Chassis
 |-- Cooler, Pump, Bypass Tank Fill
 Pump Enclosure, S/M w/ Crosslays
 |-- Crosslay Cover, Vinyl
 |-- Running Boards, Non-Skid Aluminum Diamondplate
 |-- Gauges, Master, 4-1/2", 30-0-600 PSI
 |-- Gauge, Discharge 2-1/2" 30-0-600 Class 1
 |-- Elec Interface w/Fast Idle System
 |-- Piping, Class 1 HP Hose and Stainless Steel Pipe

 |-- Inlet, Left Panel 2-1/2"

 |-- Discharge, LS Panel (2) 2-1/2"
 |-- Discharge, RS Panel (2) 2-1/2"
 |-- Discharge, Crosslays, (2) 1-1/2"
 |-- Discharge, Deck Gun, 3" Centered
 |-- Deck Gun Outlet Capped, Customer Supplies Gun
 |-- Discharge, Rear of Body Left Side (1) 2-1/2"

 Tank to Pump Line, 3"
 Tank Fill, 2"
 == Body / Pumper - 1001.001 01/19/10 ==

 Water Tank 1000 Gallon, 20 Gallon Foam Cell
 |-- Warranty, Water/Foam Tank Lifetime
 |-- Gauge, Water Tank Level Indicator

 Subframe- Aluminum / Pumper Body
 |-- Body Construction / Material / Aluminum
 Body, 35/35 FHRD-L / L-R w/ External Equip. Storage
 |-- Doors, Roll-Up 35/35

 |-- Ladder Brackets, Side Mtd, Above Cmpt.s RS
 |-- Ladder Folding, Storage, Top of Cmpt.s RS
 |-- Hose, Soft Suction, 6" NST x 15' Couplings
 Hose Bed Divider, (1)
 Hose Bed Cover, Red w/Weighted Flap and Snaps

 Tailboard, 12" Deep
 Body Trim, Aluminum Diamondplate, Pumpers
 Rubrail, with Reflective Stripe

DESCRIPTION

Vent, Compartment

Hand Rails, Body

Steps, Folding (4)

Tow Eyes, Rear

Mud Flaps, Rear Axle (2)

== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Pumper / Commercial - 1001.001 01/19/10 ==

- |-- Electrical, 12 Volt Description
- |-- Warning Light System, NFPA
- |-- Warning Lights, Whelen Halogen Pkg, Commercial
 - |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
- |-- Reflectors NFPA/FMVSS Compliant
- |-- Lights, Clearance & Marker (7)
- |-- Lights, Side Running Board and Rear Step
- |-- Lights, Underbody
- |-- Light, Open Door Indicator, Flashing LED
- |-- Lights, Rear Deck Unity AG-S, 6"
- |-- Lights, Body Compartments
- |-- Lights, Midship Directional , 30'+ OAL
- |-- Light Bracket, License Plate
- |-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

- |-- Paint, Cab, Single Color 2-Door Cab
- |-- Paint, Chassis, Black
- |-- Paint, Body, Single Color
- |-- Finish, Compartment Interior, Zolatone Finish
- |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

- |-- Ladder, 14' Roof
- |-- Ladder, 24'-2 Section
- |-- Ladder, 10' Folding Attic

QUOTATION

American LaFrance

OHIO STS

\$226,197.00

American LaFrance 2 Door Navistar Pumper
Top Mount Hale QFLO 1250 Pump
Formed Aluminum Pumper Body

07/26/2011

Quote No: ALF AC10-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

Certificate of Compliance, NFPA 1901

Chassis, Navistar 2 Door DuraStar, 4400 Series

Engine, MaxxForce DT 300HP

Standard Engine Protection W/O De-rate

Front Axle, AAC 12,000#, Package

Rear Axle, Single, 23,000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 68 MPH Maximum

Dust Shields, Single Axle, Front and Rear Brakes

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Chromed Plastic Hood Mounted

Mirrors, Dual Bright Heated West Coast, LH/RH Remote

Steering Column, Tilt & Telescoping Adjustable

Daytime Running Lights

Power Supply 12VDC (1)

Seat, Non-Suspended Driver's

Seat, Non-Suspended High Back Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder

Rollover Stability, Commercial Chassis

Seatbelt Warning System

Helmet Storage, Each Seating Position

Tire Inflation Indicators, for Chassis w/Single Rear Axle

== Bumper Package / M2 - 1001.001 01/19/10 ==

Bumper, Front, Chrome

|-- Air Horns, Hood Mounted

DESCRIPTION

|-- Switches, Air Horn (1) Driver / (1) Officer
 |-- Siren, Electronic w/100 Watt Speaker
 == Chassis Mods M2 - 1001.001 01/19/10 ==
 Light, Engine Compartment
 Battery "On" Light, Green
 Receptacle, 12V for Fire House Charging System
 |-- Air Charging Connector, LS
 Label, Fluid & Seating Capacity, Cab
 Label, Overall Travel Height, Cab
 Labels, Crew Area and Rear Body Step
 == Pump / Enclosure / Commercial - 1001.001 01/19/10 ==
 Testing, Third Party, Pumpers
 Pump, Hale Qflo Plus1250 GPM, Single Stage
 |-- Cooler, Engine, Custom or Commercial Chassis
 |-- Cooler, Pump, Bypass Tank Fill
 Pump Enclosure, T/M w/ Crosslays
 |-- Crosslay Cover, Vinyl
 |-- Running Boards, Non-Skid Aluminum Diamondplate
 |-- Gauges, Master, 4-1/2", 30-0-600 PSI
 |-- Gauge, Discharge 2-1/2" 30-0-600 Class 1
 |-- Elec Interface w/Fast Idle System
 |-- Piping, Class 1 HP Hose and Stainless Steel Pipe

 |-- Inlet, Left Panel 2-1/2"

 |-- Discharge, LS Panel (2) 2-1/2"
 |-- Discharge, RS Panel (2) 2-1/2"
 |-- Discharge, Crosslays, (2) 1-1/2"
 |-- Discharge, Deck Gun, 3" Centered
 |-- Deck Gun Outlet Capped, Customer Supplies Gun
 |-- Discharge, Rear of Body Left Side (1) 2-1/2"

 Tank to Pump Line, 3"
 Tank Fill, 2"
 == Body / Pumper - 1001.001 01/19/10 ==

 Water Tank 1000 Gallon, 20 Gallon Foam Cell
 |-- Warranty, Water/Foam Tank Lifetime
 |-- Gauge, Water Tank Level Indicator

 Subframe- Aluminum / Pumper Body
 |-- Body Construction / Material / Aluminum
 Body, 35/35 FHRD-L / L-R w/ External Equip. Storage
 |-- Doors, Roll-Up 35/35

 |-- Ladder Brackets, Side Mtd, Above Cmpt.s RS
 |-- Ladder Folding, Storage, Top of Cmpt.s RS
 |-- Hose, Soft Suction, 6" NST x 15' Couplings
 Hose Bed Divider, (1)
 Hose Bed Cover, Red w/Weighted Flap and Snaps

 Tailboard, 12" Deep
 Body Trim, Aluminum Diamondplate, Pumpers
 Rubrail, with Reflective Stripe

DESCRIPTION

Vent, Compartment

Hand Rails, Body

Steps, Folding (4)

Tow Eyes, Rear

Mud Flaps, Rear Axle (2)

== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Pumper / Commercial - 1001.001 01/19/10 ==

- |-- Electrical, 12 Volt Description
- |-- Warning Light System, NFPA
- |-- Warning Lights, Whelen Halogen Pkg, Commercial
 - |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
- |-- Reflectors NFPA/FMVSS Compliant
- |-- Lights, Clearance & Marker (7)
- |-- Lights, Side Running Board and Rear Step
- |-- Lights, Underbody
- |-- Light, Open Door Indicator, Flashing LED
- |-- Lights, Rear Deck Unity AG-S, 6"
- |-- Lights, Body Compartments
- |-- Lights, Midship Directional , 30'+ OAL
- |-- Light Bracket, License Plate
- |-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

- |-- Paint, Cab, Single Color 2-Door Cab
- |-- Paint, Chassis, Black
- |-- Paint, Body, Single Color
- |-- Finish, Compartment Interior, Zolatone Finish
- |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

- |-- Ladder, 14' Roof
- |-- Ladder, 24'-2 Section
- |-- Ladder, 10' Folding Attic

QUOTATION

American LaFrance

OHIO STS
\$223,832.00

American LaFrance 2 Dr Navistar Rescue Pumper
Side Mount Hale QFLO 1250 Pump
Formed Aluminum Rescue Pumper Body

07/26/2011

Quote No: ALF AC11-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

Certificate of Compliance, NFPA 1901

Chassis, Navistar 2 Door DuraStar, 4400 Series

Chassis Surcharge (ALF)

Engine, MaxForce DT 300HP

Standard Engine Protection W/O De-rate

Front Axle, AAC 12,000#, Package

Rear Axle, Single, 26,000#, Package

|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

Dust Shields, Single Axle, Front and Rear Brakes

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Chromed Plastic Hood Mounted

Mirrors, Dual Bright Heated West Coast, LH/RH Remote

Steering Column, Tilt & Telescoping Adjustable

Daytime Running Lights

Power Supply 12VDC (1)

Seat, Air Ride Driver's

Seat, Non-Suspension Officers seat

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder

Rollover Stability, Commercial Chassis

Seatbelt Warning System

Helmet Storage, Each Seating Position

Tire Inflation Indicators, for Chassis w/Single Rear Axle

== Bumper Package / M2 - 1001.001 01/19/10 ==

Bumper, Front, Chrome

DESCRIPTION

|-- Air Horns, Hood Mounted
|-- Switches, Air Horn (1) Driver / (1) Officer
|-- Siren, Electronic w/100 Watt Speaker
== Chassis Mods M2 - 1001.001 01/19/10 ==
Light, Engine Compartment
Battery "On" Light, Green
Receptacle, 12V for Fire House Charging System
|-- Air Charging Connector, LS
Label, Fluid & Seating Capacity, Cab
Label, Overall Travel Height, Cab
Labels, Crew Area and Rear Body Step
== Pump / Enclosure / Commercial - 1001.001 01/19/10 ==
Testing, Third Party, Pumpers
Pump, Hale Qflo Plus1250 GPM, Single Stage
|-- Cooler, Engine, Custom or Commercial Chassis
|-- Cooler, Pump, Bypass Tank Fill
Pump Enclosure, S/M w/ Crosslays
|-- Crosslay Cover, Vinyl
|-- Running Boards, Non-Skid Aluminum Diamondplate
|-- Gauges, Master, 4-1/2", 30-0-600 PSI
|-- Gauge, Discharge 2-1/2" 30-0-600 Class 1
|-- Elec Interface w/Fast Idle System
|-- Piping, Class 1 HP Hose and Stainless Steel Pipe

|-- Inlet, Left Panel 2-1/2"

|-- Discharge, LS Panel (2) 2-1/2"
|-- Discharge, RS Panel (2) 2-1/2"
|-- Discharge, Crosslays, (2) 1-1/2"
|-- Discharge, Deck Gun, 3" Centered
|-- Deck Gun Outlet Capped, Customer Supplies Gun
|-- Discharge, Rear of Body Left Side (1) 2-1/2"

Tank to Pump Line, 3"
Tank Fill, 2"
== Body / Rescue Pumper - 1001.001 01/19/10 ==

Water Tank 1000 Gallon, 20 Gallon Foam Cell
|-- Warranty, Water/Foam Tank Lifetime
|-- Gauge, Water Tank Level Indicator

Subframe- Aluminum / Pumper Body
|-- Body Construction / Material / Aluminum
Body, 44/44 FHRD-L/FHRD-R w/ Internal Equip. Storage
|-- Doors, Roll-Up 44/44

|-- Ladder Bracket / Folding Tank / Hard Suction Hose
|-- Ladder Pocket, Vertical Cmpt. Rear of Body RS
|-- Ladder Folding, Storage, Vertical Rear Cmpt. RS
|-- Pike Pole Tubes, (2) In Ladder Compartment
|-- Hose Trays, Vertical Rear Cmpt. LS
Hose Bed Dividers, Rescue Pumper (1)
Hose Bed Cover, Red w/Weighted Flap and Snaps

DESCRIPTION

Tailboard, 12" Deep

Body Trim, Aluminum Diamondplate, Pumpers

Rubrail, with Reflective Stripe

Vent, Compartment

Hand Rails, Body

Steps, Folding (4)

Tow Eyes, Rear

Mud Flaps, Rear Axle (2)

== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Resc. Pumper / Commercial - 1001.001 01/19/

- |-- Electrical, 12 Volt Description
- |-- Warning Light System, NFPA
- |-- Warning Lights, Whelen Halogen Pkg, Commercial
 - |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
- |-- Reflectors NFPA/FMVSS Compliant
- |-- Lights, Clearance & Marker (7)
- |-- Lights, Side Running Board and Rear Step
- |-- Lights, Underbody
- |-- Light, Open Door Indicator, Flashing LED
- |-- Lights, Rear Deck Unity AG-S, 6"
- |-- Lights, Body Compartments
- |-- Lights, Midship Directional , 30'+ OAL
- |-- Light Bracket, License Plate
- |-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

- |-- Paint, Cab, Single Color 2-Door Cab
- |-- Paint, Chassis, Black
- |-- Paint, Body, Single Color
- |-- Finish, Compartment Interior, Zolatone Finish
- |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

- |-- Ladder, 14' Roof
- |-- Ladder, 24'-2 Section
- |-- Ladder, 10' Folding Attic

QUOTATION

American LaFrance

OHIO STS

\$228,932.00

American LaFrance 2 Dr Navistar Rescue Pumper
Top Mount Hale QFLO 1250 Pump
Formed Aluminum Rescue Pumper Body

07/26/2011

Quote No: ALF AC12-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

Certificate of Compliance, NFPA 1901

Chassis, Navistar 2 Door DuraStar, 4400 Series

MaxxForce DT 300HP

Standard Engine Protection W/O De-rate

Front Axle, 12,000#, Package

Rear Axle, Single, 26,000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 68 MPH Maximum

Dust Shields, Single Axle, Front and Rear Brakes

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Chromed Plastic Hood Mounted

Mirrors, Dual Bright Heated West Coast, LH/RH Remote

Steering Column, Tilt & Telescoping Adjustable

Daytime Running Lights

Power Supply 12VDC (1)

Seat, Non-Suspended Driver's

Seat, Non-Suspension Officers

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder

Rollover Stability, Commercial Chassis

Seatbelt Warning System

Helmet Storage, Each Seating Position

Tire Inflation Indicators, for Chassis w/Single Rear Axle

== Bumper Package / M2 - 1001.001 01/19/10 ==

Bumper, Front, Chrome

|-- Air Horns, Hood Mounted

DESCRIPTION

|-- Switches, Air Horn (1) Driver / (1) Officer
 |-- Siren, Electronic w/100 Watt Speaker
 == Chassis Mods M2 - 1001.001 01/19/10 ==
 Light, Engine Compartment
 Battery "On" Light, Green
 Receptacle, 12V for Fire House Charging System
 |-- Air Charging Connector, LS
 Label, Fluid & Seating Capacity, Cab
 Label, Overall Travel Height, Cab
 Labels, Crew Area and Rear Body Step
 == Pump / Enclosure / Commercial - 1001.001 01/19/10 ==
 Testing, Third Party, Pumpers
 Pump, Hale Qflo Plus1250 GPM, Single Stage
 |-- Cooler, Engine, Custom or Commercial Chassis
 |-- Cooler, Pump, Bypass Tank Fill
 Pump Enclosure, T/M w/ Crosslays
 |-- Crosslay Cover, Vinyl
 |-- Running Boards, Non-Skid Aluminum Diamondplate
 |-- Gauges, Master, 4-1/2", 30-0-600 PSI
 |-- Gauge, Discharge 2-1/2" 30-0-600 Class 1
 |-- Elec Interface w/Fast Idle System
 |-- Piping, Class 1 HP Hose and Stainless Steel Pipe

 |-- Inlet, Left Panel 2-1/2"

 |-- Discharge, LS Panel (2) 2-1/2"
 |-- Discharge, RS Panel (2) 2-1/2"
 |-- Discharge, Crosslays, (2) 1-1/2"
 |-- Discharge, Deck Gun, 3" Centered
 |-- Deck Gun Outlet Capped, Customer Supplies Gun
 |-- Discharge, Rear of Body Left Side (1) 2-1/2"

 Tank to Pump Line, 3"
 Tank Fill, 2"
 == Body / Rescue Pumper - 1001.001 01/19/10 ==

 Water Tank 1000 Gallon, 20 Gallon Foam Cell
 |-- Warranty, Water/Foam Tank Lifetime
 |-- Gauge, Water Tank Level Indicator

 Subframe- Aluminum / Pumper Body
 |-- Body Construction / Material / Aluminum
 Body, 44/44 FHRD-L/FHRD-R w/ Internal Equip. Storage
 |-- Doors, Roll-Up 44/44

 |-- Ladder Bracket / Folding Tank / Hard Suction Hose
 |-- Ladder Pocket, Vertical Cmpt. Rear of Body RS
 |-- Ladder Folding, Storage, Vertical Rear Cmpt. RS
 |-- Pike Pole Tubes, (2) In Ladder Compartment
 |-- Hose Trays, Vertical Rear Cmpt. LS
 Hose Bed Dividers, Rescue Pumper (1)
 Hose Bed Cover, Red w/Weighted Flap and Snaps

 Tailboard, 12" Deep

DESCRIPTION

Body Trim, Aluminum Diamondplate, Pumpers
 Rubrail, with Reflective Stripe
 Vent, Compartment

Hand Rails, Body
 Steps, Folding (4)
 Tow Eyes, Rear
 Mud Flaps, Rear Axle (2)
 == Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Resc. Pumper / Commercial - 1001.001 01/19/

|-- Electrical, 12 Volt Description
 |-- Warning Light System, NFPA
 |-- Warning Lights, Whelen Halogen Pkg, Commercial
 |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
 |-- Reflectors NFPA/FMVSS Compliant
 |-- Lights, Clearance & Marker (7)
 |-- Lights, Side Running Board and Rear Step
 |-- Lights, Underbody
 |-- Light, Open Door Indicator, Flashing LED
 |-- Lights, Rear Deck Unity AG-S, 6"
 |-- Lights, Body Compartments
 |-- Lights, Midship Directional , 30'+ OAL
 |-- Light Bracket, License Plate
 |-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

|-- Paint, Cab, Single Color 2-Door Cab
 |-- Paint, Chassis, Black
 |-- Paint, Body, Single Color
 |-- Finish, Compartment Interior, Zolatone Finish
 |-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"
 |-- Striping, Reflective 4" NFPA
 |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

|-- Ladder, 14' Roof
 |-- Ladder, 24'-2 Section
 |-- Ladder, 10' Folding Attic

Quotation

American LaFrance

OHIO STS	American LaFrance 2 Door Flatbed Brush Truck
\$78,728.00	300 Gallon Skid Unit w/ Hale HPXB200 Pump Formed Aluminum Tread Plate Body

Quote No:

07/25/11

ALF AB01

Page 1

Description
Certificate of Compliance, NFPA 1906
CHASSIS
Chassis Ford F-450 Standard Cab
Engine, 6.8 Liter EFI V-10 362HP
Transmission, 5 Speed Automatic
GVW, 16,500#
Wheel Base, 141"
CA 60"
Front Axle, 7000#
Rear Axle, 12,000#
Rear Axle Ratio, 4.10 Ltd Slip
Wheels, Painted Steel
Tires, 225 Max Trac 19.5
Fuel Tank, 40 Gallon Aft Axle
Front Bumper, Chrome

07/25/11

ALF AB01

Page 2

Description
Brake Controller
XL Decore Package
Seat, 40/20/40 Bench
Rear Bumper, Steel ICC
Mud Flaps, Rear Axle (2)
Body
Standard Aluminum Flatbed Body formed of Aluminum Tread Plate
Sub-frame, Extruded Aluminum
Standard Curb Side Compartment formed of Aluminum Tread Plate, Vented
Standard Driver's Side Compartment formed of Aluminum Tread Plate, Vented
Standard Driver's Side Hose Lay formed of Aluminum Tread Plate
Hose Lay Cover, Canvass
Doors, Swing Up formed from Aluminum Tread Plate
Rear Steps, Folding (2)
Electrical, 12 Volt
Warning Light System, NFPA
Lights, Warning – LED
Lights, Marker – Halogen
Lights, Tail/Turn/Backup – Halogen
Siren, Electronic
Speaker, 100 Watt (1)
Booster Reel, Hannay Painted Steel
Skid Unit
Tank, 300 Gallon Poly
Pump, Hale HPXB-200 with 18HP Vanguard Gasoline Engine
Pump Fuel Tank, 2 ½ Gallon
Manifold, 4" Steel Custom
Instrument Panel, Lighted
Gauge, Master
07/25/11
ALF AB01
Page 3

Description
Primer, Exhaust Type
Valve, Tank to Pump Apollo 2 ½"
Discharge, 2 ½" (1)
Discharge , 1 ½" (2)
Discharge, 1"(3)
Valve, Apollo 2 ½" (1)
Valve, Apollo 1 ½" (1) Bypass/Recirculation
Valve, Apollo 1" (1) Hose Reel
Suction, 2 ½"
Striping
Striping, Reflective 4" NFPA
Chevron, Reflective NFPA

Quotation

American LaFrance

OHIO STS \$94,294.00	American LaFrance 2 Door Flatbed Brush Truck with transverse compartment 300 Gallon Skid Unit w/ Hale HP275 Pump Formed Aluminum Tread Plate Body
-------------------------	--

Quote No:

07/25/11

ALF AB02

Page 1

Description
Certificate of Compliance, NFPA 1906
CHASSIS
Chassis Ford F-550 Standard Cab
Engine, 6.8 Liter V-10 362HP
Transmission, 5 Speed Automatic
GVW, 18,000#
Wheel Base, 141"
CA 60"
Front Axle, 7000#
Rear Axle, 13,660#
Rear Axle Ratio, 4.88 Ltd Slip
Wheels, Painted Steel
Tires, 225 Max Trac
Fuel Tank, 40 Gallon Aft Axle
Front Bumper, Chrome

Description
Brake Controller
XL Decore Package
Seat, 40/20/40 Bench
Rear Bumper, Steel ICC
Mud Flaps, Rear Axel (2)
Body
Standard Aluminum Flatbed Body formed of Aluminum Tread Plate
Sub-frame, Extruded Aluminum
Standard Curb Side Compartment formed of Aluminum Tread Plate, Vented
Standard Driver's Side Compartment formed of Aluminum Tread Plate, Vented
Standard Driver's Side Hose Lay formed of Aluminum Tread Plate
Hose Lay Cover, Canvass
Doors, Swing Up formed from Aluminum Tread Plate
Rear Steps, Folding (2)
Electrical, 12 Volt
Warning Light System, NFPA
Lights, Warning – LED
Lights, Marker – Halogen
Lights, Tail/Turn/Backup – Halogen
Siren, Electronic
Speaker, 100 Watt (1)
Booster Reel, Hannay Painted Steel
Skid Unit
Tank, 300 Gallon Poly
Pump, Hale HP275 with 35HP Vanguard Gasoline Engine
Pump Fuel, Supplied from Chassis Tank
Manifold, 4" Steel Custom
Instrument Panel, Lighted
Gauge, Master

Description
Primer, Electric Oil Less
Valve, Tank to Pump Apollo 2 ½"
Discharge, 2 ½" (1)
Discharge , 1 ½" (2)
Discharge, 1"(3)
Valve, Apollo 2 ½" (1)
Valve, Apollo 1 ½" (1) Bypass/Recirculation
Valve, Apollo 1" (1) Hose Reel
Suction, 2 ½"
Striping
Striping, Reflective 4" NFPA
Chevron, Reflective NFPA

WALK AROUND



RESCUE

Engineered and constructed for functionality, safety, and rigorous duty requirements. Available for Medium and Heavy-Duty applications.

- Mission oriented custom layouts. 12-24 ST, STL & 17-21 ft Alum.
- Ergonomically engineered equipment placement
- Roll-up or optional hinged door options available
- Bolted in accessories expedite future reconfigurations
- Medium and Heavy-Duty aluminum or stainless
- Extensive custom and commercial chassis load ranges
- Compartments floors reinforced to handle 750 lb load rating
- Recessed roof mounted light towers and generator options



WALK AROUND



Recessed light tower mounting



Wheel well compartment, pvc toolboxes, and bottle storage



Ladders and pikepole storage



Trays and shelving with mission specific layouts



Hydraulic generator



Breathing air fill station and storage

These are the typical specifications for the Walk Around Rescue:

PRODUCT CAPABILITIES: Full-use Rescues, Extrication, Air/Light, Trench Rescue, Hazardous Materials; each body is capable of exceeding the requirements of the application. Designed to adapt as the vehicle mission expands, user can reconfigure compartmentation accessories with common hand tools.

Extensive engineering reviews to include weight distribution, center of gravity, and electrical load analysis insure technical compliance. A real world approach to equipment placement further insures access to equipment with minimal risk to crew.

CHASSIS: American LaFrance Eagle®, Metropolitan and Freightliner M2.

BODY CONSTRUCTION:

Formed stainless steel or aluminum fully welded construction available in Medium/Heavy-Duty.

BODY SUB-FRAME: Structural stainless steel or aluminum frame welded integral to body creating a unitized compartment system. Rubber isolated frame mounting.

COMPARTMENT ACCESSORIES: All trays, shelves, toolboards, and slide out drawers have been certified at their particular rating to insure proper application in service. Roll-up doors with the option of hinged doors further permit custom tailoring of compartment access.

For your nearest American LaFrance dealer, call 1-717-859-1176.

Some specifications and features shown or mentioned in this brochure are optional and are available upon request at extra cost. Specifications are subject to change without notice. ©2009, American LaFrance, LLC. All rights reserved.



QUOTATION

American LaFrance

OHIO STS

\$166,313.00

American LaFrance 2 Door Freightliner Rescue
14' Walk-Around Aluminum Rescue Body
53/60/53 Compartments

07/26/2011

Quote No: ALF AD01-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

== Chassis M2 2-D Pumper - 1001.001 01/19/10 ==

Certificate of Compliance, NFPA 1901

Chassis, Freightliner M2 106 2-Door

Engine, Cummins ISC8.3-300HP

Standard Engine Protection W/O De-rate

Front Axle, 12,000#, Package

Rear Axle, Single, 23,000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Painted Plastic Hood Mounted

Mirrors, Dual Painted West Coast

Steering Column, Fixed

"Select" 12VDC Power Supplies

Seat, Non-Suspended Driver's

Seat, Non-Suspension High Back Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder

Rollover Stability, Commercial Chassis

Seatbelt Warning System

Helmet Storage, Each Seating Position

Tire Inflation Indicators, for Chassis w/Single Rear Axle

== Bumper Package / M2 - 1001.001 01/19/10 ==

Bumper, Front, Painted

|-- Air Horns, Hood Mounted

|-- Lanyard Control

DESCRIPTION

|-- Siren, Electronic w/100 Watt Speaker
== Chassis Mods M2 - 1001.001 01/19/10 ==
Light, Engine Compartment
Battery "On" Light, Green
Receptacle, 12V for Fire House Charging System
|-- Air Charging Connector, LS
Label, Fluid & Seating Capacity, Cab
Label, Overall Travel Height, Cab
Labels, Crew Area and Rear Body Step
== Body / Special Services Rescue - 1001.001 01/19/1

Subframe- Aluminum / Special Services Body
|-- Body Construction / Material / Aluminum
Special Services Body, 14' Walk-Around: 53/60/53
|-- Doors, Roll-Up 53/60/53

Tailboard, 12" Deep
Body Trim, Aluminum Diamondplate, Pumpers
Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Special Service Resc. / Commercial - 1001.00

|-- Electrical, 12 Volt Description
|-- Warning Light System, NFPA
|-- Warning Lights, Whelen Halogen Pkg, Commercial
|-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
|-- Reflectors NFPA/FMVSS Compliant
|-- Lights, Clearance & Marker (7)
|-- Lights, Side Running Board and Rear Step
|-- Lights, Underbody
|-- Light, Open Door Indicator, Flashing LED
|-- Lights, Body Compartments
|-- Lights, Midship Directional, 30'+ OAL
|-- Light Bracket, License Plate
|-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

|-- Paint, Cab, Single Color 2-Door Cab
|-- Paint, Chassis, Black
|-- Paint, Body, Single Color

DESCRIPTION

|-- Finish, Compartment Interior, Zolatone Finish
|-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"

Scene Lights, (2) Whelen, 900
== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

QUOTATION

American LaFrance

OHIO STS
\$170,170.00

American LaFrance 2 Door Freightliner Rescue
16' Walk-Around Aluminum Rescue Body
44/44/60/44 Compartments

07/26/2011

Quote No: ALF AD02-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==
== Chassis M2 2-D Pumper - 1001.001 01/19/10 ==
Certificate of Compliance, NFPA 1901
Chassis, Freightliner M2 106 2-Door

Engine, Cummins ISC8.3-300HP

Standard Engine Protection W/O De-rate

Front Axle, 12,000#, Package

Rear Axle, Single, 23,000#, Package
|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Painted Plastic Hood Mounted
Mirrors, Dual Painted West Coast

Steering Column, Fixed
"Select" 12VDC Power Supplies
Seat, Non-Suspended Driver's
Seat, Non-Suspension High Back Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder
Rollover Stability, Commercial Chassis
Seatbelt Warning System
Helmet Storage, Each Seating Position
Tire Inflation Indicators, for Chassis w/Single Rear Axle
== Bumper Package / M2 - 1001.001 01/19/10 ==
Bumper, Front, Painted
|-- Air Horns, Hood Mounted
|-- Lanyard Control

DESCRIPTION

|-- Siren, Electronic w/100 Watt Speaker
== Chassis Mods M2 - 1001.001 01/19/10 ==
Light, Engine Compartment
Battery "On" Light, Green
Receptacle, 12V for Fire House Charging System
|-- Air Charging Connector, LS
Label, Fluid & Seating Capacity, Cab
Label, Overall Travel Height, Cab
Labels, Crew Area and Rear Body Step
== Body / Special Services Rescue - 1001.001 01/19/1

Subframe- Aluminum / Special Services Body
|-- Body Construction / Material / Aluminum
Special Services Body, 16' Walk-Around: 44/44/60/44
|-- Doors, Roll-Up 44/44/60/44

Tailboard, 12" Deep
Body Trim, Aluminum Diamondplate, Pumpers
Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Special Service Resc. / Commercial - 1001.00

|-- Electrical, 12 Volt Description
|-- Warning Light System, NFPA
|-- Warning Lights, Whelen Halogen Pkg, Commercial
|-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
|-- Reflectors NFPA/FMVSS Compliant
|-- Lights, Clearance & Marker (7)
|-- Lights, Side Running Board and Rear Step
|-- Lights, Underbody
|-- Light, Open Door Indicator, Flashing LED
|-- Lights, Body Compartments
|-- Lights, Midship Directional, 30'+ OAL
|-- Light Bracket, License Plate
|-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

|-- Paint, Cab, Single Color 2-Door Cab
|-- Paint, Chassis, Black
|-- Paint, Body, Single Color

DESCRIPTION

|-- Finish, Compartment Interior, Zolatone Finish
|-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"

Scene Lights, (2) Whelen, 900
== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

QUOTATION

American LaFrance

OHIO STS
\$180,700.00

American LaFrance 2 Door Freightliner Rescue
18' Walk-Around Aluminum Rescue Body
53/53/60/53 Compartments

07/29/2011

Quote No: ALF AD03-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==
== Chassis M2 2-D Pumper - 1001.001 01/19/10 ==
Certificate of Compliance, NFPA 1901
Chassis, Freightliner M2 106 2-Door

Engine, Cummins ISC8.3-300HP

Standard Engine Protection W/O De-rate

Front Axle, 12,000#, Package

Rear Axle, Single, 23,000#, Package
|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Painted Plastic Hood Mounted
Mirrors, Dual Painted West Coast

Steering Column, Fixed
"Select" 12VDC Power Supplies
Seat, Non-Suspended Driver's
Seat, Non-Suspension High Back Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder
Rollover Stability, Commercial Chassis
Seatbelt Warning System
Helmet Storage, Each Seating Position
Tire Inflation Indicators, for Chassis w/Single Rear Axle
== Bumper Package / M2 - 1001.001 01/19/10 ==
Bumper, Front, Painted
|-- Air Horns, Hood Mounted
|-- Lanyard Control

DESCRIPTION

|-- Siren, Electronic w/100 Watt Speaker
== Chassis Mods M2 - 1001.001 01/19/10 ==
Light, Engine Compartment
Battery "On" Light, Green
Receptacle, 12V for Fire House Charging System
|-- Air Charging Connector, LS
Label, Fluid & Seating Capacity, Cab
Label, Overall Travel Height, Cab
Labels, Crew Area and Rear Body Step
== Body / Special Services Rescue - 1001.001 01/19/1

Subframe- Aluminum / Special Services Body
|-- Body Construction / Material / Aluminum
Special Services Body, 18' Walk-Around: 53/53/60/53
|-- Doors, Roll-Up 53/53/60/53

Tailboard, 12" Deep
Body Trim, Aluminum Diamondplate, Pumpers
Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Special Service Resc. / Commercial - 1001.00

|-- Electrical, 12 Volt Description
|-- Warning Light System, NFPA
|-- Warning Lights, Whelen Halogen Pkg, Commercial
|-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
|-- Reflectors NFPA/FMVSS Compliant
|-- Lights, Clearance & Marker (7)
|-- Lights, Side Running Board and Rear Step
|-- Lights, Underbody
|-- Light, Open Door Indicator, Flashing LED
|-- Lights, Body Compartments
|-- Lights, Midship Directional, 30'+ OAL
|-- Light Bracket, License Plate
|-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

|-- Paint, Cab, Single Color 2-Door Cab
|-- Paint, Chassis, Black
|-- Paint, Body, Single Color

DESCRIPTION

|-- Finish, Compartment Interior, Zolatone Finish
|-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"

Scene Lights, (2) Whelen, 900
== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

QUOTATION

American LaFrance

OHIO STS

\$186,089.00

American LaFrance 2 Door Freightliner Rescue
20' Walk-Around Aluminum Rescue Body
60/60/68/54 Compartments

07/29/2011

Quote No: ALF AD04-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

== Chassis M2 2-D Pumper - 1001.001 01/19/10 ==

Certificate of Compliance, NFPA 1901

Chassis, Freightliner M2 106 2-Door

Engine, Cummins ISC8.3-300HP

Standard Engine Protection W/O De-rate

Front Axle, 12,000#, Package

Rear Axle, Single, 31,000#, Package

|-- Tires, Standard 315/80R Rear Drive

Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Painted Plastic Hood Mounted

Mirrors, Dual Painted West Coast

Steering Column, Fixed

"Select" 12VDC Power Supplies

Seat, Non-Suspended Driver's

Seat, Non-Suspension High Back Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder

Rollover Stability, Commercial Chassis

Seatbelt Warning System

Helmet Storage, Each Seating Position

Tire Inflation Indicators, for Chassis w/Single Rear Axle

== Bumper Package / M2 - 1001.001 01/19/10 ==

Bumper, Front, Painted

|-- Air Horns, Hood Mounted

|-- Lanyard Control

DESCRIPTION

|-- Siren, Electronic w/100 Watt Speaker
== Chassis Mods M2 - 1001.001 01/19/10 ==
Light, Engine Compartment
Battery "On" Light, Green
Receptacle, 12V for Fire House Charging System
|-- Air Charging Connector, LS
Label, Fluid & Seating Capacity, Cab
Label, Overall Travel Height, Cab
Labels, Crew Area and Rear Body Step
== Body / Special Services Rescue - 1001.001 01/19/1

Subframe- Aluminum / Special Services Body
|-- Body Construction / Material / Aluminum
Special Services Body, 20' Walk-Around: 60/60/68/54
|-- Doors, Roll-Up 60/60/68/54

Tailboard, 12" Deep
Body Trim, Aluminum Diamondplate, Pumpers
Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Special Service Resc. / Commercial - 1001.00

|-- Electrical, 12 Volt Description
|-- Warning Light System, NFPA
|-- Warning Lights, Whelen Halogen Pkg, Commercial
|-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
|-- Reflectors NFPA/FMVSS Compliant
|-- Lights, Clearance & Marker (7)
|-- Lights, Side Running Board and Rear Step
|-- Lights, Underbody
|-- Light, Open Door Indicator, Flashing LED
|-- Lights, Body Compartments
|-- Lights, Midship Directional, 30'+ OAL
|-- Light Bracket, License Plate
|-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

|-- Paint, Cab, Single Color 2-Door Cab
|-- Paint, Chassis, Black
|-- Paint, Body, Single Color

DESCRIPTION

|-- Finish, Compartment Interior, Zolatone Finish
|-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"

Scene Lights, (2) Whelen, 900
== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

QUOTATION

American LaFrance

OHIO STS
\$249,932.00

American LaFrance Custom Chassis Rescue
14' Walk-Around Aluminum Rescue Body
53/60/53 Compartments

07/26/2011

Quote No: ALF AD05-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==
== Metropolitan Pumper for Liberty - 1001.001 01/19/10 =
Certificate of Compliance, NFPA 1901
Chassis, Metropolitan Custom Crew, Flat Roof

Engine, 2010 EPA Cummins ISC8.3 330HP
|-- Engine Brake, Cummins C-Brake , (1) Switch

Alternator, 270 Amp
Standard Engine Protection W/O De-rate

Front Axle, Meritor 18,000#, Package

Rear Axle, Single, Meritor 24,000#, Package
|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control

Wheels, Standard Steel Disc

Fenderette, Standard
Mirrors, Mekra, Black, 16" x 7" M2 Style

Steering Column, Tilt & Telescoping Adjustable
Air Conditioning Front and Rear
"Select" 12VDC Power Supplies
Seat, Air Ride Driver's
Seat, Non-Suspended High Back Officer's
Seats, Rear Facing SCBA, (2)
Seats, Forward Facing (2) ABTS SCBA, Rear Wall

SAFETY SYSTEMS, CUSTOM CHASSIS

Vehicle Data Recorder
Rollover Stability (Electronic Stability Control)
Seat Belt Warning System
Helmet Storage, Each Seating Position

DESCRIPTION

Tire Inflation Indicators, for Chassis w/Single Rear Axle
 == Bumper Package / Custom - 1001.001 01/19/10 ==
 Bumper, Front, Polished Stainless Steel
 |-- Air Horns, Thru the Bumper Mtd. (2)
 |-- Switch, Horn/Air Horn Selector, Cab Dash Mtd
 |-- Siren, Electronic w/100 Watt Speaker
 == Chassis Mods Custom - 1001.001 01/19/10 ==
 Receptacle, 12V for Fire House Charging System
 |-- Air Charging Connector, LS
 Fuel Fill, Custom Chassis
 Label, Fluid & Seating Capacity, Cab
 Label, Overall Travel Height, Cab
 Labels, Crew Area and Rear Body Step
 == Body / Special Services Rescue - 1001.001 01/19/10

Subframe- Aluminum / Special Services Body
 |-- Body Construction / Material / Aluminum
 Special Services Body, 14' Walk-Around: 53/60/53
 |-- Doors, Roll-Up 53/60/53

Tailboard, 12" Deep
 Body Trim, Aluminum Diamondplate
 Rubrail, with Reflective Stripe
 Vent, Compartment

Hand Rails, Body
 Steps, Folding (4)
 Tow Eyes, Rear
 Mud Flaps, Rear Axle (2)
 == Cmpt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Special Services Rescue / Custom - 10

-- Electrical, 12 Volt Description
 -- Warning Light System, NFPA
 -- Warning Lights, Liberty Pumper, Whelen Halo Pkg
 |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
 -- Reflectors NFPA/FMVSS Compliant
 -- Lights, Clearance & Marker (7)
 -- Lights, Side Running Board and Rear Step
 -- Lights, Underbody
 -- Light, Open Door Indicator, Flashing LED
 -- Lights, Body Compartments
 -- Lights, Midship Directional , 30'+ OAL
 -- Light Bracket, License Plate
 -- Back-Up Alarm, Liberty

-- Painting, Alm Body, Pumper/Rescue/Tanker Custom
 -- Paint, Cab, Single Color 4-Door Cab (Liberty Standard Color)
 -- Paint, Chassis, Black

DESCRIPTION

- |-- Paint, Body, Single Color
- |-- Finish, Compartment Interior, Zolatone Finish
- |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

QUOTATION

American LaFrance

OHIO STS

\$253,786.00

American LaFrance Custom Chassis Rescue
16' Walk-Around Aluminum Rescue Body
44/44/60/44 Compartments

07/26/2011

Quote No: ALF AD06-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

== Metropolitan Pumper for Liberty - 1001.001 01/19/10 =

Certificate of Compliance, NFPA 1901

Chassis, Metropolitan Custom Crew, Flat Roof

Engine, 2010 EPA Cummins ISC8.3 330HP

|-- Engine Brake, Cummins C-Brake , (1) Switch

Alternator, 270 Amp

Standard Engine Protection W/O De-rate

Front Axle, Meritor 18,000#, Package

Rear Axle, Single, Meritor 24,000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control

Wheels, Standard Steel Disc

Fenderette, Standard

Mirrors, Mekra, Black, 16" x 7" M2 Style

Steering Column, Tilt & Telescoping Adjustable

Air Conditioning Front and Rear

"Select" 12VDC Power Supplies

Seat, Air Ride Driver's

Seat, Non-Suspended High Back Officer's

Seats, Rear Facing SCBA, (2)

Seats, Forward Facing (2) ABTS SCBA, Rear Wall

SAFETY SYSTEMS, CUSTOM CHASSIS

Vehicle Data Recorder

Rollover Stability (Electronic Stability Control)

Seat Belt Warning System

Helmet Storage, Each Seating Position

DESCRIPTION

Tire Inflation Indicators, for Chassis w/Single Rear Axle
 == Bumper Package / Custom - 1001.001 01/19/10 ==
 Bumper, Front, Polished Stainless Steel
 |-- Air Horns, Thru the Bumper Mtd. (2)
 |-- Switch, Horn/Air Horn Selector, Cab Dash Mtd
 |-- Siren, Electronic w/100 Watt Speaker
 == Chassis Mods Custom - 1001.001 01/19/10 ==
 Receptacle, 12V for Fire House Charging System
 |-- Air Charging Connector, LS
 Fuel Fill, Custom Chassis
 Label, Fluid & Seating Capacity, Cab
 Label, Overall Travel Height, Cab
 Labels, Crew Area and Rear Body Step
 == Body / Special Services Rescue - 1001.001 01/19/10

Subframe- Aluminum / Special Services Body
 |-- Body Construction / Material / Aluminum
 Special Services Body, 16' Walk-Around: 44/44/60/44
 |-- Doors, Roll-Up 44/44/60/44

Tailboard, 12" Deep
 Body Trim, Aluminum Diamondplate
 Rubrail, with Reflective Stripe
 Vent, Compartment

Hand Rails, Body
 Steps, Folding (4)
 Tow Eyes, Rear
 Mud Flaps, Rear Axle (2)
 == Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpnts, Special Services Rescue / Custom - 10

-- Electrical, 12 Volt Description
 -- Warning Light System, NFPA
 -- Warning Lights, Liberty Pumper, Whelen Halo Pkg
 |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
 -- Reflectors NFPA/FMVSS Compliant
 -- Lights, Clearance & Marker (7)
 -- Lights, Side Running Board and Rear Step
 -- Lights, Underbody
 -- Light, Open Door Indicator, Flashing LED
 -- Lights, Body Compartments
 -- Lights, Midship Directional , 30'+ OAL
 -- Light Bracket, License Plate
 -- Back-Up Alarm, Liberty

-- Painting, Alm Body, Pumper/Rescue/Tanker Custom
 -- Paint, Cab, Single Color 4-Door Cab (Liberty Standard Color)
 -- Paint, Chassis, Black

DESCRIPTION

- |-- Paint, Body, Single Color
- |-- Finish, Compartment Interior, Zolatone Finish
- |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

QUOTATION

American LaFrance

OHIO STS
\$268,377.00

American LaFrance Custom Chassis Rescue
18' Walk-Around Aluminum Rescue Body
53/53/60/53 Compartments

08/01/2011

Quote No: ALF AD07-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==
== Metropolitan Pumper for Liberty - 1001.001 01/19/10 =
Certificate of Compliance, NFPA 1901
Chassis, Metropolitan Custom Crew, Flat Roof

Engine, 2010 EPA Cummins ISC8.3 330HP
|-- Engine Brake, Cummins C-Brake , (1) Switch

Alternator, 270 Amp
Standard Engine Protection W/O De-rate

Front Axle, Meritor 18,000#, Package

Rear Axle, Single, Meritor 24,000#, Package
|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control

Wheels, Standard Steel Disc

Fenderette, Standard
Mirrors, Mekra, Black, 16" x 7" M2 Style

Steering Column, Tilt & Telescoping Adjustable
Air Conditioning Front and Rear
"Select" 12VDC Power Supplies
Seat, Air Ride Driver's
Seat, Non-Suspended High Back Officer's
Seats, Rear Facing SCBA, (2)
Seats, Forward Facing (2) ABTS SCBA, Rear Wall

SAFETY SYSTEMS, CUSTOM CHASSIS

Vehicle Data Recorder
Rollover Stability (Electronic Stability Control)
Seat Belt Warning System
Helmet Storage, Each Seating Position

DESCRIPTION

Tire Inflation Indicators, for Chassis w/Single Rear Axle
 == Bumper Package / Custom - 1001.001 01/19/10 ==
 Bumper, Front, Polished Stainless Steel
 |-- Air Horns, Thru the Bumper Mtd. (2)
 |-- Switch, Horn/Air Horn Selector, Cab Dash Mtd
 |-- Siren, Electronic w/100 Watt Speaker
 == Chassis Mods Custom - 1001.001 01/19/10 ==
 Receptacle, 12V for Fire House Charging System
 |-- Air Charging Connector, LS
 Fuel Fill, Custom Chassis
 Label, Fluid & Seating Capacity, Cab
 Label, Overall Travel Height, Cab
 Labels, Crew Area and Rear Body Step
 == Body / Special Services Rescue - 1001.001 01/19/10

Subframe- Aluminum / Special Services Body
 |-- Body Construction / Material / Aluminum
 Special Services Body, 18' Walk-Around: 53/53/60/53
 |-- Doors, Roll-Up 53/53/60/53

Tailboard, 12" Deep
 Body Trim, Aluminum Diamondplate
 Rubrail, with Reflective Stripe
 Vent, Compartment

Hand Rails, Body
 Steps, Folding (4)
 Tow Eyes, Rear
 Mud Flaps, Rear Axle (2)
 == Cmpt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Special Services Rescue / Custom - 10

-- Electrical, 12 Volt Description
 -- Warning Light System, NFPA
 -- Warning Lights, Liberty Pumper, Whelen Halo Pkg
 |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
 -- Reflectors NFPA/FMVSS Compliant
 -- Lights, Clearance & Marker (7)
 -- Lights, Side Running Board and Rear Step
 -- Lights, Underbody
 -- Light, Open Door Indicator, Flashing LED
 -- Lights, Body Compartments
 -- Lights, Midship Directional , 30'+ OAL
 -- Light Bracket, License Plate
 -- Back-Up Alarm, Liberty

-- Painting, Alm Body, Pumper/Rescue/Tanker Custom
 -- Paint, Cab, Single Color 4-Door Cab (Liberty Standard Color)
 -- Paint, Chassis, Black

DESCRIPTION

|-- Paint, Body, Single Color
|-- Finish, Compartment Interior, Zolatone Finish
|-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"
|-- Striping, Reflective 4" NFPA
|-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

QUOTATION

American LaFrance

OHIO STS

\$273,767.00

American LaFrance Custom Chassis Rescue
20' Walk-Around Aluminum Rescue Body
60/60/68/54 Compartments

08/01/2011

Quote No: ALF AD08-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

== Metropolitan Pumper for Liberty - 1001.001 01/19/10 =

Certificate of Compliance, NFPA 1901

Chassis, Metropolitan Custom Crew, Flat Roof

Engine, 2010 EPA Cummins ISC8.3 330HP

|-- Engine Brake, Cummins C-Brake , (1) Switch

Alternator, 270 Amp

Standard Engine Protection W/O De-rate

Front Axle, Meritor 18,000#, Package

Rear Axle, Single, Meritor 24,000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Traction Control

Wheels, Standard Steel Disc

Fenderette, Standard

Mirrors, Mekra, Black, 16" x 7" M2 Style

Steering Column, Tilt & Telescoping Adjustable

Air Conditioning Front and Rear

"Select" 12VDC Power Supplies

Seat, Air Ride Driver's

Seat, Non-Suspended High Back Officer's

Seats, Rear Facing SCBA, (2)

Seats, Forward Facing (2) ABTS SCBA, Rear Wall

SAFETY SYSTEMS, CUSTOM CHASSIS

Vehicle Data Recorder

Rollover Stability (Electronic Stability Control)

Seat Belt Warning System

Helmet Storage, Each Seating Position

DESCRIPTION

Tire Inflation Indicators, for Chassis w/Single Rear Axle

== Bumper Package / Custom - 1001.001 01/19/10 ==

Bumper, Front, Polished Stainless Steel

|-- Air Horns, Thru the Bumper Mtd. (2)

|-- Switch, Horn/Air Horn Selector, Cab Dash Mtd

|-- Siren, Electronic w/100 Watt Speaker

== Chassis Mods Custom - 1001.001 01/19/10 ==

Receptacle, 12V for Fire House Charging System

|-- Air Charging Connector, LS

Fuel Fill, Custom Chassis

Label, Fluid & Seating Capacity, Cab

Label, Overall Travel Height, Cab

Labels, Crew Area and Rear Body Step

== Body / Special Services Rescue - 1001.001 01/19/10

Subframe- Aluminum / Special Services Body

|-- Body Construction / Material / Aluminum

Special Services Body, 20' Walk-Around: 60/60/68/54

|-- Doors, Roll-Up 60/60/68/54

Tailboard, 12" Deep

Body Trim, Aluminum Diamondplate

Rubrail, with Reflective Stripe

Vent, Compartment

Hand Rails, Body

Steps, Folding (4)

Tow Eyes, Rear

Mud Flaps, Rear Axle (2)

== Cmpt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Special Services Rescue / Custom - 10

|-- Electrical, 12 Volt Description

|-- Warning Light System, NFPA

|-- Warning Lights, Liberty Pumper, Whelen Halo Pkg

|-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen

|-- Reflectors NFPA/FMVSS Compliant

|-- Lights, Clearance & Marker (7)

|-- Lights, Side Running Board and Rear Step

|-- Lights, Underbody

|-- Light, Open Door Indicator, Flashing LED

|-- Lights, Body Compartments

|-- Lights, Midship Directional, 30'+ OAL

|-- Light Bracket, License Plate

|-- Back-Up Alarm, Liberty

|-- Painting, Alm Body, Pumper/Rescue/Tanker Custom

|-- Paint, Cab, Single Color 4-Door Cab (Liberty Standard Color)

|-- Paint, Chassis, Black

DESCRIPTION

|-- Paint, Body, Single Color
|-- Finish, Compartment Interior, Zolatone Finish
|-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"
|-- Striping, Reflective 4" NFPA
|-- Chevron, Reflective NFPA

== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

QUOTATION

American LaFrance

OHIO STS
\$173,532.00

American LaFrance 2 Door Navistar Rescue
14' Walk-Around Aluminum Rescue Body
53/60/53 Compartments

07/26/2011

Quote No: ALF AD09-

Page 1

DESCRIPTION

Certificate of Compliance, NFPA 1901
Chassis, Navistar 2 Door DuraStar, 4400 Series

Engine, MaxxForce DT 300HP

Standard Engine Protection W/O De-rate

Front Axle, 12,000#, Package

Rear Axle, Single, 23,000#, Package
|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

Dust Shields, Single Axle, Front and Rear Brakes

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Chromed Plastic Hood Mounted
Mirrors, Dual Bright Heated West Coast, LH/RH Remote

Steering Column, Tilt & Telescoping Adjustable
Daytime Running Lights
Power Supply 12VDC (1)
Seat, Air Ride Driver's
Seat, Non-Suspension High Back Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder
Rollover Stability, Commercial Chassis
Seatbelt Warning System
Helmet Storage, Each Seating Position
Tire Inflation Indicators, for Chassis w/Single Rear Axle
== Bumper Package / M2 - 1001.001 01/19/10 ==
Bumper, Front, Chrome
|-- Air Horns, Hood Mounted
|-- Switches, Air Horn (1) Driver / (1) Officer

DESCRIPTION

|-- Siren, Electronic w/100 Watt Speaker
== Chassis Mods M2 - 1001.001 01/19/10 ==
Light, Engine Compartment
Battery "On" Light, Green
Receptacle, 12V for Fire House Charging System
|-- Air Charging Connector, LS
Label, Fluid & Seating Capacity, Cab
Label, Overall Travel Height, Cab
Labels, Crew Area and Rear Body Step
== Body / Special Services Rescue - 1001.001 01/19/1

Subframe- Aluminum / Special Services Body
|-- Body Construction / Material / Aluminum
Special Services Body, 14' Walk-Around: 53/60/53
|-- Doors, Roll-Up 53/60/53

Tailboard, 12" Deep
Body Trim, Aluminum Diamondplate, Pumpers
Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Special Service Resc. / Commercial - 1001.00

|-- Electrical, 12 Volt Description
|-- Warning Light System, NFPA
|-- Warning Lights, Whelen Halogen Pkg, Commercial
|-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
|-- Reflectors NFPA/FMVSS Compliant
|-- Lights, Clearance & Marker (7)
|-- Lights, Side Running Board and Rear Step
|-- Lights, Underbody
|-- Light, Open Door Indicator, Flashing LED
|-- Lights, Body Compartments
|-- Lights, Midship Directional, 30'+ OAL
|-- Light Bracket, License Plate
|-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

|-- Paint, Cab, Single Color 2-Door Cab
|-- Paint, Chassis, Black
|-- Paint, Body, Single Color

DESCRIPTION

|-- Finish, Compartment Interior, Zolatone Finish
|-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"

Scene Lights, (2) Whelen, 900
== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

QUOTATION

American LaFrance

OHIO STS
\$177,565.00

American LaFrance 2 Door Navistar Rescue
16' Walk-Around Aluminum Rescue Body
44/44/60/44 Compartments

07/26/2011

Quote No: ALF AD10-

Page 1

DESCRIPTION

Certificate of Compliance, NFPA 1901
Chassis, Navistar 2 Door DuraStar, 4400 Series

Engine, MaxxForce DT 300HP

Standard Engine Protection W/O De-rate

Front Axle, 12,000#, Package

Rear Axle, Single, 23,000#, Package
|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

Dust Shields, Single Axle, Front and Rear Brakes

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Chromed Plastic Hood Mounted
Mirrors, Dual Bright Heated West Coast, LH/RH Remote

Steering Column, Tilt & Telescoping Adjustable
Daytime Running Lights
Power Supply 12VDC (1)
Seat, Air Ride Driver's
Seat, Non-Suspension High Back Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder
Rollover Stability, Commercial Chassis
Seatbelt Warning System
Helmet Storage, Each Seating Position
Tire Inflation Indicators, for Chassis w/Single Rear Axle
== Bumper Package / M2 - 1001.001 01/19/10 ==
Bumper, Front, Chrome
|-- Air Horns, Hood Mounted
|-- Switches, Air Horn (1) Driver / (1) Officer

DESCRIPTION

|-- Siren, Electronic w/100 Watt Speaker
== Chassis Mods M2 - 1001.001 01/19/10 ==
Light, Engine Compartment
Battery "On" Light, Green
Receptacle, 12V for Fire House Charging System
|-- Air Charging Connector, LS
Label, Fluid & Seating Capacity, Cab
Label, Overall Travel Height, Cab
Labels, Crew Area and Rear Body Step
== Body / Special Services Rescue - 1001.001 01/19/1

Subframe- Aluminum / Special Services Body
|-- Body Construction / Material / Aluminum
Special Services Body, 16' Walk-Around: 44/44/60/44
|-- Doors, Roll-Up 44/44/60/44

Tailboard, 12" Deep
Body Trim, Aluminum Diamondplate, Pumpers
Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Special Service Resc. / Commercial - 1001.00

|-- Electrical, 12 Volt Description
|-- Warning Light System, NFPA
|-- Warning Lights, Whelen Halogen Pkg, Commercial
|-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
|-- Reflectors NFPA/FMVSS Compliant
|-- Lights, Clearance & Marker (7)
|-- Lights, Side Running Board and Rear Step
|-- Lights, Underbody
|-- Light, Open Door Indicator, Flashing LED
|-- Lights, Body Compartments
|-- Lights, Midship Directional, 30'+ OAL
|-- Light Bracket, License Plate
|-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

|-- Paint, Cab, Single Color 2-Door Cab
|-- Paint, Chassis, Black
|-- Paint, Body, Single Color

DESCRIPTION

|-- Finish, Compartment Interior, Zolatone Finish
|-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"

Scene Lights, (2) Whelen, 900
== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

QUOTATION

American LaFrance

OHIO STS

\$186,972.00

American LaFrance 2 Door Navistar Rescue
18' Walk-Around Aluminum Rescue Body
53/53/60/53 Compartments

07/26/2011

Quote No: ALF AD11-

Page 1

DESCRIPTION

Certificate of Compliance, NFPA 1901
Chassis, Navistar 2 Door DuraStar, 4400 Series

Engine, MaxxForce DT 300HP

Standard Engine Protection W/O De-rate

Front Axle, 12,000#, Package

Rear Axle, Single, 23,000#, Package
|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

Dust Shields, Single Axle, Front and Rear Brakes

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Chromed Plastic Hood Mounted
Mirrors, Dual Bright Heated West Coast, LH/RH Remote

Steering Column, Tilt & Telescoping Adjustable
Daytime Running Lights
Power Supply 12VDC (1)
Seat, Air Ride Driver's
Seat, Non-Suspension High Back Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder
Rollover Stability, Commercial Chassis
Seatbelt Warning System
Helmet Storage, Each Seating Position
Tire Inflation Indicators, for Chassis w/Single Rear Axle
== Bumper Package / M2 - 1001.001 01/19/10 ==
Bumper, Front, Chrome
|-- Air Horns, Hood Mounted
|-- Switches, Air Horn (1) Driver / (1) Officer

DESCRIPTION

|-- Siren, Electronic w/100 Watt Speaker
== Chassis Mods M2 - 1001.001 01/19/10 ==
Light, Engine Compartment
Battery "On" Light, Green
Receptacle, 12V for Fire House Charging System
|-- Air Charging Connector, LS
Label, Fluid & Seating Capacity, Cab
Label, Overall Travel Height, Cab
Labels, Crew Area and Rear Body Step
== Body / Special Services Rescue - 1001.001 01/19/1

Subframe- Aluminum / Special Services Body
|-- Body Construction / Material / Aluminum
Special Services Body, 18' Walk-Around: 53/53/60/53
|-- Doors, Roll-Up 53/53/60/53

Tailboard, 12" Deep
Body Trim, Aluminum Diamondplate, Pumpers
Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Special Service Resc. / Commercial - 1001.00

|-- Electrical, 12 Volt Description
|-- Warning Light System, NFPA
|-- Warning Lights, Whelen Halogen Pkg, Commercial
|-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
|-- Reflectors NFPA/FMVSS Compliant
|-- Lights, Clearance & Marker (7)
|-- Lights, Side Running Board and Rear Step
|-- Lights, Underbody
|-- Light, Open Door Indicator, Flashing LED
|-- Lights, Body Compartments
|-- Lights, Midship Directional, 30'+ OAL
|-- Light Bracket, License Plate
|-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

|-- Paint, Cab, Single Color 2-Door Cab
|-- Paint, Chassis, Black
|-- Paint, Body, Single Color

DESCRIPTION

|-- Finish, Compartment Interior, Zolatone Finish
|-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"

Scene Lights, (2) Whelen, 900
== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

QUOTATION

American LaFrance

OHIO STS
\$192,168.00

American LaFrance 2 Door Navistar Rescue
20' Walk-Around Aluminum Rescue Body
60/60/68/54 Compartments

07/26/2011

Quote No: ALF AD12-

Page 1

DESCRIPTION

Certificate of Compliance, NFPA 1901
Chassis, Navistar 2 Door DuraStar, 4400 Series

Engine, MaxxForce DT 300HP

Standard Engine Protection W/O De-rate

Front Axle, 12,000#, Package

Rear Axle, Single, 23,000#, Package
|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

Dust Shields, Single Axle, Front and Rear Brakes

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Chromed Plastic Hood Mounted
Mirrors, Dual Bright Heated West Coast, LH/RH Remote

Steering Column, Tilt & Telescoping Adjustable
Daytime Running Lights
Power Supply 12VDC (1)
Seat, Air Ride Driver's
Seat, Non-Suspension High Back Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder
Rollover Stability, Commercial Chassis
Seatbelt Warning System
Helmet Storage, Each Seating Position
Tire Inflation Indicators, for Chassis w/Single Rear Axle
== Bumper Package / M2 - 1001.001 01/19/10 ==
Bumper, Front, Chrome
|-- Air Horns, Hood Mounted
|-- Switches, Air Horn (1) Driver / (1) Officer

DESCRIPTION

|-- Siren, Electronic w/100 Watt Speaker
== Chassis Mods M2 - 1001.001 01/19/10 ==
Light, Engine Compartment
Battery "On" Light, Green
Receptacle, 12V for Fire House Charging System
|-- Air Charging Connector, LS
Label, Fluid & Seating Capacity, Cab
Label, Overall Travel Height, Cab
Labels, Crew Area and Rear Body Step
== Body / Special Services Rescue - 1001.001 01/19/1

Subframe- Aluminum / Special Services Body
|-- Body Construction / Material / Aluminum
Special Services Body, 20' Walk-Around: 60/60/68/54
|-- Doors, Roll-Up 60/60/68/54

Tailboard, 12" Deep
Body Trim, Aluminum Diamondplate, Pumpers
Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Pumper / Res. Pumper / Tanker - 1001.001 01/19/1

== Elec. Cmpts, Special Service Resc. / Commercial - 1001.00

|-- Electrical, 12 Volt Description
|-- Warning Light System, NFPA
|-- Warning Lights, Whelen Halogen Pkg, Commercial
|-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
|-- Reflectors NFPA/FMVSS Compliant
|-- Lights, Clearance & Marker (7)
|-- Lights, Side Running Board and Rear Step
|-- Lights, Underbody
|-- Light, Open Door Indicator, Flashing LED
|-- Lights, Body Compartments
|-- Lights, Midship Directional, 30'+ OAL
|-- Light Bracket, License Plate
|-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

|-- Paint, Cab, Single Color 2-Door Cab
|-- Paint, Chassis, Black
|-- Paint, Body, Single Color

DESCRIPTION

|-- Finish, Compartment Interior, Zolatone Finish
|-- Undercoating

|-- Letters, (60) Scotchlite Reflective, 3"

Scene Lights, (2) Whelen, 900
== Equipment Package / Pumpers / Rescue Pmp - 1001.001 01/1

QUOTATION

American LaFrance

OHIO STS
\$216,607.00

American LaFrance 2 Door Freightliner S/A Tanker
Side Mount Hale QPAK 750 Pump
Formed Aluminum Single Axle Tanker Body

07/26/2011

Quote No: ALF AE01-

Page 1

DESCRIPTION

== Chassis M2 106 2-D Single Axle Tanker - 1001.001 01/19/1
Certificate of Compliance, NFPA 1901
Chassis, Freightliner M2 106 2-Door Single Axle Tanker

Engine, 2010 EPA Cummins ISC8.3 - 300HP

Standard Engine Protection W/O De-rate

Front Axle, Meritor 14,600#, Package

Rear Axle, Single, Meritor 31,000#, Package
|-- Tires, Standard 315R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

WABCO 4S/4M ABS With Out Traction Control

Wheels, Standard Steel Disc

Grille, Painted Plastic Hood Mounted
Mirrors, Dual Painted West Coast

Steering Column, Fixed
"Select" 12VDC Power Supplies
Seat, Non-Suspended Driver's
Seat, Two-Man Mid-Back Bench

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder
Rollover Stability, Commercial Chassis
Seatbelt Warning System
Helmet Storage, Each Seating Position
Tire Inflation Indicators, for Chassis w/Single Rear Axle
== Bumper Package / M2 - 1001.001 01/19/10 ==
Bumper, Front, Painted
|-- Air Horns, Hood Mounted
|-- Lanyard Control
|-- Siren, Electronic w/100 Watt Speaker

DESCRIPTION

== Chassis Mods M2 - 1001.001 01/19/10 ==

Light, Engine Compartment

Battery "On" Light, Green

Receptacle, 12V for Fire House Charging System

|-- Air Charging Connector, LS

Label, Fluid & Seating Capacity, Cab

Label, Overall Travel Height, Cab

Labels, Crew Area and Rear Body Step

== Pump / Enclosure / Tankers - 1001.001 01/19/10 ==

Testing, Third Party, Pumpers

Pump, QPAK 750 GPM

|-- Cooler, Engine, Custom or Commercial Chassis

|-- Cooler, Pump, Bypass Tank Fill

Pump Enclosure, S/M w/ Crosslays

|-- Crosslay Cover, Vinyl

|-- Running Boards, Non-Skid Aluminum Diamondplate

|-- Gauges, Master, 4-1/2", 30-0-600 PSI

|-- Gauge, Discharge 2-1/2" 30-0-600 Class 1

|-- Elec Interface w/Fast Idle System

|-- Piping, Class 1 HP Hose and Stainless Steel Pipe

|-- Inlet, Left Panel 2-1/2"

|-- Discharge, LS Panel (2) 2-1/2"

|-- Discharge, RS Panel (1) 2- 1/2" & (1) 3"

|-- Discharge, Crosslays, (2) 1-1/2"

|-- Discharge, Deck Gun, 3" Centered

|-- Deck Gun Outlet Capped, Customer Supplies Gun

Tank to Pump Line, 3"

Tank Fill, 2-1/2" (Tanker)

== Body / Tanker Single Axle - 1001.001 01/19/10 ==

Water Tank 2000 Gallon, 20 Gallon Foam Cell

|-- Warranty, Water/Foam Tank Lifetime

|-- Gauge, Water Tank Level Indicator

|-- Tank Fill, Rear Direct, 2-1/2"

Subframe- Aluminum / Tanker Body

|-- Body Construction / Material / Aluminum

Body, 74-23 Low L / Low R, Single Axle

|-- Doors, Roll-Up 74/23

|-- Dump, 10" Newton S/S Rear, Manual Oper, for Poly Tnk

|-- Dump, Elbow, 10" Newton

|-- Ladder Bracket / Folding Tank / Hard Suction Hose

|-- Folding Tank Storage, Flip Down, Manual LS

|-- Hose, Soft Suction, 6" NST x 15' Couplings

Hose Bed Divider, (1)

Hose Bed Cover, Red w/Weighted Flap and Snaps

Step, Rear 9" Intermediate

Tailboard, 12" Deep

Body Trim, Aluminum Diamondplate, Pumpers

DESCRIPTION

Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Tanker - 1001.001 01/19/10 ==

== Elec. Cmpts, S/A Tanker / Commercial - 1001.001 01/19/10

- |-- Electrical, 12 Volt Description
- |-- Warning Light System, NFPA
- |-- Warning Lights, Whelen Halogen Pkg, Commercial
 - |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
- |-- Reflectors NFPA/FMVSS Compliant
- |-- Lights, Clearance & Marker (7)
- |-- Lights, Side Running Board and Rear Step
- |-- Lights, Underbody
- |-- Light, Open Door Indicator, Flashing LED
- |-- Lights, Rear Deck Unity AG-S, 6"
- |-- Lights, Body Compartments
- |-- Lights, Midship Directional , 30'+ OAL
- |-- Light Bracket, License Plate
- |-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

- |-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

- |-- Paint, Cab, Single Color 2-Door Cab
- |-- Paint, Chassis, Black
- |-- Paint, Body, Single Color
- |-- Finish, Compartment Interior, Zolatone Finish
- |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Tanker - 1001.001 01/19/10 ==

QUOTATION

American LaFrance

OHIO STS
\$254,016.00

American LaFrance 2 Door Freightliner T/A Tanker
Side Mount Hale QPAK 750 Pump
Formed Aluminum Tandem Axle Tanker Body

07/26/2011

Quote No: ALF AE02-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

== Chassis M2 106 2-D Tandem Axle Tanker - 1001.001 01/19/1

Certificate of Compliance, NFPA 1901

Chassis, Freightliner M2 106 2-Door Tandem Axle Tanker

Standard Engine Protection W/O De-rate

Front Axle, Meritor 18,000#, Package

Rear Axle, Tandem, Meritor 46,000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 60 MPH Maximum

WABCO 4S/4M ABS With Out Traction Control

Wheels, Standard Steel Disc

Grille, Painted Plastic Hood Mounted

Mirrors, Dual Painted West Coast

Steering Column, Fixed

"Select" 12VDC Power Supplies

Seat, Non-Suspended Driver's

Seat, Two-Man Mid-Back Bench

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder

Rollover Stability, Commercial Chassis

Seatbelt Warning System

Helmet Storage, Each Seating Position

Tire Inflation Indicators, for Chassis w/Tandem Rear Axle

== Bumper Package / M2 - 1001.001 01/19/10 ==

Bumper, Front, Painted

|-- Air Horns, Hood Mounted

|-- Lanyard Control

|-- Siren, Electronic w/100 Watt Speaker

== Chassis Mods M2 - 1001.001 01/19/10 ==

Light, Engine Compartment

DESCRIPTION

Battery "On" Light, Green
 Receptacle, 12V for Fire House Charging System
 |-- Air Charging Connector, LS
 Label, Fluid & Seating Capacity, Cab
 Label, Overall Travel Height, Cab
 Labels, Crew Area and Rear Body Step
 == Pump / Enclosure / Tankers - 1001.001 01/19/10 ==
 Testing, Third Party, Pumpers
 Pump, QPAK 750 GPM
 |-- Cooler, Engine, Custom or Commercial Chassis
 |-- Cooler, Pump, Bypass Tank Fill
 Pump Enclosure, S/M w/ Crosslays
 |-- Crosslay Cover, Vinyl
 |-- Running Boards, Non-Skid Aluminum Diamondplate
 |-- Gauges, Master, 4-1/2", 30-0-600 PSI
 |-- Gauge, Discharge 2-1/2" 30-0-600 Class 1
 |-- Elec Interface w/Fast Idle System
 |-- Piping, Class 1 HP Hose and Stainless Steel Pipe

 |-- Inlet, Left Panel 2-1/2"

 |-- Discharge, LS Panel (2) 2-1/2"
 |-- Discharge, RS Panel (1) 2- 1/2" & (1) 3"
 |-- Discharge, Crosslays, (2) 1-1/2"
 |-- Discharge, Deck Gun, 3" Centered
 |-- Deck Gun Outlet Capped, Customer Supplies Gun

 Tank to Pump Line, 3"
 Tank Fill, 2-1/2" (Tanker)
 == Body / Tanker Tandem Axle - 1001.001 01/19/10 ==

 Water Tank 2500 Gallon, 20 Gallon Foam Cell
 |-- Warranty, Water/Foam Tank Lifetime
 |-- Gauge, Water Tank Level Indicator
 |-- Tank Fill, Rear Direct, 2-1/2"

 Subframe- Aluminum / Tanker Body
 |-- Body Construction / Material / Aluminum
 Body, 63-43 Low L / Low R, Tandem Axle
 |-- Doors, Roll-Up 63/43
 |-- Dump, 10" Newton S/S Rear, Manual Oper, for Poly Tnk
 |-- Dump, Elbow, 10" Newton

 |-- Ladder Bracket / Folding Tank / Hard Suction Hose
 |-- Folding Tank Storage, Flip Down, Manual LS
 |-- Hose, Soft Suction, 6" NST x 15' Couplings
 Hose Bed Divider, (1)
 Hose Bed Cover, Red w/Weighted Flap and Snaps

 Step, Rear 9" Intermediate
 Tailboard, 12" Deep
 Body Trim, Aluminum Diamondplate, Tankers
 Rubrail, with Reflective Stripe
 Vent, Compartment

DESCRIPTION

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Tanker Tandem Axle - 1001.001 01/19/10 ==

== Elec. Cmpts, T/A Tanker / Commercial - 1001.001 01/19/10

- |-- Electrical, 12 Volt Description
- |-- Warning Light System, NFPA
- |-- Warning Lights, Whelen Halogen Pkg, Commercial
 - |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
- |-- Reflectors NFPA/FMVSS Compliant
- |-- Lights, Clearance & Marker (7)
- |-- Lights, Side Running Board and Rear Step
- |-- Lights, Underbody
- |-- Light, Open Door Indicator, Flashing LED
- |-- Lights, Rear Deck Unity AG-S, 6"
- |-- Lights, Body Compartments
- |-- Lights, Midship Directional , 30'+ OAL
- |-- Light Bracket, License Plate
- |-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

- |-- Paint, Cab, Single Color 2-Door Cab
- |-- Paint, Chassis, Black
- |-- Paint, Body, Single Color
- |-- Finish, Compartment Interior, Zolatone Finish
- |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Tanker - 1001.001 01/19/10 ==

QUOTATION

American LaFrance

OHIO STS
\$292,828.00

American LaFrance Custom S/A Tanker
Side Mount Hale QPAK 750 Pump
Formed Aluminum Single Axle Tanker

07/26/2011

Quote No: ALF AE03-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==
== Metropolitan S/A Liberty Tanker - 1001.001 01/19/10 =
Certificate of Compliance, NFPA 1901
Chassis, Metropolitan Custom Crew, Flat Roof S/A Tanker

Engine, 2010 EPA Cummins ISC8.3 330HP
|-- Engine Brake, Cummins C-Brake , (1) Switch

Alternator, 270 Amp
Standard Engine Protection W/O De-rate

Front Axle, Meritor 18,000#, Package

Rear Axle, Single, Meritor 31,000#, Package
|-- Tires, Standard 315R Rear Drive
Rear Axle Ratio for 60 MPH Maximum

WABCO 4S/4M ABS With Out Traction Control

Wheels, Standard Steel Disc

Fenderette, Standard
Mirrors, Mekra, Black, 16" x 7" M2 Style

Steering Column, Tilt & Telescoping Adjustable
Air Conditioning Front and Rear
"Select" 12VDC Power Supplies
Seat, Air Ride Driver's
Seat, Non-Suspended High Back Officer's
Seats, Rear Facing SCBA, (2)
Seats, Forward Facing (2) ABTS SCBA, Rear Wall

SAFETY SYSTEMS, CUSTOM CHASSIS

Vehicle Data Recorder
Rollover Stability (Electronic Stability Control)
Seat Belt Warning System
Helmet Storage, Each Seating Position

DESCRIPTION

Tire Inflation Indicators, for Chassis w/Single Rear Axle

== Bumper Package / Custom - 1001.001 01/19/10 ==

Bumper, Front, Polished Stainless Steel

|-- Air Horns, Thru the Bumper Mtd. (2)

|-- Switch, Horn/Air Horn Selector, Cab Dash Mtd

|-- Siren, Electronic w/100 Watt Speaker

== Chassis Mods Custom - 1001.001 01/19/10 ==

Receptacle, 12V for Fire House Charging System

|-- Air Charging Connector, LS

Fuel Fill, Custom Chassis

Label, Fluid & Seating Capacity, Cab

Label, Overall Travel Height, Cab

Labels, Crew Area and Rear Body Step

== Pump / Enclosure / Tankers - 1001.001 01/19/10 ==

Testing, Third Party, Pumpers

Pump, QPAK 750 GPM

|-- Cooler, Engine, Custom or Commercial Chassis

|-- Cooler, Pump, Bypass Tank Fill

Pump Enclosure, S/M w/ Crosslays

|-- Crosslay Cover, Vinyl

|-- Running Boards, Non-Skid Aluminum Diamondplate

|-- Gauges, Master, 4-1/2", 30-0-600 PSI

|-- Gauge, Discharge 2-1/2" 30-0-600 Class 1

|-- Elec Interface w/Fast Idle System

|-- Piping, Class 1 HP Hose and Stainless Steel Pipe

|-- Inlet, Left Panel 2-1/2"

|-- Discharge, LS Panel (2) 2-1/2"

|-- Discharge, RS Panel (2) 2-1/2"

|-- Discharge, Crosslays, (2) 1-1/2"

|-- Discharge, Deck Gun, 3" Centered

|-- Deck Gun Outlet Capped, Customer Supplies Gun

Tank to Pump Line, 3"

Tank Fill, 2-1/2" (Tanker)

== Body / Tanker Single Axle - 1001.001 01/19/10 ==

Water Tank 2000 Gallon, 20 Gallon Foam Cell

|-- Warranty, Water/Foam Tank Lifetime

|-- Gauge, Water Tank Level Indicator

|-- Tank Fill, Rear Direct, 2-1/2"

Subframe- Aluminum / Tanker Body

|-- Body Construction / Material / Aluminum

Body, 74-23 Low L / Low R, Single Axle

|-- Doors, Roll-Up 74/23

|-- Dump, 10" Newton S/S Rear, Manual Oper, for Poly Tnk

|-- Dump, Elbow, 10" Newton

|-- Ladder Bracket / Folding Tank / Hard Suction Hose

|-- Ladder Brackets, Side Mtd, Above Cmpt.s RS

|-- Ladder Folding, Storage, Top of Cmpt.s RS

|-- Folding Tank Storage, Flip Down, Manual LS

|-- Hose, Soft Suction, 6" NST x 15' Couplings

DESCRIPTION

Hose Bed Divider, (1)
Hose Bed Cover, Red w/Weighted Flap and Snaps

Step, Rear 9" Intermediate
Tailboard, 12" Deep
Body Trim, Aluminum Diamondplate, Pumpers
Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Tanker - 1001.001 01/19/10 ==

== Elec. Cmpts, S/A Tanker / Custom - 1001.001 01/19/10 ==

- |-- Electrical, 12 Volt Description
- |-- Warning Light System, NFPA
- |-- Warning Lights, Liberty Pumper, Whelen Halo Pkg
 - |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
- |-- Reflectors NFPA/FMVSS Compliant
- |-- Lights, Clearance & Marker (7)
- |-- Lights, Side Running Board and Rear Step
- |-- Lights, Underbody
- |-- Light, Open Door Indicator, Flashing LED
- |-- Lights, Rear Deck Unity AG-S, 6"
- |-- Lights, Body Compartments
- |-- Lights, Midship Directional , 30'+ OAL
- |-- Light Bracket, License Plate
- |-- Back-Up Alarm, Liberty

- |-- Painting, Alm Body, Pumper/Rescue/Tanker Custom
 - |-- Paint, Cab, Single Color 4-Door Cab (Liberty Standard Color)
 - |-- Paint, Chassis, Black
 - |-- Paint, Body, Single Color
 - |-- Finish, Compartment Interior, Zolatone Finish
 - |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Tanker - 1001.001 01/19/10 ==

QUOTATION

American LaFrance

OHIO STS

\$314,179.00

American LaFrance Custom T/A Tanker
Side Mount Hale QPAK 750 Pump
Formed Aluminum Tandem Axle Tanker Body

07/26/2011

Quote No: ALF AE04-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==
== Metropolitan T/A Liberty Tanker - 1001.001 01/19/10 =
Certificate of Compliance, NFPA 1901
Chassis, Metropolitan Custom Crew, Flat Roof T/A Tanker

Engine, 2010 EPA Cummins ISC8.3 330HP
|-- Engine Brake, Cummins C-Brake , (1) Switch

Alternator, 270 Amp
Standard Engine Protection W/O De-rate

Front Axle, Meritor 18,000#, Package

Rear Axle, Tandem, Meritor 46,000#, Package
|-- Tires, Standard 11R Rear Drive
Rear Axle Ratio for 60 MPH Maximum

WABCO 4S/4M ABS With Out Traction Control

Wheels, Standard Steel Disc

Fenderette, Standard
Mirrors, Mekra, Black, 16" x 7" M2 Style

Steering Column, Tilt & Telescoping Adjustable
Air Conditioning Front and Rear
"Select" 12VDC Power Supplies
Seat, Air Ride Driver's
Seat, Non-Suspended High Back Officer's
Seats, Rear Facing SCBA, (2)
Seats, Forward Facing (2) ABTS SCBA, Rear Wall

SAFETY SYSTEMS, CUSTOM CHASSIS

Vehicle Data Recorder
Rollover Stability (Electronic Stability Control)
Seat Belt Warning System
Helmet Storage, Each Seating Position

DESCRIPTION

Tire Inflation Indicators, for Chassis w/Tandem Rear Axles

== Bumper Package / Custom - 1001.001 01/19/10 ==

Bumper, Front, Polished Stainless Steel

|-- Air Horns, Thru the Bumper Mtd. (2)

|-- Switch, Horn/Air Horn Selector, Cab Dash Mtd

|-- Siren, Electronic w/100 Watt Speaker

== Chassis Mods Custom - 1001.001 01/19/10 ==

Receptacle, 12V for Fire House Charging System

|-- Air Charging Connector, LS

Fuel Fill, Custom Chassis

Label, Fluid & Seating Capacity, Cab

Label, Overall Travel Height, Cab

Labels, Crew Area and Rear Body Step

== Pump / Enclosure / Tankers - 1001.001 01/19/10 ==

Testing, Third Party, Pumpers

Pump, QPAK 750 GPM

|-- Cooler, Engine, Custom or Commercial Chassis

|-- Cooler, Pump, Bypass Tank Fill

Pump Enclosure, S/M w/ Crosslays

|-- Crosslay Cover, Vinyl

|-- Running Boards, Non-Skid Aluminum Diamondplate

|-- Gauges, Master, 4-1/2", 30-0-600 PSI

|-- Gauge, Discharge 2-1/2" 30-0-600 Class 1

|-- Elec Interface w/Fast Idle System

|-- Piping, Class 1 HP Hose and Stainless Steel Pipe

|-- Inlet, Left Panel 2-1/2"

|-- Discharge, LS Panel (2) 2-1/2"

|-- Discharge, RS Panel (1) 2- 1/2" & (1) 3"

|-- Discharge, Crosslays, (2) 1-1/2"

|-- Discharge, Deck Gun, 3" Centered

|-- Deck Gun Outlet Capped, Customer Supplies Gun

Tank to Pump Line, 3"

Tank Fill, 2-1/2" (Tanker)

== Body / Tanker Tandem Axle - 1001.001 01/19/10 ==

Water Tank 2500 Gallon, 20 Gallon Foam Cell

|-- Warranty, Water/Foam Tank Lifetime

|-- Gauge, Water Tank Level Indicator

|-- Tank Fill, Rear Direct, 2-1/2"

Subframe- Aluminum / Tanker Body

|-- Body Construction / Material / Aluminum

Body, 63-43 Low L / Low R, Tandem Axle

|-- Doors, Roll-Up 63/43

|-- Dump, 10" Newton S/S Rear, Manual Oper, for Poly Tnk

|-- Dump, Elbow, 10" Newton

|-- Ladder Bracket / Folding Tank / Hard Suction Hose

|-- Ladder Brackets, Side Mtd, Above Cmpt.s RS

|-- Ladder Folding, Storage, Top of Cmpt.s RS

|-- Folding Tank Storage, Flip Down, Manual LS

|-- Hose, Soft Suction, 6" NST x 15' Couplings

DESCRIPTION

Hose Bed Divider, (1)
Hose Bed Cover, Red w/Weighted Flap and Snaps

Step, Rear 9" Intermediate
Tailboard, 12" Deep
Body Trim, Aluminum Diamondplate, Tankers
Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Tanker Tandem Axle - 1001.001 01/19/10 ==

== Elec. Cmpts, T/A Tanker / Custom - 1001.001 01/19/10 ==

- |-- Electrical, 12 Volt Description
- |-- Warning Light System, NFPA
- |-- Warning Lights, Liberty Pumper, Whelen Halo Pkg
 - |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
- |-- Reflectors NFPA/FMVSS Compliant
- |-- Lights, Clearance & Marker (7)
- |-- Lights, Side Running Board and Rear Step
- |-- Lights, Underbody
- |-- Light, Open Door Indicator, Flashing LED
- |-- Lights, Rear Deck Unity AG-S, 6"
- |-- Lights, Body Compartments
- |-- Lights, Midship Directional , 30'+ OAL
- |-- Light Bracket, License Plate
- |-- Back-Up Alarm, Liberty

- |-- Painting, Alm Body, Pumper/Rescue/Tanker Custom
 - |-- Paint, Cab, Single Color 4-Door Cab (Liberty Standard Color)
 - |-- Paint, Chassis, Black
 - |-- Paint, Body, Single Color
 - |-- Finish, Compartment Interior, Zolatone Finish
 - |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Tanker - 1001.001 01/19/10 ==

QUOTATION

American LaFrance

OHIO STS
\$229,089.00

American LaFrance 2 Door Navistar S/A Tanker
Side Mount Hale QPAK 750 Pump
Formed Aluminum Single Axle Tanker Body

07/26/2011

Quote No: ALF AE05-

Page 1

DESCRIPTION

Certificate of Compliance, NFPA 1901
Chassis, Navistar 2 Door DuraStar, 4400 Series

Engine,MaxxForce DT300HP

Standard Engine Protection W/O De-rate

Front Axle, 14,600#, Package

Rear Axle, Single, 30,000#, Package
|-- Tires, Standard 315R Rear Drive
Rear Axle Ratio for 68 MPH Maximum

Dust Shields, Single Axle, Front and Rear Brakes

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Chromed Plastic Hood Mounted
Mirrors, Dual Bright Heated West Coast, LH/RH Remote

Steering Column, Tilt & Telescoping Adjustable
Daytime Running Lights
Power Supply 12VDC (1)
Seat, Non-Suspended Driver's
Seat, Non Suspension Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder
Rollover Stability, Commercial Chassis
Seatbelt Warning System
Helmet Storage, Each Seating Position
Tire Inflation Indicators, for Chassis w/Single Rear Axle
== Bumper Package / M2 - 1001.001 01/19/10 ==
Bumper, Front, Chrome
|-- Air Horns, Hood Mounted
|-- Switches, Air Horn (1) Driver / (1) Officer

DESCRIPTION

|-- Siren, Electronic w/100 Watt Speaker
 == Chassis Mods M2 - 1001.001 01/19/10 ==
 Light, Engine Compartment
 Battery "On" Light, Green
 Receptacle, 12V for Fire House Charging System
 |-- Air Charging Connector, LS
 Label, Fluid & Seating Capacity, Cab
 Label, Overall Travel Height, Cab
 Labels, Crew Area and Rear Body Step
 == Pump / Enclosure / Tankers - 1001.001 01/19/10 ==
 Testing, Third Party, Pumpers
 Pump, QPAK 750 GPM
 |-- Cooler, Engine, Custom or Commercial Chassis
 |-- Cooler, Pump, Bypass Tank Fill
 Pump Enclosure, S/M w/ Crosslays
 |-- Crosslay Cover, Vinyl
 |-- Running Boards, Non-Skid Aluminum Diamondplate
 |-- Gauges, Master, 4-1/2", 30-0-600 PSI
 |-- Gauge, Discharge 2-1/2" 30-0-600 Class 1
 |-- Elec Interface w/Fast Idle System
 |-- Piping, Class 1 HP Hose and Stainless Steel Pipe

 |-- Inlet, Left Panel 2-1/2"

 |-- Discharge, LS Panel (2) 2-1/2"
 |-- Discharge, RS Panel (1) 2- 1/2" & (1) 3"
 |-- Discharge, Crosslays, (2) 1-1/2"
 |-- Discharge, Deck Gun, 3" Centered
 |-- Deck Gun Outlet Capped, Customer Supplies Gun

 Tank to Pump Line, 3"
 Tank Fill, 2-1/2" (Tanker)
 == Body / Tanker Single Axle - 1001.001 01/19/10 ==

 Water Tank 2000 Gallon, 20 Gallon Foam Cell
 |-- Warranty, Water/Foam Tank Lifetime
 |-- Gauge, Water Tank Level Indicator
 |-- Tank Fill, Rear Direct, 2-1/2"

 Subframe- Aluminum / Tanker Body
 |-- Body Construction / Material / Aluminum
 Body, 74-23 Low L / Low R, Single Axle
 |-- Doors, Roll-Up 74/23
 |-- Dump, 10" Newton S/S Rear, Manual Oper, for Poly Trnk
 |-- Dump, Elbow, 10" Newton

 |-- Ladder Bracket / Folding Tank / Hard Suction Hose
 |-- Folding Tank Storage, Flip Down, Manual LS
 |-- Hose, Soft Suction, 6" NST x 15' Couplings
 Hose Bed Divider, (1)
 Hose Bed Cover, Red w/Weighted Flap and Snaps

 Step, Rear 9" Intermediate
 Tailboard, 12" Deep

DESCRIPTION

Body Trim, Aluminum Diamondplate, Pumpers
Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Tanker - 1001.001 01/19/10 ==

== Elec. Cmpts, S/A Tanker / Commercial - 1001.001 01/19/10

- |-- Electrical, 12 Volt Description
- |-- Warning Light System, NFPA
- |-- Warning Lights, Whelen Halogen Pkg, Commercial
 - |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
- |-- Reflectors NFPA/FMVSS Compliant
- |-- Lights, Clearance & Marker (7)
- |-- Lights, Side Running Board and Rear Step
- |-- Lights, Underbody
- |-- Light, Open Door Indicator, Flashing LED
- |-- Lights, Rear Deck Unity AG-S, 6"
- |-- Lights, Body Compartments
- |-- Lights, Midship Directional , 30'+ OAL
- |-- Light Bracket, License Plate
- |-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

- |-- Paint, Cab, Single Color 2-Door Cab
- |-- Paint, Chassis, Black
- |-- Paint, Body, Single Color
- |-- Finish, Compartment Interior, Zolatone Finish
- |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Tanker - 1001.001 01/19/10 ==

QUOTATION

American LaFrance

OHIO STS
\$278,346.00

American LaFrance 2 Door Navistar T/A Tanker
Side Mount Hale QPAK 750 Pump
Formed Aluminum Tandem Axle Tanker Body

07/26/2011

Quote No: ALF AE06-

Page 1

DESCRIPTION

== SELECT BOILERPLATE - 1001.001 01/19/10 ==

Certificate of Compliance, NFPA 1901

Chassis, Navistar 2 Door WorkStar, 7600 Series

Engine, MaxxForce 13, 410HP

Standard Engine Protection W/O De-rate

Front Axle, 18,000#, Package

Rear Axle, Tandem, 46,000#, Package

|-- Tires, Standard 11R Rear Drive

Rear Axle Ratio for 60 MPH Maximum

Dust Shields, Tandem Axles, Front and Rear Brakes

Differential Lock, Driver Controlled, Forward, Tandem Axle

WABCO 4S/4M ABS With Traction Control & ESC

Wheels, Standard Steel Disc

Grille, Chromed Plastic Hood Mounted

Mirrors, Dual Bright Heated West Coast, LH/RH Remote

Steering Column, Tilt & Telescoping Adjustable

Daytime Running Lights

Power Supply 12VDC (1)

Seat, Non-Suspended Driver's

Seat, Non Suspension Officer's

SAFETY SYSTEMS, COMMERCIAL CHASSIS

Vehicle Data Recorder

Rollover Stability, Commercial Chassis

Seatbelt Warning System

Helmet Storage, Each Seating Position

Tire Inflation Indicators, for Chassis w/Tandem Rear Axle

== Bumper Package / M2 - 1001.001 01/19/10 ==

Bumper, Front, Chrome

|-- Air Horns, Hood Mounted

|-- Switches, Air Horn (1) Driver / (1) Officer

DESCRIPTION

|-- Siren, Electronic w/100 Watt Speaker
== Chassis Mods M2 - 1001.001 01/19/10 ==
Light, Engine Compartment
Battery "On" Light, Green
Receptacle, 12V for Fire House Charging System
|-- Air Charging Connector, LS
Label, Fluid & Seating Capacity, Cab
Label, Overall Travel Height, Cab
Labels, Crew Area and Rear Body Step
== Pump / Enclosure / Tankers - 1001.001 01/19/10 ==
Testing, Third Party, Pumpers
Pump, QPAK 750 GPM
|-- Cooler, Engine, Custom or Commercial Chassis
|-- Cooler, Pump, Bypass Tank Fill
Pump Enclosure, S/M w/ Crosslays
|-- Crosslay Cover, Vinyl
|-- Running Boards, Non-Skid Aluminum Diamondplate
|-- Gauges, Master, 4-1/2", 30-0-600 PSI
|-- Gauge, Discharge 2-1/2" 30-0-600 Class 1
|-- Elec Interface w/Fast Idle System
|-- Piping, Class 1 HP Hose and Stainless Steel Pipe

|-- Inlet, Left Panel 2-1/2"

|-- Discharge, LS Panel (2) 2-1/2"
|-- Discharge, RS Panel (1) 2- 1/2" & (1) 3"
|-- Discharge, Crosslays, (2) 1-1/2"
|-- Discharge, Deck Gun, 3" Centered
|-- Deck Gun Outlet Capped, Customer Supplies Gun

Tank to Pump Line, 3"
Tank Fill, 2-1/2" (Tanker)
== Body / Tanker Tandem Axle - 1001.001 01/19/10 ==

Water Tank 2500 Gallon, 20 Gallon Foam Cell
|-- Warranty, Water/Foam Tank Lifetime
|-- Gauge, Water Tank Level Indicator
|-- Tank Fill, Rear Direct, 2-1/2"

Subframe- Aluminum / Tanker Body
|-- Body Construction / Material / Aluminum
Body, 63-43 Low L / Low R, Tandem Axle
|-- Doors, Roll-Up 63/43
|-- Dump, 10" Newton S/S Rear, Manual Oper, for Poly Trnk
|-- Dump, Elbow, 10" Newton

|-- Ladder Bracket / Folding Tank / Hard Suction Hose
|-- Folding Tank Storage, Flip Down, Manual LS
|-- Hose, Soft Suction, 6" NST x 15' Couplings
Hose Bed Divider, (1)
Hose Bed Cover, Red w/Weighted Flap and Snaps

Step, Rear 9" Intermediate
Tailboard, 12" Deep

DESCRIPTION

Body Trim, Aluminum Diamondplate, Tankers
Rubrail, with Reflective Stripe
Vent, Compartment

Hand Rails, Body
Steps, Folding (4)
Tow Eyes, Rear
Mud Flaps, Rear Axle (2)
== Cmpnt.s Tanker Tandem Axle - 1001.001 01/19/10 ==

== Elec. Cmpts, T/A Tanker / Commercial - 1001.001 01/19/10

- |-- Electrical, 12 Volt Description
- |-- Warning Light System, NFPA
- |-- Warning Lights, Whelen Halogen Pkg, Commercial
 - |-- Lights, Tail/Turn/Backup w/ Warning Lights-Halogen
- |-- Reflectors NFPA/FMVSS Compliant
- |-- Lights, Clearance & Marker (7)
- |-- Lights, Side Running Board and Rear Step
- |-- Lights, Underbody
- |-- Light, Open Door Indicator, Flashing LED
- |-- Lights, Rear Deck Unity AG-S, 6"
- |-- Lights, Body Compartments
- |-- Lights, Midship Directional , 30'+ OAL
- |-- Light Bracket, License Plate
- |-- Back-Up Alarm, Code 3 Model D50C Constant 97 DB

|-- Painting, Alm Body, Pumper/Rescue/Tanker Com 2-Door

- |-- Paint, Cab, Single Color 2-Door Cab
- |-- Paint, Chassis, Black
- |-- Paint, Body, Single Color
- |-- Finish, Compartment Interior, Zolatone Finish
- |-- Undercoating

- |-- Letters, (60) Scotchlite Reflective, 3"
- |-- Striping, Reflective 4" NFPA
- |-- Chevron, Reflective NFPA

== Equipment Package / Tanker - 1001.001 01/19/10 ==

AMERICAN LAFRANCE			
Product Code	Option Code	Option Description	Offered Price
		<u>CHASSIS OPTIONS</u>	
AB	AB0101	F-350 Standard Cab 6.2 V-8 Gasoline Engine	(\$6,125.00)
AB	AB0102	F-450 2 Door Extended Cab 6.8 V-10 Gasoline Engine	\$2,185.00
AB	AB0103	F-450 4 Door Crew Cab 6.8 V-10 Gasoline Engine	\$3,470.00
AB	AB0104	F-350 Standard Cab 6.7 V-8 Diesel Engine	\$178.00
AB	AB0105	F-450 2 Door Standard Cab 6.7 V-8 Diesel Engine	\$7,612.00
AB	AB0106	F-450 2 Door Extended Cab 6.7 V-8 Diesel Engine	\$9,740.00
AB	AB0107	F-450 4 Door Crew Cab 6.7 V-8 Diesel Engine	\$11,083.00
AB	486114	Aluminum Wheels - (4)	\$2,052.00
AB	MAPBX	Console, Map Box	\$1,080.00
AB	10D2650	Nerf Bars, 2-Door	\$594.00
AB	10D2660	Nerf Bars, 4-Door	\$644.00
AB	AB0108	Wheel Covers, Polished Stainless Steel	\$486.00
AB	AB0109	Two Tone Cab, One Color, Paint 2 Door Cab	\$3,240.00
AB	AB0110	Two Tone Cab, One Color, Paint 4 Door Cab	\$4,100.00
AB	80A424	Two Tone Cab Color, Two Colors, Paint (Not Ford) (Black or White Chassis Only)	\$6,480.00
AB	AB0111	Trailer Hitch, 2 1/2" Receiver Tube with & Blade Female Plug	\$702.00
		<u>COMPARTMENTATION AND HOSE BED OPTIONS/CHANGES</u>	
AB	AB0112	Preconnect Hose Lay - 1 1/2 Elkhart Valve	\$918.00
AB	AB0113	Preconnect Hose Lay - 1 1/2 Akron Valve	\$958.00
AB	AB0114	Aluminum Tread Plate Hose Bed Compartment with Aluminum Tread Plate Cover	\$2,430.00
		<u>FIRE PUMP, AND PLUMBING OPTIONS/CHANGES</u>	
AB	AB0115	Hale HP275 35HP Gasoline Powered Pump (Gasoline Chassis)	\$3,780.00
AB	AB0116	Darley 2 1/2 AGE 26HP Diesel Engine Powered Pump Diesel Chassis)	\$7,560.00
AB	AB0117	Remote Start for Pump In Cab	\$1,080.00
AB	FBT	Front Bumper Turret	\$8,640.00
AB	AB0118	Hour Meter	\$295.00
AB	AB0119	Exhaust Heat Shield	\$216.00
AB	AB0120	Up-Grade to Elkhart Valves	\$1,140.00

AB	ABX01	Custom plumbing in addition to standard	\$8,500.00
AB	AB0121	Up-Grade to Akron Valves	\$1,455.00
		<u>BOOSTER TANKS, FOAM SYSTEMS OPTIONS/CHANGES</u>	
AB	AB0122	Decrease Size of Tank from Base to 225 Gallon	(\$150.00)
AB	AB0123	Blizzard Wizard Class "A" Round the Pump Foam System with 8 Gallon Tank	\$1,398.00
AB	ABX02	Custom/Special tank configuration	\$3,000.00
AB	AB0124	FoamPro 1601 Class A Foam System with 8 Gallon Tank	\$8,532.00
		<u>CHASSIS AND BODY OPTIONS/CHANGES</u>	
AB	AB0125	Adjustable Compartment Shelf	\$324.00
AB	AB0126	Slide-Out Compartment Tray.	\$864.00
		<u>HOSE REEL OPTIONS</u>	
AB	AB0127	Up-Grade to a Hannay Polished Aluminum Reel	\$486.00
		<u>WINCH SYSTEMS</u>	
AB	AB0128	Winch, Warn 12,000 lb capacity with polished Stainless Steel Brush Guard	\$4,320.00
AB	AB0129	Winch, Warn 9,500 lb capacity Multi-Mount with Polished S.S. Brush Guard	\$4,590.00
PUBLISHED OPTIONS OFFERED			
PRODUCT CODE	OPTION CODE	OPTION DESCRIPTION	Offered Price
		<u>CHASSIS OPTIONS</u>	
AB	AB0201	F-550 2 Door Extended Cab 6.8 V-10 Gasoline Engine	\$3,123.00
AB	AB0202	F-550 4 Door Crew Cab 6.8 V-10 Gasoline Engine	\$4,196.00
AB	AB0203	F-550 2 Door Standard Cab 6.7 V-8 Diesel Engine	\$8,617.00
AB	AB0204	F-550 2 Door Extended Cab 6.7 V-8 Diesel Engine	\$10,736.00
AB	AB0205	F-550 4 Door Crew Cab 6.7 V-8 Diesel Engine	\$11,809.00
AB	486114	Aluminum Wheels - (4)	\$2,052.00
AB	MAPBX	Console, Map Box	\$1,080.00
AB	10D2650	Nerf Bars, 2-Door	\$594.00
AB	10D2660	Nerf Bars, 4-Door	\$644.00
AB	AB0206	Wheel Covers, Polished Stainless Steel	\$486.00
AB	AB0207	Two Tone Cab, One Color, Paint 2 Door Cab	\$3,240.00
AB	AB0208	Two Tone Cab, One Color, Paint 4 Door Cab	\$4,100.00
AB	80A424	Two Tone Cab Color, Two Colors, Paint (Not Ford) (Black or White Chassis Only)	\$6,480.00

AB	AB0209	Trailer Hitch, 2 1/2" Reciever Tube with & Blade Female Plug	\$702.00
		<u>COMPARTMENTATION AND HOSE BED OPTIONS/CHANGES</u>	
AB	AB0210	Preconnect Hose Lay - 1 1/2 Apollo Valve	\$810.00
AB	AB0211	Preconnect Hose Lay - 1 1/2 Elkhart Valve	\$918.00
AB	AB0212	Preconnect Hose Lay - 1 1/2 Akron Valve	\$958.00
AB	AB0213	Aluminum Tread Plate Hose Bed Compartment with Aluminum Tread Plate Cover	\$2,430.00
		<u>FIRE PUMP, AND PLUMBING OPTIONS/CHANGES</u>	
AB	AB0214	Hale HPXB-200 18HP Gasoline Powered Pump (Gasoline or Diesel Chassis)	(\$3,780.00)
AB	AB0215	Darley 2 1/2 AGE 26HP Diesel Engine Powered Pump (Diesel Chassis)	\$7,560.00
AB	AB0216	Remote Start for Pump In Cab	\$1,080.00
AB	FBT	Front Bumper Turret	\$8,640.00
AB	AB0217	Hour Meter	\$295.00
AB	AB0218	Exhaust Heat Shield	\$216.00
AB	AB0219	Up-Grade to Elkhart Valves	\$1,140.00
AB	AB0220	Up-Grade to Akron Valves	\$1,455.00
		<u>BOOSTER TANKS, FOAM SYSTEMS OPTIONS/CHANGES</u>	
AB	AB0221	Decrease Size of Tank from Base to 225 Gallon	(\$150.00)
AB	AB0222	Blizzard Wizard Class "A" Round the Pump Foam System with 8 Gallon Tank	\$1,398.00
AB	AB0223	FoamPro 1601 Class A Foam System with 8 Gallon Tank	\$8,532.00
		<u>CHASSIS AND BODY OPTIONS/CHANGES</u>	
AB	AB0224	Adjustable Compartment Shelf	\$324.00
AB	AB0225	Adjustable Transverse Compartment Shelf	\$540.00
AB	AB0226	Slide-Out Compartment Tray.	\$864.00
		<u>HOSE REEL OPTIONS</u>	
AB	AB0227	Up-Grade to a Hannay Polished Aluminum Reel	\$486.00
		<u>WINCH SYSTEMS</u>	
AB	AB0228	Winch, Warn 12,000 lb capacity with polished Stainless Steel Brush Guard	\$4,320.00
AB	AB0229	Winch, Warn 9,500 lb capacity Multi-Mount with Polished S.S. Brush Guard	\$4,590.00
PUBLISHED OPTIONS OFFERED			
PRODUCT CODE	OPTION CODE	OPTION DESCRIPTION	Offered Price
		<u>CHASSIS OPTIONS</u>	

AB	AB0301	F-550 2 Door Standard Cab 6.8 V-10 Gasoline Engine	(\$10,935.00)
AB	AB0302	F-550 2 Door Extended Cab 6.8 V-10 Gasoline Engine	(\$8,043.00)
AB	AB0303	F-550 4 Door Crew Cab 6.8 V-10 Gasoline Engine	(\$7,049.00)
AB	AB0304	F-550 2 Door Standard Cab 6.7 V-8 Diesel Engine	(\$2,956.00)
AB	AB0305	F-550 2 Door Extended Cab 6.7 V-8 Diesel Engine	(\$994.00)
AB	486114	Aluminum Wheels - (4)	\$2,052.00
AB	10D2650	Nerf Bars, 2-Door	\$594.00
AB	10D2660	Nerf Bars, 4-Door	\$644.00
AB	AB0306	Two Tone Cab, One Color, Paint 2 Door Cab	\$3,240.00
AB	AB0307	Two Tone Cab, One Color, Paint 4 Door Cab	\$4,100.00
AB	80A424	Two Tone Cab Color, Two Colors, Paint (Not Ford) (Black or White Chassis Only)	\$6,480.00
AB	AB0308	Trailer Hitch, 2 1/2" Reciever Tube with & Blade Female Plug	\$702.00
		<u>COMPARTMENTATION AND HOSE BED OPTIONS/CHANGES</u>	
AB	AB0309	Preconnect Hose Lay - 1 1/2 Elkhart Valve	\$918.00
AB	AB0310	Preconnect Hose Lay - 1 1/2 Akron Valve	\$958.00
		<u>FIRE PUMP, AND PLUMBING OPTIONS/CHANGES</u>	
AB	AB0311	Hale HPXB-200 18HP Gasoline Powered Pump (Gasoline or Diesel Chassis)	(\$7,000.00)
AB	AB0312	Hale HP275 35HO Vanguard Gasoline Powered Pump	(\$3,500.00)
AB	FBT	Front Bumper Turret	\$8,640.00
		<u>BOOSTER TANKS, FOAM SYSTEMS OPTIONS/CHANGES</u>	
AB	AB0313	Decrease Size of Tank from Base to 225 Gallon	(\$150.00)
AB	AB0314	Blizzard Wizard Class "A" Round the Pump Foam System with 8 Gallon Tank	\$1,398.00
AB	AB0315	FoamPro 1601 Class A Foam System with 8 Gallon Tank	\$8,532.00
		<u>CHASSIS AND BODY OPTIONS/CHANGES</u>	
AB	AB0316	Adjustable Compartment Shelf	\$324.00
AB	AB0317	Adjustable Transverse Compartment Shelf	\$540.00
AB	AB0318	Slide-Out Compartment Tray.	\$864.00
		<u>WINCH SYSTEMS</u>	
AB	AB0319	Winch, Warn 12,000 lb capacity with polished Stainless Steel Brush Guard	\$4,320.00
AB	AB0320	Winch, Warn 9,500 lb capacity Multi-Mount with Polished S.S. Brush Guard	\$4,590.00
		<u>SCENE LIGHT OPTIONS</u>	
AB	AB0321	Extendable Scene Lights, 12 Volt 300 Watt with ATP Covers (1Pair)	\$2,430.00

AB	AB0322	Extendable Scene Lights, 12 Volt 150 Watt HID with ATP Covers (1 Pair)	\$2,700.00
		<u>Generator Options</u>	
AB	AB0323	Honda (EU3000iS) 3000 Watt Generator	\$2,980.00
AB	AB0324	Pull-out Tray for Generator	\$810.00
PUBLISHED OPTIONS OFFERED			
PRODUCT CODE	OPTION CODE	OPTION DESCRIPTION	Offered Price
		<u>CHASSIS OPTIONS</u>	
AB	AB0401	F-550 2 Door Standard Cab 6.8 V-10 Gasoline Engine (Gasoline Pump Option Only)	(\$7,049.00)
AB	486114	Aluminum Wheels - (4)	\$2,052.00
AB	10D2650	Nerf Bars, 2-Door	\$594.00
AB	10D2660	Nerf Bars, 4-Door	\$644.00
AB	AB0402	Two Tone Cab, One Color, Paint 2 Door Cab	\$3,240.00
AB	80A424	Two Tone Cab Color, Two Colors, Paint (Not Ford) (Black or White Chassis Only)	\$6,480.00
AB	AB0403	Trailer Hitch, 2 1/2" Reciever Tube with & Blade Female Plug	\$702.00
		<u>FIRE PUMP, AND PLUMBING OPTIONS/CHANGES</u>	
AB	AB0404	Hale HPXB-200 18HP Gasoline Powered Pump (Gasoline or Diesel Chassis)	(\$7,000.00)
AB	AB0405	Hale HP275 35HO Vanguard Gasoline Powered Pump	(\$3,500.00)
AB	FBT	Front Bumper Turret	\$8,640.00
		<u>BOOSTER TANKS, FOAM SYSTEMS OPTIONS/CHANGES</u>	
AB	AB0406	Decrease Size of Tank from Base to 225 Gallon	(\$150.00)
AB	AB0407	Blizzard Wizard Class "A" Round the Pump Foam System with 8 Gallon Tank	\$1,398.00
AB	AB0408	FoamPro 1601 Class A Foam System with 8 Gallon Tank	\$8,532.00
		<u>CHASSIS AND BODY OPTIONS/CHANGES</u>	
AB	AB0409	Adjustable Compartment Shelf	\$324.00
AB	AB0410	Adjustable Transverse Compartment Shelf	\$540.00
AB	AB0411	Slide-Out Compartment Tray.	\$864.00
AB	ABX03	Custom/Special body configuration	\$9,856.00
AB	AB0412	Pull-out Tool Boards	\$1,728.00
		<u>WINCH SYSTEMS</u>	
AB	AB0413	Winch, Warn 12,000 lb capacity with polished Stainless Steel Brush Guard	\$4,320.00
AB	AB0414	Winch, Warn 9,500 lb capacity Multi-Mount with Polished S.S. Brush Guard	\$4,590.00

		<u>SCENE LIGHT OPTIONS</u>	
AB	AB0415	Extendable Scene Lights, 12 Volt 300 Watt with ATP Covers (1Pair)	\$2,430.00
AB	AB0416	Extendable Scene Lights, 12 Volt 150 Watt HID with ATP Covers (1 Pair)	\$2,700.00
AB	AB0417	Extendable Scene Lights, 120 Volt 750 Watt with ATP Covers (1 Pair)	\$2,430.00
		<u>Generator Options</u>	
AB	AB0418	Honda (EU3000iS) 3000 Watt Generator	\$2,980.00
AB	AB0419	Pull-out Tray for Generator	\$810.00
AB	AB0420	Onan 5500 Watt Quiet Diesel Generator w/ 4 Switch Breaker Box and Two Outlets	
AB	AB0421	Onan 12,000 Watt Quiet Diesel Generator w/ 8 Switch Breaker Box and Two Outlets	