



OHIO/DAS
State Term Schedule
Price List
2013

Effective 2013






Surface Mounted Lifts

STS
Effective
2013


Conventional / Two-Post / Asymmetric

	MODEL NUMBER	DESCRIPTION	*RISE	CAPACITY	STS PRICE
	SPOA10	Surface Mounted, Frame Contact Lift. Electric-Hydraulic Operation. True Asymmetrical Design For Easy Vehicle Entry. Factory Rotated Columns Allow Doors Of Vehicle To Be Fully Opened While Properly Positioned On Lift. Arm Restraints -- All Arms.	78" (1981 mm)	10,000 lbs. (4536 kg)	\$3,731.15
	SPOA10 with 3-stage RA arms	Same as SPOA10 with 3-stage FRONT arms. The NEW 3-stage arms allow for an increase in overall arm sweep and minimum arm reach to precisely lift vehicles that are: • Primarily Uni-body construction; • Visually marked OE designated pick-up points on the vehicle; • Wider stance and lower profile; • Accommodates short and long wheelbase vehicles			\$3,937.36
	SPOA10 with 3-stage TA arms	Same as SPOA10 with 3-stage FRONT arms and truck adapters. Primarily for use with fram vehicles (For RA adapters also order FJ6225).			\$3,937.36

Shockwave Equipped/ Two-Post Lift Options

	SPOA10-RASW	Same as SPOA10-RA 2-Post lift only Shockwave Equipped. Standard with 3-Stage FRONT arms, round adapters. Primarily used on unibody vehicles.	83" (2115 mm)	10,000 lbs. (4536 kg)	\$5,362.78
	SPOA10-TASW	Same as SPOA10-TA 2-Post lift only Shockwave Equipped. Standard with 3-Stage FRONT arms, truck adapters. Primarily used on framed vehicles.			\$5,362.78

Conventional / Two-Post / Symmetric

	SPO10	Surface Mounted, Frame Contact Lift. Overhead Equalization System. Electric-Hydraulic Operation. Arm Restraints-All Arms	78" (1981 mm)	10,000 lbs. (4536 kg)	\$3,731.15
	SPO10-RA	Same as SPO10 With Front and Rear 3 Stage Arms with FJ6214 Thread-Up RA Truck Comes with (4) FJ6171-1 Extensions 3 1/2" Tall and (4) FJ6171-2 Extensions 5" Tall			\$4,219.58
	SPO10-TA	Same as SPO10 With Front and Rear 3 Stage Arms Truck Adapter. Comes with (4) FJ6171-1 Extensions 3 1/2" Tall and (4) FJ6171-2 Extensions 5" Tall.			\$4,219.58
	SPO12-TALC	Surface Mounted, Frame Contact Lift For Low Ceiling Application. Overhead Equalization System, Arm Restraints-All Arms, Electric-Hydraulic Operation. Comes with Truck Adapter.	78" (1981 mm)	12,000 lbs. (5443 kg)	\$6,122.84
	SPO12-TA	Surface Mounted Frame Contact Lift With Front and Rear 3 Stage Arms with FJ6214 Thread-Up Adapter and (4) FJ6171-1 Extensions 3 1/2" Tall and (4) FJ6171-2 Extensions 5" Tall	81 1/16" (2059 mm)		\$5,840.63
	SPO15	Surface Mounted, Frame Contact Lift. Clear Floor, Arm Restraints-All Arms, Electric-Hydraulic Operation With Overhead Adjustments of 15 ft. 6 in., 16 ft., and 16 ft. 6 in. Includes Air Operated Single Point Release Locking Latches. Comes With Slack Cables.	89 1/2" (2273 mm)	15,000 lbs. (6804 kg)	\$10,875.09
	SPO15-LC	Same as above-With Overhead Adjustments of 13 ft. 6 in. and 14 ft. 6 in.			
	FJ5115	Aircraft Tug Adapters. Converts An SPO15 Lift From A Vehicle Lift Into A 14,000LBS. Air TugLift. Kit Contans Two Cross Beams And Adapters			\$1,895.17
	SPO18	Surface Mounted, Frame Contact Lift. Clear Floor, Arm Restraints-All Arms, Electric-Hydraulic Operation With Overhead Adjustments of 15 ft. 6 in., 16 ft., and 16 ft. 6 in. Includes Air Operated Single Point Release Locking Latches. Comes With Slack Cables.	89 1/2" (2273 mm)	18,000 lbs. (8165 kg)	\$14,971.94
	SPO18-LC	Same as above-With Overhead Adjustments of 13 ft. 6 in. and 14 ft. 6 in.			

Technician Productivity Options

	81"-RISE	Additional 3" rise available for SPO10 and S10i models. Specify 81"-RISE when ordering.	\$155.75
	84"-RISE	Additional 3" rise available for SPO12 and S12i models. Specify 84"-RISE when ordering.	\$155.75
	EH1	For 10,000 lb. models: Includes 3" additional rise standard and provides 1 ft. extended height (models SPO10 and S10i).	\$304.02
	EH1	For 12,000 lb. models: Includes 3" additional rise standard and provides 1 ft. extended height (models SPO12 and S12i).	\$318.98
	EH2	For 10,000 lb. models: Includes 3" additional rise standard and provides 2 ft. extended height (models SPO10 and S10i).	\$490.92
	EH2	For 12,000 lb. models: Includes 3" additional rise standard and provides 2 ft. extended height (models SPO12 and S12i).	\$520.83
	EH4	For 10,000 lb. models: Includes 3" additional rise standard and provides 4 ft. extended height (models SPO10 and S10i).	\$864.10

* NOTE: Lift Rise Is Measured From Floor To Top Of Either Pad, Runway, Or Adapter In The Highest Position.

NOTE: Standard Colors Red And Blue. Gray, Yellow And Black Are Available At No Additional Charge, But Are Considered Non-Standard And Subject To Lead Time Restrictions And Order Cancellation Penalties. Other Non-Standard Colors Or Shade Variations Are Available For An Additional Charge, But Also Subject To Lead Time Restrictions And Cancellation Penalties. Consult Factory For Additional Pricing.

NOTE: All Accessories Shown Above May Be Used With Most Frame Contact Models. See page 5 for all accessories.

Use Of Adapters Does Not Change Lift Capacity. Fits any Surface Mounted or Inground, Frame-Engaging Rotary Lift, Manufactured Since October 1973.

Copyright © 2012 by Rotary Lift/A Vehicle Service Group LLC Brand.. All Rights Reserved.


All Drawings, Illustrations, Model Numbers And Descriptions Are All Copyrighted Materials. Unauthorized Use Is Prohibited.



Surface Mounted Lifts

STS
Effective
2013

Conventional / Two-Post / Turf Maintenance

	MODEL NUMBER	DESCRIPTION	*RISE	CAPACITY	STS PRICE
	TL07	2-Post Surface Mounted Lift Electric-Hydraulic Operation. Can Accommodate 3 or 4 Wheel Vehicles.	68" (1727 mm)	7,000 lbs. (3175 kg)	\$5,688.61
	TL07-EH2	Same As TL07 Above -- Provides 2' extra height and 3" additional rise.	71" (1803 mm)		\$6,179.54
	TL07-EH4	Same As TL07 Above -- Provides 4' extra height and 3" additional rise.			\$6,552.71
Rail Bolster Kit	FJ5123	Rail Bolster Kit for SPO9 200/400 Series. Derates Lift to 7,000lbs Capacity (317kg)			\$2,996.63
	FJ5204	Rail Bolster Kit for SPO10-500 Series and Above. Derates Lift to 7,000lbs Capacity (317kg)			\$2,996.63

SmartLifts

Liquid Detection and Conventional / SmartLift

	MODEL NUMBER*	DESCRIPTION	**RISE	CAPACITY	STS PRICE
	SL210-FA	Conventional SmartLift with New Trio™ Superstructure and FLIP UP ADAPTERS . Two Plunger, Side by Side, Fully Contained, Electric-Hydraulic Operation. Rigid Equalized. 8 1/2" Plunger Diameter. Drive Thru. Includes Air Actuated, Multi-Position Locks, 208-230 Volt, Single Phase Power Unit.	81 1/2" (2045 mm)	10,000 lbs. (4536 kg)	\$7,365.73
	SL210-RA	Conventional SmartLift with New Trio™ Superstructure and RUBBER ADAPTERS . Two Plunger, Side by Side, Fully Contained, Electric-Hydraulic Operation. Rigid Equalized. 8 1/2" Plunger Diameter. Drive Thru. Includes Air Actuated, Multi-Position Locks, 208-230 Volt, Single Phase Power Unit.	76 7/8" (1953 mm)	10,000 lbs. (4536 kg)	\$7,365.73
	SL210-TA	Conventional SmartLift with New Trio™ Superstructure and TRUCK ADAPTERS . Two Plunger, Side by Side, Fully Contained, Electric-Hydraulic Operation. Rigid Equalized. 8 1/2" Plunger Diameter. Drive Thru. Includes Air Actuated, Multi-Position Locks, 208-230 Volt, Single Phase Power Unit.			\$7,365.73
	SL210i-FA	Smart Lift With New Trio Superstructure and Flip Up Adapters . Two Plunger Side By Side, Fully Contained, Electric-Hydraulic Operation. LDS-Liquid Detection System. Rigid Equalization. 8 1/2" Plunger Diameter. Drive Thru. Includes Air Actuated Multi Locks 208-230 Volt Single Phase Power Unit	81 1/8" (20461 mm)	10,000 lbs. (4536 kg)	\$7,671.00
	SL210i-RA	Smart Lift With New Trio Superstructure and Rubber Adapters . Two Plunger Side By Side, Fully Contained, Electric-Hydraulic Operation. LDS-Liquid Detection System. Rigid Equalization. 8 1/2" Plunger Diameter. Drive Thru. Includes Air Actuated Multi Locks 208-230 Volt Single Phase Power Unit	76 7/8" (1953 mm)	10,000 lbs. (4536 kg)	\$7,671.00
	SL210i-TA	Smart Lift With New Trio Superstructure and Truck Adapters . Two Plunger Side By Side, Fully Contained, Electric-Hydraulic Operation. LDS-Liquid Detection System. Rigid Equalization. 8 1/2" Plunger Diameter. Drive Thru. Includes Air Actuated Multi Locks 208-230 Volt Single Phase Power Unit	76 7/8" (1953 mm)	10,000 lbs. (4536 kg)	\$7,671.00
	SL212	Conventional SmartLift with Two Plunger, Side by Side, Fully Contained, Electric-Hydraulic Operation. Rigid Equalized. 8 1/2" Plunger Diameter. Drive Thru. Includes Air Actuated, Multi-Position Locks, 208-230 Volt, Single Phase Power Unit. Stack Adapters.	84 1/4" (2140 mm)	12,000 lbs. (5443 kg)	\$9,197.35
	SL212i	Two Plunger, Side By Side, Fully Contained, Electric-Hydraulic Operation. Rigid Equalized. 8 1/2" Plunger Diameter. Drive Thru. Includes Air Actuated, Multi-Position Locks, 208-230 Volt, Single Phase Power Unit. Stack Adapters.			\$9,508.85

Smart Lift Trio Adapter Kits and Control Mounting Options

	T100271	Adapter Extension Kit for SL210 with NEW TRIO Superstructure . Provides additional lifting height when vehicles require additional clearance or use on front or rear to level vehicle on lift. Includes four (4) T130660 (3.5" tall extension) and four (4) T130661 (5" tall extension).			\$191.88
	T100272	Rubber adapter kit for the NEW Trio Superstructure . Includes four (4) FJ6219 adapters.			\$253.56
	T100273	Truck adapter kit for the NEW Trio Superstructure . Includes four (4) T110564 adapters.			\$253.56
	T100274	Flip up adapter kit for the NEW Trio Superstructure . Includes components for four (4) arms.			\$253.56
Control Mounting Option	T100280	Power unit Stand For Use With Conventional and Single Phase One Touch Controls For Mounting One or Two Power Units.			\$120.86

* NOTE: Lift Rise Is Measured From Floor To Top Of Either Pad, Runway, Or Adapter In The Highest Position.

NOTE: Standard Colors Red And Blue. Gray, Yellow And Black Are Available At No Additional Charge, But Are Considered Non-Standard And Subject To Lead Time Restrictions And Order Cancellation Penalties. Other Non-Standard Colors Or Shade Variations Are Available For An Additional Charge, But Also Subject To Lead Time Restrictions And Cancellation Penalties. **Consult Factory For Additional Pricing.**

NOTE: Inbay Lifts Require A 110v Drop For The GFCI Outlet, Except For SmartLift.

NOTE: All Accessories Shown Above May Be Used With Most Frame Contact Models.

Use Of Adapters **Does Not** Change Lift Capacity. Fits any Surface Mounted or Inground, Frame-Engaging Rotary Lift, Manufactured Since October 1973.

Copyright © 2012 by Rotary Lift/A Vehicle Service Group LLC Brand. All Rights Reserved.
All Drawings, Illustrations, Model Numbers And Descriptions Are All Copyrighted Materials. Unauthorized Use Is Prohibited.





Surface Mounted Lifts

Four-Post Lifts

STS
Effective
2013

Conventional Four-Post

	MODEL NUMBER	DESCRIPTION	*RISE	CAPACITY	MAXIMUM WHEELBASE RANGE	STS PRICE
	SMO14S	OPEN FRONT or Open Rear Surface Mounted, Runway-Type, Drive-On Lift, With 20" Wide Fixed Runways. Runways and Ramps Have An Oil Resistant, Non-Skid Coating. Includes Dual Function Sentinel Lock System™ (Patented), Filter Lubricator Regulator (Part# S130080). Electric-Hydraulic Operation. Includes Adjustable Latch Bars. Predrilled For Internal Airline Kit.	73-3/4" (1873 mm)	14,000 lbs. (6350 kg)	158-1/2" (4025 mm)	\$6,448.05
	SMO14L				192-1/2" (4892 mm)	\$6,448.05
	SMO14EL2				212-1/2" (5400 mm)	\$6,777.62
	SM14S	Same As Above Except With CLOSED FRONT.	73-3/4" (1873 mm)	14,000 lbs. (6350 kg)	158" (4013 mm)	\$5,180.87
	SM14L				182-1/2" (4636 mm)	\$5,180.87
	SM14EL2				206-1/2" (5245 mm)	\$5,509.19
	FA647				2 ft. runway extension for SM/SMO 12,000 lb. Series.	
	S10060	2 ft. runway extension for SM/SMO 14,000 lb. Series.		\$554.47		
NOTE: Narrow Bay Models Available For SM/SMO Series (10" Narrow Overall Width For Narrow Bay Application).						
	SM101	Extended Length Is Ideal For Limousines.	73-3/4" (1873 mm)	10,000 lbs. (4536 kg)	245" (6096 mm)	\$7,110.92
	SM18	Heavy Duty Surface Mounted Runway-Type Drive-On Lift Runways and Ramps Have An Oil Resistant, Non-Skid Coating. Includes Air Operated Single Point Release Locking Latches, Filter Lubricator Regulator. Electric-Hydraulic Operation.	68" (1727 mm)	18,000 lbs. (8165 kg)	194" (4928 mm)	\$7,436.75
	SM18-EL2				230" (5842 mm)	\$8,148.22
	SM30 Series	Heavy Duty Surface Mounted Runway-Type Drive-On Lift, With 24" Wide Runway That Can Be Set For Variable Tread Width Setting. Runways and Ramps Have An Oil Resistant, Non-Skid Coating. Includes Air Operated Single Point Release Locking Latches. Internal Air Line with Quick Disconnects, Electric-Hydraulic Operation.	68" (1727 mm)	30,000 lbs. (13,608 kg)	235" (5969 mm)	\$13,887.29
	SM30S	Overall Length 25'-8 1/8".				
	SM30L	Overall Length 28'-8 1/8".				
	SM30-EL3	Overall Length 31'-8 1/8".				
	S100012	2 ft. runway extension for SM18.				\$323.34
	S100018	3 ft. runway extension for SM300 - 200.				\$1,169.99
	FA641-18	3 ft. runway extension for SM300 - 100.				\$1,583.04
	RFL25	Heavy Duty Surface Mounted Runway-Type Drive-On Lift, With 24" Wide Runway That Can Be Set For Variable Tread Width Setting. Runways and Ramps Have An Oil Resistant, Non-Skid Coating. Includes Air Operated Single Point Release Locking Latches. Internal Air Line with Quick Disconnects. Electric-Hydraulic Operation. For Raising Forklifts.	68" (1727 mm)	25,000 lbs. (11,340 kg)	163" (4140 mm)	\$18,463.23

*NOTE: Lift rise is measured from floor to top of either pad, runway, or adapter in the highest position.

Four-Post Wheel Alignment Action Rack Systems with Rolling Jacks

	MODEL NUMBER	DESCRIPTION	*RISE	SYSTEM CAPACITY	Maximun Wheelbase Range	STS PRICE
Stainless Steel Gauges and Rolling Jacks Included!	ARO14S	Includes: • Open Front Action Rack • Four-Post Lift • (2) FA5153 Stainless Steel Radius Gauges • (2) 7,000 lb. Cap. Rolling Jacks • (1) Set 4WS Rear Slip Plates • Patented (Dual Protection Sentinel Lock System)™ • (1) FC134-17 Portable Work Step • Level At All Locking Heights • (1) Internal Air Line Kit • (4) Wiring Access Holes • Runways and Ramps have an Oil Resistant Non-skid Coating • Filter Lubricator Regulator	73-3/4" (1873mm)	14,000 lbs. (6350kg)	158-1/2" (4025mm)	\$17,783.54
	ARO14L				192-1/2" (4892mm)	\$17,783.54
	ARO14EL2				212-1/2" (5400mm)	\$18,096.28
	AR14S	Includes: • Closed Front Action Rack • Four-Post Lift • (1) pair FA5153 (CS) Stainless Steel Radius Gauges • (2) 7,000 lb. Cap. Rolling Jacks • (1) Set 4WS Rear Slip Plates • Air Actuated Locking Latches • (1) FC134-17 Portable Work Step • Level At All Locking Heights • (1) Internal Air Line Kit • (4) Wiring Access Holes • Runways and Ramps have an Oil Resistant Non-skid Coating • Filter Lubricator Regulator	73-3/4" (1873mm)	14,000 lbs. (6350kg)	158-1/2" (4025mm)	\$16,516.98
	AR14L				192-1/2" (4892mm)	\$16,516.98
	AR14EL2				212-1/2" (5400mm)	\$16,829.72

Efficiency Packages



	S100077	Package Includes Two (2) RJ7000 Rolling Bridges And Airline Kit (uninstalled).	\$5,233.82
	S100017	Package Includes Two (2) RJ6000 Rolling Bridges, Airline Kit (uninstalled), bolt-on alignment package and stainless steel radius gauge for SM/SMO123.	\$6,955.80
	S100021	Package Includes Two (2) SJ6000 Swing Air Jacks And Airline Kit (uninstalled).	\$5,812.59
	S100078	Package Includes Two (2) RJ7000 Rolling Bridges, Airline Kit (uninstalled) And S100074 Bolt-On Alignment Package.	\$7,230.54

*NOTE: Lift rise is measured from floor to top of either pad, runway, or adapter in the highest position, except for SmartLift in which rise indicates plunger stroke from finished floor.



Surface Mounted Lifts

STS
Effective
2013

Drive-On Space Saver Alignment Rack						
	MODEL NUMBER	DESCRIPTION	*RISE	SYSTEM CAPACITY	Maximum Wheelbase Range	STS Price
	YA12	Alignment Lift - Exclusive Yspace provides techs additional room to work faster and easier compared to traditional scissor lifts, patented design allows for true up/down movement minimizing bay space required. Adjustable radius gauge pockets (radius gauges not included) and oversized slip plates to accommodate 4 wheel alignments on wheelbase ranges from 71 1/2" to 158". Ramp chocks include rollers for smooth operation and ramps have non-skid coating. Includes (2) RJ6000 rolling jacks, portable work step, internal airline, Filter/Regulator/Lubricator and Z100005 Turnplate filler kit for 14" x 14" x 1-1/2" radius gauges.	68" (1727 mm)	12,000 lbs. (5443 kg)	179-1/2" (4559 mm)	\$20,334.72
	YA12-EL1	Same as above with longer wheelbase.	68" (1727 mm)	12,000 lbs. (5443 kg)	189-1/2" (4813 mm)	\$20,334.72
Drive-On Space Saver General Service Lift						
	Y12	Flat Top General Service Lift - Exclusive Yspace provides techs additional room to work faster and easier compared to traditional scissor lifts, patented design allows for true up/down movement minimizing bay space required. Ramp chocks include rollers for smooth operation and ramps have non-skid coating.	68" (1727 mm)	12,000 lbs. (5443 kg)	179-1/2" (4559 mm)	\$13,514.74
	Y12-EL1	Same as above with longer wheelbase.	68" (1727 mm)	12,000 lbs. (5443 kg)	189-1/2" (4813 mm)	\$13,514.74
Accessories for YA12 and Y12						
	Z100006	Extended rear ramps (add \$51 when ordering with lift in place of standard ramps).				\$500.27
	Z100007	Flush rear ramps (add \$51 when ordering with lift in place of standard ramps).				\$500.27
	Z100008	Standard front ramps (drive-thru).				\$490.30
	Z100010	Flush front ramps (drive-thru).				\$509.61
	Z100012	Full Size Base Shim Kit (6 shims @ 1/4" & shims @ 1/8" = total 2 1/4")				\$232.38
	Z100013	Full Size Base Shim Kit (4 shims @ 1/2" = total 2")				\$232.38
	FA5157	Carbon steel 12" x 14" x 1-1/2" radius gauge (2 required).				\$371.93
	Z100014	Stainless steel rear slip plate base kit.				\$1,328.86
	Z100016	LED light kit.				\$697.76
	Z100017	Hose relocate kit. Longer hoses and wires to locate control cabinet in front of lift (rear is standard).				\$255.43

*NOTE: Lift rise is measured from floor to top of either pad, runway, or adapter in the highest position, except for SmartLift in which rise indicates plunger stroke from finished floor.



Lift Accessories

STS
Effective
2013

Frame Engaging Lift Accessories**

	MODEL NUMBER	DESCRIPTION	STS Price
	FJ6115BK	EH (Extended Height) Auxiliary Adapters For Use When Raising Certain Vans Or Pick-Ups. Maximum Height 14 3/8" (365 mm). Capacity 2,500 lbs. (1,134 kg) Maximum Per Adapter. Fits Any Surface Mount Or Inground, Frame-Engaging, Rotary Lift Manufactured Since October 1973. Includes (4) FJ696 Adapters and 2 Piece Column or Wall-Mounted Adapter Rack FJ6114.	\$242.97
	FJ6195YL	NEw extended height auxiliary adapters' version of FJ6115. 3" (76 mm) additional rise for a total 17 3/8" (454 mm). Includes a set of (2) FJ6196 adapters. Capacity is 2,500 lbs. (1,134 kg) per adapter.	\$162.60
	FJ6212KITYL	Shorter version of FJ6115. Kit includes a set of (4) FJ6212 adapters and 2 piece column or wall mounted adapter rack FJ6114. Adapter height 7 3/8". Capacity 2,500 lbs. (1,134 kg)	\$217.43
	FJ6133BK	EH (Extended Height) Required To Lift 1988 Or Newer General Motors GMT400 Pickup Trucks. Maximum Height: 14" (356 mm) Capacity 2,500 lbs. (1,134 kg) Maximum Per Adapter. Fits Any Surface Mount Or Inground, Frame-Engaging, Rotary Lift Manufactured Since October 1973. Includes (4) FJ6101 Adapters and 2 Piece Column or Wall-Mounted Adapter Rack FJ6114.	\$258.55
	FJ6137BK	Required For Raising Mini-Vans With Running Boards (i.e. Aerostar, Astro, Caravan, Voyager). Adjustable Range Provides 4 7/8" to 6 3/4" Additional Height. Polymer Contact Surface Protects Undercoated Surfaces. Fits Any Surface Mount Or Inground, Frame-Engaging, Rotary Lift Manufactured Since October 1973. Includes (4) FJ7858 Adapters and 2 Piece Column or Wall-Mounted Adapter Rack FJ6114.	\$282.22
1/2"	FJ6138BK	Polymer Pad Adapter Provides 1/2" Additional Clearance. Fits Any Frame Engaging Rotary Lift Manufactured Since October 1973. Includes (4) FJ697 Adapters, 2 Piece Column or Wall-Mounted Adapter Rack FJ6142.	\$149.52
1"	FJ6190YL	Step Polymer Pad Adapter Provides 1" Additional Clearance. Fits Any Frame Engaging Rotary Lift Manufactured Since October 1973. Includes (4) FJ6189 Adapters, 2 Piece Column or Wall-Mounted Adapter Rack FJ6142.	\$157.00
2-1/2"	FJ6139BK	High Step Polymer Pad Adapter Provides 2 1/2" Additional Clearance. Fits Any Frame Engaging Rotary Lift Manufactured Since October 1973. Includes (4) FJ698 Adapters, 2 Piece Column or Wall-Mounted Adapter Rack FJ6142.	\$157.00
	FJ6100BK	Includes (4) FJ696, (4) FJ697 And (4) FJ698 Plus 2 Piece Column or Wall-Mounted Adapter Organizer Rack Part #FJ6108.	\$476.60
	FJ6104BK	Includes (4) FJ6101, (4) FJ697 And (4) FJ698 Plus 2 Piece Column or Wall-Mounted Adapter Organizer Rack Part #FJ6108.	\$493.42
	FJ6105BK	Includes (2) FJ696, (2) FJ6101, (4) FJ697, (4) FJ698 Plus 2 Piece Column or Wall-Mounted Adapter Organizer Rack Part #FJ6108.	\$485.94
	FJ6117BK	Includes (4) FJ7858, (4) FJ697, (4) FJ698 Plus 2 Piece Column Adapter Organizer Rack Part #FJ6108.	\$500.89
	FJ6197	Set of four (4) FJ6214 Rubber Adapters. Required for use on 3-stage arms when lifting trucks or other frame vehicles.	\$248.58
	FJ6225	Set of four (4) FJ6202 Round Adapters. For use on 3-stage arms when lifting Uni-Body construction vehicles.	\$248.58
	FJ7880BK	Adapter Extension Kit For RA SPOA10 And SL210 Series Lift Models. Provides Additional Lifting Height When Vehicles Require Additional Clearance Or Use On Front Or Rear To Level Vehicle On Lift. Includes (4) FJ6171-1 Extensions 3 1/2" Tall, (4) FJ6171-2 Extensions 5" Tall and FJ6127 Rack Kit With Mounting Hardware.	\$188.15
	FJ6200	Set of Four (4) FJ6201 Thread-Up Adapters For SPO12 (-10, 300, 400 and 500 Series)	\$316.48
	N539	Column Base Plate Cover. Fits SPOA7-200 and Above, SPOA9-200 and Above, all SPOA10 Series Lifts.	\$29.90 each
	FA5911BK	Air/Electric Utility Box Includes Filter/Lubricator/Regulator. Mounts Easily On Any 2-Post Surface Lift Except 84 and 74 Series Lift. Provides Easy Access To Both Air And Electrical Outlets Making The Full Rise Lift A Complete Work Station.	\$336.42
	FA5910BK	Air/Electric Utility Box Same As Above Excluding Filter/Lubricator/Regulator.	\$211.20
	FA915	Air/Electric Utility Box Includes Filter/Lubricator/Regulator. Mounts Easily On Any 4-Post Surface Lift (except for SM300). Provides Easy Access To Both Air And Electrical Outlets Making The Full Rise Lift A Complete Work Station.	\$336.42
	FA916	Air/Electric Utility Box Same As Above Excluding Filter/Lubricator/Regulator.	\$209.33
	FA2259	Air/Electric Utility Box Includes Filter/Lubricator/Regulator. Mounts Easily On SM300 Series Lift. Provides Easy Access To Both Air and Electrical Outlets Making The Full Rise Lift A Complete Work Station.	\$336.42
	FA2260	Air/Electric Utility Box Same as Above Excluding Filter/Lubricator/Regulator	\$218.05
Full Size Shim Kit	FA5112	Full Size Shim Kits For 2-Post Light Duty Models Installations With Sloped Floors Requiring Full Size Base Shims or For Use With Front post On SMO123. Includes A Variety of Thicknesses To Allow Shimming Up To 1/2" In Height. Note: Shimming In Excess of 1/2" Per Column Requires Different Anchors--Consult Factory.	\$144.54
Three-Stage Arm/Movable Pad Retrofit Kits			
	N2244YL	Three Stage telescoping arms for accommodating smaller vehicles without excessive maneuvering of vehicle (for models SPOA9 and SPOA7 200-400 Series). Kits include four arms.	\$1,036.05
	N2224/N2225	Three Stage telescoping arms for accommodating smaller vehicles without excessive maneuvering of vehicle (for models SPOA9 and SPOA10 500 Series). Kits include four arms.	\$1,036.05

*NOTE: All Accessories Shown Above May Be Used With Most Frame Contact Models.
Use Of Adapters **Does Not** Change Lift Capacity. Fits any Surface Mounted or Inground, Frame-Engaging Rotary Lift, Manufactured Since October 1973.

Electrical / Power Unit / Overhead Switch Options

Three Phase Power	Optional 4-HP 3kw, 3 Phase, 60 Hz Power Unit For Use With Four-Post Series, SL Series (Both in bay and Non-in bay), Two-Post Overhead Design Lifts Only (Both in bay and Non-in bay). Must Specify When Ordering. Price In Addition To Standard Unit Price. 208/230 or 460 Volt Must Be Specified.	\$211.20
--------------------------	---	-----------------



Lift Accessories

STS
Effective
2013

Two-Post/Lift Accessories

	MODEL NUMBER	DESCRIPTION	STS Price
	N823	Door Defender: Allows technicians to easily enter and exit the vehicle without damaging their customer's vehicle. Low profile solid rubber guard designed to fit over the two-post lift carriage. Includes 1 Door Defender, adhesive to attach to the lift and instructions.	\$70.40
	FA5191	Tool Holder (Patent Pending) Keeps air guns, torque sticks and other tools within reach. Mounts easily in holes already drilled and tapped in the two-post column.	\$54.20

Two-Post/Wash Bay Accessories

N3106/N3105	Stainless Steel Equalizer Cables For SPO9/SPOA9 Lifts.	\$173.82 each (2 required)
FJ7923	Stainless Steel Latch Cable.	\$31.77
FA595	Splash Guard To Protect Power Unit Motor Assembly.	\$43.61
FA7129	Power Unit Bracket Extension.	\$28.04

Drive-On Lift Accessories

	MODEL NUMBER	DESCRIPTION	STS Price
	S100074	4-Wheel Alignment Retrofit Kit for SM/SMO series 4-post lifts. Rollback version (ideal for 3-D alignment equipment). Kit consists of bolt-on kit, front turning Stainless Steel Radius Gauge Kit, rear slip plate kit and all necessary hardware (drilling and tapping required). Recommended for use with (2) Rolling Jacks for performing 4-Wheel Alignment. FC7117 kit.	\$2,330.64
	S100080	Same as S100074 less radius gauges.	\$1,366.86
	S100083	Same as S100074 with Carbon Steel Radius Gauges.	\$2,113.22
	FA5413	4-Wheel Alignment Retrofit Kit for SM18 series 4-post lifts. Rollback version (ideal for 3-D alignment equipment). Kit consists of 2 FA5157 front turning carbon steel radius gauge kit, rear slip plate kit and all necessary hardware. (drilling and tapping required) Recommended for use with (2) Rolling Jacks for performing 4-Wheel Alignment. FC7117 kit. SS option S130205 gauges only.	\$2,322.54
	FC5396	A Wheel Alignment Conversion Package For SM30 Series Lifts Including: (1) FC5394 Heavy Duty Carbon Steel Turntables (Pair) And Guides; (2) FC5396-21 Rear Leveling Plates; (1) FC5395 Heavy Duty Bolt On Work Step Kit; Recoil Hose; Necessary Hardware And Instructions. (Drilling Required.) FC7117 kit.	\$3,907.46
	FC7117 KIT	Filler adapter kit for Rotary alignment racks/bolt-on alignment kits to accommodate three dimensional visual alignment instrumentation systems. Included with purchase of any new Rotary alignment rack or bolt-on kit -- effective 2011. Standard color is yellow.	\$31.15
	FC5974	Radius gauge filler plate kit fits lifts with long recess.	\$171.95
	FC5102	Radius gauge filler plate kit fits lifts with standard recess.	\$144.54
	RJ6000	Rolling Jack For SM/SMO14, AR/ARO14.	6,000 lbs. (2722 kg) \$2,334.38
	RJ6000-R	Rolling Jack For SM121, SM/SMO122 and AR/ARO122 Prior To April 2000.	
	RJ7000	Rolling Jack For SM/SMO14, AR/ARO14.	7,000 lbs. (3175 kg) \$2,472.06
	RJ9000-1	Rolling Jack For SM181 Only Series Lifts. For Passenger Cars and Light Trucks Only!	
	RJ9000-2	Rolling Jack For SM30 Series Lifts.	9,000 lbs. (4082 kg) \$3,124.35
	RJ9001	Rolling Jack For SM18 Series Lifts.	\$2,802.88
	FC5710	Heavy Duty Rolling Jack For SM300, Series Lifts. Capacity, Air/Oil Operated. Supplied With FD291 Combination Front Straight Axle/"Flip Up" Rear Axle Support. Will Accommodate All Adapters Typically Used With FD282 Inground Saddle.	15,000 lbs. (6804 kg) \$6,172.06
	SJ6000	Swing Air Jack For AR/SM Series Lifts.	6,000 lbs. (2722 kg) \$2,910.66
	SJ8000	Swing Air Jack For AR/SM Series Lifts.	8,000 lbs. (3629 kg) \$3,306.26
	FJ2427	Flat Polymer Pad Adapter Adds 1-1/2" Height. Rubber Pad Surface Measures 4-3/4" x 6-5/16". Protects Vehicles With Factory Applied Undercoating. 3,500 lbs. capacity per adapter.	\$9.35 Each (2 required)
	FJ2428	Flat Polymer Pad Adapter Adds 3" Height. Rubber Pad Surface Measures 4-3/4" x 6-5/16". Protects Vehicles With Factory Applied Undercoating. 3,500 lbs. capacity per adapter.	\$14.33 Each (2 required)
	SB100017	Extended Height Adapter Kit To Pick Up SUV Straight Axle Type Vehicles. Kit includes (2) SB300055 7" Adapters. For RJ7000.	\$94.70
	SB100003	Extended Height Adapter Kit To Pick Up SUV Straight Axle Type Vehicles. Kit includes (2) SB300019 7" Adapters. For RJ6000.	
	FJ6211	Extended height adapters for pad lifts for use when lifting SUVs on pad lifts. Includes (4) FJ6205 7" truck adapters.	\$209.95 (set of 4)

***NOTE:** All Accessories Shown Above May Be Used With Most Frame Contact Models.
Use Of Adapters **Does Not** Change Lift Capacity. Fits any Surface Mounted or Inground, Frame-Engaging Rotary Lift, Manufactured Since October 1973.

Electrical / Power Unit / Overhead Switch Options

Three Phase Power	Optional 4-HP 3kw, 3 Phase, 60 Hz Power Unit For Use With Four-Post Series, SL Series (Both in bay and Non-in bay), Two-Post Overhead Design Lifts Only (Both in bay and Non-in bay) . Must Specify When Ordering. Price In Addition To Standard Unit Price. 208/230 or 460 Volt Must Be Specified.	\$211.20
-------------------	--	----------



Lift Accessories

STS
Effective
2013

Drive-On Lift Accessories

	MODEL NUMBER	DESCRIPTION	STS Price
	FC5193	Flat Rubber Pad Adapters Add 1 1/4" Height. Rubber Pad Surface Measures 6" Square. Optional for RJ9000 Rolling Jacks Only.	\$56.07 Each (2 Required)
	FC5231	Flat Rubber Pad Adapters Add 2 5/8" Height. Rubber Pad Surface Measures 6" Square. Optional for RJ9000 Rolling Jacks Only.	\$61.05 Each (2 Required)
	FC5213	Flat Rubber Pad Adapters Add 3 1/2" Height (low position), 4 1/2" Height (high position). Rubber Pad Surface Measures 4 1/2" Square. Protects Vehicles With Factory Applied Undercoating. Optional for RJ9000 Rolling Jacks Only.	\$68.53 Each (2 Required)
	FC5213-12	Flat Rubber Pad Adapters Insert Adds 5 7/8" Height (Use with FC5213 Adapters). Rubber Pad Surface Measures 4 1/2" Square. Protects Vehicles With Factory Applied Undercoating. Base Not Included. Optional for RJ9000 Rolling Jacks Only.	\$44.86 Each (2 Required)
	S100045	DOR Drive-Thru Ramp Kit for SmartLift. Includes Spacer.	\$419.28
	S100075	Ramp Chock Kit For Drive-Thru Bay Operation For Models SM/SMO14 and SM101. Ramps Have An Oil Resistant, Non-Skid Coating. Includes Two (2) S110302 Ramps (40-1/2") and Hinge Pins.	\$419.28
	S100076	Extended Ramp Chock Kit For Models SM/SMO14 and SM101. Ramps Have An Oil Resistant, Non-Skid Coating. 9" Longer Ramp Length Than Standard To Reduce Ramp Up Angle For Passenger Cars With Low Ground Clearance. (\$51 Adder Only When Substituted For Standard Length Ramps On New Lift Order.) Includes Two (2) S110303 Ramps (49-7/16") and Hinge Pins.	\$431.12
	S100013	Extended Ramp Chock Kit For Model SM18. Ramps Have An Oil Resistant, Non-Skid Coating. 6 1/2" Longer Ramp Length Than Standard To Reduce Ramp Up Angle For Passenger Cars With Low Ground Clearance. (\$51 Adder Only When Substituted For Standard Length Ramps On New Lift Order.) Includes Two (2) S110085 Ramps and Hinge Pins.	\$596.21
	FC5825	Ramp Chock Kit For Drive-Thru Bay Operation For Model SM18. Ramps Have An Oil Resistant, Non-Skid Coating. Includes Two (2) FC5810-43 Ramps and Hinge Pins.	\$548.24
	FC5780-3 (2 Required)	Additional Ramp Chocks For Drive-Thru Bay Operation For SM300-200 Series Lifts. Ramps (40") Have An Oil Resistant, Non-Skid Coating. For SM300-100 Series Lifts, Order # FC5225-52.	\$336.42
	FC663	Rolling Jack Tray For SM/SMO122, SM/SMO123 and SM/SMO14. (Bottle Jacks Are Not Included)	\$392.49
	FC5378	Bolt On Work Steps For All 4-Post Series Lifts.	\$399.97 (Pair)
	FC5967	30 Gallon (114 Liter) Low Profile Rolling Drain Pan With Splash Guard, Drain Valve And Dust Cap. For QL4P, SM/SMO122, SM/SMO14 and SM18 (fits YA-12 only at 43" setting).	\$618.64
	FC5968	30 Gallon (114 Liter) Low Profile Rolling Drain Pan With Splash Guard, Drain Valve And Dust Cap. For SM30 Series Lifts.	\$783.73
	FC5247	8 Foot Long Oil Drain Hose With Quick Connect Fitting.	\$77.88
Internal Air Line Kit	FC5760	Internal Air Line Kit (retrofit) For SM/SMO12 and SM18 Series.	\$297.17
	FC5760-14	Internal Air Line Kit (retrofit) For SM/SMO14 Short, L, EL, QL12 and Y-Lift.	
	FC5759	Internal Air Line Kit (retrofit) For SM/SMO12 Short. Not Available For SM30 Series.	
Light Kit	Liflyte 1000	4 post light kit with 140" led light strip.	\$545.75
	Liflyte 1003	4 post light kit with 175" led light strip.	\$566.93
	Z140061	288" transformer lead extension.	\$148.90



Lift Accessories

STS
Effective
2013

Drive-On Shim Kits

	MODEL NUMBER	DESCRIPTION	STS Price
Full Shim Kits	FC5414	Full Size 1/4" Shim Kits For Installations With Sloped Flooring Requiring Full Size Base Shims. Allows Shimming From 2" To 4" Height On Rear End of Lift. For SM/SMO123, AR/ARO123, QL Models, SM18 and SM30 Lifts.	\$262.28
	S100093	Full Size Shim Kit For Front Of SMO14/ARO14 Open Front Lifts. Contains Two 1/4" Shims And Four 1/16" Shims.	\$144.54

Wheel Service Accessories

	FC134-17	Portable Work Step. 350 lb. capacity.	\$77.88
	TT1001	Stainless Steel Turning Radius Gauge Kit. Includes (2) FA5153 S/S radius gauges; and Four Retaining Bars -- Part # FA5153-1. (3,000 lbs. (1360 kg) capacity)	\$1,140.09
	FA5155	Standard Turning Radius Gauge Kit. Includes Two Standard Turning Radius Gauges -- Part #FA5157; and Four Retaining Bars -- Part #FA5153-1. (4,500 lbs. (2041 kg) capacity)	\$794.95
	S130205	Stainless Steel Turning Radius Gauge (Two Required Per Lift). No Pointer. 4,500 lbs. (2,041kg) capacity.	\$482.20 each (2 required)
	FC5268	Four Wheel Steer Slip Plate Kit (retrofit) for SM123 Series and below (only does 1 side).	\$634.21
Stainless Steel Shield Kit	FC7118	Rear stainless steel shield kit for AR/ARO12.	\$700.88

Electrical/Power Unit/Overhead Switch Options

Three Phase Power		Optional 4-HP 3kw, 3 Phase, 60 Hz Power Unit For Use With Y Lift Series, Four-Post Series, SL Series, Two-Post Overhead Design Lifts Only. Must Specify When Ordering. Price In Addition To Standard Unit Price. 208/230 or 460 Volt Must Be Specified.	\$211.20
	FA7118	Overhead Cutoff Switch Assembly Mounts Easily On Ceiling Or Overhead Beams Where Limited Ceiling Height Or Excess Vehicle Height Is A Problem. Single Phase Electrical Required.	\$188.15



Heavy Duty Inground Modular Concept Units Self-Contained

STS
Effective
2013

Movable Plunger Modular Unit					
	***MODEL NUMBER	CAPACITY	DESCRIPTION	RISE	STS PRICE
	MOD30M-10	30,000 lbs. (13608 kg)	Modular Movable Jack Unit With** 10' Long Track. (*Unit not equipped with Saddle or Adapters)	70" (1778mm)	\$39,933.05
	MOD30M-18	30,000 lbs. (13608 kg)	Modular Movable Jack Unit With** 18' Long Track. (*Unit not equipped with Saddle or Adapters)	70" (1778mm)	\$39,933.05
	MOD30M-21	30,000 lbs. (13608 kg)	Modular Movable Jack Unit With** 21' Long Track. (*Unit not equipped with Saddle or Adapters)	70" (1778mm)	\$39,933.05
	MOD30M-24	30,000 lbs. (13608 kg)	Modular Movable Jack Unit With **24' Long Track. (*Unit not equipped with Saddle or Adapters)	70" (1778mm)	\$39,933.05

* See Adapter Kits to select Saddle and Adapters in accordance to lift application.
 ** See the Wheelbase Chart to select the required frame length.
 *** Wider pocket opening available upon request.

Standard Equipment: Specified Track Length, Totally Contained Steel Enclosure Sealed and Protected With Enviroguard, LDS Liquid Detection System, Multi-Stage Piston Assembly, Multi-Position Remote Release Locks, Electronic Jack Spotting Device, Programable Height Positions.

Stationary Plunger Modular Unit					
	**MODEL NUMBER	CAPACITY	DESCRIPTION	RISE	STS PRICE
	MOD30S	30,000 lbs. (13608 kg)	Modular Stationary Jack Unit. (*Unit not equipped with Saddle or Adapters)	70" (1778mm)	\$22,965.65

*See Adapter Kits to select adapters according to lift application.
 ** Wider pocket opening available upon request.

Standard Equipment: Specified Track Length, Totally Contained Steel Enclosure Sealed and Protected With Enviroguard, LDS Liquid Detection System, Multi-Stage Piston Assembly, Multi-Position Remote Release Locks, Programable Height Positions.

Modular Unit Controls			
	**MODEL NUMBER	DESCRIPTION	STS PRICE
	MC2	For 2-Post Lift Configuration - Console With VEC Equalized Controls.	\$9,842.15
	MC3	For 3-Post Lift Configuration - Console With VEC Equalized Controls.	\$14,998.10

Note: When ordering controls, place a dash after the model number and add the voltage require.
EXAMPLE - (MC2-230V).



Adapter Kits

STS
Effective
2013

Adapter Kits for Modular Lift Configurations

	**MODEL NUMBER	DESCRIPTION	STS PRICE
	AK-SBA60-2	Adapter kit for <u>most</u> <i>School Bus</i> applications. For use on (2-Post lift configuration).	\$3,157.99
	AK-HTA60-2	Adapter kit for <u>most</u> <i>Heavy Duty Truck</i> applications. For use on (2-Post lift configuration).	\$3,157.99
	AK-ULP60-2	Adapter kit for <u>most</u> <i>Low Profile Transit Bus</i> operations. For use on (2-Post lift configuration).	\$3,824.60
	AK-ULP90-3	Adapter kit for <u>most</u> <i>Transit Bus</i> applications. For use on (3-Post lift configuration).	\$5,404.53
	AK-HTA90-3	Adapter kit for <u>most</u> <i>Heavy Duty Truck</i> applications. For use on (3-Post lift configuration).	\$4,737.29
	AK-XPAD	Single post frame contact adapter. 9000 lbs. for most passenger cars.	\$5,198.94
	FD2361BK	Universal Adapter Stand Kit.	\$121.49

Accessories and Options

	**MODEL NUMBER	DESCRIPTION	STS PRICE
	MC10009	Optional Hand Held Pendant Control	\$4,083.77
	FD2356	Low Profile Saddle (no adapters) (flat plate)	\$1011.13
	FD2408	Ultra Flat Low Profile Saddle with 2 sets of inserts included (choose 2 part #s FD2379, FD2380, FD2381, FD2383, FD2384, FD2385). See adapter guide for description. Compatible with older MOD 30s.	\$2,244.05
	FD2382	3 Hole Sliding Adapter For FD2347 Saddle -- must order 2.	\$237.99
	FD7172	2HP slip clutch kit.	\$1,148.81
	MC100021	Liquid Evacuation Kit for 2-Post MOD30.	\$1,713.25
	MC100022	Liquid Evacuation Kit for 3-Post MOD30.	\$2,336.25
	FA2452	MOD30 single locking leg replacement (new style).	\$897.12




EFX60

Heavy Duty Inground Scissor Lift (2-post only)

Include IN20597 with EFX order!

**STS
Effective
2013**

Movable Scissor Unit

	**MODEL NUMBER	CAPACITY	DESCRIPTION	*RISE	STS PRICE
	EFX-60-10	30,000 lbs. (13608 kg)	Movable scissor jack unit with 10' track, 120" of travel, not equipped with adapter kits.	70" (1778mm)	\$39,933.05
	EFX-60-13	30,000 lbs. (13608 kg)	Movable scissor jack unit with 13' track, 156" of travel, not equipped with adapter kits.	70" (1778mm)	\$39,933.05
	EFX-60-17	30,000 lbs. (13608 kg)	Movable scissor jack unit with 17' track, 204" of travel, not equipped with adapter kits.	70" (1778mm)	\$39,933.05


Stationary Scissor Unit

	**MODEL NUMBER	CAPACITY	DESCRIPTION	*RISE	STS PRICE
	EFX-60-S	30,000 lbs. (13608 kg)	Stationary scissor, 48" pocket opening, not equipped with adapter kits.	70" (1778mm)	\$22,965.65

Scissor Unit Controls

	**MODEL NUMBER	DESCRIPTION	STS PRICE
	2 Scissor Control	2-post configuration console, 10hp 3ph motor available in 208, 230 460 and 575v.	\$9,842.15
	3 Scissor Control	3-post configuration console, 10hp 3ph motor available in 208, 230 460 and 575v.	\$14,998.10

Adapter Kits for Scissor Lift Configurations

	**MODEL NUMBER	DESCRIPTION	STS PRICE
	AK-SBA60-2	Adapter kit for <u>most School Bus</u> applications. For use on (2-Post lift configuration).	\$3,157.99
	AK-HTA60-2	Adapter kit for <u>most Heavy Duty Truck</u> applications. For use on (2-Post lift configuration).	\$3,157.99
	AK-TRLP60-2	Adapter kit for <u>most Low Profile Transit Bus</u> operations. For use on (2-Post lift configuration).	\$3,157.99
	FD2361BK	Universal Adapter Stand Kit.	\$121.49

Accessories and Options

**MODEL NUMBER	DESCRIPTION	STS PRICE
EFX0509165000	2 Scissor Pendant - hand held. No Festoon.	\$4,114.92
EFX1008161000	3 Scissor Pendant - hand held. No Festoon.	\$5,390.20
EFX0906211002	Shims available in 10 gauge thickness	\$4.36
EFX0906211003	Shims available in 10 gauge thickness	\$4.98
EFX0906211004	Shims available in 10 gauge thickness	\$5.61



Parallelogram Lifts

STS
Effective
2013

Rotary Advantage Parallelogram Lifts (without tape switches)

	MODEL NUMBER	DESCRIPTION	MAXIMUM WHEELBASE	CAPACITY	RUNWAY LENGTH	STS PRICE
	36/28 S	4-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	300 in. (7620 mm)	36,000 lbs. (16330 kg)	28 ft. (8.5m)	\$62,570.38
	36/28 F	4-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$70,913.60
	50/26 S	4-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	276 in. (7010 mm)	50,000 lbs. (22680 kg)	26 ft. (7.9m)	\$68,825.93
	50/26 F	4-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$77,168.52
	50/28 S	4-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	290 in. (7366 mm)	50,000 lbs. (22680 kg)	28 ft. (8.5m)	\$72,997.53
	50/28 F	4-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$81,538.24
	45/35 S	6-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	384 in. (9754 mm)	45,000 lbs. (20412 kg)	35 ft. (10.6m)	\$83,431.54
	45/35 F	6-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$91,766.03
	50/32 S	6-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	348 in. (8839 mm)	50,000 lbs. (22680 kg)	32 ft. (9.7m)	\$77,168.52
	50/32 F	6-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$85,511.11
	50/48 S	6-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	540 in. (13716 mm)	50,000 lbs. (22680 kg)	48 ft. (14.6m)	\$107,579.64
	50/48 F	6-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$118,194.31
	75/30 S	6-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	324 in. (8230 mm)	75,000 lbs. (34020 kg)	30 ft. (9.1m)	\$85,511.11
	75/30 F	6-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$93,854.33
	75/48 S	8-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	540 in. (13716 mm)	75,000 lbs. (34020kg)	48 ft. (14.6m)	\$107,579.64
	75/48 F	8-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$118,194.31
	100/42 S	8-Leg Surface Mounted Clear Floor Open Base Parallelogram Lift	468 in. (11887 mm)	100,000 lbs. (45360 kg)	42 ft. (12.8m)	\$112,629.67
	100/42 F	8-Leg Flush Mounted Clear Floor Open Base Parallelogram Lift				\$123,059.94

NOTE: Shims, Full Base Plate Shims and Anchors are NOT provided with Rotary Parallelogram Lifts. Consult the Equipment Function Requirements (EFRs) for the specific lift model. EFRs are available through Rotary Lift Customer Service and on the RDW.


NOTE: Because of the environment of the typical wash bay application for the Rotary Parallelogram Lift, the entire lift is subjected to harsh cleaning chemicals, road chemicals coming off of the vehicles and constant contact with water and moisture. Even though we take extra precautions to assure that the surfaces of the lifts and listed components of the Wash Bay Kit Option are properly prepared, primed and finished, we do not have any control over the environment and we can only guarantee the surface to be free from rust and other corrosion for a period of one year from the date of installation. Any expressed or implied warranty to the contrary, is excluded and is not covered. In all cases, the standard Rotary Limited Warranty applies.



Parallelogram Lifts

STS
Effective
2013

Rotary Advantage Accessories

	MODEL NUMBER	DESCRIPTION	STS Price
	RJ25000	25,000 lbs. (11340 kg) Rolling Jack	\$7,239.26
	RJ42000	42,000 lbs. (19051 kg) Rolling Jack	\$7,574.43
	RJ50000	50,000 lbs. (22680 kg) Rolling Jack	\$7,908.36
	APAIRKIT	Built-in Air	\$1,934.42
8 ft. Drive-thru Ramp	APRAMP8	8 ft. (2.44m) Drive-thru Ramp Kit (with lift)	\$3,340.53
8 ft. Drive-thru Ramp (w/o lift)	APRAMP8DTKIT	8' Drive-Thru Ramp Kit (without lift)	\$4,110.55
10 ft. Drive-thru Ramp	APRAMP10	10 ft. (3m) Ramps (adder to standard lift cost)	\$685.30
Light Kit	APLIGHT	Light Kit (pair)	\$616.15
Descent Alarm	APAUDALARM	Audible Descent Alarm	\$333.93
Height Limiter	APAUHT	Height Limiter	\$309
Tapeswitch		Tapeswitch (per ft. example: 75/48 outside only 112x48=5376) When ordering specify Inside, Outside or Both.	\$69.78
Shim	AP00402	.125" x 3" x 3" Finger Shims (2.54mm x 76.2mm x 76.2mm)	\$3.74
Shim	AP00403	Shim -- 3" Finger; .250 Thick (6.35mm x 76.2mm x 76.2mm)	\$4.36
Shim	AP00405	.060" x 4" x 4" Finger Shims (1.53mm x 101.6mm x 101.6mm)	\$3.74
Shim	AP00406	.120" x 4" x 4" Finger Shims (2.54mm x 101.6mm x 101.6mm)	\$4.36
Shim	AP00407	.25" x 4" x 4" Finger Shims (6.35mm x 101.6mm x 101.6mm)	\$4.98
Laptop Programmer	AP03705	Programmer with cord (Gen 2, 3, 4, 5) -- software for laptop running WindowsXP and Win7 (laptop not included). Does not run on Win7 Starter.	\$454.17
Laptop Cord	AC100003	Cord for Laptop Programmer (FA7654 and FA7655)	\$216.80
Remote Panel	AP02583	Remote Control Panel	\$2,649.62
	AP09525	High Lift Wheel Dolly -- 850 lbs. (386 kg) Capacity. Rise 71". Side Shift 17".	\$3,245.21
Washbay Kit*	Includes zinc galvanized primer with marine grade epoxy top coat, stainless steel baseplate, EnviroGuard coated control panel and stainless steel remote panel included.	4-Leg	\$14,600
		6-Leg	\$18,670.06
		8-Leg	\$22,735.76

***NOTE:** Because of the environment of the typical wash bay application for the Rotary Parallelogram Lift, the entire lift is subjected to harsh cleaning chemicals, road chemicals coming off of the vehicles and constant contact with water and moisture. Even though we take extra precautions to assure that the surfaces of the lifts and listed components of the Wash Bay Kit Option are properly prepared, primed and finished, we do not have any control over the environment and we can only guarantee the surface to be free from rust and other corrosion for a period of one year from the date of installation. Any expressed or implied warranty to the contrary, is excluded and is not covered. In all cases, the standard Rotary Limited Warranty applies. Washbay lifts are not available for Extended Warranty.



Hydraulic Portable Lifts


STS
Effective
2013

Hydraulic Portable Truck And Bus Lifts

	MODEL NUMBER	DESCRIPTION	*RISE	COMBINED TOTAL SYSTEM CAPACITY	STS PRICE
 	MCH418	Portable Lift. Wheel Pick-Up, Electro Hydraulic 4-Unit System with Movable Forks. 24VDC Battery Operated with 110 Volt Single Phase Charging.	69" (1753 mm)	72,000 lbs. (32,727 kg)	\$32,810.09
	MCH618	Portable Lift. Wheel Pick-Up, Electro Hydraulic 6-Unit System with Movable Forks. 24VDC Battery Operated with 110 Volt Single Phase Charging.	69" (1753 mm)	108,000 lbs. (49,091 kg)	\$49,214.29
	MCH418 (without batteries)	Portable Lift. Wheel Pick-Up, Electro Hydraulic 4-Unit System with Movable Forks. Without batteries.	69" (1753 mm)	72,000 lbs. (32,727 kg)	\$32,046.44
	MCH618 (without batteries)	Portable Lift. Wheel Pick-Up, Electro Hydraulic 6-Unit System with Movable Forks. Without batteries.	69" (1753 mm)	108,000 lbs. (49,091 kg)	\$48,069.66
	MCH418W	A wireless version of the MCH418.	69" (1753 mm)	72,000 lbs. (32,727 kg)	\$37,355.21
	MCH618W	A wireless version of the MCH618.	69" (1753 mm)	108,000 lbs. (49,091 kg)	\$56,033.09

*Lift Rise Is Measured From Floor Level To Bottom Of Adapter.

Hydraulic Portable Truck And Bus Lifts Accessories And Options

	MODEL NUMBER	DESCRIPTION	STS PRICE
	ML41	Saddle Cross Beam With Two (2) Support Blocks For Frame Pick-Up. For HP and MCH Models. 32,000 lbs Capacity at 72" adapter spread. 24,000 lbs. Capacity at 49" adapter spread.	\$1,402.37
	RS18	Screw-Type Adjustable 56.1"-82.3" (1425mm - 2090mm). 18,000 lbs. (8165 kg) Capacity.	\$637.33
	RS1852	Screw-Type Adjustable 34.3 "-55.5" (870mm - 1410mm).	\$566.93
	RS33	Screw-Type Adjustable 55.31"-82.28" (1405mm - 2090mm). 33,000 lbs. (14970 kg) Capacity.	\$1,108.94
	M140004	Forklift Ramp Kit used with the MCH418 series to utilize two MCH columns to service forklifts. Easily attaches to the base of the column and provides clearance needed to raise 4-wheeled forklifts with a weight of 10,000 lbs. (NOTE: Most 6,000 lb. capacity trucks weigh 10,000 lbs. or less; however, the truck weight should be verified before being lifted.) For Drive-on/Back-off operation.	\$5,196.44
	M140012	Same as above for Drive-through operation.	\$5,196.44
	FD2353	Ramp style cross beam with (2) ramps for RV pick-up. Capacity 22,000 lbs. For HP and MCH Models.	\$1,619.18
	M140005	Fore and Aft, frame-engagement lifting kit for use with two MCH418 series columns. Maximum capacity 7,500 lbs. per MCH column. FOR MCH MODELS ONLY.	\$1,835.36
	M110108	Cart for fore and aft frame lifting kit for storage and moving.	\$583.13
	M140002	24VDC led service lamp kit (2 lamps) for MCH418 series lifts. Operates on column's battery power. FOR MCH MODELS ONLY.	\$520.83
	M140001	Long Fork Kit. Each kit includes two 22" forks (8" longer than standard) and two 8" leg extensions. Reduces capacity of column to 12,000 lbs. FOR MCH MODELS ONLY.	\$657.27 (each column)
	M140041	Long Fork Kit. Each kit includes two 20" forks (6" longer than standard) and two 8" leg extensions. Reduces capacity of column to 14,500 lbs. FOR MCH MODELS ONLY.	
	M140015	Drive-on runway assembly for use with MCH418/618 Mobile Columns. 60,000 lbs. capacity. Length 33 feet. (MCH4+)	\$20,416.96
Pendant Control	M140003	Pendant for MCH4 or 6.	\$1,039.79
	M140014	Service Chip for MCH's.	\$0
Wireless Upgrade	M140024	Wireless upgrade kit -- upgrades a single column. RETROFITABLE FOR ALL MCH LIFTS.	\$1,270.92
Weight Gauge	M140019	Weight gauge for Monarch power unit.	\$122.11
	M120304BK	Large wheel adapter (per column).	\$87.22