



## WHOLEGOODS PRICE BOOK

# STATE OF OHIO STATE TERM SCHEDULE 2013

1502 E. Walnut St., Seguin, TX 78155 800-882-5756 800-882-5758 fax  
www.terrainking.com boom@terrainking.com oemparts@terrainking.com



**STATE OF OHIO STATE TERM SCHEDULE**  
**2013 CONTRACT DISCOUNT STRUCTURE**

**Universal Price book**

PRODUCT	DISCOUNT
KBS -Sickle Bar	20%
Flail King	20%

**Hydraulic Price book**

PRODUCT	DISCOUNT
KB Boom	20%
Terrain Master	20%
KBR Rotary	20%
Multi-Unit Discount	
5+	2%
9+	3%



## KBS- Sickle Bar Mower

### 6' Mid-Mount Sickle Bar

**STANDARD SPECIFICATIONS**

- ◆ Full Hydraulic Drive of Cutter Knife
- ◆ Hydraulically Actuated Breakaway
- ◆ Hydraulic Lift and Tilt
- ◆ Knife Speed Governor
- ◆ 3" Heavy Duty Industrial Rock Guards
- ◆ Reversible Hydraulic Motor
- ◆ Safety Transport Locks
- ◆ Self-Contained Hydraulics
- ◆ Cutting Capacity: 1/2" diameter material
- ◆ Tractor Req: Min. 3,000 lbs. and a 25 HP rating

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
<b>Sickle Bar Mower Base Unit (One Choice Required)</b>				
31804117207	6' Switchblade Single RH w/ Serrated Knives	723		12,422
<b>Options</b>				
CALL	Additional Operators and Parts Manuals (Hard Copy)			51
CALL	Additional Operators, Parts & Service Manuals (CD Format)			51
3080487100	Knife Holder Brackets (Order Quantity 2 per Unit)	9		125
30802988134	Kubota M5040/M6040/M7040 Pump Guard Kit			296
3000800000	Factory Mounting & Oil			1,945
CALL	Special Mower Paint			377
30002991505	Additional 12 Month Warranty			2,020

<b>Mount Kit (One Choice Required)</b>				
PRODUCT ORDER CODE	TRACTOR DESCRIPTION	MAX. TIRE SIZE		LIST PRICE
		FRONT	REAR	
30802987344 32002990138	Kubota L5740 Cab 4wd (Mid-Mount PTO Req'd)	9.5-16	14.9-26	4,847
30802986297 32002986298	Kubota M5040/M6040/M7040 ROPS 2 & 4wd	12.5/80-18	16.9-28	4,847
30802984775 32002984776	Kubota M5040/M6040/M7040 Cab 2 & 4wd	11.2-24	16.9-30	4,847
CALL	Kubota M8560/9960 Cab 2 & 4wd	10-16/ 12.4-24	18.4-30	4,847



1502 E. Walnut St., Seguin, TX 78155  
 800-882-5756 800-882-5758 fax  
 boom@terrainking.com  
 oemparts@terrainking.com



## Flail King 74, 88, 96 Flail Mowers

- ◆ 74", 88", 96" Cutting Widths
- ◆ 10-Gauge Unitized Cutter Housing
- ◆ 5/16" Side Plates
- ◆ CAT I or CAT II Three-Point Hitch
- ◆ 4-1/2" x 5/16" Wall Cuttershaft
- ◆ 1-15/16" Bore Greaseable, Self Aligning Cuttershaft Bearings
- ◆ 60 HP Gearbox
- ◆ CAT 4 Driveline
- ◆ Belt Drive from Gearbox to Cuttershaft with Automatic Spring Tension
- ◆ 6" Adjustable Rear Roller
- ◆ 1" - 6" Cutting Height
- ◆ Front & Rear Deflectors
- ◆ Factory Set-Up
- ◆ Cutting Capacity: 1" diameter material
- ◆ 74" Req: Min 35 HP
- ◆ 88" Req: Min 40 HP
- ◆ 96" Req: Min 50 HP

PRICING EFFECTIVE February 15, 2013

ORDER CODE	DESCRIPTION	APPROX WEIGHT	LIST PRICE
34802990739	74" Flail King , Center, 3 oz Knives	930	6,931
34802990740	74" Flail King, Center, 4 oz Knives	930	7,133
348988037	88" Flail King, Center, 3 oz Knives	1035	7,029
348988040	88" Flail King, Center, 4 oz Knives	1035	7,270
348988058	96" Flail King, Center, 3 oz Knives	1170	7,828
348988067	96" Flail King, Center, 4 oz Knives	1170	8,092
OPTIONS			
37002990357A	Additional Operators and Parts Manuals		52
30002991274	Rear Mower High Wear Kit		733
308701150	Lift Chain	7	99
30000889899	Additional 12 Month Warranty		2006

\*7oz knives available upon request

1502 E. Walnut St., Seguin, TX 78155

800-882-5756 800-882-5758 fax

boom@terrainking.com

oemparts@terrainking.com





## KB1800 BOOM 18' Articulated Model

C\ Jc'GHG

PRICING EFFECTIVE February 15, 2013

ORDER CODE	DESCRIPTION	APPROX WEIGHT	LIST PRICE
<b>18' BASE UNIT (One Choice Required)</b>			
30004831821	KB1800 Boom with Lever Controls	5,000	37,107
30004831820	KB1800 Boom with Electronic Joystick	5,000	44,252
<b>MOWER HEAD (One Choice Required)</b>			
34802986190	5' Rotary w/Ctr Hyd Door, Blade Bar & Head Swivel	1,115	14,690
34802986203	5' Rotary w/Ctr Hyd Door, Blade Bar (No Head Swivel)	1,061	12,664
34802986251	4' Heavy Duty Flail w/Ctr Hyd Door & Head Swivel	12,314	14,541
34802986253	4' Heavy Duty Flail w/Ctr Hyd Door (No Head Swivel)	777	12,515
34802986252	4' Flail w/3oz Grass Knives Head Swivel	---	15,731
34802986235	Saw Head - 4 Blade (No Head Swivel)	1098	15,598
<b>OPTIONS</b>			
30002983328A	Additional Operators and Parts Manuals		54
33002989326	Quick Hitch Kit *		3,948
33002989327	Hydraulic Kit for Quick Hitch Head **		523
30002975647	Flail Jack Stand Kit ***		342
30002988458	Rotary Head High Wear Kit		1,309
30002988459	Flail-Axe Head High Wear Kit		2,041
30002988460	Saw Head High Wear Kit		4,896
30002990017	Grass Flail Head High Wear Kit		4,896
30002985029	Mount Labor, Calcium Chloride & Oil		7,623
30000889809	Additional 12 Month Warranty		4,701

- ◆ 18' minimum horizontal reach
- ◆ 17' 1" minimum vertical reach
- ◆ 7' 4" below grade reach
- ◆ Two section articulated boom.
- ◆ Inner Boom Arm: 6" x 6" x 1/4" Alloy Steel Tubing
- ◆ Outer Boom Arm: 5" x 5" x 1/4" Alloy Steel Tubing
- ◆ 2" diam. main pivot pins with greaseable, Connex® bushings
- ◆ Turret-style turning arm with 180° hydraulic swing
- ◆ Self-contained hydraulic system with joystick or lever controls
- ◆ 20 gal front-mounted reservoir
- ◆ 35 gal total system volume
- ◆ Motor circuit gear pump rated 30 gpm (53 hp) and 3,000 psi at 2,200 rpm
- ◆ Control circuit gear pump rated 12 gpm (21 hp) and 3,000 psi at 2,200 rpm
- ◆ 2,400# frame counterweight and 500# wheel weight included
- ◆ 3/4" Full-frame mount kit design included in base price
- ◆ Shields® Premier polycarbonate windows with Supercoat™ finish
- ◆ 8,000# minimum tractor weight with a 95" minimum wheelbase
- ◆ 95 minimum net engine horsepower
- ◆ 84 minimum pto horsepower

Note:

- Terrain King KB series booms are recommended for cab tractor applications only
- Designed to fit Kubota M96S & M108S tractor models or approved equal
- Minimum applicable tire combination: 13.6R24/18.4R34 radials or approved equal
- Rear wheel design (cast or pressed steel) must be specified when ordering

\* Includes all components to convert the boom and one head

\*\* Required to convert additional heads

\*\*\* Required to level the head for quick hitch applications



1502 E. Walnut St., Seguin, TX 78155

800-882-5756 800-882-5758 fax

boom@terrainking.com

oemparts@terrainking.com

R21513



## KB2200 BOOM 22' Articulated Model

C\ jc`GHG

PRICING EFFECTIVE February 15, 2013

ORDER CODE	DESCRIPTION	APPROX WEIGHT	LIST PRICE
<b>22' BASE UNIT (One Choice Required)</b>			
30004832221	KB2200 Boom with Lever Controls	5,200	38,962
30004832220	KB2200 Boom with Electronic Joystick	5,200	45,509
<b>MOWER HEAD (One Choice Required)</b>			
34802986190	5' Rotary w/Ctr Hyd Door, Blade Bar & Head Swivel	1,115	14,690
34802986203	5' Rotary w/Ctr Hyd Door, Blade Bar (No Head Swivel)	1,061	12,664
34802986251	4' Heavy Duty Flail w/Ctr Hyd Door & Head Swivel	12,314	14,541
34802986253	4' Heavy Duty Flail w/Ctr Hyd Door (No Head Swivel)	777	12,515
34802986252	4' Flail w/3oz Grass Knives Head Swivel	---	15,731
34802986235	Saw Head - 4 Blade (No Head Swivel)	1098	15,598
<b>OPTIONS</b>			
30002983328A	Additional Operators and Parts Manuals		54
33002989326	Quick Hitch Kit *		3,948
33002989327	Hydraulic Kit for Quick Hitch Head **		523
30002975647	Flail Jack Stand Kit ***		342
30002988458	Rotary Head High Wear Kit		1,309
30002988459	Flail-Axe Head High Wear Kit		2,041
30002988460	Saw Head High Wear Kit		4,896
30002990017	Grass Flail Head High Wear Kit		4,896
30002985029	Mount Labor, Calcium Chloride & Oil		7,623
30000889809	Additional 12 Month Warranty		4,701

- ◆ 22' minimum horizontal reach
- ◆ 19' 7" minimum vertical reach
- ◆ 9' 7" below grade reach
- ◆ Two section articulated boom.
- ◆ Inner Boom Arm: 6" x 6" x 1/4" Alloy Steel Tubing
- ◆ Outer Boom Arm: 5" x 5" x 1/4" Alloy Steel Tubing
- ◆ 2" diam. main pivot pins with greaseable, Connex® bushings
- ◆ Turret-style turning arm with 180° hydraulic swing
- ◆ Self-contained hydraulic system with joystick or lever controls
- ◆ 20 gal front-mounted reservoir
- ◆ 35 gal total system volume
- ◆ Motor circuit gear pump rated 30 gpm (53 hp) and 3,000 psi at 2,200 rpm
- ◆ Control circuit gear pump rated 12 gpm (21 hp) and 3,000 psi at 2,200 rpm
- ◆ 2,400# frame counterweight and 1,300# wheel weight included
- ◆ 3/4" Full-frame mount kit design included in base price
- ◆ Shields® Premier polycarbonate windows with Supercoat™ finish
- ◆ 8,000# minimum tractor weight with a 95" minimum wheelbase
- ◆ 95 minimum net engine horsepower
- ◆ 84 minimum pto horsepower

**Note:**

- Terrain King KB series booms are recommended for cab tractor applications only
- Designed to fit Kubota M96S & M108S tractor models or approved equal
- Minimum applicable tire combination: 13.6R24/18.4R34 radials or approved equal
- Rear wheel design (cast or pressed steel) must be specified when ordering

\* Includes all components to convert the boom and one head  
 \*\* Required to convert additional heads  
 \*\*\* Required to level the head for quick hitch applications

1502 E. Walnut St., Seguin, TX 78155  
 800-882-5756 800-882-5758 fax  
 boom@terrainking.com  
 oemparts@terrainking.com





## Terrain Master 74 and 88 Right-Hand Flail Mowers C\Jc'GHG

- ◆ 74"and 88" Cutting Widths
- ◆ Full-Length Welded Tubular Frame with Transport Lock
- ◆ 25-Gallon Reservoir with 10 Micron Filtration
- ◆ Piston Pump Rated @ 24 GPM @ 3800 PSI
- ◆ 2-Spool Valve with Float Detent Position
- ◆ Automatic Cut-Off Switch
- ◆ 10-Gauge Unitized Cutter Housing
- ◆ 1/2" Inboard & 5/16" Outboard Side Plates
- ◆ Replaceable Skid Shoes
- ◆ 4-1/2" x 5/16" Wall Cuttershaft
- ◆ 1-5/16" Bore Greaseable, Self-aligning Cuttershaft Bearings
- ◆ 60 HP Piston Motor
- ◆ Belt Drive From Motor To Cuttershaft with Automatic Spring Tension
- ◆ 6" Adjustable Rear Roller
- ◆ 1" to 6" Cutting Height
- ◆ Front and Rear Safety Deflectors

PRICING EFFECTIVE February 15, 2013

ORDER CODE	DESCRIPTION	APPROX WEIGHT	LIST PRICE
348988005	74" Terrain Master, 3 oz Knives	1200	20,553
348988008	74" Terrain Master, 4 oz Knives	1205	20,693
348988009	88" Terrain Master, 3 oz Knives	1250	20,780
348988012	88" Terrain Master, 4 oz Knives	1255	20,915
<b>MOUNT KIT (Required)</b>			
30002985128 30002985084	M105S Cab/4wd (18.4-30 12.4-24) *4wd requires clipped foot guard		8,918
30802990553 30002990554	M8540/M9540 Cab/2wd/4wd (18.4-30 12.4-24) *4wd requires clipped foot guard		8,918
<b>OPTIONS</b>			
348988058	96" Flail King, Center, 3 oz Knives	1170	7,828
348988067	96" Flail King, Center, 4 oz Knives	1170	8,092
300107519	74" Right Hand Clipped Foot Guard	37	359
300107524	88" Right Hand Clipped Foot Guard	42	430
37002990357A	Additional Operators and Parts Manuals		52
300801022	Mounting Labor & Oil		5,283
30002987303	Right Wing High Wear Kit		740
30002991274	Rear Mower High Wear Kit		733
308701150	Lift Chain	7	99
30000889899	Additional 12 Month Warranty		4,701

\*7oz knives available upon request

1502 E. Walnut St., Seguin, TX 78155

800-882-5756 800-882-5758 fax

boom@terrainking.com

oemparts@terrainking.com





# Terrain Master 19'4" and 21'7"

## Tri-Wing Flail Mowers

C\|c'GHG

### BASE UNIT SPECIFICATIONS

- 19'4" and 21'7" Overall Cutting Widths
- Full-Length Welded Tubular Frame with Transport Lock
- 25-Gallon Reservoir with 10 Micron Filtration
- Tandem Piston Pumps Rated @ 24 GPM @ 3800 PSI
- 4-Spool Valve with Float Detent Position

### WING MOWER SPECIFICATIONS

- 74", or 88" Cutting Widths
- 1/2" Inboard & 5/16" Outboard Side Plates
- Replaceable Skid Shoes
- 4-1/2" x 5/16" Wall Cuttershaft
- 1-5/16" Bore Greaseable, Self-aligning Cuttershaft Bearings
- 53 HP Piston Motor
- Belt Drive From Motor To Cuttershaft with Automatic Spring Tension
- 6" Adjustable Rear Roller
- 1" to 6" Cutting Height
- Front and Rear Safety Deflectors
- Automatic Cut-Off Switch
- 10-Gauge Unitized Cutter Housing

### REAR MOWER SPECIFICATIONS

- 96" Cutting Width
- 10-Gauge Unitized Cutter Housing
- 5/16" Side Plates
- CAT I or CAT II Three-Point Hitch
- 4-1/2" x 5/16" Wall Cuttershaft
- 1-5/16" Bore Greaseable, Self-Aligning Cuttershaft Bearings
- 60 HP Gearbox
- 6" Adjustable Rear Roller
- 1" to 6" Cutting Height
- Front and Rear Safety Deflectors
- CAT 4 Driveline
- Belt Drive From Gearbox To Cuttershaft with Automatic Spring Tension

### PRICING EFFECTIVE February 15, 2013

ORDER CODE	DESCRIPTION	APPROX WEIGHT	LIST PRICE
34802990743	19'4" Terrain Master, 3 oz Knives	4570	43,588
34802990744	19'4" Terrain Master, 4 oz Knives	4574	43,910
34802990745	21'7" Terrain Master, 3 oz Knives	4620	44,276
34802990746	21'7" Terrain Master, 4 oz Knives	4624	44,595
<b>MOUNT KIT (Required)</b>			
30002990742	M108S Cab/2wd/4wd (13.6-24 18.4-34) Cast Rims		13,858
<b>OPTIONS</b>			
37002990357A	Additional Operators and Parts Manuals		52
300803399	Mounting Labor & Oil		8,589
1-30002991274 2-30002987303	Rear Mower High Wear Kit Right Wing/Left Wing High Wear Kits		2,211
308701150	Lift Chain	7	99
33002972480	Left-Wing Remote Positioning System		2,915
30000889899	Additional 12 Month Warranty		4,701

\*7oz knives available upon request

1502 E. Walnut St., Seguin, TX 78155

800-882-5756 800-882-5758 fax

boom@terrainking.com

oemparts@terrainking.com





## KBR Rotary Mower 60" Mid-Mount Rotary

### STANDARD SPECIFICATIONS

- ◆ Welded Steel Plate Frame Braced to the Front Bolster & Rear Axle
- ◆ 60-Gallon Hydraulic Reservoir with 12-Micron Filtration
- ◆ Lift Frame Capable of Tilting the Head 180°
- ◆ Lift Frame is Capable of Lifting the Head 17" Above & 6" Below Grade Level
- ◆ Exterior Boom Arm 5"x5"x1/4" Steel Tubing
- ◆ Stacked Hydraulic Pump Rated @ 51 GPM @ 2500 PSI
- ◆ 2-Spool, Open Center, Tapered Positive Metering Valve
- ◆ Tractor Req: 60 HP
- ◆ Cutting Capacity: 2" material
- ◆ Standard (1) year limited parts and labor warranty

### HEAD SPECIFICATIONS

- ◆ 60" Boom-Axe Style Head
- ◆ 1/4" Gauge Deck with 3/8" Side Skirts
- ◆ Channel Reinforcements on the Top Deck
- ◆ Spindle Mounting Plate is 1" at the Spindle
- ◆ 90 HP Gear Motor Directly Splined to the Spindle
- ◆ 4-1/2"x9" Hardened Spindle
- ◆ 1-1/4"x6" Blades, 360° Swing
- ◆ 360° Swinging Updraft Blades
- ◆ Full-Length Replaceable Skid Shoes
- ◆ Front & Rear Chain Guards

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT	LIST PRICE
<b>Mower Base Unit (One Choice Required)</b>			
31804950005	Rotary- Extreme Service Extension Arm-Cab	2,300	6,756
31804950009	Rotary- Breakaway Extension Arm-Cab	2,370	8,944
<b>Mower Head (One Choice Required)</b>			
34802964876	60" Rotary with Bar, Front & Rear Chain Guards	1,050	9,030
34802964878	60" Rotary with Pan, Front & Rear Chain Guards	1,100	9,872
34802964884	60" Breakaway Rotary with Bar, Front & Rear Chain Guards	1,050	9,724
34802964886	60" Breakaway Rotary with Pan, Front & Rear Chain Guards	1,100	10,653
<b>Mount Kit (One Choice Required)</b>			
30002989855	M108S Cab 4wd- Under Fender Tank		6,901
Call	M8540/8560 Cab 2 & 4 WD- Under Fender Tank		6,901
Call	M9540/9960 Cab 2 & 4 WD- Under Fender Tank		6,901
<b>Options</b>			
Call	Additional Operators and Parts Manuals		54
Call	Wheel Weight Kit-500 lbs.		1,266
Call	Wheel Weight Kit-1300 lbs.		2,709
30002963045	Mounting Labor & Oil		6,294
Call	Special Mower Paint (02791800)		887
Call	Special Tractor Paint		5,978
30000889899KBR	Additional 12 Month Warranty (00889899)		4,167



1502 E. Walnut St., Seguin, TX 78155  
 800-882-5756 800-882-5758 fax  
 boom@terrainking.com  
 oemparts@terrainking.com