

TERRAINKING™

Engineering Practical Solutions™

A Member of Alamo Group

OHIO STS CONTRACT 800317 - STS 515

EFFECTIVE 9-19-2014

Wholegoods Pricing



Full Line

Full Line Price Book

Section

Index

KB1800-2200 Booms

Terrain Master RH

Terrain Master DW

Flail King

KSM60 Mower

KSB6 Mower

STATE OF OHIO STATE TERM SCHEDULE
2014 CONTRACT DISCOUNT STRUCTURE

PRODUCT	DISCOUNT
KSB6	20%
Flail King	20%
KB Boom	20%
Terrain Master	20%
KSM60	20%
Multi-Unit Discount	
5+	2%
9+	3%



KB1800-2200 Mid-Mount Boom Mowers

STANDARD SPECIFICATIONS

- ◆ Bolt-On Undermount with Front and Rear Attached Rails
- ◆ Exclusive Slewing Ring Bearing is Featured for Boom Maneuverability
- ◆ Standard Boom Structure Made from Alloy Steel
- ◆ Main Pivot Features 2' Chrome Pins with Greaseable, Hardened Steel Bushings
- ◆ Self Contained Front Mounted Hydraulic System
- ◆ Oil-to-Air Cooler with Electric Fan
- ◆ Ability to Mow Horizontally within 6" of Rear Tire with Swivel Heads
- ◆ Boom Features Dipper and Lift
- ◆ Boom Reach Specs: **18' Models**= Up 17'-1", Out-18', Down 9'-8"
22' Models= Up-19' 7", Out-22', Down-12' 1"
- ◆ 180° Horizontal Boom Swing
- ◆ Axle-Mounted Boom Rest
- ◆ Mount Kit, all Wheel Weight, and Polycarbonate Window Included in Base Price
- ◆ Tractor Req: Min of 8,500 lbs and 90 HP. Min 90" Wheelbase and 18" Ground Clearance

HEAD SPECIFICATIONS

- ◆ 58" Cutting Diameter
- ◆ Alloy Deck Material with Double Wall Side Skirt
- ◆ 4-1/2"x9" Heat-Treated Alloy Spindle
- ◆ 152 HP Motor Direct-Coupled
- ◆ 2-1/2" x 5" Stacked Three-Leaf Blade Bar, Alloy Steel
- ◆ 5/8" x 5" High-Carbon Alloy Steel Blade, 360° Swing
- ◆ Standard (1) year limited parts and labor warranty.

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Boom Mower Base Unit (One Choice Required)				
30004831820	KB1800 Boom with Electronic Joystick Control	5,000		46,022
30004831821	KB1800 Boom with Cable/Lever Control	5,000		38,591
30004832220	KB2200 Boom with Electronic Joystick Control	5,200		47,330
30004832221	KB2200 Boom with Cable/Lever Control	5,200		40,520
Mower Head (One Choice Required)				
34802986190	5' Rotary w/ Center Hyd Door, Blade Bar & Head Swivel	1,115		15,278
34802986203	5' Rotary w/ Center Hyd Door, Blade Bar (No Head Swivel)	1,061		13,170
34802986251	4' Heavy Duty Flail w/ Center Hyd Door & Head Swivel	968		15,123
34802986253	4' Heavy Duty Flail w/ Center Hyd Door (No Head Swivel)	777		13,016
34802986252	4' Heavy Duty Flail w/ Center Hyd Door & Head Swivel Equipped w/ Special SHD Cuttershaft w 3 oz Knives	787		16,360
34802986235	90" Saw Head- 4 Blade (No Head Swivel)	968		16,222
34802988854	M22 Maintainer Head (Hitch Post Mounted)			13,384



1502 E. Walnut St., Seguin, TX 78155
 800-882-5756 800-882-5758 fax
 boom@terrainking.com
 oemparts@terrainking.com

KB1800-2200

Mid-Mount Boom Mowers

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT	LIST PRICE
Options			
30002983328A	Additional Operators and Parts Manuals		54
33002989326	Quick Hitch Kit- Base*		4,106
33002989327	Hydraulic Kit for Additional Heads- For Use With Quick Hitch Kit- Base**		544
30002975647	Jack Stand Kit- Heavy Duty Flail ***		355
30802990399	Jack Stand Kit- M22- Maintainer ***		680
30002988458	High Wear Kit- Rotary Head		1,224
30002988459	High Wear Kit- Heavy Duty Flail Head		1,907
30002990017	High Wear Kit- Heavy Duty Head w/ SHD Cuttershaft		1,432
30002988460	High Wear Kit- Saw Head		2,590
30002985029	Mounting Labor, Calcium Chloride, and Oil		7,112
30000889809	Additional 12 Month Warranty		4,385

* Kit includes all components to convert the boom and one head

** Kit includes all hydraulic components to convert one head

*** Required to level the head for Quick Hitch applications



Terrain Master RH 62, 74 and 88 Right-Hand Flail Mowers

STANDARD SPECIFICATIONS

- ◆ Full-Length Welded Tubular Frame with Transport Lock
 - ◆ 10-Gauge Unitized Cutter Housing
 - ◆ 1/2" Inboard & 5/16" Outboard Side Plates
 - ◆ Replaceable Skid Shoes
 - ◆ 4-1/2" x 5/16" Wall Cuttershaft
 - ◆ 1-5/16" Bore Greaseable, Self-aligning Cuttershaft Bearings
 - ◆ Belt Drive from Gearbox to Cuttershaft with Automatic Spring Tension
 - ◆ 6" Adjustable Rear Roller
 - ◆ 1" - 6" Cutting Height Adjustment
 - ◆ 74", or 88" Cutting Widths
 - ◆ Piston Pump Rated @ 24 GPM @ 3800 PSI
 - ◆ 2-Spool Valve with Float Detent Position
 - ◆ Automatic Cut-Off Switch
 - ◆ 60 HP Piston Motor
 - ◆ 25-Gallon Reservoir with 10 Micron Filtration
 - ◆ Front & Rear Deflectors
- General Specs:**
- ◆ Cutting Capacity: 1" diameter material
 - ◆ Standard (1) year limited parts and labor warranty

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Base Unit (One Choice Required)				
348988001	62" RH Terrain Master, 3 oz Knives	1,200		20,489
348988004	62" RH Terrain Master, 4 oz Knives	1,205		20,634
348988005	74" RH Terrain Master, 3 oz Knives	1,200		21,376
348988008	74" RH Terrain Master, 4 oz Knives	1,205		21,521
348988009	88" RH Terrain Master, 3 oz Knives	1,200		21,611
348988012	88" RH Terrain Master, 4 oz Knives	1,205		21,752
Mount Kit (One Choice Required)				
30002985128 30002985084	M108S- Series Cab 2 & 4wd (4wd models require clipped foot guards below)			8,918
30802990553 30002990554	M8560-9960S- Series Cab 2 & 4wd (4wd models require clipped foot guards below)			8,918
Options				
348988058	96" Flail King, Centered, 3 oz. knives	1170		8,141
348988067	96" Flail King, Centered, 4 oz. knives	1185		8,415
300107532	62" RH Clipped Foot Guard (Required on 4wd Models)			373
300107519	74" RH Clipped Foot Guard (Required on 4wd Models)			410
300107524	88" RH Clipped Foot Guard (Required on 4wd Models)			447
37002990357A	Additional Operators and Parts Manuals			54
308701150	Lift Chain (2 Ea. Required on Centered Units)	7		103
30002987303	High Wear Kit- Right Wing Mowers			692
30002991274	High Wear Kit- Rear Flail Mower			685
300801022	Mounting Charges- Labor & Oil			4,928
30000889899	Additional 12 Month Warranty			4,385



1502 E. Walnut St., Seguin, TX 78155
 800-882-5756 800-882-5758 fax
 boom@terrainking.com
 oemparts@terrainking.com



Terrain Master 19'4" and 21'7"

Tri-Wing Flail Mowers

STANDARD SPECIFICATIONS

Base Unit

- ◆ 19'4" and 21'7" Overall Cutting Widths
- ◆ Full-Length Welded Tubular Frame with Transport Lock
- ◆ 25-Gallon Reservoir with 10 Micron Filtration
- ◆ Tandem Piston Pumps Rated @ 24 GPM @ 3800 PSI
- ◆ 4-Spool Valve with Float Detent Position
- ◆ 1-15/16" Bore Greaseable, Self Aligning Cuttershaft Bearings

Wing Mower Specifications

- ◆ 74", or 88" Cutting Widths
- ◆ 1/2" Inboard & 5/16" Outboard Side Plates
- ◆ Replaceable Skid Shoes
- ◆ 4-1/2" x 5/16" Wall Cuttershaft
- ◆ 1-5/16" Bore Greaseable, Self-aligning Cuttershaft Bearings
- ◆ 53 HP Piston Motor
- ◆ Belt Drive from Gearbox to Cuttershaft with Automatic Spring Tension
- ◆ 6" Adjustable Rear Roller
- ◆ 1" - 6" Cutting Height Adjustment
- ◆ Front & Rear Deflectors

Wing Mower Specifications Continued

- ◆ Automatic Cut-Off Switch
- ◆ 10-Gauge Unitized Cutter Housing

Rear Mower Specifications

- ◆ 96" Cutting Width
- ◆ 10-Gauge Unitized Cutter Housing
- ◆ 5/16" Side Plates
- ◆ CAT I or CAT II Three-Point Hitch
- ◆ 4-1/2" x 5/16" Wall Cuttershaft
- ◆ 1-15/16" Bore Greaseable, Self Aligning Cuttershaft Bearings
- ◆ 60 HP Gearbox
- ◆ 6" Adjustable Rear Roller
- ◆ 1" - 6" Cutting Height Adjustment
- ◆ Front & Rear Deflectors
- ◆ CAT 4 Driveline
- ◆ Belt Drive from Gearbox to Cuttershaft with Automatic Spring Tension

General Specs:

- ◆ Cutting Capacity: 1" diameter material
- ◆ Standard (1) year limited parts and labor warranty

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT	LIST PRICE
Base Unit (One Choice Required)			
34802990743	19'4" Terrain Master, 3 oz Knives	4,570	45,666
34802990744	19'4" Terrain Master, 4 oz Knives	4,574	46,105
34802990745	21'7" Terrain Master, 3 oz Knives	4,620	46,047
34802990746	21'7" Terrain Master, 4 oz Knives	4,624	46,379
Mount Kit (One Choice Required)			
30002990742	M108S- Series Cab 2 & 4wd	1,170	14,412
30002994030	M8560-9960S- Series Cab 2 & 4wd	1,170	14,412
300107532	62" RH Clipped Foot Guard (Required on 4wd Models)		373
300107533	62" LH Clipped Foot Guard (Required on 4wd Models)		373
300107519	74" RH Clipped Foot Guard (Required on 4wd Models)		410
300107520	74" LH Clipped Foot Guard (Required on 4wd Models)		410
300107524	88" RH Clipped Foot Guard (Required on 4wd Models)		447
300107525	88" LH Clipped Foot Guard (Required on 4wd Models)		447



1502 E. Walnut St., Seguin, TX 78155
 800-882-5756 800-882-5758 fax
 boom@terrainking.com
 oemparts@terrainking.com



Terrain Master 19'4" and 21'7" Tri-Wing Flail Mowers

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Options				
37002990357A	Additional Operators and Parts Manuals			54
308701150	Lift Chain (2 Ea. Required on Centered Units)	7		103
33002972480	Left-Wing Remote Positioning System			3,032
30002987303	High Wear Kit- Right & Left Wing Mowers (2 required)			692
30002991274	High Wear Kit- Rear Flail Mower			685
300803399	Mounting Charges- Labor & Oil			8,013
30000889899	Additional 12 Month Warranty			4,385



1502 E. Walnut St., Seguin, TX 78155
800-882-5756 800-882-5758 fax
boom@terraining.com
oemparts@terraining.com



FLAIL KING 74, 88, 96

3-Point Mount Flail Mowers

STANDARD SPECIFICATIONS

- ◆ 74", 88", 96" Cutting Widths
- ◆ 10-Gauge Unitized Cutter Housing
- ◆ 5/16" Side Plates
- ◆ CAT I or CAT II Three-Point Hitch
- ◆ 4-1/2" x 5/16" Wall Cuttershaft
- ◆ 1-15/16" Bore Greaseable, Self Aligning Cuttershaft Bearings
- ◆ 60 HP Gearbox
- ◆ CAT 4 Driveline
- ◆ Belt Drive from Gearbox to Cuttershaft with Automatic Spring Tension
- ◆ 6" Adjustable Rear Roller
- ◆ 1" - 6" Cutting Height Adjustment
- ◆ Front & Rear Deflectors
- ◆ Factory Set-Up
- ◆ Cutting Capacity: 1" diameter material
- ◆ Standard (1) year limited parts and labor warranty

Tractor Requirements

- ◆ 74" Req: Min 35 HP
- ◆ 88" Req: Min 40 HP
- ◆ 96" Req: Min 50 HP

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT	LIST PRICE
Base Unit (One Choice Required)			
34802990739	74" Flail King , Center, 3 oz Knives	930	7,208
34802990740	74" Flail King, Center, 4 oz Knives	930	7,419
348988037	88" Flail King , Center, 3 oz Knives	1,035	7,310
348988040	88" Flail King, Center, 4 oz Knives	1,035	7,561
348988058	96" Flail King , Center, 3 oz Knives	1,170	8,141
348988067	96" Flail King, Center, 4 oz Knives	1,170	8,416
Options			
37002990357A	Additional Operators and Parts Manuals		54
308701150	Lift Chain (2 Ea. Required on Centered Units)	7	103
30002991274	High Wear Kit- Rear Flail Mower		685
30000889899	Additional 12 Month Warranty		1,872
30000888990	Dealer Mounting- Setup Fee		225



1502 E. Walnut St., Seguin, TX 78155
 800-882-5756 800-882-5758 fax
 boom@terrainking.com
 oemparts@terrainking.com



KSM60

60" Mid-Mount Rotary

STANDARD SPECIFICATIONS

- ◆ Welded Steel Plate Frame Braced to the Front Bolster & Rear Axle
- ◆ 53-Gallon Hydraulic Reservoir with 12-Micron Filtration
- ◆ Lift Frame Capable of Tilting the Head 180°
- ◆ Lift Frame is Capable of Lifting the Head 17" Above & 6" Below Grade Level
- ◆ Exterior Boom Arm 5"x5"x1/4" Steel Tubing
- ◆ Stacked Hydraulic Pump Rated @ 51 GPM @ 2500 PSI
- ◆ 2-Spool, Open Center, Tapered Positive Metering Valve
- ◆ Min Tractor Req: 60 PTO HP
- ◆ Cutting Capacity: 2" material
- ◆ Standard (1) year limited parts and labor warranty

HEAD SPECIFICATIONS

- ◆ 60" Rotary Head
- ◆ 1/4" Gauge Deck with 3/8" Side Skirts
- ◆ Channel Reinforcements on the Top Deck
- ◆ Spindle Mounting Plate is 1" at the Spindle
- ◆ 90 HP Gear Motor Directly Splined to the Spindle
- ◆ 4-1/2"x9" Hardened Spindle
- ◆ 1-1/4"x6" Blades, 360° Swing
- ◆ 360° Swinging Updraft Blades
- ◆ Full-Length Replaceable Skid Shoes
- ◆ Front & Rear Chain Guards

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Mower Base Unit (One Choice Required)				
31804950005	Rotary- Extreme Service Extension Arm-Cab	2,300		7,026
31804950009	Rotary- Breakaway Extension Arm-Cab	2,370		9,302
Mower Head (One Choice Required)				
34802964876	60" Rotary with Bar, Front & Rear Chain Guards	1,050		9,391
34802964878	60" Rotary with Pan, Front & Rear Chain Guards	1,100		10,267
34802964884	60" Breakaway Rotary with Bar, Front & Rear Chain Guards	1,050		10,113
34802964886	60" Breakaway Rotary with Pan, Front & Rear Chain Guards	1,100		11,079
Mount Kit (One Choice Required)				
30002989855	M108S Cab 2 & 4wd- Under Fender Tank			7,177
30002993586	M8560/9960 Cab 2 & 4wd- Under Fender Tank			7,177
Options				
348FK96185CC	96" Flail King- 18.5" Offset Rear Flail Unit- CC Knives			8,690
348FK96185ES	96" Flail King- 18.5" Offset Rear Flail Unit- ES Knives			8,965
30002972609	Wheel Weight Kit-500 lbs.			1,316
30002971789	Wheel Weight Kit-1300 lbs.			2,818
30002897300	Additional Operators and Parts Manuals			54
30002963045	Mounting Labor & Oil			6,624
30002791800V6	Special Mower Paint (02791800)			933
30000889899KBR	Additional 12 Month Warranty (00889899)			4,385



1502 E. Walnut St., Seguin, TX 78155
 800-882-5756 800-882-5758 fax
 boom@terrainking.com
 oemparts@terrainking.com



KSB6

6' Mid-Mount Sickle Bar

STANDARD SPECIFICATIONS

- ◆ Full Hydraulic Drive of Cutter Knife
- ◆ Hydraulically Actuated Breakaway
- ◆ Hydraulic Lift and Tilt
- ◆ Knife Speed Governor
- ◆ 3" Heavy Duty Industrial Rock Guards
- ◆ Reversible Hydraulic Motor
- ◆ Safety Transport Locks
- ◆ Self-Contained Hydraulics
- ◆ Cutting Capacity: 1/2" diameter material
- ◆ Tractor Req: Min. 3,000 lbs. and a 25 HP rating

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Sickle Bar Mower Base Unit (One Choice Required)				
31804117207	KSB6 Single RH w/ Serrated Knives	723		12,918
Options				
370002993751A	Additional Operators and Parts Manuals (Hard Copy)			54
370002993751ACD	Additional Operators, Parts & Service Manuals (CD Format)			54
3080487100	Knife Holder Brackets (Order Quantity 2 per Unit)	9		130
30802988134	Kubota M5040/M6040/M7040 Pump Guard Kit			308
3000800000	Factory Mounting & Oil			2,047
CALL	Special Mower Paint			397
30002991505	Additional 12 Month Warranty			2,044

Mount Kit (One Choice Required)				
PRODUCT ORDER CODE	TRACTOR DESCRIPTION	MAX. TIRE SIZE		LIST PRICE
		FRONT	REAR	
30802992899	Kubota L5740 Cab 4wd (Mid-Mount PTO Req'd)	9.5-16	14.9-26	5,041
30802992900	Kubota M5040/M6040/M7040 ROPS 2 & 4wd	12.5-18	16.9-28	5,041
30802992901	Kubota M5040/M6040/M7040 Cab 2 & 4wd	11.2-24	16.9-30	5,041
30802993749	Kubota M8560/9960 Cab 2 & 4wd	12.4-24	18.4-30	5,041



1502 E. Walnut St., Seguin, TX 78155
 800-882-5756 800-882-5758 fax
 boom@terrainking.com
 oemparts@terrainking.com

TERRAINKING™

Engineering Practical Solutions™

A Member of Alamo Group



Sold Exclusively By Kubota Dealers

OEM PERFORMANCE PARTS
TERRAINKING™

Terrain King™ OEM Performance Parts offer the safety, durability and warranty protection you expect. OEM Parts are available through your local dealer. For a list of these authorized dealers in your area, visit www.terrainking.com and click the authorized dealer tab.

the CuttingEdge
Safetyprogram™

Ask your local dealer for information on upcoming OSHA certified safety training courses. Please visit www.terrainking.com/safety to learn more.