

Kut Kwick Corporation

Price List

Effective January 1, 2017

STS515

Contract 800364

Table of Contents

Pricing and Option Pricing for SSM38-72D	pg 2
Pricing and Option Pricing for MSM83-88D	pg 3
Pricing and Option Pricing for BM83-88D	pg 4
Pricing and Option Pricing for FM83-88D	pg 5

KUT KWICK CORPORATION
Post Office Box 984, Brunswick, GA 31521-0984
Telephone 800-248-5945
E-Mail: mowers@kutkwick.com
Web site: www.kutkwick.com

FACTORY PRICE LIST EFFECTIVE January 1, 2017

SuperSlopeMaster SSM SERIES

STANDARD SPECIFICATIONS:

Mower: Slope cutting to 40 degrees, riding, 72" cut, rear discharge, outfront rotary, 38 HP water-cooled diesel, speed to 8 mph, skid steered through twin, closed loop hydraulic drive systems, independently powering 26" x 12"-12" dual drive wheels on each side at the rear. 19" x 6" puncture proof casters support the cutter deck from the front. For safety, the operator is seated on a tilting seat located at the rear extremity of the machine. The cutter deck has 1 1/2" to 6 1/2" of height adjustment, the cutter assembly is decked with 1/4" thick steel; the deck supports the chassis from the front while pivoting to the sides to follow the contour of the turf. Standard with Roll Bar and retractable seat belt.

<u>MODEL NUMBER</u>	<u>WIDTH OF CUT</u>	<u>CUTTER TYPE</u>	<u>H.P. ENGINE</u>	<u>TYPE OF FUEL</u>	<u>FACTORY BASE PRICE FOB BRUNSWICK, GA</u>
SSM38-72D	72"	Rotary	38	DIESEL	\$ 64,999.00

OPTIONS AND ACCESSORIES: are listed below. They are priced to be installed as an addition to or a substitution for basic equipment at the time of original manufacture. Add the price indicated for the elected option or accessory to the base price.

<u>DESCRIPTION</u>	<u>ADD-ON</u>
HIGH LIFT BLADES - 3/8" thick	No Charge
MEDIUM LIFT BLADES - 3/8" thick	No Charge
CANOPY - Factory installation at time of manufacture	\$ 863.00
LIGHT KIT - Factory installation at time of manufacture	\$ 614.00
ROTARY BEACON - In lieu of flashing light included in light kit above - Factory installation at time of manufacture	\$ 147.00
DELUXE ENGINE GAUGE PACKAGE - Includes oil pressure, volt meter, water temperature, hour meter - Factory installation at time of manufacture	\$ 478.00

CRATING: A crating charge of \$700.00 net will apply when required for shipping (overseas) or when requested by customer.

KUT KWICK CORPORATION

Post Office Box 984, Brunswick, GA 31521-0984

Telephone 800-248-5945

E-Mail: mowers@kutkwick.com

Web site: www.kutkwick.com

FACTORY PRICE LIST EFFECTIVE January 1, 2017

MegaSlopeMaster MSM SERIES

STANDARD SPECIFICATIONS:

TRACTOR: Mower: Slope cutting to 40 degrees, riding 88" cut, rear discharge out front rotary standard with 3/8" thick flat blades, self-propelled and steered through twin, closed loop hydraulic systems, independently powering 38" x 18" - 20" drive wheels, 83 HP water cooled, turbo-charged diesel engine. Operator seated at the rear extremity of the machine for safety in a tilting seat. Cutter deck supported with 19" x 6" puncture proof casters, 4" through 10" height adjustment, decked with thick steel, and supports the chassis from the front while pivoting to the sides to follow the contour of the ground. Standard with 4-point ROPS and 4-point harness.

TRACTION UNIT:

<u>MODEL NUMBER</u>	<u>WIDTH OF CUT</u>	<u>CUTTER TYPE</u>	<u>H.P. ENGINE</u>	<u>TYPE OF FUEL</u>	<u>FACTORY BASE PRICE FOB BRUNSWICK, GA</u>
MSM83-88D	88"	Rotary	83	Diesel	\$ 96,499.00

OPTIONS AND ACCESSORIES: are listed below. They are priced to be installed as an addition to or a substitution for basic equipment at the time of original manufacture. Add the price indicated for the elected option or accessory to the base price.

DESCRIPTION

ADD ON

Dual drive wheels - Required for 40 degree cutting - Outside tire size - 38x14.00x20 - Factory installation at time of manufacture	\$ 2,549.00
Cab Protection Enclosure - Protection against stinging insects. This protection consists of a combination of expanded metal, screening, lexan and 2 cab doors. - Factory installation at time of manufacture	\$ 4,044.00
A/C Option - Air conditioning Only. Environmental control offers greater operator comfort & increased productivity. - Factory installation at time of manufacture	\$ 13,599.00
Light Kit - Factory installation at time of manufacture	\$ 716.00
Rotary Beacon - In lieu of flashing light included in light kit above - Factory installation at time of manufacture	\$ 172.00

KUT KWICK CORPORATION
Post Office Box 984, Brunswick, GA 31521-0984
Telephone 800-248-5945
E-Mail: mowers@kutkwick.com
Web site: www.kutkwick.com

FACTORY PRICE LIST EFFECTIVE January 1, 2017

BrushMaster BM SERIES

STANDARD SPECIFICATIONS:

TRACTOR: Industrial brushcutting/mower, riding, 88" cut, rear discharge, outfront rotary. 83HP water-cooled diesel engine. Standard with three 3/8" thick flat blades. The machine is self-propelled and skid steered through twin, closed loop hydraulic systems, independently powering 44 x 18.4-16.1 drive wheels. For safety, the operator is seated at the rear extremity of the machine. Caster type cutter with 19" x 6" puncture proof casters, the cutter deck has 4" through 10" of height adjustment. The cutter assembly is decked with 1/4" thick steel. The deck supports the chassis from the front while pivoting to the sides to follow the contour of the ground. Standard with 4 point ROPS and retractable seat belt.

TRACTION UNIT:

<u>MODEL NUMBER</u>	<u>WIDTH OF CUT</u>	<u>CUTTER TYPE</u>	<u>H.P. ENGINE</u>	<u>TYPE OF FUEL</u>	<u>FACTORY BASE PRICE FOB BRUNSWICK, GA</u>
BM83-88D	88"	Rotary	83	Diesel	\$ 96,499.00

OPTIONS AND ACCESSORIES: are listed below. They are priced to be installed as an addition to or a substitution for basic equipment at the time of original manufacture. Add the price indicated for the elected option or accessory to the base price.

DESCRIPTION

ADD ON

Cab Protection Enclosure

\$ 4,044.00

- Protection against stinging insects. This protection consists of a combination of expanded metal, screening, lexan and 2 cab doors.
- Factory installation at time of manufacture

A/C Option

\$ 13,599.00

- Air conditioning Only. Environmental control offers greater operator comfort & increased productivity.
- Factory installation at time of manufacture

KUT KWICK CORPORATION

Post Office Box 984, Brunswick, GA 31521-0984

Telephone 800-248-5945

E-Mail: mowers@kutkwick.com

Web site: www.kutkwick.com

FACTORY PRICE LIST EFFECTIVE January 1, 2017

FireMaster FM SERIES

STANDARD SPECIFICATIONS:

TRACTOR: Industrial brushcutting/mower, riding, 88" cut, rear discharge, outfront rotary. 83HP water-cooled diesel engine. Standard with three 3/8" thick flat blades. The machine is self-propelled and skid steered through twin, closed loop hydraulic systems, independently powering 44 x 18.4-16.1 drive wheels. For safety, the operator is seated at the rear extremity of the machine. Caster type cutter with 19" x 6" puncture proof casters, the cutter deck has 4" through 10" of height adjustment. The cutter assembly is decked with 1/4" thick steel. The deck supports the chassis from the front while pivoting to the sides to follow the contour of the ground. Standard with 4 point ROPS and retractable seat belt.

TRACTION UNIT:

<u>MODEL NUMBER</u>	<u>WIDTH OF CUT</u>	<u>CUTTER TYPE</u>	<u>H.P. ENGINE</u>	<u>TYPE OF FUEL</u>	<u>FACTORY BASE PRICE FOB BRUNSWICK, GA</u>
FM83-88D	88"	Rotary	83	Diesel	\$ 115,396.00

INCLUDED ACCESSORIES are listed below. They are installed at the time of original manufacture.

DESCRIPTION

Cabin Configuration:

All FireMaster machines are factory equipped with a recirculating closed system air conditioner to protect the operator from smoke and other contaminants. The cabin enclosure has metal framed doors. The door windows, as well as the rear opening, are all covered with Lexan sheeting. The key windows are covered by metal guarding.

Fire Protection Package:

-GPS for navigating to areas to be cleared, to fires and/or lightning strikes, and to roadways for escape routes.

-Fire Shelter Tent (large) - Forest Service Spec 5100-606

-Forward and rear facing work lights