

STATE OF OHIO  
DEPARTMENT OF ADMINISTRATIVE SERVICES  
GENERAL SERVICES DIVISION  
OFFICE OF PROCUREMENT SERVICES  
4200 SURFACE ROAD, COLUMBUS, OH 43228-1395

MANDATORY USE CONTRACT FOR: LAW ENFORCEMENT UNIFORMS FOR THE OHIO DEPARTMENT OF NATURAL RESOURCES

CONTRACT No.: OT900014

EFFECTIVE DATES: 07/01/13 to 06/30/16

The Department of Administrative Services has accepted bids submitted in response to Invitation to Bid No. \_\_\_\_\_ that opened on 02/27/13. The evaluation of the bid response(s) has been completed. The bidder(s) listed herein have been determined to be the lowest responsive and responsible bidder(s) and have been awarded a contract for the items(s) listed. The respective bid response, including the [Terms and Conditions for Bidding, Standard Contract Terms and Conditions, and Supplemental Contract Terms and Conditions](#), special contract terms & conditions, any bid addenda, specifications, pricing schedules and any attachments incorporated by reference and accepted by DAS become a part of this Requirements Contract.

This Requirements Contract is effective beginning and ending on the dates noted above unless, prior to the expiration date, the Contract is renewed, terminated or cancelled in accordance with the Contract Terms and Conditions.

This Requirements Contract is available to THE OHIO DEPARTMENT OF NATURAL RESOURCES, as applicable.

Agencies are eligible to make purchases of the listed supplies and/or services in any amount and at any time as determined by the agency. The State makes no representation or guarantee that agencies will purchase the volume of supplies and/or services as advertised in the Invitation to Bid.

SPECIAL NOTE: State agencies may make purchases under this Requirements Contract up to \$2500.00 using the state of Ohio payment card. Any purchase that exceeds \$2500.00 will be made using the official state of Ohio purchase order (ADM-0523). Any non-state agency, institution of higher education or Cooperative Purchasing member will use forms applicable to their respective agency.

Questions regarding this and/or the Requirements Contract may be directed to:

Walt Schneider, CPPB  
walter.schneider@das.state.oh.us

This Requirements Contract and any Amendments thereto are available from the DAS Web site at the following address:

<http://www.ohio.gov/procure>

Signed: \_\_\_\_\_  
Robert Blair, Director Date

TABLE OF CONTENTS

<u>CLAUSES</u>	<u>PAGE NO.</u>
Brand Specific	3
Contract Award	3
Contract Renewal	3
Delivery and Acceptance	3
Disclosure of Subcontractors	6
Evaluation	3
Fixed Price with Economic Adjustment	4
Secure Online Web-Based Custom Catalog	5
Sweatshop Free	5
Usage Reports	6
Specifications	7 – 31
Contract Items	32 - 34
Contractor's Index	35

### SPECIAL CONTRACT TERMS AND CONDITIONS

AMENDMENTS TO CONTRACT TERMS AND CONDITIONS: The following Amendments to the Contract Terms and Conditions do hereby become a part hereof. In the event that an amendment conflicts with the Contract Terms and Conditions, the Amendment will prevail.

PRIMARY VENDOR CONTRACT: This bid is issued to establish a Primary Vendor contract. This contract resulting from this bid will be made with one supplier capable of providing a complete uniform service and meeting the uniform needs for the Ohio Department of Natural Resources (ODNR) as listed herein. By the signature affixed to Page 1, of this Bid, the Bidder certifies that the items offered are in compliance with all bid requirements and specifications.

BRAND SPECIFIC: The items specified in this bid are being bid as Brand Specific. No alternates will be accepted for award. Bid is in accordance with the Ohio Administrative Code 123:5-1-10 (I). The Department of Administrative Services (DAS) and the Ohio Department of Natural Resources (ODNR) have examined various manufacturers' fabric, colors and durability. Based on the intent to standardize all uniform components within the state, the agency has determined that the acceptable brands shall include, Flying Cross by Fechheimer, Fechheimer, Blauer, Elbeco, Uncle Mike's, Broome, Stratton, Bates, Thorogood and Danner. The manufacturer/style number has been specified for each item. Consideration will not be given for any alternates bid.

DELIVERY AND ACCEPTANCE: Items designated as Stock Items will be delivered to the agency as soon as practicable but within thirty (30) days after receipt of order. Items designated as both winter and summer items will be delivered to the agency as soon practicable but within sixty (60) days after receipt of order. Items designated winter or summer or Make-to-Order items will be delivered to the participating agency as soon as practicable but within thirty (90) days after receipt of order. All items will be delivered in accordance with paragraphs S-8, S-9, and S-10 of the SUPPLEMENTAL CONTRACT TERMS AND CONDITIONS. The delivery location will be noted on the purchase order issued by the participating agency. Acceptance (transfer of title) will occur upon the inspection and written confirmation by the ordering agency that the supplies delivered conform to the requirements set forth in the Contract. Unless otherwise provided in the Contract, acceptance shall be conclusive except as regards to latent defects, fraud, or such gross mistakes as amount to fraud.

AUTHORIZED DEALER STATEMENT: Bidders responding to this bid must be an authorized dealer or manufacturer of the products bid. Bidders should submit a letter with their bid response certifying that they are the manufacturer or an authorized dealer for all products bid. This certification must be on the manufacturer's letterhead and must be signed by a duly authorized representative of the manufacturer. The bidder should include the certification in the sealed bid package but, will be required to provide the said certification letter within seven (7) calendar days after notification, to the Office of State Purchasing. Failure to submit the certification letter within the stated time period may result in the bidder being deemed as not responsive.

REFERENCES TO ALTERNATE TERMS: Any reference, which may appear on any price list, specification or literature, to any terms and conditions, such as F.O.B. Shipping Point or Prices Subject to Change, will not be part of any contract with the successful bidder(s) and will be disregarded by the state of Ohio.

EVALUATION: Bids will be evaluated in accordance with Article I-5 of the "Instructions to Bidders". In addition the agency's estimated annual usage will be multiplied by the Bidder's offered prices and summed for all items to determine the lowest responsive and responsible bidder. ODNR may evaluate samples as required to determine the items conform to the stated specifications. Bidders should confirm that all pricing lines have been completed, including the catalog percentage discount for items not specifically listed.

CONTRACT AWARD: The contract will be awarded to the lowest responsive and responsible bidder capable of providing a turn-key uniform delivery and alteration service and an online, secure, custom catalog for ordering as described on page 5 of this bid by low lot total. Low lot total will be determined by multiplying the unit cost by the estimated usage listed of each item in the bid and then adding each of the item totals together to arrive at a total for all items. Failure to bid all items may result in the bidder being deemed not responsive.

MINIMUM ORDERS: Any item(s) ordered from a contract awarded pursuant to this bid shall be shipped F.O.B. destination, freight prepaid, subject to a minimum order of not less than fifty dollars (\$ 50.00). Orders placed for less than \$ 50.00 shall be subject to section S-10 of the Contract Supplemental Terms and Conditions.

CONTRACT RENEWAL: This contract may be renewed for one (1) month, at the state's option. Additionally, this contract may be renewed, by agreement, any number of times for any period of time under the same prices, terms and conditions stated herein. The cumulative total of all renewals by agreement may not exceed three (3) years.

**DESCRIPTIVE LITERATURE:** The Bidder may be required to submit descriptive literature of the supplies or services being offered. If requested, the literature will be used in the evaluation process to determine the lowest responsive and responsible bidder. If not provided as part of the bid response, the Bidder must provide said literature within seven (7) calendar days after request/notification by the Office of Procurement Services to do so. Any references, that may appear in the descriptive literature, that may alter the terms and conditions and specifications of the bid (e.g. F.O.B. Shipping Point or Prices Subject to Change), will not be part of any contract and will be disregarded by the state of Ohio. Failure of the bidder to furnish descriptive literature either as part of their bid response or within the time specified herein will deem the bidder not responsive.

**PRODUCT SAMPLES:** The bidder(s) may be required to submit samples of the supplies being offered. Any samples required will be used in the evaluation process to determine the lowest responsive and responsible bidder. If not included as part of their bid response, the bidder will be required to provide the samples within seven (7) calendar days after notification. Failure to provide the samples within the stated time period will result in the bidder being deemed not responsive. After award of the contract, the samples will be used as a basis of comparison with actual product delivered under contract. Any variation between the samples and product being delivered will be considered as an event of default. Any variations between the samples and actual product being delivered that are due to manufacturer changes may be acceptable and shall require prior written approval from DAS.

**MANUFACTURER'S SPECIFICATIONS:** Manufacturer's specification sheets should be submitted with the bid for each item/manufacturer bid. Specification sheets shall be labeled with the name of the manufacturer, the style number, and the bid item number from the specifications or the bid pricing sheets below. The state acknowledges that it may receive bids from multiple distributors bidding the same manufacturer's products. In such situations, specification sheets/samples may be submitted by manufacturer(s) on behalf of multiple distributors, provided that such specification sheets/samples are accompanied by written documentation, on manufacturer's letterhead, signed by an authorized representative of the manufacturer, listing the named distributor(s) for whom the specification sheets are provided. Any bidder not appearing on this listing and who has failed to furnish requested specification sheets/samples may be considered not-responsive. If not included as part of their bid response, the bidder will be required to provide the specification sheets within seven (7) calendar days after notification. Failure to provide the specification sheets within the stated time period will result in the bidder being deemed not responsive.

**FIXED-PRICE WITH ECONOMIC ADJUSTMENT:** The contract prices(s) will remain firm for the first six (6) months duration of the contract. Thereafter, the Contractor may submit a request to increase their price(s) to be effective thirty (30) calendar days after acceptance by DAS. No price adjustment will be permitted prior to the effective date of the increase received by the Contractor from his suppliers, or on purchase orders that are already being processed, or on purchase orders that have been filled and are awaiting shipment. If the Contractor receives orders requiring quarterly delivery, the increase will apply to all deliveries made after the effective date of the price increase.

The price increase must be supported by a general price increase in the cost of the finished supplies, due to increases in the cost of raw materials, labor, freight, Workers' Compensation and/or Unemployment Insurance, etc. Detailed documentation, to include a comparison list of the contract items and proposed price increases, must be submitted to support the requested increase. Supportive documentation should include, but is not limited to: copies of the old and the current price lists or similar documents which indicate the original base cost of the product to the Contractor and the corresponding increase, and/or copies of correspondence sent by the Contractor's supplier on the supplier's letterhead, which contain the above price information and explains the source of the increase in such areas as raw materials, freight, fuel or labor, etc.

Should there be a decrease in the cost of the finished product due to a general decline in the market or some other factor, the Contractor is responsible to notify DAS immediately. The price decrease adjustment will be incorporated into the contract and will be effective on all purchase orders issued after the effective date of the decrease. If the price decrease is a temporary decrease, such should be noted on the invoice. In the event that the temporary decrease is revoked, the contract pricing will be returned to the pricing in effect prior to the temporary decrease. For quarterly deliveries, any decrease will be applied to deliveries made after the effective date of the decrease. Failure to comply with this provision will be considered as a default and will be subject to Provision I.C. "Termination/Suspension" and Provision II. of the "Contract Remedies:" of the "Standard Contract Terms and Conditions".

**SWEATSHOP FREE:** By the signature affixed to this ITB, Bidder certifies that all facilities used for the production of the supplies or performance of services offered in the bid are in compliance with applicable domestic labor, employment, health and safety, environmental and building laws. This certification applies to any and all suppliers and/or subcontractors used by the Bidder in furnishing the supplies or services described in the bid and awarded to the Bidder. If DAS receives a complaint alleging non-compliance with sweatshop free requirements, DAS may enlist the services of an independent monitor to investigate allegations of such non-compliance on the part of the Contractor, any sub-contractors or suppliers used by the Contractor in performance of the Contract. If allegations are proven to be accurate, the Contractor will be advised by DAS of the next course of action to resolve the complaint and the Contractor will be responsible for any costs associated with the investigation. Items that will be considered in an investigation include, but are not limited to standards for wages, occupational safety and work hours.

**SECURE ONLINE WEB-BASED CUSTOM CATALOG:** The awarded contractor will provide a secure on-line, web based custom catalog (hereafter referred to as "the catalog") containing the items awarded on this contract and other items authorized by the ODNR Director of Enforcement. The catalog shall be the primary ordering and sourcing media for all items awarded in the ensuing contract and must conform to the following requirements:

- A. The catalog shall include only items authorized by the ensuing state of Ohio Department of Natural Resources contract and which are approved for the online catalog by the ODNR Director of Enforcement.
- B. The catalog shall include links to applicable sizing charts, ordering information, alteration instructions cleaning instructions, and ODNR Enforcement policy issues related to the issuing and wearing of each uniform item. The ODNR will have the authority to add links and uniform policy information to other State of Ohio contracts from this website.
- C. The catalog will allow for payment using the state of Ohio procurement or debit card.
- D. The catalog will be maintained by the successful contractor and updated as required to include notification of back-ordered items, recalls and other pertinent uniform apparel information.
- E. Ohio Department of Natural Resources authorized personnel from facilities state-wide will utilize the catalog for purchase of their uniform requirements.
- F. The catalog will be available and accessible only to ODNR employees and other users authorized by the state of Ohio DAS Office of Procurement Services or the Ohio Department of Natural Resources.
- G. The catalog must be password protected and contain appropriate security procedures to protect users and their credit card or financial information.
- H. The catalog shall contain a photo and a complete description of each item, the item's contract price available to state of Ohio Department of Natural Resources users and other users authorized by the Ohio Department of Natural Resources.
- I. No item shall be added or deleted from the catalog without the written permission of the state of Ohio DAS Office of Procurement Services or the Ohio Department of Natural Resources Director of Enforcement.

Bidders should submit with their bid a comprehensive statement documenting their ability and capability of providing an online, secure, web-based custom catalog as described in A. through I. above. Failure to submit said documentation with the bid may deem your bid not responsive. If not submitted with the bid this item must be provided within 7 working days of request.

**AUTOMOBILE LIABILITY INSURANCE REQUIREMENTS AND CHECKLIST - Reference: Supplemental Contract Terms & Conditions – Page 10, Article S-13**

Automobile Liability - Automobile Insurance is required for anyone coming onto State Property to deliver goods or to perform services using a vehicle, which is owned, leased or rented by the Contractor. Any Bidder, Broker, or Subcontractor who will be on State Property, but not delivering goods or performing services, is required to carry Automobile Liability insurance that complies with the State and Federal laws regarding financial responsibility.

Contractor will indicate, by checking the appropriate box(es) below, which mode of transportation will apply to this contract.

- Bidder/Broker ("The Contractor") or their Sub Contractor will make delivery or be performing services using a vehicle that is owned, leased or rented. Provide Certificate of Insurance documenting automobile liability with a Combined Single Limit of \$500,000.00.
- Goods/Services will be delivered via common carrier.
- No employee or representative of the contractor will have cause to be on State property to make deliveries or to perform services.

DISCLOSURE OF SUBCONTRACTORS / JOINT VENTURES (See Page RA – 10 of 14, Standard Contract Terms and Conditions, Section V, Item Q): Bidders seeking to enter into a supplies contract shall disclose the following:

List names of subcontractors who will be performing work under the Contract.

NONE

---

---

By the signature affixed to Page 1 of this Bid, Bidder hereby certifies that the above information is true and accurate. The Bidder agrees that no changes will be made to this list of subcontractors or locations where work will be performed or data will be stored without prior written approval of DAS. Any attempt by the Bidder/Contractor to change or otherwise alter subcontractors or locations where work will be performed or locations where data will be stored, without prior written approval of DAS, will be deemed as a default. If a default should occur, DAS will seek all legal remedies as set forth in the Terms and Conditions which may include immediate cancellation of the Contract. Failure to complete this section may deem your bid not responsive.

USAGE REPORTS: Every six (6) months the contractor must submit a report (written or on disk or via e-mail in Excel format) indicating sales generated by this contract. The report shall list usage by customer, by line item, showing the quantities/dollars generated by this contract. The report shall be forwarded to the Office of Procurement Services, 4200 Surface Road, Columbus, OH 43228-1395, Attn: Walter Schneider ([walter.schneider@das.state.oh.us](mailto:walter.schneider@das.state.oh.us))

Bidders shall complete the following:

Contains recycled materials – Y/N: N if Yes \_\_\_\_\_%. (Will not be part of the evaluation)

## SPECIFICATIONS

### I. Scope

- A. These specifications cover the procurement of law enforcement uniform components for delivery to various Ohio Department of Natural Resources facilities, to include Men's and Women's long and short sleeve shirts, trousers, dress blouses (coats), mock-turtlenecks, hats, shoes and boots, uniform accessories and other services and items as specified in this Invitation To Bid. The successful bidder will provide ODNR's uniform needs as required by the contract and provide all sizing, fitting and customizing services to ODNR employees and facilities. Ordering will be provided through a secure, online password protected website as specified. Workmanship and material are to be first quality throughout.

### II. Requirements

- A. Winter and Summer Items – Ordering Periods: All items shall be from the manufacturer and the manufacturer's item number specified and provided by the awarded contractor. The Ohio Department of Natural Resources required order period for items designated herein as Winter items is May 1 through May 31. Required order period for items designated herein as Summer items is November 1 through November 30. The required order period for items designated as both Winter and Summer Items is May 1 through May 31 and November 1 through November 30. All items designated as stock items shall be available for ordering and purchase anytime. All orders are subject to the DELIVERY AND ACCEPTANCE clause on page 3 of this Invitation To Bid/Contract.

- B. Bidders should include Instructions on measuring and/or applicable sizing charts with their bid response. If not included with the bid response, the Bidder will have seven (7) calendar days after request to provide measuring and/or applicable sizing charts. Bidders must specify whether they are using standard or metric system measurements in their sizing charts.

The awarded contractor shall provide trained personnel to conduct measuring (and/or use sizing samples) and be available to any ODNR purchaser covered by this contract within a reasonable period of time agreed upon (not to exceed 2 weeks without purchaser's express approval).

The awarded contractor shall provide trouser hemming at no charge.

Insignia, emblems or patches supplied by the agency are to be sewn on as specified at no charge. All items shall be affixed in accordance with ODNR instructions and uniform policy.

- C. Items will be shipped to the location specified by the agency or division placing the order. Any items shipped in error, or incorrectly, for whatever reason, will be picked up by the contractor or his designee.
- D. All materials are to be first quality, new, unused and without flaws or defects which adversely affect appearance, durability and function.
- E. All items will have loose threads removed, and are to be pressed, shaped and properly finished in accordance with industry standards.
- F. Each item is to be packaged and marked for the individual and location of ordering agency as specified.
- G. All items found to be defective, misfit or not in accordance with specifications, although accepted through oversight or otherwise, will be replaced, repaired or altered at the expense of the contractor, including all transportation costs.
- H. All items will have a minimum one (1) year warranty against workmanship or fabric defects.
- I. The contractor shall maintain an inventory at an agency approved level for all items designated as stock items.
- J. Where applicable all garments shall be designed to withstand institutional laundering.
- K. All Items are to be labeled, including size, Item #, country of origin, care instructions where applicable and other information pertinent to U.S. labeling laws.

III. Measurements and sizing (Sizes to be according to the Federal Commercial Standard)

- A. Long Sleeve Shirts: Men's: Will be ordered by neck size and sleeve length.  
Women's: Will be ordered by bust size.
- B. Short Sleeve Shirts: Men's: Will be ordered by neck size. Women's: Will be ordered by bust size.
- C. Trousers/Pants: Men's: Will be ordered by waist size and inseam length. Women's: Will be ordered by women's garment size & inseam. Hemmed pants are to possess a 1-1/2" bottom seam.
- D. Dress Blouse: Will be made to order.
- E. Mock Turtleneck: Will be ordered by Alpha Size.
- F. Outerwear: Will be ordered by Alpha Size.
- G. Shoes & Boots Will be ordered by U.S. Size Standard.

DETAILED SPECIFICATIONS

MEN'S LONG SLEEVE SHIRT - WINTER ITEM, FLYING CROSS BY FECHHEIMER, ITEM 319X6604  
(Pricing Page Items 1 – 2)

FABRIC:

Content: 65% Dacron Polyester / 35% Rayon  
Weight: 11.0 oz. / linear yard

COLOR: Silver Tan with Forest Green Shoulder Straps

STYLE:

To be Flying Cross Model 319X6604. Dress style, top center placket front, full cut tapered fit, banded collar, long sleeves with barrel cuffs, and dress shirttail. Two plain breast pockets with topstitched scalloped flaps. Topstitched forest green shoulder straps. Exterior badge holder with metal eyelets. Matching inside yoke and collar band of Dacron/Cotton Poplin. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.

COLLAR & STAND:

Collar points to measure 3" long with ultrasonically fused-in Mylar stays. Collar to have woven interlining of #285 Stabilized Mello-Press. Stays to be 2 3/4" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar height at rear 1-1/2". Collar topstitched 1/4" off the edge. Collar stand to measure 1-5/16" at rear and band to be interlined with "Crease-N-Tack." Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.

FRONT:

The left front shall have a top center placket 1-3/4" wide with two rows of stitches 7/8" apart. The shirt will have 7 buttons and buttonholes on the front; spacing between each will be 3-3/4" except the spacing between the neck button and the first button on the front, which will be 3-1/4". Top center placket to have woven interlining of #550 Stabilized Mello-Press. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable.

SHOULDER STRAPS:

Forest Green Shoulder straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Interlined with #550 Stabilized Mello-Press. Shoulder strap to have functional buttonhole to attach to sewn button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT

Exterior holder to finish 1-1/8" wide by 2-1/4" deep with two metal eyelets positioned vertically 1-1/4" apart with bottom eyelet centered 1-1/2" above left pocket flap.

POCKETS:

Two plain breast patch pockets with rounded corners. Pocket to measure 5-5/8" wide, 6" deep. Left breast pocket to have 1- 1/2" pencil stitch. Each pocket to have hook Velcro, 3/4" long by 1/2" wide, positioned on both edges of pocket to

correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.

FLAPS:

Two piece deep scalloped design to measure 5-7/8" across and 2-3/4" in depth at center point, 2-1/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #550 Stabilized Mello-Press. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.

SLEEVES:

To be long sleeves with approximate 4 1/2" sleeve vent. Sleeve shall have a one-piece, elbow reinforcement and vent facing. Elbow reinforcement shall extend into the sleeve-closing seam.

CUFFS:

Two piece 1/2-inch hemmed cuff with 1/4" topstitching. Cuffs to measure 3" in depth with rounded corners (barrel). Cuffs to have two buttons and corresponding buttonholes set vertically with one button and buttonhole in center of facing. Cuffs to have woven interlining of #550 Stabilized Mello-Press.

EMBLEMS:

Agency supplied emblems are to be sewn onto each sleeve, centered 1" down from shoulder seam.

BUTTONS:

First grade 22-ligne melamine.

SEWING:

Collar, shoulder straps, pocket flaps and cuffs to be topstitched 1/4" off the edge. Sleeve inserting and side close felling seams are to be safety stitched.

THREAD:

All sewing threads to be color fast polyester wrap to match.

INTERLININGS:

Collar interlined with #285 Stabilized Mello-Press. Cuffs, pocket flaps, shoulder straps and top center to be interlined with #550 Stabilized Mello-Press. Collar band to be interlined with Crease-N-Tack.

MILITARY CREASES:

There shall be five sharp silicone military creases on all shirts. One crease on each front to be centered vertically. Front creases shall be through pockets and flaps. Spacing for three military creases across shirt back to be proportionate to the size of the shirt.

CONSTRUCTION:

Collar, flaps, shoulder straps and cuffs are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.

MEN'S LONG SLEEVE SHIRT WITH FRONT ZIPPER – WINTER ITEM, FLYING CROSS BY FECHHEIMER, ITEM 319X6604Z (Pricing Page Items 3 – 4)

FABRIC:

Content: 65% Dacron Polyester / 35% Rayon

Weight: 11.0 oz. / linear yard

COLOR: Silver Tan with Forest Green Shoulder Straps

STYLE:

To be Flying Cross Model 319X6604Z. Dress style, top center placket front with zipper, full cut tapered fit, banded collar, long sleeves with barrel cuffs, and dress shirttail. Two plain breast pockets with topstitched scalloped flaps. Topstitched forest green shoulder straps. Exterior badge holder with metal eyelets. Matching inside yoke and collar band of Dacron/Cotton Poplin. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.

COLLAR & STAND:

Collar points to measure 3" long with ultrasonically fused-in Mylar stays. Collar to have woven interlining of #285 Stabilized Mello-Press. Stays to be 2 3/4" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar height at rear 1-1/2". Collar topstitched 1/4" off the edge. Collar stand to measure 1-5/16" at rear and band to be interlined with "Crease-N-Tack." Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.

FRONT:

The left front shall have a top center placket 1-3/4" wide with two rows of stitches 7/8" apart. The shirt will have 7 buttons and buttonholes on the front; spacing between each will be 3-3/4" except the spacing between the neck button and the first button on the front, which will be 3-1/4". Top center placket to have woven interlining of #550 Stabilized Mello-Press. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable. A 15" nylon zipper, to be set below the second button and buttonhole, shall accomplish front closure. The top, second and bottom buttons to be attached to the right front, the balance to be sewn over the buttonholes on the left front.

SHOULDER STRAPS:

Forest Green Shoulder straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Interlined with #550 Stabilized Mello-Press. Shoulder strap to have functional buttonhole to attach to sewn button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT

Exterior holder to finish 1-1/8" wide by 2-1/4" deep with two metal eyelets positioned vertically 1-1/4" apart with bottom eyelet centered 1-1/2" above left pocket flap.

POCKETS:

Two plain breast patch pockets with rounded corners. Pocket to measure 5-5/8" wide, 6" deep. Left breast pocket to have 1- 1/2" pencil stitch. Each pocket to have hook Velcro, 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.

FLAPS:

Two piece deep scalloped design to measure 5-7/8" across and 2-3/4" in depth at center point, 2-1/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #550 Stabilized Mello-Press. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.

SLEEVES:

To be long sleeves with approximate 4 1/2" sleeve vent. Sleeve shall have a one-piece, elbow reinforcement and vent facing. Elbow reinforcement shall extend into the sleeve-closing seam.

WOMEN'S LONG SLEEVE SHIRT – WINTER ITEM, FLYING CROSS BY FECHHEIMER, ITEM 203X6604 (Pricing Pages Items 5 – 6)FABRIC:

Content: 65% Dacron Polyester / 35% Rayon

Weight: 11.0 oz. / linear yard

COLOR: Silver Tan with Forest Green Shoulder Straps

STYLE:

To be Flying Cross Model 203X6604. Dress style, top center placket front, full cut tapered fit, banded collar, long sleeves with barrel cuffs, and dress shirttail. Two plain breast pockets with topstitched scalloped flaps. Topstitched forest green shoulder straps. Exterior badge holder with metal eyelets. Matching inside yoke and collar band of Dacron/Cotton Poplin. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.

COLLAR & STAND:

Collar points to measure 2-7/8" long with ultrasonically fused-in Mylar stays. Collar to have woven interlining of #285 Stabilized Mello-Press. Stays to be 2 1/2" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar height at rear 1-1/2". Collar topstitched 1/4" off the edge. Collar stand to measure 1-5/16" at rear and band to be interlined with "Crease-N-Tack." Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.

FRONT:

The right front shall have a top center placket 1-1/2" wide with two rows of stitches 7/8" apart. The shirt will have 6 buttons and buttonholes on the front; spacing between each will be 3-1/2" except the spacing between the neck button and the first button on the front, which will be 3-1/4". Top center placket to have woven interlining of #550 Stabilized Mello-Press. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable.

SHOULDER STRAPS:

Forest Green Shoulder straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Interlined with #550 Stabilized Mello-Press. Shoulder strap to have functional buttonhole to attach to sewn button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT

Exterior holder to finish 1-1/8" wide by 2-1/4" deep with two metal eyelets positioned vertically 1-1/4" apart with bottom eyelet centered 1-1/2" above left pocket flap.

POCKETS:

Two plain breast patch pockets with rounded corners. Pocket to measure 5" wide, 5" deep. Each pocket to have hook Velcro, 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.

FLAPS:

Two piece deep scalloped design to measure 5-1/4" across and 2-1/4" in depth at center point, 1-3/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left flap to have invisible pencil opening 1-1/4". (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #550 Stabilized Mello-Press. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.

SLEEVES:

To be long sleeves with approximate 4 1/2" sleeve vent. Sleeve shall have a one-piece, elbow reinforcement and vent facing. Elbow reinforcement shall extend into the sleeve-closing seam.

CUFFS:

Two piece 1/2-inch hemmed cuff with 1/4" topstitching. Cuffs to measure 2 1/2" in depth with rounded corners (barrel cuffs). Cuffs to be two button adjustable. Cuffs to have woven interlining of #550 Stabilized Mello-Press.

EMBLEMS:

Agency supplied emblems are to be sewn onto each sleeve, centered 1" down from shoulder seam.

BUTTONS:

First grade 22-ligne melamine.

SEWING:

Collar, shoulder straps, pocket flaps and cuffs to be topstitched 1/4" off the edge. Sleeve inserting and side close felling seams are to be safety stitched.

THREAD:

All sewing threads to be color fast polyester wrap to match.

INTERLININGS:

Collar interlined with #285 Stabilized Mello-Press. Cuffs, pocket flaps, shoulder straps and top center to be interlined with #550 Stabilized Mello-Press. Collar band to be interlined with Crease-N-Tack.

MILITARY CREASES:

There shall be five sharp silicone military creases on all shirts. One crease on each front to be centered vertically. Front creases shall be through pockets and flaps. Spacing for three military creases across shirt back to be proportionate to the size of the shirt.

CONSTRUCTION:

Collars, flaps and cuffs are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.

WOMEN'S LONG SLEEVE SHIRT WITH ZIPPER – WINTER ITEM, FLYING CROSS BY FECHHEIMER, ITEM 203X6604Z  
(Pricing Pages Items 7 – 8)

FABRIC:

Content: 65% Dacron Polyester / 35% Rayon

Weight: 11.0 oz. / linear yard

COLOR: Silver Tan with Forest Green Shoulder Straps

STYLE:

To be Flying Cross Model 203X6604Z. Dress style, top center placket front with zipper, full cut tapered fit, banded collar, long sleeves with barrel cuffs, and dress shirttail. Two plain breast pockets with topstitched scalloped flaps. Topstitched forest green shoulder straps. Exterior badge holder with metal eyelets. Matching inside yoke and collar band of Dacron/Cotton Poplin. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.

COLLAR & STAND:

Collar points to measure 2-7/8" long with ultrasonically fused-in Mylar stays. Collar to have woven interlining of #285 Stabilized Mello-Press. Stays to be 2 1/2" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar height at rear 1-1/2". Collar topstitched 1/4" off the edge. Collar stand to measure 1-5/16" at rear and band to be interlined with "Crease-N-Tack." Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.

FRONT:

The right front shall have a top center placket 1-1/2" wide with two rows of stitches 7/8" apart. The shirt will have 6 buttons and buttonholes on the front; spacing between each will be 3-1/2" except the spacing between the neck button and the first button on the front, which will be 3-1/4". Top center placket to have woven interlining of #550 Stabilized Mello-Press. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable. An 11 1/2" nylon zipper, to be set below the second button and buttonhole, shall accomplish front closure. The top, second and bottom buttons to be attached to the left front, the balance to be sewn over the buttonholes on the right front.

SHOULDER STRAPS:

Forest Green Shoulder straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Interlined with #550 Stabilized Mello-Press. Shoulder strap to have functional buttonhole to attach to sewn button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT

Exterior holder to finish 1-1/8" wide by 2-1/4" deep with two metal eyelets positioned vertically 1-1/4" apart with bottom eyelet centered 1-1/2" above left pocket flap.

POCKETS:

Two plain breast patch pockets with rounded corners. Pocket to measure 5" wide, 5" deep. Each pocket to have hook Velcro, 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.

FLAPS:

Two piece deep scalloped design to measure 5-1/4" across and 2-1/4" in depth at center point, 1-3/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left flap to have invisible pencil opening 1-1/4". (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #550 Stabilized Mello-Press. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.

SLEEVES:

To be long sleeves with approximate 4 1/2" sleeve vent. Sleeve shall have a one-piece, elbow reinforcement and vent facing. Elbow reinforcement shall extend into the sleeve-closing seam.

CUFFS:

Two piece 1/2-inch hemmed cuff with 1/4" topstitching. Cuffs to measure 2 1/2" in depth with rounded corners (barrel cuffs). Cuffs to be two button adjustable. Cuffs to have woven interlining of #550 Stabilized Mello-Press.

**EMBLEMS:**

Agency supplied emblems are to be sewn onto each sleeve, centered 1" down from shoulder seam.

**BUTTONS:**

First grade 22-ligne melamine.

**SEWING:**

Collar, shoulder straps, pocket flaps and cuffs to be topstitched 1/4" off the edge. Sleeve inserting and side close felling seams are to be safety stitched.

**THREAD:**

All sewing threads to be color fast polyester wrap to match.

**INTERLININGS:**

Collar interlined with #285 Stabilized Mello-Press. Cuffs, pocket flaps, shoulder straps and top center to be interlined with #550 Stabilized Mello-Press. Collar band to be interlined with Crease-N-Tack.

**MILITARY CREASES:**

There shall be five sharp silicone military creases on all shirts. One crease on each front to be centered vertically. Front creases shall be through pockets and flaps. Spacing for three military creases across shirt back to be proportionate to the size of the shirt.

**CONSTRUCTION:**

Collars, flaps and cuffs are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.

**MEN'S SHORT SLEEVE SHIRT – SUMMER ITEM, FLYING CROSS BY FECHHEIMER, ITEM 669X6604 (Pricing Pages Items 9 – 10)****FABRIC:**

Content: 65% Dacron Polyester / 35% Rayon

Weight: 11.0 oz. / linear yard

**COLOR:** Silver Tan with Forest Green Shoulder Straps

**STYLE:**

To be Flying Cross Model 669X6604. Dress style, top center placket front, full cut tapered fit, convertible collar, short sleeves, and dress shirttail. Two plain breast pockets with topstitched scalloped flaps. Topstitched forest green shoulder straps. Exterior badge holder with metal eyelets. Matching inside yoke of Dacron/Cotton Poplin. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.

**COLLAR:**

Convertible collar shall be one piece. Collar points to measure 3" long with ultrasonically fused-in Mylar stays. Collar to have woven interlining of #285 Stabilized Mello-Press. Stays to be 2 3/4" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar topstitched 1/4" off the edge. Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.

**FRONT:**

Each front shall have a facing approximately 3" in width. The left front shall have a top center placket 1-1/2" wide with two rows of stitches 7/8" apart. Stitching on top center is not to be visible on the turn-back facing. The shirt will have 7 buttons and buttonholes on the front; spacing between each will be 3-3/4" except the spacing between the neck button and the first button on the front, which will be approximately 3". Top center placket to have woven interlining of #550 Stabilized Mello-Press. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable.

**SHOULDER STRAPS:**

Forest Green Shoulder straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Interlined with #550 Stabilized Mello-Press. Shoulder strap to have functional buttonhole to attach to sewn button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable.

**BADGE REINFORCEMENT:**

Exterior holder to finish 1-1/8" wide by 2-1/4" deep with two metal eyelets positioned vertically 1-1/4" apart with bottom eyelet centered 1-1/2" above left pocket flap.

**POCKETS:**

Two plain breast patch pockets with rounded corners. Pocket to measure 5-5/8" wide, 6" deep. Left breast pocket to have 1- 1/2" pencil stitch. Each pocket to have hook Velcro, 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.

**FLAPS:**

Two piece deep scalloped design to measure 5-7/8" across and 2-3/4" in depth at center point, 2-1/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #550 Stabilized Mello-Press. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.

**SLEEVES:**

Sleeves are to be straight and whole and to have a 3/4" hem and to finish at a minimum of 9 1/2" long from shoulder seam.

**EMBLEMS:**

Agency supplied emblems are to be sewn onto each sleeve, centered 1" down from shoulder seam.

**BUTTONS:**

First grade 22-ligne melamine.

**SEWING:**

Collar, shoulder straps and pocket flaps to be topstitched 1/4" off the edge. Sleeve inserting and side close felling seams are to be safety stitched.

**THREAD:**

All sewing threads to be color fast polyester wrap to match.

**INTERLININGS:**

Collar interlined with #285 Stabilized Mello-Press. Pocket flaps shoulder straps and top center to be interlined with #550 Stabilized Mello-Press.

**MILITARY CREASES:**

There shall be five sharp silicone military creases on all shirts. One crease on each front to be centered vertically. Front creases shall be through pockets and flaps. Spacing for three military creases across shirt back to be proportionate to the size of the shirt.

**CONSTRUCTION:**

Collars, straps and flaps are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.

**MEN'S SHORT SLEEVE SHIRT WITH ZIPPER – SUMMER ITEM, FLYING CROSS BY FECHHEIMER ITEM 669X6604Z  
(Pricing Pages Items 11 – 12)****FABRIC:**

Content: 65% Dacron Polyester / 35% Rayon

Weight: 11.0 oz. / linear yard

**COLOR:** Silver Tan with Forest Green Shoulder Straps

**STYLE:**

To be Flying Cross Model 669X6604Z. Dress style, top center placket front with zipper, full cut tapered fit, convertible collar, short sleeves, and dress shirttail. Two plain breast pockets with topstitched scalloped flaps. Topstitched forest green shoulder straps. Exterior badge holder with metal eyelets. Matching inside yoke of Dacron/Cotton Poplin. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.

**COLLAR:**

Convertible collar shall be one piece. Collar points to measure 3" long with ultrasonically fused-in Mylar stays. Collar to have woven interlining of #285 Stabilized Mello-Press. Stays to be 2 3/4" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar topstitched 1/4" off the edge. Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.

**FRONT:**

Each front shall have a facing approximately 3" in width. The left front shall have a top center placket 1-1/2" wide with two rows of stitches 7/8" apart. Stitching on top center is not to be visible on the turn-back facing. The shirt will have 7 buttons and buttonholes on the front; spacing between each will be 3-3/4" except the spacing between the neck button and the first button on the front, which will be approximately 3". Top center placket to have woven interlining of #550 Stabilized Mello-Press. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable. A 15" nylon zipper, to be set below the second button and buttonhole, shall accomplish front closure. The top, second and bottom buttons to be attached to the right front, the balance to be sewn over the buttonholes on the left front.

**SHOULDER STRAPS:**

Forest Green Shoulder straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Interlined with #550 Stabilized Mello-Press. Shoulder strap to have functional buttonhole to attach to sewn button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable.

**BADGE REINFORCEMENT:**

Exterior holder to finish 1-1/8" wide by 2-1/4" deep with two metal eyelets positioned vertically 1-1/4" apart with bottom eyelet centered 1-1/2" above left pocket flap.

**POCKETS:**

Two plain breast patch pockets with rounded corners. Pocket to measure 5-5/8" wide, 6" deep. Left breast pocket to have 1- 1/2" pencil stitch. Each pocket to have hook Velcro, 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.

**FLAPS:**

Two piece deep scalloped design to measure 5-7/8" across and 2-3/4" in depth at center point, 2-1/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #550 Stabilized Mello-Press. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.

**SLEEVES:**

Sleeves are to be straight and whole and to have a 3/4" hem and to finish at a minimum of 9 1/2" long from shoulder seam.

**EMBLEMS:**

Agency supplied emblems are to be sewn onto each sleeve, centered 1" down from shoulder seam.

**BUTTONS:**

First grade 22-ligne melamine.

**SEWING:**

Collar, shoulder straps and pocket flaps to be topstitched 1/4" off the edge. Sleeve inserting and side close felling seams are to be safety stitched.

**THREAD:**

All sewing threads to be color fast polyester wrap to match.

**INTERLININGS:**

Collar interlined with #285 Stabilized Mello-Press. Pocket flaps shoulder straps and top center to be interlined with #550 Stabilized Mello-Press.

**MILITARY CREASES:**

There shall be five sharp silicone military creases on all shirts. One crease on each front to be centered vertically. Front creases shall be through pockets and flaps. Spacing for three military creases across shirt back to be proportionate to the size of the shirt.

**CONSTRUCTION:**

Collars, straps and flaps are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.

WOMEN'S SHORT SLEEVE SHIRT – SUMMER ITEM, FLYING CROSS BY FECHHEIMER, ITEM 253X6604  
(Pricing Pages Items 13 – 14)

FABRIC:

Content: 65% Dacron Polyester / 35% Rayon  
Weight: 11.0 oz. / Linear yard

COLOR: Silver Tan with Forest Green Shoulder Straps

STYLE:

To be Flying Cross Model 253X6604. Dress style, top center placket front, full cut tapered fit, convertible collar, short sleeves, and dress shirttail. Two plain breast pockets with topstitched scalloped flaps. Topstitched forest green shoulder straps. Exterior badge holder with metal eyelets. Matching inside yoke and banana band of Dacron/Cotton Poplin. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.

COLLAR:

Convertible collar shall be one piece. Collar points to measure 2 7/8" long with ultrasonically fused-in Mylar stays. Collar to have woven interlining of #285 Stabilized Mello-Press. Stays to be 2 1/2" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar topstitched 1/4" off the edge. Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.

FRONT:

Each front shall have a facing approximately 3" in width. The right front shall have a top center placket 1-1/2" wide with two rows of stitches 7/8" apart. Stitching on top center is not to be visible on the turn-back facing. The shirt will have 6 buttons and buttonholes on the front; spacing between each will be 3-1/2" except the spacing between the neck button and the first button on the front, which will be 2 1/2". Top center placket to have woven interlining of #550 Stabilized Mello-Press. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable.

SHOULDER STRAPS:

Forest Green Shoulder straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Interlined with #550 Stabilized Mello-Press. Shoulder strap to have functional buttonhole to attach to sewn button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT:

Exterior holder to finish 1-1/8" wide by 2-1/4" deep with two metal eyelets positioned vertically 1-1/4" apart with bottom eyelet centered 1-1/2" above left pocket flap.

POCKETS:

Two plain breast patch pockets with rounded corners. Pocket to measure 5" wide, 5" deep. Each pocket to have hook Velcro, 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.

FLAPS:

Two piece deep scalloped design to measure 5-1/4" across and 2-1/4" in depth at center point, 1-3/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left flap to have invisible pencil opening 1-1/4". (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #550 Stabilized Mello-Press. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.

SLEEVES:

Sleeves are to be straight and whole and to have a 3/4" hem and to finish at a minimum of 8 1/2" long from shoulder seam.

EMBLEMS:

Agency supplied emblems are to be sewn onto each sleeve, centered 1" down from shoulder seam.

BUTTONS:

First grade 22-ligne melamine.

SEWING:

Collar, shoulder straps and pocket flaps to be topstitched 1/4" off the edge. Sleeve inserting and side close felling seams are to be safety stitched.

THREAD:

All sewing threads to be color fast polyester wrap to match.

INTERLININGS:

Collar interlined with #285 Stabilized Mello-Press. Pocket flaps, shoulder straps and top center to be interlined with #550 Stabilized Mello-Press.

MILITARY CREASES:

There shall be five sharp silicone military creases on all shirts. One crease on each front to be centered vertically. Front creases shall be through pockets and flaps. Spacing for three military creases across shirt back to be proportionate to the size of the shirt.

CONSTRUCTION:

Collar, straps and flaps are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.

WOMEN'S SHORT SLEEVE SHIRT WITH ZIPPER – SUMMER ITEM, FLYING CROSS BY FECHHEIMER, ITEM 253X6604Z  
(Pricing Pages Items 15 – 16)

FABRIC:

Content: 65% Dacron Polyester / 35% Rayon  
Weight: 11.0 oz. / Linear yard  
COLOR Silver Tan with Forest Green Shoulder Straps

STYLE:

To be Flying Cross Model 253X6604Z. Dress style, top center placket front with zipper, full cut tapered fit, convertible collar, short sleeves, and dress shirrtail. Two plain breast pockets with topstitched scalloped flaps. Topstitched forest green shoulder straps. Exterior badge holder with metal eyelets. Matching inside yoke and banana band of Dacron/Cotton Poplin. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.

COLLAR:

Convertible collar shall be one piece. Collar points to measure 2 7/8" long with ultrasonically fused-in Mylar stays. Collar to have woven interlining of #285 Stabilized Mello-Press. Stays to be 2 1/2" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar topstitched 1/4" off the edge. Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.

FRONT:

Each front shall have a facing approximately 3" in width. The right front shall have a top center placket 1-1/2" wide with two rows of stitches 7/8" apart. Stitching on top center is not to be visible on the turn-back facing. The shirt will have 6 buttons and buttonholes on the front; spacing between each will be 3-1/2" except the spacing between the neck button and the first button on the front, which will be 2 1/2". Top center placket to have woven interlining of #550 Stabilized Mello-Press. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable. An 11 1/2" nylon zipper, to be set below the second button and buttonhole, shall accomplish front closure. The top, second and bottom buttons to be attached to the left front, the balance to be sewn over the buttonholes on the right front.

SHOULDER STRAPS:

Forest Green Shoulder straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Interlined with #550 Stabilized Mello-Press. Shoulder strap to have functional buttonhole to attach to sewn button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT:

Exterior holder to finish 1-1/8" wide by 2-1/4" deep with two metal eyelets positioned vertically 1-1/4" apart with bottom eyelet centered 1-1/2" above left pocket flap.

POCKETS:

Two plain breast patch pockets with rounded corners. Pocket to measure 5" wide, 5" deep. Each pocket to have hook Velcro, 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.

FLAPS:

Two piece deep scalloped design to measure 5-1/4" across and 2-1/4" in depth at center point, 1-3/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left flap to have invisible pencil opening 1-1/4". (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #550 Stabilized Mello-Press. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.

SLEEVES:

Sleeves are to be straight and whole and to have a 3/4" hem and to finish at a minimum of 8 1/2" long from shoulder seam.

EMBLEMS:

Agency supplied emblems are to be sewn onto each sleeve, centered 1" down from shoulder seam.

BUTTONS:

First grade 22-ligne melamine.

SEWING:

Collar, shoulder straps and pocket flaps to be topstitched 1/4" off the edge. Sleeve inserting and side close felling seams are to be safety stitched.

THREAD:

All sewing threads to be color fast polyester wrap to match.

INTERLININGS:

Collar interlined with #285 Stabilized Mello-Press. Pocket flaps, shoulder straps and top center to be interlined with #550 Stabilized Mello-Press.

MILITARY CREASES:

There shall be five sharp silicone military creases on all shirts. One crease on each front to be centered vertically. Front creases shall be through pockets and flaps. Spacing for three military creases across shirt back to be proportionate to the size of the shirt.

CONSTRUCTION:

Collar, straps and flaps are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.

MEN'S AND WOMEN'S CLASS A TROUSER WITH STRIPE – WINTER & SUMMER ITEM, FLYING CROSS BY FECHHEIMER, MEN'S - ITEM 47285DNR; WOMEN'S ITEM 47295DNR (Bid Price Items 17, 18, 19 and 20)

FABRIC:

Content: 75% Polyester/25% Wool

Weight: 12 oz. per linear yard

Weave: Serge

COLOR: Forest Green

STYLE:

Trousers shall be manufactured from an up-to-date men's or women's uniform trouser pattern. The trouser styling shall be T-1: plain front, two (2) quarter top front pockets, and two (2) hip pockets professionally finished with no visible topstitching. Work wear industrial style construction is unacceptable and shall be cause for rejection.

LINING MATERIAL:

The pocketing and fly lining material shall be 70% Polyester / 30% Cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 48 count. Pocketing must have a durable press finish and the color of the pocketing must be black.

FREEDOM-FLEX WAISTBAND SYSTEM:

Trouser shall be made with a special Freedom-Flex Waistband System that will allow the wearer waist expansion of 2 1/2" to 3". The waistband shall measure a minimum of 1-7/8" wide when finished. The flexible expansion split portion of the waistband shall be to the front of the trouser side seam and there shall be a 3/4-inch wide side belt loop positioned to 'hide' the expansion split of the waistband.

The waistband curtain shall consist of two different styles for maximum waistband expansion to enhance wearer comfort, fit, and appearance. The front of the trouser (to the expansion split) waistband curtain style shall consist of a 2-inch wide elastic section that incorporates Tru-Grip, a ½" surface area composed of thin 55 gauge rubber for maximum comfort and performance. The Tru-Grip acts to help keep shirts tucked in securely. (Use of a single silicone strip or strips instead of ½" wide rubberized surface area shall be cause for rejection.)

The back half of the trouser waistband curtain shall finish a minimum 2-1/8" wide and is to be made of black pocketing material and shall be attached to the top of the trouser with a zigzag stitch. The waistband curtain must also contain Tru-Grip and will line up with the Tru-Grip on the front of the expansion split. (Substitution of a silicone strip or strips in place of Tru-Grip shall not be acceptable and shall be cause for rejection.)

The waistband curtain is composed of a wet laid non-woven canvas weighing 3.3 oz. per square yard. The canvas is covered in the same color and material as the pocketing. The ½" rubberized surface area is positioned 1-¼" up from the bottom of the curtain.

The specifications for the rubberized Tru-Grip curtain are as follows:

Width: 1-1/8-inch

Warp: 300 Denier Texturized Polyester

Filling: 300 Denier Texturized Polyester

Rubber: 55 Gauge

Count: 32-36 yarns per inch

Contents: 59% Polyester/41% Rubber

To complete the Freedom-Flex Waistband System, there shall be a 1-1/4" wide elastic component sewn into the back half of the waistband curtain to allow for the stretch and recovery of the waistband to comfortably fit the wearer's waist size.

There shall be a bartack for strength and durability sewn at the stress point on the waistband where it joins the front elasticized waistband curtain joining stitching (positioned, on the waistband above the front pocket.)

The waistband closure shall be accomplished with one crush proof hook and eye centered on the waistband for wearer comfort. The hook and eye shall be reinforced with a 7/8" non-woven tape that is anchored with topstitching through and through to the top of the waistband (bartacks in place of topstitching shall be cause for rejection). In addition to the stitching of the waistband when it is set onto the trouser, the waistband must also be topstitched below the waistband seam of the trouser to be finished to allow for alterations (with ample fabric and curtain material to allow trouser size to be increased at least one size). The outlet in the seat is to be proportional to the waist outlet so the seat may also be let out. Seat seam must be sewn with a tandem needle machine (double-needle stitch) for maximum stretch.

#### BELT LOOPS:

There shall be a minimum of seven belt loops 3/4" in width of double thickness. Each loop must have a non-woven interlining for added durability. All loops (except back center) must be sewn into the top and bottom of the waistband ("dropped" belt loops that are tacked to the outside of the trouser all around waist shall be cause for rejection). The top of the belt loops (except back center) shall be sewn into the waistband curtain seam with a Rocap machine using a zigzag stitch. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband to allow for easier waist alteration.

#### FLY:

Trouser shall have a brass metal zipper with memory lock brass slider secured by metal stopper at base. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic trouser fabric (tabs made of pocketing material or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same material and color as the pocketing. The fly lining shall be sewn to the left fly continuing below the zipper into the crotch area in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. Topstitching of fly to be installed with automatic "J" stitch equipment eliminating puckering and providing a clean finish. There shall be a firm straight bartack at the bottom of the fly going through the zipper tape for maximum strength. Bartack shall line up with starting point of "J" stitch.

#### SEAT:

Seat must be sewn with a Tandem Needle Machine (double-needle stitch) for maximum durability.

POCKETS:

The two (2) front pockets will be quarter top style with a minimum opening of 6" and a minimum depth of 5-3/4" measured from the bottom of the opening. Front pockets to have firm straight bartacks at top and bottom of pocket openings. Pockets shall be constructed using the stitch, turn, and topstitch method. Front pocket facing and barrier to be made of the basic trouser fabric. Facing shall be minimum of 1" and barrier shall measure a minimum of 2" (measured to the inside edge of pocket lining).

The two (2) hip pockets shall have a minimum 5-3/8" wide (bartack to bartack) opening and a minimum depth of 5-3/4" measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on an automatic welt machine. The welts shall be finished in such a manner that there is no topstitching (topstitched hip pockets shall be cause for rejection). The corners of the hip pocket openings shall have straight bartacks for reinforcement (use of triangular bartacks shall be cause for rejection). Hip pocket facing and barrier are to be made of basic trouser fabric. Facing shall be a minimum of 3/4" and the barrier shall be a minimum of 1-1/2". The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the tab to form an opening for a button. A button shall be located below the bottom welt corresponding in location with the tab, which shall be interlined with non-woven for added durability. There shall be a dart centered above each hip pocket to waistband. Dart shall be approximately 2-3/4" long tapered from 3/8" at waistband and shall be installed with automatic equipment for a clean non-puckered finish.

The watch pocket shall be located on the right front at the waistband. This pocket shall have a minimum opening of 2-5/8" and a minimum depth of 2-7/8". The front of the pocket shall be made of pocketing fabric and the back of the pocket shall be made of basic fabric and the two pieces are securely stitched together. Each corner of the pocket opening shall have firm straight bartacks.

For the Men's style 47285DNR only the watch pocket shall be located on the right front at the waistband. This pocket shall have a minimum opening of 2-5/8" and a minimum depth of 2-7/8". The front of the pocket shall be made of pocketing fabric and the back of the pocket shall be made of basic fabric and the two pieces are securely stitched together. Each corner of the pocket opening shall have firm straight bartacks.

CREASES:

The leg creases, front and back will have a silicone bead put in by using the Lintrak process.

STITCHING, PRESSING & FINISHING:

Trouser must be stitched with matching thread. Trouser must be neatly pressed on Hothead Presses and properly shaped. Outseams and inseams are edge serged on automatic equipment for uniformity of quality and shall be pressed open for a smooth pucker-free finish with repeated cleaning and pressing. Trouser must be cleaned and finished to eliminate loose threads.

CLOTH STRIPE:

There is to be a 1" cloth stripe sewn from the waistband to the bottom of the trouser on the outside of the trouser. Cloth stripe is to be black fabric, 75% polyester / 25% wool, serge weave.

REQUIRED SIZES MEN'S:

Trouser must be available from stock in the following sizes:

SHORT RISE:	28 - 42 (EVEN ONLY)
REGULAR RISE:	28 - 58 (EVEN ONLY OVER 38)
LONG RISE:	32 - 44 (EVEN ONLY)

REQUIRED SIZES, WOMEN'S

Trouser must be available from stock in the following sizes:

WOMEN'S	4 - 18
---------	--------

LABELS:

Trouser must have a permanent label providing care instructions and small woven label indicating waist size. A removable paper ticket showing the size, fabric content, cut number, and WPL or RN number must be on the outside of the waistband. Ticket to be matchbook style installed with plastic staples for easy removal without damaging trouser material and showing size when trousers are stacked.

MEN'S AND WOMEN'S BRUSH PANTS – WINTER & SUMMER ITEM, FLYING CROSS BY FECHHEIMER, MEN'S ITEM ODNRTRS01 – WOMEN'S ITEM ODNRTRSW01 (Bid Price Items 21 and 22)

FABRIC:

Content: 65% Polyester / 35% Cotton  
Weight: 6 ½ oz. per square yard  
Weave: Dauntless  
Color: Green

FABRIC:

Content: 100% Nylon  
Weight: 5 ½ oz. per square yard  
Weave: Plain  
Color: Green

STYLE:

The men's trouser shall be manufactured from a men's uniform trouser pattern. The women's trouser shall be manufactured from a women's uniform trouser pattern. The trouser shall incorporate a plain front, two (2) quarter top front pockets and two (2) hip pockets and two cargo pockets. Trouser to be straight leg style. Trouser shall have double fabric reinforcement on both legs made of green nylon fabric. Reinforcement shall begin at mid-thigh and back knee and extend to the bottom of the trouser.

LINING MATERIAL:

The pocketing and fly lining material shall be 70% Polyester / 30% Cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 48 count. Pocketing must have a durable press finish and the color of the pocketing must be black.

POCKET DESIGN:

The two (2) front pockets will be quarter top style with a minimum opening of 6" and a minimum depth of 5 3/4" measured from the bottom of the pocket opening.

The two (2) hip pockets shall have a minimum opening of 5 1/2" and a minimum depth of 5 3/4" measured from the bottom of the pocket opening. Hip pockets shall be constructed with rectangular flaps measuring 5 ½"X 2 1/8". The corners of the hip pocket and flap shall have Velcro tabs 1"X 1 ½" to secure pocket.

CARGO POCKET:

There shall be two cargo pockets, one on each side seam. There will be double-section pleated patch pockets with flaps. The pockets will be centered across the side seam and placed approximately 2" below the bottom of the front quarter-top pocket, measuring from the top of the pocket flap. The pocket shall be constructed of dark forest green ambush fabric. The outside measurements of the pocket are 7" wide x 8½" deep with mitered bottom corners. There shall be a 1½" center pleat on each pocket. The pocket flap shall be rectangular and measure 7 1/2" wide, 2 1/4" deep. The flap shall be sewn across the top to the inner pocket. The corners of the cargo pockets and flaps shall have Velcro tabs 1"X 1 ½" to secure pocket. There shall be a black vision zipper sewn behind the inner pocket and to the trouser leg so that the zipper is recessed 1" from the top of the pocket flap.

WAISTBAND:

The trouser will include the Freedom Fit® with Tru-Grip waistband curtain designed to provide the wearer with maximum comfort, functionality, and professional appearance. The waistband itself shall be constructed using the "closed method" and shall measure a minimum of 1-7/8" wide when finished. The waistband closure shall be accomplished with a single crush proof hook and eye centered on the waistband for maximum wearer comfort. The hook and eye shall be reinforced with 7/8-inch non-woven stay tape that is anchored with topstitching through and through to the top of the waistband (bartacks in place of topstitching shall be cause for rejection). In addition to the stitching of the waistband when it is set onto the trouser, the waistband must also be topstitched below the waistband seam through the waistband curtain for added strength. The back center seam of the trouser to be finished to allow for alterations (with ample basic trouser fabric and waistband curtain material to allow trouser size to be increased at least one size). The outlet in the seat is to be in proportion to waist outlet so seat may also be let out. Seat seam must be sewn with a tandem needle machine (double-needle stitch) for maximum strength.

The Freedom Fit Waistband Curtain with Tru-Grip is composed with a two zone stretch feature to provide the wearer maximum comfort and security.

The top part of the waistband curtain is a lower stretch zone designed to give with the wearer's movements including sitting or bending. This upper zone of the waistband curtain is composed of a 1-1/2-inch 30% stretch monofilament elastic that is around the entire waistband providing stability, preventing waistband rollover, and allowing for a comfort stretch with wearer movement. The specifications for the upper elastic are as follows:

Width: 1-1/2-inch

Stretch: 30%

Warp: 150 Denier textured polyester, 21 ends

Filling element 1: .011" diameter transparent type 66 Nylon, one end

Filling element 2: 150 denier textured polyester, 2 ends

Elastomer: 840 denier transparent spandex, 21 ends

Overall contents: 59% polyester, 41% rubber.

The upper zone of the waistband curtain interlining (elastic band) is to be lined in the same color and material as the trouser pocketing and it shall be cut on a 45-degree bias to allow for maximum stretch. The waistband trouser fabric shall be cut across the cloth to allow for maximum stretch in synergy with the Freedom Fit with Tru-Grip Waistband Curtain.

The lower part or lower zone of the waistband shall be the same color as the trouser pocketing. It is designed to stretch over the hips for comfort, help keep the trouser securely positioned on the wearer's waist, and to help prevent slippage. This lower portion of the waistband curtain is made with 65% stretch elastic. This zone also incorporates Tru-Grip, a 1/2" wide rubberized surface area which acts to hold the shirt in place inside the trouser to help keep shirt tails tucked into the waist for a neat and professional appearance. (Use of a single silicone strip or strips instead of 1/2" wide rubberized surface area shall be cause for rejection.) The specifications for the lower elastic are as follows:

Width: 1-3/4-inch

Stretch: 65%

Face: 70/2 stretch nylon, 104 ends

Binder: 150/2 textured polyester, 32 ends

Edge: 70/2 stretch nylon, 11 ends

Figure: 100/2 stretch nylon, 16 ends

Rubberized area: 55 gauge rubber, 33 ends

Catch Thread: 70/2 stretch nylon, 1 end

Elastomer Core: 1680 Lycra, 38 ends

Elastomer top cover: 150/1 textured polyester, 1 end

Elastomer bottom cover: 100/1 bright nylon, 1 end

Filling: 250 monofilament nylon, 2 ends

Overall contents: 46% nylon, 15% polyester, 25% rubber, 14% spandex.

FLY:

Trouser shall have a brass metal zipper with memory lock brass slider secured by metal stopper at base. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic trouser fabric (tabs made of pocketing material or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same material and color as the pocketing. The fly lining shall be sewn to the left fly continuing below the zipper into the crotch area in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. Topstitching of fly to be installed with automatic "J" stitch equipment eliminating puckering and providing a clean finish. There shall be a firm straight bartack at the bottom of the fly going through the zipper tape for maximum strength. Bartack shall line up with starting point of "J" stitch.

BELT LOOPS:

There shall be a minimum of seven belt loops 1" in width of double thickness. Each loop must have a non-woven interlining for added durability. All loops (except back center) must be sewn into the top and bottom of the waistband ("dropped" belt loops that are tacked to the outside of the trouser all around waist shall be cause for rejection). The top of the belt loops (except back center) shall be sewn into the waistband curtain seam with a Rocap machine using a zigzag stitch. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband to allow for easier waist alteration.

STITCHING, PRESSING & FINISHING:

Trouser must be stitched with matching thread. Trouser must be neatly pressed on Hothead Presses and properly shaped. Outseams and inseams are edge serged on automatic equipment for uniformity of quality and shall be pressed open for a smooth pucker-free finish with repeated cleaning and pressing. Trouser must be cleaned and finished to eliminate loose threads.

LABELS:

Trouser must have a care label permanently affixed that also indicates the size. A paper ticket showing the size, fabric content, cut number, and WPL number must be on the outside of the waistband.

REQUIRED SIZES:

Trouser must be available in the following sizes:

Men's:               REGULAR RISE: 29 - 50 (EVEN ONLY OVER 40)

Women's:           REGULAR Rise: 4 – 22 (EVEN SIZES ONLY)

MEN'S AND WOMEN'S DUTY UNIFORM TROUSER – STOCK ITEM – BDU BY BLAUER, MEN'S ITEM 8830, WOMEN'S ITEM 8830W (Bid price items 23 & 24)

FABRIC:

6.5 Oz 65% polyester / 35% cotton fiber blend rip-stop material. Machine washable and dry cleanable.

INTERLINING:

100% Polyester

COLOR:     OD Green

GENERAL REQUIREMENTS:

Garments must carry a warranty covering defects in materials and workmanship for one (1) year. Garments must be manufactured to ISO 9001 quality assurance standard (AG1607).

DESIGN AND CONSTRUCTION:

BDU (S.W.A.T.) trouser design. Tailored split-seam construction. Dress uniform style. Two front quarter pockets. Two pleated BDU style cargo side pockets. Two hip pockets with flaps. Snap front closure. Stretch waistband with side spot elastic. Belt loops inserted at the bottom of waistband and tacked to the top. Reinforced knees with inside patches of pocketing fabric. Knee patches shall accept optional removable knee pads. The patterning shall be loose fitting through the seat and thighs to allow unrestrained movement. Trouser shall be machine washable and dry cleanable.

INSEAMS:

Inseams shall be Unhemmed at a minimum length of 37".

REQUIRED SIZES:

Trouser must be available in the following sizes:

Men's: Regular Rise. Even waist sizes 28 – 54; Odd sizes 31 – 37

Women's Regular Rise. Even dress sizes 6 – 24

LABELS:

Trouser must be labeled providing care instructions, country of manufacture and waist size. Labels must comply with all U.S. label laws and regulations.

ODNR MEN'S AND WOMEN'S DRESS BLOUSE – MAKE TO ORDER ITEM, FECHHEIMER BROTHERS DRESS COAT #  
ODNR DRESS BLOUSE – MADE TO ORDER (Bid Price Item 25)

FABRIC:

RAEFORD #6038-92727 75% DACRON / 25% WOOL WEAVE: SERGE 11 1/2-12 OZ. BREAKING STRENGTH: 130 LBS WARP 100 LBS FILLING CONSTRUCTION: 75 ENDS/INCH 69 PICKS/INCH COLOR: OD GREEN Fabric to be manufactured utilizing yarn spun on the long staple fiber length worsted spinning system. The average individual staple length shall be 3 1/2".

BASIC DESIGN:

Four (4) button, single breasted straight front, semi-form fitting, with notch lapels and epaulets.

BUTTONS:

Four (4) 36 Ligne Gilt buttons sewn on front 4" apart and one (1) 24 Ligne Gilt " button on each pocket flap.

COLLAR:

Shall not be over 1 7/8" wide in back when finished. To be stiffened with best quality Belgium elastic. Under collar of all wool collar cloth, closely padded.

EDGES AND SEAMS:

Edges to be single stitched 3/16". Plain seams, pressed open.

POCKETS:

Two (2) lower scalloped flaps, no pockets, two (2) breast scalloped flaps. Lower and breast flaps to button with gilt "P" buttons. One (1) inside reinforced breast pocket piped with same material 6" wide and 7" deep.

LINING:

Coat is to be fully lined with navy blue rayon or 70 Denier nylon.

VENT:

Shall be back center.

BELT HOOKS:

Coat shall have two belt hooks set into back side seams at waist level.

BADGE TAB:

Separate oval badge tab made of cloth about 1 1/2" wide and 2 1/4" long with two (2) metal eyelets, about 1 1/8" apart, sewn to the outside left breast of the coat, so that the lower point of the badge is 1/2" above the breast pocket.

BUTTONHOLES:

All buttonholes, excepting shoulder strap buttonhole, shall be made to a full 1/2" from the edges of the seam and pocket flaps. The ends of all buttonholes shall be bartacked. All buttonholes to be "cut after" machine made buttonholes. All thread used in making buttonholes shall be black silk, tailor's twist, colorfast and guaranteed against fading.

SWEAT SHIELDS:

A sleeve sweat shield of the same cloth as in the body of the coat, piped with rayon to be securely set under each arm over the lining.

**SHOULDER STRAP:**

To be sewn in sleeve seam directly on top of the shoulder. The strap shall come under the collar and fasten with 24 Ligne metal button at the edge of collar. Cross stitched. Shoulder Straps to be made of Raeford No. 6038-11000.

**OUTLETS:**

All body seams to have outlets of not less than 1". Turn up at sleeve cuffs to be no less than 2 ½ ".

**EMBLEMS:**

Blouse to have Department emblems centered on each sleeve sewn 1 1/2" down from the shoulder seam.

**CONSTRUCTION:**

Hymo, felt and canvas to be properly stayed together with edges taped and sewn into seams. Finest canvas, felt and hymo available and cut to fit the actual size of the coat. Heavy shoulder pads. All findings thoroughly cold water shrunk.

**LABELS:**

There shall be permanently affixed size label and care instruction label. Garment must be made in the United States of America and bear a union label.

**ODNR TACSELL 4 IN 1 JACKET WITH SOFT SHELL LINER (STOCK ITEM) BY BLAUER, BLAUER ITEMS 9820Z (JACKET AND LINER), 9820 (JACKET ONLY) AND 4660 (LINER ONLY) (Bid Price Items 26, 27, 28, 29, 30 & 31)**

**GENERAL REQUIREMENTS:**

**Tacshell Jacket:** The Tacshell Jacket must have a warranty covering at minimum defects in materials and workmanship for three (3) years. The Tacshell Jacket liner must meet ANSI/ISEA 107-2010 class II requirements. The Tacshell Jacket must be manufactured to ISO 9001 quality assurance Standard. (AG0910).

**Soft Shell Liner:** The Softshell liner must have a warranty covering at minimum defects in material and workmanship for one (1) year. The Softshell liner must be manufactured to ISO 9001 quality assurance standard. (AG1800).

**FABRIC:**

**Tacshell Jacket:** Ripstop-3 L-Stretchable Ripstop. Dobby-2L-Dobby 350mm w/light coating.  
Color: OD Green

**Soft Shell Liner:** 35% Nylon, 59% Polyester, 6% Spandex.  
Color: OD Green

**TRIM:**

**Tacshell Jacket:** Eyelets shall be 8mm aluminum. Hook and Loop shall be woven nylon base. Reflective trim shall be 1 inch wide, silver crosswalk. Seam tape shall be waterproof seam sealing tape, color: gray. Snaps shall be 20 ligne prong style with closed backs, gunmetal finish on brass, heavy duty closure, 24 ligne nylon cap. Brushed pocketing shall be 100% polyester brushed tricot, color: black. Zippers shall be: Front – vision one-way double pull size #5, 27 ½ inches (size L/reg color: black). Side Seam – coil, one-way, size #5, 11.5 inches (size L/reg, color: black). Liner – Vision size#5, one-way double pull 25 ½ inches (size L/reg, color: black). Sleeve – coil, one-way, size #5, 10 inches (Size L/reg, color: black). Napoleon Pocket – coil, one-way, size #3, 7 inches (size L/reg, color: black). Collar – coil, one-way, size #3 9 ½ inches (size L/Reg, color: black)

**Soft Shell Liner:** Interlining shall be 100% polyester, non-woven. Brushed pocketing shall be 2x1 twill, 100% polyester fill, polyester/rayon warp. Reflective Piping 3/16" wide silver reflective piping (two tone only). Elastic shall be 1" knitted elastic (dry cleanable). Zippers shall be: front – delrin, one-way, size#5, 26 ½ inches long; pocket – nylon coil, size #3, 7 inches long. (zipper size commensurate with jacket size – size specified for L/Reg, color: black).

**DESIGN AND CONSTRUCTION:**

**Tacshell Jacket:** B.Dry waterproof, windproof, breathable waist length jacket. Optional zip-out liner. Double entry lower pockets with flaps. Double storm flaps cover vision zipper. Hidden napoleon mesh pocket. Crosswalk reflective trim inside cuffs and on collar. Sleeve zippers. Side zippers with snap tabs. Three piece sleeve with sleeve tab adjustment. Front and back yoke flaps with pull down panels. Epaulets and badge tab. Mic tab on front storm fly. Detachable hood in collar with zipper.

DESIGN AND CONSTRUCTION (continued):

Soft Shell Liner: Zippered front inner fly w/zipper extending to top of collar. Stand Up Collar. Side openings with zipper closure. Napoleon pocket on left chest. Partial elasticized hem. Lower zippered single welt pockets with brushed flannel lining.

REQUIRED SIZES:

Tacshell Jacket: Unisex Regular XS – 3 XL, Long M – 3XL

Soft Shell Liner: Unisex Regular XS – 3XL, Long M – 3XL

CUSTOMIZATION:

Tacshell Jacket: Front right chest pull down tab shall have "DNR" in 1 inch bright yellow letters affixed to silver reflective crosswalk fabric. Front left chest pull down tab shall have "POLICE" in 1 inch bright yellow letters affixed to silver reflective crosswalk fabric. The rear pull down tab shall have "POLICE" in 3 ½ inch bright yellow letters affixed to silver reflective crosswalk fabric. Agency supplied emblems are to be sewn onto each sleeve, centered on the sleeve pocket.

Soft Shell Liner: Microphone tabs shall be installed one each on the left and right shoulder seams at the center of the seam halfway between the sleeve seam and collar seam and one on the right chest next to the zipper and the top edge starting at the existing sewn seam on the jacket (at the direction of the ODNR Enforcement Liaison Officer). Agency supplied emblems are to be sewn onto each sleeve, centered 1" down from shoulder seam. An agency supplied badge emblem is to be sewn onto the left chest area.

OTHER:

Tacshell Jacket and Soft Shell Liner: These garments shall be bid and sold on any ensuing contract as follows:

1. Combination 4-in-1 Tacshell Jacket and Softshell Liner Combined
2. Tacshell Jacket Only
3. Softshell Liner Only

BATES MEN'S 3-EYE PADDED COLLAR LEATHER CHUKKA BOOT - STOCK, ITEM #78 (Bid Price Item 32)

UPPER: Black, Smooth cowhide

UPPER LINING: Drilex Camo 2-tone with 098 foam

EYELETS: #115 Blind Nickle

BOXTOE: Knilon Core Thermo-plastic

COUNTER: Thermo-plastic

INSOLE: 5 Iron Texon

SHANK: Fiberglass

WELT: Goodyear storm welt

MIDSOLE: 5 Iron Black Hi-tech

INSOLE INSERT: Covered polyurethane foam, orthotically designed with dual density heel and forepart pads

WELT STITCHING: Nylon Braided Cotton

OUTSOLE: 211 Polyurethane Basket weave Outsole. Oil resisting, skid resistant, non marking.

SIZES:

B Width: 3 – 9  
D Width: 3 – 12, 13, 14  
E Width: 3 – 12, 13, 14  
3E Width: 6 – 12, 13, 14

MEN'S ACADEMY OXFORD BY THOROGOOD – ITEM # 834-6041 (STOCK ITEM) (Bid Price Item 33)

UPPER: Black Smooth High Shine Leather (not gloss)

LINING: Comfort Weave

INSOLE: Removable EVA Footbed with Poron® 4000 Heel Pad

SHANK: Engineered Composite

OUTSOLE: Oil and Slip Resistant Blown Rubber

SIZES:

Men's and Women's Dual Gender  
Regular Width: 3 – 12, 13, 14, 15  
Wide 3 – 12, 13, 14, 15  
Extra Wide 3 – 12, 13, 14, 15

MEN'S AND WOMEN'S UNINSULATED ACADIA BOOT BY DANNER – STOCK, ITEM 21210 MEN'S / 21210W WOMEN'S - Bid Pricing Item 34 (men's) and Item 39 (women's)

LAST: Construction using Danner last #650. Lasts are made in both half and full sizes to accommodate a better fit. Women's specific last in half and full sizes.

SHANK: Fiberglass shank cut to length in production to each size offered.

LINING: W. L. Gore's GoreTex waterproof breathable bootie. The GoreTex bootie must be a single seam construction with serge stitched seams and the seams must be sealed with W. L. Gore approved seam sealing tape, and shall be inserted into the upper of the boot to cover the entire length and width of the boot.

UPPER: Made of a combination of 2.0 – 2.2 mm full grain black polishable leather and 1000 Denier nylon.  
Construction and Attachment: Upper is attached to midsole and outsole using multi-layer stitchdown process utilizing Poron/Texon dual density insole board, 3.2 mm rubber /5.5 mm polyurethane midsole, and Vibram 138 Kletterlift outsole.

SPECIAL FEATURES: Lace to toe

SIZES:

Men's	B Width	8 – 12, 13,14
	D Width	7 – 12, 13, 14, 15, 16
	EE Width	6 – 12, 13
Women's	Med. Width	5 – 10

MEN'S AND WOMEN'S INSULATED ACADIA 400 BOOT BY DANNER – STOCK, STYLE/ITEM 22600 MEN'S / 22600W WOMEN'S - Bid Price Item 35 (men's) Bid Price Item 40 (women's)

LAST: Construction using Danner last #650. Lasts are made in both half and full sizes to accommodate a better fit. Women's specific last in half and full sizes.

SHANK: Fiberglass shank cut to length in production to each size offered.

LINING: W. L. Gore's GoreTex waterproof breathable bootie bonded to 400 grams of 3M Thinsulate Ultra Insulation. The GoreTex bootie must be a single seam construction with serge stitched seams and the seams must be sealed with W. L. Gore approved seam sealing tape, and shall be inserted into the upper of the boot to cover the entire length and width of the boot.

UPPER: Made of a combination of 2.0 – 2.2 mm full grain black polishable leather and 1000 Denier nylon.  
Construction and Attachment: Upper is attached to midsole and outsole using multi-layer stitchdown process utilizing Poron/Texon dual density insole board, 3.2 mm rubber/5.5mm polyurethane midsole, and Vibram 138 Kletterlift outsole.

SPECIAL FEATURES: Lace to toe

SIZES:

Men's	B Width:	8 – 12, 13,14
	D Width:	7 – 12, 13, 14, 15, 16
	EE Width:	6 – 12, 13
Women's	Med. Width:	5 – 10

MEN'S AND WOMEN'S 6 INCH KINETIC GORE TEX BOOT BY DANNER – STOCK, ITEM 28015 – MEN'S, ITEM 28080 – WOMEN'S (Bid Price Item (men's) 36, (women's) 41)

LAST: Construction using Danner last # 1368. Lasts are made in both half and full sizes to accommodate a better fit.

SHANK: Nylon

LINING: 100% waterproof and breathable GORE-TEX LINING sealed with GORE-TEX tape.

UPPER: Made of a combination of 2.0 – 2.2 mm full grain black polishable leather and ripstop ballistic nylon.

OUTSOLE: Low Lug Danner Kinetic Rubber Outsole

CONSTRUCTION & ATTACHMENT: The upper is cemented down to polyurethane midsole and attached rubber outsole.

SPECIAL FEATURES: Speed lacing system with lace garage. Women's shoe made on women's specific last.

SIZES:

Men's	D Width:	6 – 12, 13, 14, 15, 16
	EE Width:	7 – 12, 13, 15
Women's	Med Width:	5 – 11

MEN'S 8 INCH KINETIC GORE TEX BOOT BY DANNER – STOCK , ITEM 28010 (Bid Price Item 37)

LAST: Construction using Danner last # 1368. Lasts are made in both half and full sizes to accommodate a better fit.

SHANK: Nylon

LINING: W. L. Gore's Gore Tex waterproof breathable bootie sealed with Gore Tex waterproof tape.

UPPER: Made of a combination of 2.0 – 2.2 mm full grain black polishable leather and ripstop ballistic nylon.

OUTSOLE: Low Lug Danner Kinetic Rubber Outsole

CONSTRUCTION & ATTACHMENT: The upper is cemented down to polyurethane midsole with attached rubber outsole.

SPECIAL FEATURES: Speed lacing system with lace garage.

SIZES:

Men's                      D Width: 6 – 12, 13, 14, 15, 16  
                                 EE Width: 7 – 12, 13, 15

WOMEN'S DURA SHOCK OXFORD BY BATES – ITEM # 752, STOCK (Bid Price item 38)

UPPER: Black, Smooth Cowhide

UPPER LINING: Drilex Camo

BOX TOE COUNTER: Thermo-Plastic

INSOLE: 3 ½ Iron Texon

INSOLE INSERT: Durashock 2 with dual density, Polyurethane and shock absorbing heel and forepart pads.

SHANK: Fiberglass

OUTSOLE: Polyurethane direct attach, Dress military Durashocks

SIZES:

Women's:                Narrow, 6 – 11, 12  
                                 Medium, 4 – 11, 12  
                                 Wide, 4 – 11, 12  
                                 Extra Wide, 6 – 11

MEN'S AND WOMEN'S MOCK TURTLENECK – Ufx™ BY ELBECO, STOCK, ITEM 8920 (Bid Price Item 42)

DESIGN: Loose fit pullover, mock turtleneck with durable side seams and full neck with long sleeves and cuffs.

MATERIAL: Body, collar and cuffs shall be made of 63% Nylon / 23% Micro Poly / 14% Spandex, 6.5 Ounces per square yard. X-EEDE "Moisture Transport System", abrasion resistant, pill-proof, permanent anti-microbial technology, odor, mildew and bacteria resistant.

COLOR: Black

COLLAR: Mock turtleneck shall be self-fabric and retain shape. Collar will finish 2" in height .

SLEEVES: Long sleeve, set-in type 2 ½ cuffs made of self-fabric.

SEAMS & STITCHING: Seams shall conform to FED-STD-751. Stitches 10 to 12 per inch. No raw edges, run-offs, pleats, puckers or open seams shall be permitted. An external cover stitch shall secure the neck. Shoulder seams shall have a 3/16" wide covered elastic cord sewn into the seams. Ends of all stitching shall be backstitched or overstitched not less than ½" except where ends are turned under or caught in other seams or stitching.

LABELING: Each garment shall have a size and identification label in the neck and a care and content label inserted in the seam at the bottom of the shirt.

SIZES: Unisex SM – 3XL

ALL HATS: PACKING & SHIPPING: Hats are to be packed one to a box with the size and item number indicated on the outside of each box. Hats are to be packed in shipping containers of sufficient integrity and strength to withstand transportation by common carrier and to assure safe and damage free arrival at the final delivery point.

HAT, STRAW, CAMPAIGN STYLE - STOCK, DOUBLE BRIM, STRATTON ITEM # S-40DB (Bid Price Item 43)

QUALITY:

#1 Quality Toyo Braid, Tight Weave. 5 ½ To 6 MM Seven Strand Width.

COLOR:

Conservation Green

CROWN:

Montana Peak Traditional Four Dent Style. Crown to Be 5 ½" High

BRIM:

To Be 3" Wide Straight Flat Set. Two Separate Brims Joined for Extra Strength and Shape Retention. Brims Are Sewn Together. Heavily Stiffened And Shower Proofed. Made of 5 – 51/2 MM Bedford Hemp Braid.

STIFFENING:

Crown Double Dipped. Brim Triple Dipped With #21 Sizing By Kempen Paint Company.

CROWN EYELETS:

One Eyelet On Each Side And One In The Rear Of Hat, All Three To Be 2 ¾" Above The Brim.

BRIM EYELETS:

3/8" Oval, One On Each Side, To Accommodate The Chin Strap, Eyelets Centered On Each Side.

BADGE EYELETS:

To Customer Specifications, Normally One In Front 2 1/8" Above The Brim.

SWEAT BAND:

Head Culture Foam Sweat With Oil Silk Liner.

HAT BAND:

9 Ligne, yarn Dyed Grosgrain, ¾" Wide With Bow On The Left Side.

SIZES:

6 ½ Through 7 7/8

HAT, FELT, CAMPAIGN STYLE - STOCK, STRATTON ITEM # F-40 (Bid Price Item 44)

QUALITY:

Equal To Or Better Than The 868 Special As Manufactured By Stratton Hats, Inc. Of Chicago Also Listed As The F-40 Campaign Style Felt Hat.

COLOR:

Conservation Green

CROWN:

Montana Peak Traditional Four Dent Style. Crown to Be 5 ½" High

BRIM:

To Be 3" Wide Straight Flat Set. Flat Set, Double Thickness, Heavily Spirit Proofed (Shellac And Alcohol Only)

CROWN EYELETS:

One Eyelet On Each Side And One In The Rear Of Hat, All Three To Be 2 ¾" Above The Brim.

BRIM EYELETS:

3/8" Oval, One On Each Side, To Accommodate The Chin Strap, Eyelets Centered On Each Side.

BADGE EYELETS:

To Customer Specifications, Normally One In Front 2 1/8" Above The Brim

SWEAT BAND:

Genuine Leather, First Selection 1 5/8" Wide, With Oil Silk Underneath 1 1/6" Wide.

HAT BAND:

9 Ligne, yarn Dyed Grosgrain, ¾" Wide With Bow On The Left Side..

SIZES:

6 ½ Through 7 7/8

RAIN COVER FOR CAMPAIGN HAT - STOCK, STRATTON ITEM RC-MP (Bid Price Item 45)

SIZES:

State hat style and head size.

THREE PIECE BLACK HAT STRAP - STOCK, STRATTON ST-3P-BK (Bid Price Item 46)

3-piece black leather strap. Center strap 1/2" wide. Ends 3/8" wide with snap-type swivel and closure; Color: Black

HAT CORD, SILVER WITH SILVER ACORNS – STOCK, STRATTON CD-SR (Bid Price Item 47)

HAT CORD, GOLD WITH GOLD ACORNS - STOCK, STRATTON CD-GD (Bid Price Item 48)

HAT TRAP – STOCK. (Bid Price Item 49)

Will protect the entire hat from accidental crushing, fading, or brim warping when used in accordance with manufacturer's recommendations. Lightweight and durable with handle.

RENOVATION – STRATTON CAMPAIGN FELT HAT (Bid Price Item 50)

Hats shall be shipped to the Stratton factory where they shall be washed in top grade dry cleaning solution to assure cleanliness. The crown and brim shall be reshaped on original molds. New sweatband and ribbon shall be installed. Renovated hats shall be packaged in a new containers which are compliant with the packing and shipping specification above and shall be shipped back to the owner. Straw hats may not be reconditioned.

ULTRA INNER DUTY BELT BY UNCLE MIKE'S, STOCK – ITEM #'S 87811, 87821, 87831, 87841, 87842 (Bid Price Item 51)

CONSTRUCTION: Constructed of two layers of Mil-spec 1 1/2" wide nylon webbing, the outside layer of which shall be lined with a layer of 1 1/2" loop material throughout the length of the belt. The inside layer of the belt shall be lined on one end with a section of 1 1/2" wide hook, approximately 8 inches long. The four layers shall be sewn together by nylon thread and bound along the edges with a ribbon of type 66 nylon knit material and each end tab shall be finished with a radiused, heat sealed, program stitched edge.

SIZES: The belt shall be available in cataloged sizes from 26" to 48".

BROOME CLIP-ON POLYESTER/WOOL 3" NECKTIE, ITEMS 45055, 45015, 45045 AND 45054 – STOCK ITEM (Bid Price Items 52, 53, 54, 55)

COLOR:

Forestry Green (289)

STYLE:

Polyester/Wool 3" Clip-on Tie with Buttonholes and black metal clip

SIZES:

14 1/2" Length, style 45055

18" Length, style 45015

20" Length, style 45045

22" Length, style 45054

PERCENTAGE DISCOUNT OFF RETAIL LIST PRICE FOR ITEMS NOT LISTED ABOVE (Bid Price Item 56 – This item is not subject to evaluation)

Bidders should quote a percentage discount off retail list price which will apply for any item ordered from stock by the Ohio Department of Natural Resources authorized personnel in conjunction with this contract which is available through the awarded contractor but which is not listed in the detailed specifications above.

CONTRACT PRICES

Bidder Instructions:

1. Bidders shall provide pricing for all items. Failure to bid all items may render your bid not responsive.
2. All bid prices offered shall be in United States Dollars (\$ USD)

<b>Shirts</b>						
Contract Item #	OAKS Item #	Description	Manufacturer Item/Style Number	Item Type	UoM	Bid Price (\$USD)
		Men's Long Sleeve Shirt, Flying Cross by Fechheimer, Color: Silver Tan w/Forest Green Shoulder Straps				
1	16069	Neck Size 13" through 18 1/2"	319X6604	Winter	Ea.	\$ 52.00
2	16070	Neck Size 19" & Up	319X6604	Winter	Ea.	\$ 55.00
		Men's Long Sleeve Shirt w/Zipper Front, flying Cross by Fechheimer, Color: Silver Tan w/Forest Green Shoulder Straps				
3	16074	Neck Size 13" through 18 1/2"	319X6604Z	Winter	Ea.	\$ 55.00
4	16075	Neck Size 19" & Up	319X6604Z	Winter	Ea.	\$ 58.00
		Women's Long Sleeve Shirt, Flying Cross by Fechheimer, Color: Silver Tan w/Forest Green Shoulder Straps				
5	16079	Size 30 through 46	203X6604	Winter	Ea.	\$ 52.00
6	16080	Size 48 & Up	203X6604	Winter	Ea.	\$ 55.00
		Women's Long Sleeve Shirt w/Zipper Front, Flying Cross by Fechheimer, Color: Silver Tan w/Forest Green Shoulder Straps				
7	16084	Size 30 through 46	203X6604Z	Winter	Ea.	\$ 55.00
8	16085	Size 48 & Up	203X6604Z	Winter	Ea.	\$ 58.00
		Men's Short Sleeve Shirt, Flying Cross by Fechheimer, Color: Silver Tan w/Forest Green Shoulder Straps				
9	16089	Neck Size 13" through 18 1/2"	669X6604	Summer	Ea.	\$ 48.00
10	16090	Neck Size 19" & Up	669X6604	Summer	Ea.	\$ 51.00
		Men's Short Sleeve Shirt w/Zipper Front, Flying Cross by Fechheimer, Color: Silver Tan w/Forest Green Shoulder Straps				
11	16094	Neck Size 13" through 18 1/2"	669X6604Z	Summer	Ea.	\$ 51.00
12	16095	Neck Size 19" & Up	669X6604Z	Summer	Ea.	\$ 54.00
		Women's Short Sleeve Shirt, Flying Cross by Fechheimer, Color: Silver Tan w/Forest Green Shoulder Straps				
13	16105	Size 30 through 46	253X6604	Summer	Ea.	\$ 48.00
14	16106	Size 48 & Up	253X6604	Summer	Ea.	\$ 51.00
		Women's Short Sleeve Shirt w/Zipper Front, Flying Cross by Fechheimer, Color: Silver Tan w/Forest Green Shoulder Straps				
15	16110	Size 30 through 46	253X6604Z	Summer	Ea.	\$ 51.00
16	16111	Size 48 & Up	253X6604Z	Summer	Ea.	\$ 54.00

CONTRACT PRICES

<b>Trousers</b>						
Contract Item #	OAKS Item #	Description	Manufacturer Item/Style Number	Item Type	UoM	Bid Price (\$USD)
		Men's Class A Trousers With Leg Stripe, Flying Cross by Fechheimer, Color: Forest Green				
17	16133	Short Rise 28 - 40 (Even Only)	47285DNR	Winter/Summer	Ea.	\$ 69.00
18	16134	Regular Rise 28 - 60 (Even Only Over 38)	47285DNR	Winter/Summer	Ea.	\$ 69.00
19	16135	Long Rise 32 - 42 (Even Only)	47285DNR	Winter/Summer	Ea.	\$ 69.00
		Women's Class A Trousers With Leg Stripe, Flying Cross by Fechheimer, Color: Forest Green				
20	16136	Size 4 - 24	47295DNR	Winter/Summer	Ea.	\$ 69.00
		Men's Brush Pants, Flying Cross by Fechheimer, Color: Green				
21	16143	Regular Rise 29 - 50 (Even Only Over 40)	ODNRTRS01	Winter/Summer	Ea.	\$ 128.00
		Women's Brush Pants, Flying Cross by Fechheimer, Color: Green				
22	16144	Regular Rise 4 - 22 (Even Sizes Only)	ODNRTRSW01	Winter/Summer	Ea.	\$ 128.00
		Men's Duty Uniform Pants by Blauer, Color: OD Green				
23	24358	Regular Rise Even 28 - 54, Odd 31 - 37	8830	Stock	Ea.	\$ 64.00
		Women's Duty Uniform Pants by Blauer, Color: OD Green				
24	24359	Regular Rise 6 - 24 (even Sizes Only)	8830W	Stock	Ea.	\$ 64.00

<b>Outerwear</b>						
Contract Item #	OAKS Item #	Description	Manufacturer Item/Style Number	Item Type	UoM	Bid Price (\$USD)
25	16148	ODNR Men's and Women's Dress Blouse, Fechheimer Brothers Dress Coat (Made-to-Measure)	ODNR Dress Blouse	Made to Measure	Ea.	\$ 339.00
26	24360	Tacshell Jacket 4-in-1, Jacket and Softshell Liner by Blauer, Color: OD Green, Sizes: XS - XL (Stock)	9820Z	Stock	Ea.	\$ 340.00
27	24361	Tacshell Jacket 4-in-1, Jacket and Softshell Liner by Blauer, Color: OD Green, Sizes: 2XL - 3XL (Stock)	9820Z	Stock	Ea.	\$ 340.00
28	24362	Tacshell Jacket Only, by Blauer, Color: OD Green, Sizes: XS - XL (Stock)	9820	Stock	Ea.	\$ 214.00
29	24363	Tacshell Jacket Only, by Blauer, Color: OD Green, Sizes: 2XL - 3XL (Stock)	9820	Stock	Ea.	\$ 214.00
30	24364	Soft Shell Liner Only, by Blauer, Color OD Green, Sizes: XS - XL (Stock)	4660	Stock	Ea.	\$ 126.00
31	24365	Soft Shell Liner Only, by Blauer, Color OD Green, Sizes: 2XL - 3XL (Stock)	4660	Stock	Ea.	\$ 126.00

CONTRACT PRICES

<b>Footwear</b>						
Contract Item #	OAKS Item #	Description	Manufacturer Item/Style Number	Item Type	UoM	Bid Price (\$USD)
32	16164	Men's 3-Eye, Padded Collar, Leather Chukka boot by Bates (Stock)	78	Stock	Pr	\$ 98.00
33	24366	Men's Academy Oxford by Thorogood (Stock)	834-6041	Stock	Pr	\$ 48.00
34	16166	Men's Uninsulated Acadia Boot by Danner (Stock)	21210	Stock	Pr	\$ 215.00
35	16170	Men's Insulated Acadia 400 Boot by Danner (Stock)	22600	Stock	Pr	\$ 225.00
36	24367	Men's Kinetic 6" Boot, Gore Tex, by Danner (Stock)	28015	Stock	Pr	\$ 115.00
37	24368	Men's Kinetic 8" Boot, Gore Tex by Danner (Stock)	28010	Stock	Pr	\$ 120.00
38	24369	Women's Dura Shock Oxford by Bates (Stock)	752	Stock	Pr	\$ 90.00
39	16167	Women's Uninsulated Acadia Boot by Danner (Stock)	21210W	Stock	Pr	\$ 215.00
40	16171	Women's Insulated Acadia 400 Boot by Danner (Stock)	22600W	Stock	Pr	\$ 225.00
41	24370	Women's Kinetic 6" Boot, Gore Tex by Danner (Stock)	28080	Stock	Pr	\$ 115.00

<b>Accessories</b>						
Contract Item #	OAKS Item #	Description	Manufacturer Item/Style Number	Item Type	UoM	Bid Price (\$USD)
42	24371	Mock Turtleneck, Men's and Women's Unisex Sizes, Ufx by Elbeco, Size XS - 5XL, Color: Black (Stock)	8920	Stock	Ea.	\$ 38.00
43	16155	Hat, Straw, Campaign, Double Brim by Stratton (Stock)	S-40DB	Stock	Ea.	\$ 75.00
44	16156	Hat, Felt, Campaign by Stratton (Stock)	F-40	Stock	Ea.	\$ 103.00
45	16158	Rain Cover for Campaign Hat by Stratton (Stock)	RC-MP	Stock	Ea.	\$ 6.00
46	16159	Three Piece Black Hat Strap by Stratton (Stock)	ST-3P-BK	Stock	Ea.	\$ 6.00
47	16160	Hat Cord, Silver With Silver Acorns by Stratton (Stock)	CD-SR	Stock	Ea.	\$ 7.00
48	16161	Hat Cord, Gold With Gold Acorns by Stratton (Stock)	CD-GD	Stock	Ea.	\$ 7.00
49	16162	Hat Trap by Stratton (Stock)	N/A	Stock	Ea.	\$ 72.00
50	16163	Stratton Factory Renovation for Stratton Felt and Straw Campaign Style Hat (Stock)	N/A	Stock	Ea.	\$ 49.00
51	24373	Inner Duty Belt, Ultra, Black by Uncle Mike's, Sizes: SM - 4XL	878-11,21,31,41,42,43,44	Stock	Ea.	\$ 20.00
52	16174	Broome Necktie, Clip-On Polyester/Wool 3" Wide 14 1/2" (Stock)	45055	Stock	Ea.	\$ 5.00
53	16175	Broome Necktie, Clip-On Polyester/Wool 3" Wide 18" (Stock)	45015	Stock	Ea.	\$ 5.00
54	16176	Broome Necktie, Clip-On Polyester/Wool 3" Wide 20" (Stock)	45045	Stock	Ea.	\$ 6.00
55	16177	Broome Necktie, Clip-On Polyester/Wool 3" Wide 22" (Stock)	45954	Stock	Ea.	\$ 6.00
56	24372	OPTIONAL Discount Off Vendor's Retail Price List For Items Not Listed (This item is not subject to evaluation)	N/A	N / A	Pct.	15%

**CONTRACTOR'S INDEX**

**CONTRACTOR AND TERMS**

0000042544  
Roy Tailors Uniform Company, Inc.  
1905 Dalton Avenue  
Cincinnati, OH 45214



**CONTRACTOR'S CONTACT:** Randy Loftspring

**CONTRACTOR'S IT / MIS CONTACT:** Monica Jagers

**ORDER PLACEMENT:** Orders are to be placed via Roy Tailors Uniform Co. Inc.'s proprietary Ohio Department of Natural Resources secure online ordering website.

OAKS Item Identification Number: 16192 – Freight as applicable

**CONTRACT NO.:** OT900014-1 (06/30/16)

**DELIVERY:** 30 Days ARO (Stock Items)  
60 Days ARO (Winter & Summer Items)  
90 Days ARO (Winter Items)  
90 Days ARO (Summer Items)  
See Delivery And Acceptance Clause  
See Bid Price Pages for Classification of  
Items

**TERMS:** Net 30 Days

Toll Free: 800 543 0379  
Telephone: 513 621 4787, Ext 103  
FAX: 513 621 0483

Email: [rloftspring@roytailors.com](mailto:rloftspring@roytailors.com)

Telephone: 513 621 4787  
Email: [mjagers@roytailors.com](mailto:mjagers@roytailors.com)