

progress tank

new progress, llc., 539 S. 10th Street, Kansas City, KS 66105

JACK DOHENY SUPPLIES OHIO, INC. - PRICELIST - 2-17-10

State of Ohio
Department of Administrative Services
State Term Schedule

| | | |
|--------------------------|---|---------------------------------|
| Customer | _____ | Equipment Discount 12% |
| Dealer | Jack Doheny Supplies Ohio | Attachments Discount 12% |
| Presvac | | |
| | Progress Tank | \$113,550.00 |
| | 1500 Gallon Truck Mounted Aluminum vacuum unit - non-dumping - mounted on a single axle chassis, 215 HP, Diesel Engine, Automatic Transmission, and 26,000 GVW Non-Code - non hazardous | |
| STANDARD FEATURES | | |
| | 1500 Gallons tank capacity plus 3% outage for expansion | Standard |
| | Pressure relief valve, 2" at 14 PSI | Standard |
| | Ball and seal inspection and external service for primary shut off | Standard |
| | Heavy duty external moisture trap with stainless steel floatball seating against a neoprene seat secondary shut off | Standard |
| | Vacuum pressure gauge - glycerine filled, anti shock | Standard |
| | Liquid level indicators - three (3) 5" sight glasses in rear head | Standard |
| | Top manway - One (1) 20" with neoprene gasket | Standard |
| | Grabrail at tank top | Standard |
| | Ladder to top walkway - anti skid material | Standard |
| | Rear cleanout - one (1) 20" with neoprene gasket | Standard |
| | Hose trays / fenders - full length on both sides of tank, extra heavy duty hose tray supports, rear truck light protection caps | Standard |
| | Mudguards front and rear, anti sail | Standard |
| | Rear hose hooks, two (2) | Standard |
| | Toolbox, one (1) 36" x 18" x 18" | Standard |
| | Suction valve - one (1) 4" valve complete with aluminum coupling and drip cap | Standard |
| | Internal riser pipe - 4" with deflector / wear plate | Standard |
| | Discharge valve - one (1) 6" valve complete with aluminum coupling and drip cap | Standard |
| | Bumper - heavy duty rear bumper | Standard |
| | Lights, vapour proof with all wiring in conduit, truck lites, 3 lamp rear modules, junction box, 3 in a row top clearance bar, clearance lights and reflectors | Standard |
| | Worklights, two (2) spot lights with control switch in truck cab | Standard |
| | Amber beacon - rear of tank top | Standard |
| | Back-up alarm, audible | Standard |
| | Vacuum pressure pump - Rotary vane 3" fan cooled; maximum vacuum 28.5" HG, pressure 35 psi; capacity 350 CFM; four way valve for vacuum and pressure; check valve, filter with brass screen cartridge; oil catch muffler with drain valve | Standard |

progress tank

new progress, llc., 539 S. 10th Street, Kansas City, KS 66105

JACK DOHENY SUPPLIES OHIO, INC. - PRICELIST - 2-17-10

State of Ohio
Department of Administrative Services
State Term Schedule

| | | |
|-----------------|---|---------------------|
| | Vacuum pump drive - heavy duty air engaged PTO; drive shaft with universal joints, grease fittings; right angled gearbox with machined gears; shock coupling between gearbox and pump; heavy duty pump mount and base | Standard |
| OPTIONS | | |
| Quantity | Description | List Price |
| | Upgrade to 2000 Gallon non-dumping vacuum unit - 66" or 71" diameter | \$3,250.00 |
| | Completed front lift and rear opening door (maximum diameter tank using rear lift door is 75") | \$17,000.00 |
| | Lift Axle (non-steerable) | \$8,500.00 |
| | Lift Axle (steerable) | \$11,250.00 |
| | Rear Lift Door | \$5,400.00 |
| | Second Compartment for water | \$2,100.00 |
| | Ladder under hose tray | \$250.00 |
| | 4" heated collar (installed) | \$750.00 |
| | 6" heated collar (installed) | \$850.00 |
| | Demag Wittig RFW - 200 Vacuum pump | \$13,200.00 |
| | Moro PM100 Air Cooled Vac Pump | \$7,450.00 |
| | Moro PM 200 Liquid Cooled Vac Pump | \$9,250.00 |
| | Moro PM 2600 | \$16,750.00 |
| | Washdown Kit | \$2,520.00 |
| | Hibon Blower Upgrade - 900 cfm | \$28,000.00 |
| | Jetting System - 5.6 gpm@ 1500 psi, electric hose reel, 150' of 3/8" hose; includes 2nd compartment for water | \$7,150.00 |
| | DOT 407-412 Coded tanks for all units | \$9,500.00 |
| | Strobe light | \$550.00 |
| | Arrow Stick | \$1,400.00 |
| | Whelen DOT 3-head Strobe system | \$3,810.00 |
| | Whelen DOT 4-head Strobe system | \$4,010.00 |
| | Whelen DOT 6-head Strobe system | \$4,200.00 |
| | 12" Diamond Plate hose protector | \$525.00 |
| | 30" High Sign Panel, full length both sides | \$850.00 |
| | 6" Sample port with cap | \$145.00 |
| | Extra sight glasses (each) | \$150.00 |
| | Tool Box - Aluminum | \$1,100.00 |
| | EPA Engine Emission Requirements | \$9,100.00 |
| | Polished Aluminum Upgrade - if applicable | \$3,300.00 |
| | Upgrade to International Chassis | \$4,300.00 |
| | | |
| | | |
| | Sale Price | \$113,550.00 |
| | Less STS 12% Discount | \$13,626.00 |
| | Total Sale Price | \$99,924.00 |

progress tank

new progress, llc., 539 S. 10th Street, Kansas City, KS 66105

JACK DOHENY SUPPLIES OHIO, INC. - PRICELIST - 2-17-10

State of Ohio
Department of Administrative Services
State Term Schedule

| | | |
|--------------------------|---|---------------------------------|
| Customer | | Equipment Discount 12% |
| Dealer | Jack Doheny Supplies Ohio | Attachments Discount 12% |
| Presvac | | |
| | Progress Tank | \$141,260.00 |
| | 2500 Gallon Truck Mounted Aluminum vacuum unit - non-dumping - mounted on a single axle chassis, 260 HP, Diesel Engine, Automatic Transmission, and 33,000 GVW Non-Code - non hazardous | |
| STANDARD FEATURES | | |
| | 1500 Gallons tank capacity plus 3% outage for expansion | Standard |
| | Pressure relief valve, 2" at 14 PSI | Standard |
| | Ball and seal inspection and external service for primary shut off | Standard |
| | Heavy duty external moisture trap with stainless steel floatball seating against a neoprene seat secondary shut off | Standard |
| | Vacuum pressure gauge - glycerine filled, anti shock | Standard |
| | Liquid level indicators - three (3) 5" sight glasses in rear head | Standard |
| | Top manway - One (1) 20" with neoprene gasket | Standard |
| | Grabrail at tank top | Standard |
| | Ladder to top walkway - anti skid material | Standard |
| | Rear cleanout - one (1) 20" with neoprene gasket | Standard |
| | Hose trays / fenders - full length on both sides of tank, extra heavy duty hose tray supports, rear truck light protection caps | Standard |
| | Mudguards front and rear, anti sail | Standard |
| | Rear hose hooks, two (2) | Standard |
| | Toolbox, one (1) 36" x 18" x 18" | Standard |
| | Suction valve - one (1) 4" valve complete with aluminum coupling and drip cap | Standard |
| | Internal riser pipe - 4" with deflector / wear plate | Standard |
| | Discharge valve - one (1) 6" valve complete with aluminum coupling and drip cap | Standard |
| | Bumper - heavy duty rear bumper | Standard |
| | Lights, vapour proof with all wiring in conduit, truck lites, 3 lamp rear modules, junction box, 3 in a row top clearance bar, clearance lights and reflectors | Standard |
| | Worklights, two (2) spot lights with control switch in truck cab | Standard |
| | Amber beacon - rear of tank top | Standard |
| | Back-up alarm, audible | Standard |
| | Vacuum pressure pump - Rotary vane 3" fan cooled; maximum vacuum 28.5" HG, pressure 35 psi; capacity 350 CFM; four way valve for vacuum and pressure; check valve, filter with brass screen cartridge; oil catch muffler with drain valve | Standard |

progress tank

new progress, llc., 539 S. 10th Street, Kansas City, KS 66105

JACK DOHENY SUPPLIES OHIO, INC. - PRICELIST - 2-17-10

**State of Ohio
Department of Administrative Services
State Term Schedule**

| | | |
|-----------------|---|---------------------|
| | Vacuum pump drive - heavy duty air engaged PTO; drive shaft with universal joints, grease fittings; right angled gearbox with machined gears; shock coupling between gearbox and pump; heavy duty pump mount and base | Standard |
| OPTIONS | | |
| Quantity | Description | List Price |
| | Completed front lift and rear opening door (maximum diameter tank using rear lift door is 75") | \$17,000.00 |
| | Lift Axle (non-steerable) | \$8,500.00 |
| | Lift Axle (steerable) | \$11,250.00 |
| | Rear Lift Door | \$5,400.00 |
| | Second Compartment for water | \$2,100.00 |
| | Ladder under hose tray | \$250.00 |
| | 4" heated collar (installed) | \$750.00 |
| | 6" heated collar (installed) | \$850.00 |
| | Demag Wittig RFW - 200 Vacuum pump | \$13,200.00 |
| | Moro PM100 Air Cooled Vac Pump | \$7,450.00 |
| | Moro PM 200 Liquid Cooled Vac Pump | \$9,250.00 |
| | Moro PM 2600 | \$16,750.00 |
| | Washdown Kit | \$2,520.00 |
| | Hibon Blower Upgrade - 900 cfm | \$28,000.00 |
| | Jetting System - 5.6 gpm@ 1500 psi, electric hose reel, 150' of 3/8" hose; includes 2nd compartment for water | \$7,150.00 |
| | DOT 407-412 Coded tanks for all units | \$9,500.00 |
| | Strobe light | \$550.00 |
| | Arrow Stick | \$1,400.00 |
| | Whelen DOT 3-head Strobe system | \$3,810.00 |
| | Whelen DOT 4-head Strobe system | \$4,010.00 |
| | Whelen DOT 6-head Strobe system | \$4,200.00 |
| | 12" Diamond Plate hose protector | \$525.00 |
| | 30" High Sign Panel, full length both sides | \$850.00 |
| | 6" Sample port with cap | \$145.00 |
| | Extra sight glasses (each) | \$150.00 |
| | Tool Box - Aluminum | \$1,100.00 |
| | EPA Engine Emission Requirements | \$9,100.00 |
| | Polished Aluminum Upgrade - if applicable | \$3,300.00 |
| | Upgrade to International Chassis | \$5,900.00 |
| | | |
| | Sale Price | \$141,260.00 |
| | Less STS 12% Discount | \$16,951.20 |
| | Total Sale Price | \$124,308.80 |

progress tank

new progress, llc., 539 S. 10th Street, Kansas City, KS 66105

JACK DOHENY SUPPLIES OHIO, INC. - PRICELIST - 2-17-10

2009 State of Ohio
Department of Administrative Services
State Term Schedule

| | | |
|--------------------------|---|---------------------------------|
| Customer | | Equipment Discount 12% |
| Dealer | Jack Doheny Supplies Ohio | Attachments Discount 12% |
| Presvac | | |
| | Progress Tank | \$162,230.00 |
| | 3600 Gallon Truck Mounted Aluminum vacuum unit - non-dumping - mounted on a tandem axle chassis, 310 HP, Diesel Engine, Automatic Transmission, and 54,000 GVW Non-Code - non hazardous | |
| STANDARD FEATURES | | |
| | 1500 Gallons tank capacity plus 3% outage for expansion | Standard |
| | Pressure relief valve, 2" at 14 PSI | Standard |
| | Ball and seal inspection and external service for primary shut off | Standard |
| | Heavy duty external moisture trap with stainless steel floatball seating against a neoprene seat secondary shut off | Standard |
| | Vacuum pressure gauge - glycerine filled, anti shock | Standard |
| | Liquid level indicators - three (3) 5" sight glasses in rear head | Standard |
| | Top manway - One (1) 20" with neoprene gasket | Standard |
| | Grabrail at tank top | Standard |
| | Ladder to top walkway - anti skid material | Standard |
| | Rear cleanout - one (1) 20" with neoprene gasket | Standard |
| | Hose trays / fenders - full length on both sides of tank, extra heavy duty hose tray supports, rear truck light protection caps | Standard |
| | Mudguards front and rear, anti sail | Standard |
| | Rear hose hooks, two (2) | Standard |
| | Toolbox, one (1) 36" x 18" x 18" | Standard |
| | Suction valve - one (1) 4" valve complete with aluminum coupling and drip cap | Standard |
| | Internal riser pipe - 4" with deflector / wear plate | Standard |
| | Discharge valve - one (1) 6" valve complete with aluminum coupling and drip cap | Standard |
| | Bumper - heavy duty rear bumper | Standard |
| | Lights, vapour proof with all wiring in conduit, truck lites, 3 lamp rear modules, junction box, 3 in a row top clearance bar, clearance lights and reflectors | Standard |
| | Worklights, two (2) spot lights with control switch in truck cab | Standard |
| | Amber beacon - rear of tank top | Standard |
| | Back-up alarm, audible | Standard |
| | Vacuum pressure pump - Rotary vane 3" fan cooled; maximum vacuum 28.5" HG, pressure 35 psi; capacity 350 CFM; four way valve for vacuum and pressure; check valve, filter with brass screen cartridge; oil catch muffler with drain valve | Standard |



new progress, llc., 539 S. 10th Street, Kansas City, KS 66105

JACK DOHENY SUPPLIES OHIO, INC. - PRICELIST - 2-17-10

**2009 State of Ohio
Department of Administrative Services
State Term Schedule**

| | | |
|-----------------|---|---------------------|
| | Vacuum pump drive - heavy duty air engaged PTO; drive shaft with universal joints, grease fittings; right angled gearbox with machined gears; shock coupling between gearbox and pump; heavy duty pump mount and base | Standard |
| OPTIONS | | |
| Quantity | Description | List Price |
| | Completed front lift and rear opening door (maximum diameter tank using rear lift door is 75") | \$17,000.00 |
| | Lift Axle (non-steerable) | \$8,500.00 |
| | Lift Axle (steerable) | \$11,250.00 |
| | Rear Lift Door | \$5,400.00 |
| | Second Compartment for water | \$2,100.00 |
| | Ladder under hose tray | \$250.00 |
| | 4" heated collar (installed) | \$750.00 |
| | 6" heated collar (installed) | \$850.00 |
| | Demag Wittig RFW - 200 Vacuum pump | \$13,200.00 |
| | Moro PM100 Air Cooled Vac Pump | \$7,450.00 |
| | Moro PM 200 Liquid Cooled Vac Pump | \$9,250.00 |
| | Moro PM 2600 | \$16,750.00 |
| | Washdown Kit | \$2,520.00 |
| | Hibon Blower Upgrade - 900 cfm | \$28,000.00 |
| | Jetting System - 5.6 gpm@ 1500 psi, electric hose reel, 150' of 3/8" hose; includes 2nd compartment for water | \$7,150.00 |
| | DOT 407-412 Coded tanks for all units | \$9,500.00 |
| | Strobe light | \$550.00 |
| | Arrow Stick | \$1,400.00 |
| | Whelen DOT 3-head Strobe system | \$3,810.00 |
| | Whelen DOT 4-head Strobe system | \$4,010.00 |
| | Whelen DOT 6-head Strobe system | \$4,200.00 |
| | 12" Diamond Plate hose protector | \$525.00 |
| | 30" High Sign Panel, full length both sides | \$850.00 |
| | 6" Sample port with cap | \$145.00 |
| | Extra sight glasses (each) | \$150.00 |
| | Tool Box - Aluminum | \$1,100.00 |
| | EPA Engine Emission Requirements | \$9,100.00 |
| | Polished Aluminum Upgrade - if applicable | \$3,300.00 |
| | Upgrade to International Chassis | \$7,100.00 |
| | | |
| | Sale Price | \$162,230.00 |
| | Less STS 12% Discount | \$19,467.60 |
| | Total Sale Price | \$142,762.40 |

progress tank

new progress, llc., 539 S. 10th Street, Kansas City, KS 66105

JACK DOHENY SUPPLIES OHIO, INC. - PRICELIST - 2-17-10

State of Ohio
Department of Administrative Services
State Term Schedule

| | | |
|--------------------------|---|---------------------------------|
| Customer | | Equipment Discount 12% |
| Dealer | Jack Doheny Supplies Ohio | Attachments Discount 12% |
| Presvac | | |
| | Progress Tank | \$180,820.00 |
| | 4200 Gallon Truck Mounted Aluminum vacuum unit - non-dumping - mounted on a tandem axle chassis, 350 HP, Diesel Engine, Automatic Transmission, and 60,000 GVW Non-Code - non hazardous | |
| STANDARD FEATURES | | |
| | 1500 Gallons tank capacity plus 3% outage for expansion | Standard |
| | Pressure relief valve, 2" at 14 PSI | Standard |
| | Ball and seal inspection and external service for primary shut off | Standard |
| | Heavy duty external moisture trap with stainless steel floatball seating against a neoprene seat secondary shut off | Standard |
| | Vacuum pressure gauge - glycerine filled, anti shock | Standard |
| | Liquid level indicators - three (3) 5" sight glasses in rear head | Standard |
| | Top manway - One (1) 20" with neoprene gasket | Standard |
| | Grabrail at tank top | Standard |
| | Ladder to top walkway - anti skid material | Standard |
| | Rear cleanout - one (1) 20" with neoprene gasket | Standard |
| | Hose trays / fenders - full length on both sides of tank, extra heavy duty hose tray supports, rear truck light protection caps | Standard |
| | Mudguards front and rear, anti sail | Standard |
| | Rear hose hooks, two (2) | Standard |
| | Toolbox, one (1) 36" x 18" x 18" | Standard |
| | Suction valve - one (1) 4" valve complete with aluminum coupling and drip cap | Standard |
| | Internal riser pipe - 4" with deflector / wear plate | Standard |
| | Discharge valve - one (1) 6" valve complete with aluminum coupling and drip cap | Standard |
| | Bumper - heavy duty rear bumper | Standard |
| | Lights, vapour proof with all wiring in conduit, truck lites, 3 lamp rear modules, junction box, 3 in a row top clearance bar, clearance lights and reflectors | Standard |
| | Worklights, two (2) spot lights with control switch in truck cab | Standard |
| | Amber beacon - rear of tank top | Standard |
| | Back-up alarm, audible | Standard |
| | Vacuum pressure pump - Rotary vane 3" fan cooled; maximum vacuum 28.5" HG, pressure 35 psi; capacity 350 CFM; four way valve for vacuum and pressure; check valve, filter with brass screen cartridge; oil catch muffler with drain valve | Standard |

progress tank

new progress, llc., 539 S. 10th Street, Kansas City, KS 66105

JACK DOHENY SUPPLIES OHIO, INC. - PRICELIST - 2-17-10

State of Ohio
Department of Administrative Services
State Term Schedule

| | | |
|-----------------|---|---------------------|
| | Vacuum pump drive - heavy duty air engaged PTO; drive shaft with universal joints, grease fittings; right angled gearbox with machined gears; shock coupling between gearbox and pump; heavy duty pump mount and base | Standard |
| OPTIONS | | |
| Quantity | Description | List Price |
| | Completed front lift and rear opening door (maximum diameter tank using rear lift door is 75") | \$17,000.00 |
| | Lift Axle (non-steerable) | \$8,500.00 |
| | Lift Axle (steerable) | \$11,250.00 |
| | Rear Lift Door | \$5,400.00 |
| | Second Compartment for water | \$2,100.00 |
| | Ladder under hose tray | \$250.00 |
| | 4" heated collar (installed) | \$750.00 |
| | 6" heated collar (installed) | \$850.00 |
| | Demag Wittig RFW - 200 Vacuum pump | \$13,200.00 |
| | Moro PM100 Air Cooled Vac Pump | \$7,450.00 |
| | Moro PM 200 Liquid Cooled Vac Pump | \$9,250.00 |
| | Moro PM 2600 | \$16,750.00 |
| | Washdown Kit | \$2,520.00 |
| | Hibon Blower Upgrade - 900 cfm | \$28,000.00 |
| | Jetting System - 5.6 gpm@ 1500 psi, electric hose reel, 150' of 3/8" hose; includes 2nd compartment for water | \$7,150.00 |
| | DOT 407-412 Coded tanks for all units | \$9,500.00 |
| | Strobe light | \$550.00 |
| | Arrow Stick | \$1,400.00 |
| | Whelen DOT 3-head Strobe system | \$3,810.00 |
| | Whelen DOT 4-head Strobe system | \$4,010.00 |
| | Whelen DOT 6-head Strobe system | \$4,200.00 |
| | 12" Diamond Plate hose protector | \$525.00 |
| | 30" High Sign Panel, full length both sides | \$850.00 |
| | 6" Sample port with cap | \$145.00 |
| | Extra sight glasses (each) | \$150.00 |
| | Tool Box - Aluminum | \$1,100.00 |
| | EPA Engine Emission Requirements | \$9,100.00 |
| | Polished Aluminum Upgrade - if applicable | \$3,300.00 |
| | Upgrade to International Chassis | \$9,100.00 |
| | | |
| | Sale Price | \$180,820.00 |
| | Less STS 12% Discount | \$21,698.40 |
| | Total Sale Price | \$159,121.60 |