

INVITATION TO BID

State of Ohio
Department of Administrative Services
General Services Division
Office of Procurement Services

The Original Signed Bid must be submitted to the Office of Procurement Services to receive consideration for award.		BIDDER NAME	
BID NUMBER 0B103011-C	OPENING DATE (1:00 p.m.) * FEBRUARY 25, 2011	STREET ADDRESS <input type="checkbox"/> Check if remit address is different and list on separate sheet	
General Services Division Office of Procurement Services 4200 Surface Road Columbus, OH 43228-1395 Attn: Bid Desk		CITY STATE ZIP	
		COUNTY	MBE/EDGE CERTIFICATE NUMBER
		TELEPHONE NO. ()	TOLL FREE NO. 1 - ()
		CONTACT PERSON	FAX NO. ()
REQ./INDEX NO. DRC011168157	BID NOTICE DATE FEBRUARY 4, 2011	CONTRACTOR'S E-MAIL ADDRESS	
SELECT YOUR PREFERRED METHOD OF RECEIVING PURCHASE ORDERS AND ENTER THE E-MAIL OR FAX NUMBER INFORMATION (ONLY SELECT ONE METHOD)			
<input type="checkbox"/> E-Mail <input type="checkbox"/> Fax			
In addition to the standard terms for payment, the payment terms for state agency(ies) will be 2%, 10 Days, Net 30 Days unless otherwise stated in the following space. If no discount is offered, bidder should circle "Net 30 Days". ____%, ____ Days, Net 30 Days			
PARTICIPATING AGENCY(IES): Ohio Department of Rehabilitation and Correction, Division of Business Administration, 770 West Broad Street, Columbus, OH 43222			
ADDENDUM FOR CHANGE ADDENDUM NO.: 1 REVISION DATE: 02/01/11			
THE DEPARTMENT OF ADMINISTRATIVE SERVICES, OFFICE OF PROCUREMENT SERVICES IS SOLICITING BIDS FOR: THREE(3) INSTITUTIONAL DISHWASHERS (HOBART MODEL FT922BD, HOBART MODEL CLPS86E AND HOBART MODEL FT926BD), INSTALL NEW UNITS, REMOVE AND DISPOSE OF OLD UNITS; DELIVERED, FOB DEST. PREPAID			
Attached are pages 1, 9, 11, 13 and 14 to this Invitation to Bid. Remove the corresponding pages from the existing bid and replace with the attached.			
As indicated herein, this addendum is issued to correct Specifications and also to extend the opening date until FEBRUARY 25, 2011.			
All other specifications, terms and conditions remain unchanged.			
* Indicates a change in the Bid Opening Date from: February 4, 2011 to: February 25, 2011.			

INVITATION TO BID

State of Ohio
Department of Administrative Services
General Services Division
Office of Procurement Services

The original signed bid must be submitted to the Office of Procurement Services to receive consideration for award.		BIDDER NAME	
BID NUMBER 0B103011-C	OPENING DATE (1:00 p.m.) * FEBRUARY 25, 2011	STREET ADDRESS <input type="checkbox"/> Check if remit address is different and list on separate sheet	
General Services Division Office of Procurement Services 4200 Surface Road Columbus, OH 43228-1395 Attn: Bid Desk		CITY STATE ZIP	
		COUNTY	MBE/EDGE CERTIFICATE NUMBER
		TELEPHONE NO. ()	TOLL FREE NO. 1 - ()
		CONTACT PERSON	FAX NO. ()
REQ./INDEX NO. DRC011168157	BID NOTICE DATE JANUARY 20, 2011	CONTRACTOR'S E-MAIL ADDRESS	
SELECT YOUR PREFERRED METHOD OF RECEIVING PURCHASE ORDERS AND ENTER THE E-MAIL OR FAX NUMBER INFORMATION (ONLY SELECT ONE METHOD)			
<input type="checkbox"/> E-Mail <input type="checkbox"/> Fax			
In addition to the standard terms for payment, the payment terms for state agency(ies) will be 2%, 10 Days, Net 30 Days unless otherwise stated in the following space. If no discount is offered, bidder should circle "Net 30 Days". _____%, _____ Days, Net 30 Days			
BILL TO: Ohio Department of Rehabilitation and Correction Division of Business Administration 770 West Broad Street Columbus, OH 43222		SHIP TO: See Page 5: DELIVERY AND ACCEPTANCE	
DELIVERY REQUESTED F.O.B./DEST. P.P.D. <u>90 Days ARO</u>		DELIVERY OFFERED (IF DIFFERENT) F.O.B./DEST.P.P.D. _____	
<p>THE DEPARTMENT OF ADMINISTRATIVE SERVICES, OFFICE OF PROCUREMENT SERVICES IS SOLICITING BIDS FOR:</p> <p>THREE(3) INSTITUTIONAL DISHWASHERS (HOBART MODEL FT922BD, HOBART MODEL CLPS86E AND HOBART MODEL FT926BD), INSTALL NEW UNITS, REMOVE AND DISPOSE OF OLD UNITS; DELIVERED, FOB DEST. PREPAID</p> <p>QUANTITY AND DURATION: This Invitation to Bid, which is not a contract, is considered to be a one-time procurement offer for the product(s)/service(s) as listed herein. The successful Contractor may commence performance of the awarded contract upon receipt of an official state of Ohio Purchase Order (ADM0523/ORDE). Upon completion of the contract and upon receipt of proper invoices, payment will be provided by the ordering agency. The contract will then be considered as complete and no further purchases may be placed against the contract. With the exception of approved overrun/underrun tolerances, any deviations from the quantity listed in the awarded contract shall not be permissible nor acceptable.</p> <p>INSTRUCTIONS, TERMS AND CONDITIONS FOR BIDDING; STANDARD CONTRACT TERMS AND CONDITIONS; AND SUPPLEMENTAL CONTRACT TERMS AND CONDITIONS, Rev. 10-01-07 are a part of this Invitation to Bid. Copies may be downloaded by clicking on this link: Instructions: Terms and Conditions for Bidding, Standard Contract Terms and Conditions, and Supplemental Contract Terms and Conditions. All prior versions of Instructions to Bidders, Contract Terms and Conditions are null and void.</p> <p>Any questions or clarifications regarding this Invitation to Bid should be directed to the Office of Procurement Services through the Internet at www.ohio.gov/procure. All questions should be submitted a minimum of seven (7) working days prior to the bid opening date.</p>			
PRINTED/TYPED SIGNATURE	AUTHORIZED SIGNATURE (ORIGINAL SIGNATURE ONLY) <i>(Please sign in blue ink)</i>		DATE

The original signed bid must be submitted to the Office of Procurement Services by 1:00 o'clock p.m. on the above listed opening date to receive consideration for award. It is requested that the bidder not sign their bid in black ink. Bidder certifies, by signature affixed to its bid, that the information provided by it in its bid including the certified statements, is accurate and complete. Bidder declares to have read and understood and agrees to be bound by all of the instructions, terms, conditions and specifications of this Invitation to Bid and agrees to fulfill the requirements of any awarded contract at the prices bid.

* Indicates a change in the Bid Opening Date from: February 4, 2011 to: February 25, 2011.

SPECIFICATIONS(cont.)

12. CLEAN OUT ACCESS:

Extension panels on load and unload sections to be completely removable without the use of tools for easy cleaning.

13. STRAINER SCREENS:

- a. Prewash, power wash and power rinse scrap screens to be one piece slanted design slopped toward the front of the machine and large removable 16 gauge SST scrap basket.
- b. Scrap system to be inside chamber allowing for smooth front.
- c. Both tray and basket easily removable from the front of the machine.

14. TANK HEAT:

- a. Regulated electric immersion heaters, 26 kw in the power wash and power rinse tank with solid state thermostat and positive low water protection.
- b. Equipped with a factory installed electrically integrated electric booster heater.

15. FINAL RINSE:

- a. Fresh water non-pumped final rinse water usage to be no more than 168 gallons per hour at a conveyor speed of 10 feet per minute.
- b. Fresh water rinse to be non pumped/dual design.
- c. Rinse nozzles and rinse are to be secured in a slotted mounting fixture to ensure proper spray pattern.
- d. Upper and lower rinse arms to be removable without tools for easy cleaning.
- e. Rinse activation to be sequenced through the use of photo electronic sensors mounted at the entrance end of the load chamber.
- f. Final rinse booster heater to be a 39kw unit, electrically integrated to the dish machine.

16. PRISON SECURITY PACKAGE:

- a. Hook mounted plastic strip curtains.
- b. Lockable control panel.
- c. Lexan (or equivalent) covered temperature gauge, standard for the package.
- d. Torx security screws.
- e. Lockable cover over controls, including all on/off switches.
- f. Lockable vertical inspection doors.
- g. Lockdowns on enclosure panels
- h. Protective under grid

17. WARRANTY:

* Minimum warranty period eighteen (18) months (2 & ½ years), parts & labor after acceptance.

18. CUSTOM SOILED DISH TABLE:

- a. Size and shape per attached drawing. Height of 34 inches.
- b. Stainless steel construction, minimum 14 gauge type 304, mounted on stainless steel 1-5/8" tubular legs with stainless steel feet.
- c. Welded into the dish table is a 20" x 20" x 5" deep pre-wash sink. Sink shall include removable rack guides.
- d. Water inlet that activates with disposal unit to be incorporated into sink.
- e. The sink shall have the necessary adaptor welded into the bottom to accept the existing disposal unit a Hobart #FD500.
- f. Dish table to have a 3" high raised rolled rim with all corners bullnosed.
- g. Weld a 30" x 30" x 10" high back splash to the unit.

* Indicates change to Item A17

SPECIFICATIONS(cont.)

1. Standard features to include a dirty indicator with an option shut down mode, energy saver mode, low temperature alerts for all zones, service diagnostics, de-lime notifications and operating indicators.
2. Integrated SST pump intake screen.
3. Machine to have self aligning stainless steel upper and lower wash and power rinse arms with computational fluid dynamics debossed anti-clogging nozzles.
4. Wash and power rinse pipes to be located on the exterior rear panel for an obstruction free indicator.
5. Rinse arms to include an integrated in line water filter.
6. Final rinse to be automatically activated when racks enter the rinse zone.
7. Electrical interface points for chemical connections provided as standard.
8. Vent fan and booster heater controls.
9. Automatic fill to be standard with tank water level to be automatically maintained.
10. Drain handle to be located outside of the water zone and to be automatically closed upon closing the inspection door.
11. Stainless steel front panel, frame, feet, legs; wash tank and chamber; removable strainer pans and large deep basket; integrated pump intake screen assembly; channel; stainless steel splash shields.

2. WARRANTY

1. Machine to have full 18 month manufacturer's warranty on parts and service.
2. Machine to have an extended extra 1 year warranty on the machine, blower and electric booster heater.
3. Total warranty will be not less than 30 months.

C. ITEM #3: 1: HOBART MODEL FT926BD FLIGHT-TYPE DISHWASHER

1. SPECIFICATIONS

- a. Dish machine to be fully automatic flight-type machine.
- b. Consisting of a power re-circulating prewash in the 5ft load section and re-circulating prewash water jetted over the SST surface area below the conveyor loading section to provide continues self cleaning.
- c. Power Wash, power rinse and Opti-Rinse fresh water rinse in the 8ft center section.
- d. * 13ft unload section to contain a 2 ft. chambered section with the remaining length to be open to allow for drying of the ware and unloading process.
- e. * Load and unload sections to include a 10" shelf to facilitate the loading and unloading practice.
- f. Overall length of machine to be 26' 10".
- g. * Direction of operation to be left to right.
- h. * Voltage and phase to be 480/60/3 and provide built in circuit breaker/single point for entire machine.

2. CONSTRUCTION:

- a. Tanks and chamber constructed of #16 gauge stainless steel.
- b. Tank design to be drawn with rounded corners throughout and contoured to the drain opening for easy cleaning.
- c. Chamber wide prewash, power wash and power rinse inspection doors to be fully insulated hinged doors.
- d. Prewash, power wash and power rinse SST self-draining pumps and motors integrally assembled and mounted to tanks with frame support.
- e. Stainless steel back panels and lower front panels to provide an air gap for cooler surface area and a reduction in heat loss.
- f. Easy to remove 4 ply curtains to be placed between each section to aid in heat retention.

3. PUMPS:

- a. SST self draining prewash pump to produce a flow rate of 150 gallons per minute.
- b. SST self-draining power wash and power rinse pumps to produce a flow rate of 292 gallons per minute.
- c. All pumps and impellers to be stainless steel and self-draining.
- d. Easy to reach pump clean-out to be provided for each pump.

4. MOTORS:

- a. All pump motors to be totally enclosed fan cooled 3 hp motors.
- b. Conveyor motor to be ½ hp.
- c. Each motor to have inherent overload protection.

* Indicates changes made to Item C1d, C1e, D1g and C1h

SPECIFICATIONS(cont.)

12. CLEAN OUT ACCESS:

Extension panels on load and unload sections to be completely removable without the use of tools for easy cleaning.

13. STRAINER SCREENS:

- a. Prewash, power wash and power rinse scrap screens to be one piece slanted design slopped toward the front of the machine and large removable 16 gauge SST scrap basket.
- b. Scrap system to be inside chamber allowing for smooth front.
- c. Both tray and basket easily removable from the front of the machine

14. TANK HEAT:

- a. Regulated electric immersion heaters, 26 kw in the power wash and power rinse tank with solid state thermostat and positive low water protection.
- b. Equipped with a factory installed electrically integrated electric booster heater.

15. FINAL RINSE:

- a. * Fresh water non-pumped final rinse water usage to be no more than 132 gallons per hour at a conveyor speed of 8.5 feet per minute.
- b. Fresh water rinse to be non pumped/dual design.
- c. Rinse nozzles and rinse are to be secured in a slotted mounting fixture to ensure proper spray pattern.
- d. Upper and lower rinse arms to be removable without tools for easy cleaning
- e. Rinse activation to be sequenced through the use of photo electronic sensors mounted at the entrance end of the load chamber.
- f. Final rinse booster heater to be a 39kw unit, electrically integrated to the dish machine.

16. PRISON SECURITY PACKAGE:

- a. Hook mounted plastic strip curtains.
- b. Lockable control panel.
- c. Lexan (or equivalent) covered temperature gauge, standard for the package.
- d. Torx security screws.
- e. Lockable cover over controls, including all on/off switches.
- f. Lockable vertical inspection doors.
- g. Lockdowns on enclosure panels
- h. **

17. WARRANTY:

Minimum warranty period eighteen (18) months (1 & ½ years), parts & labor after acceptance.

18. ***

* Indicates change to Item C15a.

** Indicates Item C16h removed

*** Indicates Item C18 removed

SPECIFICATIONS(cont.)

19. BIDDERS INSTALLATION SCOPE OF WORK:

- a. Disconnect and take apart existing dishwasher and remove from job site.
- b. Deliver sections of dishwasher to job site and set in place. Assemble sections and make all internal utility connections.
- c. Make final connections of water, drain and electrical lines within five (5) feet of dishwasher.
- d. * Run new 19" round sst vent pipe from dishwasher to ceiling.
- e. Install new dish table and disposer and make final utility connections.
- f. Start up dishwasher and disposer. Check operation. Do any needed adjustments.
- g. Provide training to DRC staff for both operation and maintenance of dishwasher.
- h. Installer shall be scheduled to perform installation based upon the Correctional Centers schedule and security concerns, and at a time mutually agreeable to the vendor.
- i. Employees and contractors working for the installer must pass the background check required by DRC Policy & Procedure.
- j. Compliance is required for all security issues and regulations.

20. OWNERS INSTALLATION SCOPE OF WORK:

- a. Make all utility changes for dishwasher and disposer to meet new equipment specifications.
- b. Run proper wiring from disconnect boxes to control box on dishwasher.

* Indicates change to Item C19d