

INVITATION TO BID

State of Ohio
Department of Administrative Services
General Services Division
Office of Procurement Services

The Original Signed Bid must be submitted to the Office of Procurement Services to receive consideration for award.		BIDDER NAME	
BID NUMBER OB106412	OPENING DATE (1:00 p.m.) OCTOBER 14, 2011	STREET ADDRESS <input type="checkbox"/> Check if remit address is different and list on separate sheet	
General Services Division Office of Procurement Services 4200 Surface Road Columbus, OH 43228-1395 Attn: Bid Desk		CITY STATE ZIP	
		COUNTY	MBE/EDGE CERTIFICATE NUMBER
		TELEPHONE NO. ()	TOLL FREE NO. 1 - ()
		CONTACT PERSON	FAX NO. ()
		CONTRACTOR'S E-MAIL ADDRESS	
REQ./INDEX NO. DOH0115905	BID NOTICE DATE SEPTEMBER 30, 2011		
SELECT YOUR PREFERRED METHOD OF RECEIVING PURCHASE ORDERS AND ENTER THE E-MAIL OR FAX NUMBER INFORMATION (ONLY SELECT ONE METHOD)			
<input type="checkbox"/> E-Mail <input type="checkbox"/> Fax			
In addition to the standard terms for payment, the payment terms for state agency(ies) will be 2%, 10 Days, Net 30 Days unless otherwise stated in the following space. If no discount is offered, bidder should circle "Net 30 Days". _____%, _____ Days, Net 30 Days			
<u>PARTICIPATING AGENCY(IES):</u> OHIO DEPARTMENT OF HEALTH			
ADDENDUM FOR CHANGE ADDENDUM NO.: 1 REVISION DATE: 09/30/11			
<u>THE DEPARTMENT OF ADMINISTRATIVE SERVICES, OFFICE OF PROCUREMENT SERVICES IS SOLICITING BIDS FOR:</u> TRAILER, MOBILE MORTUARY UNIT			
Attached is page 9 to this Invitation to Bid. Remove the corresponding page from the existing bid and replace with the attached.			
As indicated herein this addendum is issued to indicate an update to the wattage requirement of the commercial generator of specification 77.			

SPECIFICATIONS (Cont'd.)

YES NO

- ___ ___ 72. Furnish and install a PC-30 12 volt converter, 120V input receptacle with an automatic battery charger.
- ___ ___ 73. Converter shall be powered through the shoreline power connector.
- ___ ___ 74. Location of converter/charger combo shall be determined at pre-built meeting.
- ___ ___ 75. All high current battery cabling shall be covered for protection and utilize full-length cable runs sized to load, splices are not acceptable. Terminal ends shall be crimped with manufacturer recommended tooling and sealed using color-coded shrink-wrap. All added wiring for 12VDC load runs shall be AWG 8, 10, 12, and 14, and conform to MIL- W-1678D type D. Wire terminals used shall conform to MIL-T-7928. Terminals shall be insulated with insulation grip, Type II, Class 2, and crimped with tooling recommended by manufacturer.
- ___ ___ 76. Furnish and install four (4) 12-volt dome lights with optic lens equally spaced in the interior of trailer.

GENERATOR

- ___ ___ *77. 7000 W commercial gasoline generator with quiet run muffler, installed in an aluminum box on the tongue of trailer.
- ___ ___ 78. Fuel supply will be a minimum of 24 gallon total. There shall be two (2) 12-gallon marine type fuel tanks; both are to be mounted on top of the generator out on the tongue. These tanks are to be housed in a lockable, aluminum tread plate box, with easy ability to remove the tank for refilling. The tanks shall have marine quick disconnect to allow the fuel supply to the generator to be changed from one tank to the other. The tank housing shall be adequately vented to prevent build up of fumes.

*Indicates the update to the wattage requirement of the commercial generator specification.